

API - SNIPPT - DOC

General Keywords

All keywords can be used without individual order, as arguments.

General keyword examples:

page
limit
sort
desc

- *Pagening all Php snippets, just change the pagenumber*

`{api url}/{snippets, comments, ratings or language}?limit=5&page=1`

`{api url}/{snippets, comments, ratings or language}?sort={see list of keywords}`

`{api url}/{snippets, comments, ratings or language}?sort={see list of keywords}&desc`

datefrom
dateto

- *Both arguments datefrom and dateto has to be used, for specific date see keyword "date=2010-11-01"*

`{api url}/{snippets, comments or ratings}?datefrom=2010-01-01&dateto=2012-01-01`

Snippets

username
date
language
languageid
code
title
id
description
userid

Examples:

```
{api url}/snippets?username=superuser&language=csharp  
{api url}/snippets?id={num}  
{api url}/snippets?date=YYYY-mm-dd&language=javascript
```

Post

post to url: {api url}/snippets
fields: userid, code, desc, title, languageid, apikey

Put

put to url: {api url}/snippets
fields: id, userid, code, desc, title, languageid, apikey

Delete

delete to url: {api url}snippets/{num: snippetid}/{num: userid}/
{apikey}

Comments

userid
username
date
comment
commentid
snippetid

Examples:

```
{api url}/comments?username=superuser  
{api url}/comments?snippetid={num}  
{api url}/comments?userid={num}&date=YYYY-mm-dd
```

Post

post to url: {api url}/comments
fields: snippetid, userid, comment, apikey

Put

put to url: {api url}/comments
fields: id, commentid, userid, code, desc, title, languageid,
apikey

Delete

delete to url: {api url}/comments/{num: commentid}/{num: userid}/
{apikey}

Ratings

username
date
rating
ratingid
snippetid
userid

{api url}/ratings?username=superuser
{api url}/ratings?snippetid={num}
{api url}/ratings?userid={num}&date=YYYY-mm-dd

Post

post to url: {api url}/ratings
fields: snippetid, userid, rating, apikey

Put

put to url: {api url}/ratings
fields: id, snippetid, ratingid, userid, rating, apikey

Delete

delete to url: {api url}/ratings/{num: ratingid}/{num: userid}/
{apikey}

Languages

language
languageid

{api url}/languages?languageid={num}
{api url}/languages - *Get all avalible languages*