

# tigeRs: Princeton's R Group

Kim Kreiss & Angela Li

Workshop 1

# Introduction

# Introductions

- ▶ Kim
- ▶ Angela
- ▶ DDSS

# Today

- ▶ An overview of R/RStudio/RMarkdown
- ▶ Framework for reproducible analysis
- ▶ The tidyverse
- ▶ Apply these by going through a brief class project

## Overview of R/RStudio/RMarkdown


# R/RStudio/RMarkdown and Why?

- ▶ R is a statistical programming language great for data analysis and data science applications
- ▶ RStudio is an Integrated Development Environment (IDE)—basically just a nice interface for using R, writing/running code, and interacting with data and files
- ▶ RMarkdown is a file format that lets you combine R code, data, and text that outputs a document, report, slideshow, etc.

# Cool things you can do with R

- ▶ Easy and intuitive management of code and data
- ▶ Excellent visualization capabilities, including charts, maps, interactive dashboards etc.
- ▶ Easily output analysis into a digestible format
- ▶ can handle a wide arrange of statistical analysis, data analysis, and data science applications


## Some examples





# Some examples

Share of Creative Class Workers in NYC Census Tracts  
(by PUMA/Community District)



Source: 2019 American Community Survey 5-year estimates  
Tracts with less than 30 people are shaded grey.

## Some examples

### South of France Restaurant concentration

Number of restaurant per city district




Figure 2: 'Source: r-graph-gallery.com'

## Some examples



Figure 3: 'Source: r-graph-gallery.com'

# Some examples




Figure 4: 'Source: r-graph-gallery.com'

# Some examples

## A Pandoc Markdown Article Starter and Template \*

Steven V. Miller *Clemson University*

This document provides an introduction to R Markdown, argues for its benefits, and presents a sample manuscript template intended for an academic audience. I include basic syntax for R Markdown and a minimal working example of how the analysis itself can be conducted within R with the `knitr` package.

*Keywords:* pandoc, r markdown, knitr

### Introduction

Academic workflow, certainly in political science, is at a crossroads. The *American Journal of Political Science* (AJPS) announced a (my words) “show your work” initiative in which authors who are tentatively accepted for publication at the journal must hand over the raw code and data that produced the results shown in the manuscript. The editorial team at AJPS then reproduces the code from the manuscript. Pending successful replication, the manuscript moves toward publication. The AJPS might be at the fore of this movement, and it could be the most aggressive among political science journals, but other journals in our field have signed the joint [Data Access & Research Transparency](#) (DART) initiative. This, at a bare minimum, requires uploading code from quantitatively-oriented published articles to in-house directories hosted by the journal or to services like [Dataverse](#).

There are workflow implications to the Lacour controversy as well. Political science, for the foreseeable future, will struggle with the extent of [the data fraud perpetrated by Michael Lacour](#) in an article co-authored with Donald P. Green in *Science*, the general scientific journal of record in the United States. A failure to reproduce LaCour’s results with different samples uncovered a comprehensive effort by LaCour to “fake” data that provided results to what we felt or believed to be true (i.e. “truthiness”). However, [fake data can have real consequences](#) for both the researcher and those who want to learn from it and use it for various purposes. Even research done honestly may suffer the same fate if researchers are not diligent in their workflow.

These recent events underscore the DART push and cast a shadow over our workflow. However, good workflow has always been an issue in our discipline. Cloud storage services like [Dropbox](#) are still relatively new among political scientists. Without cloud storage, previous workflow left open the possibility that work between a home computer and an office computer was lost as a function of a corrupted thumb drive, an overheated power supply, or, among other things, the wave of viruses that [would particularly affect Microsoft users every summer](#). Social sciences, unlike engineering, have traditionally relied on software like Microsoft Word for manuscript preparation though any word processor reduces workflow to a series of clicks and strokes on a keyboard. This is a [terrible way to track changes](#) or maintain version control. The addition of collaborators only compounds all the aforementioned issues. The proverbial left hand may not know what the right hand is doing.

I think there is reason for optimism. We only struggle with it now because we have tools like [R Markdown](#) and [Pandoc](#), more generally, that make significant strides in workflow. LaTeX resolved earlier issues of corrupted binary files by reducing documents to raw markup that was little more

\*Replication files are available on the author’s Github account (<http://github.com/svmiller>). Current version: July 26, 2019; Corresponding author: [svmiller@clemson.edu](mailto:svmiller@clemson.edu).

## Goals

# Today's workshop

- ▶ Learn the basics and fundamentals of working in RStudio and RMarkdown
- ▶ Learn a framework for reproducible analysis that can be applied to homework, work assignments, etc.
- ▶ Go through an analysis together to combine these
- ▶ Leave with a file that can serve as a template for future work

# RStudio

Workshop 1 - RStudio

Workshop 1.Rmd | workshop-1.R

```
1 # This is a script
2 # You can write code here, save it, and run it when necessary
3
4 #load in libraries
5 library(tidyverse)
6
7 #set working directory
8 setwd("~/Documents/git/Princeton Classes/DDSSI/R Group Workshops/Workshop 1")
9
10 # Read in data
11 |
```

Environment | History | Connections | Tutorial

R | Global Environment

Data

|      |                         |
|------|-------------------------|
| data | 142 obs. of 5 variables |
| gg   | List of 9               |
| p    | List of 9               |
| pp   | List of 8               |

Files | Plots | Packages | Help | Viewer | Presentation

Folder | Blank File | Delete | Rename

nents > git > Princeton Classes > DDSSI > R Group Workshops > Workshop 1

| Name                             | Size     | Modified              |
|----------------------------------|----------|-----------------------|
| ..                               |          |                       |
| Workshop 1.Rproj                 | 205 B    | Feb 4, 2023, 11:50 AM |
| Workshop 1.Rmd                   | 1.7 KB   | Feb 4, 2023, 1:27 PM  |
| Workshop-1.pdf                   | 468.6 KB | Feb 4, 2023, 1:21 PM  |
| Workshop-1.html                  | 119.4 KB | Feb 4, 2023, 12:55 PM |
| network-map.png                  | 229.5 KB | Feb 4, 2023, 12:49 PM |
| choropleth-map.png               | 351.5 KB | Feb 4, 2023, 12:50 PM |
| web-lollipop-plot-with-R-the-... | 204.6 KB | Feb 4, 2023, 12:52 PM |
| scatterplot-fitted.png           | 180.1 KB | Feb 4, 2023, 12:53 PM |
| Image 2-4-23 at 1.07 PM.jpeg     | 380.9 KB | Feb 4, 2023, 1:08 PM  |
| workshop-1.R                     | 243 B    | Feb 4, 2023, 2:09 PM  |

Console | Terminal | Render | Background Jobs

```
R 4.2.2 - ~/Documents/git/Princeton Classes/DDSSI/R Group Workshops/Workshop 1/
> #pp <- ggplotly(p, tooltip="text")
> #pp
> gg
Error in yaml::yaml.load(..., eval.expr = TRUE) :
Scanner error: mapping values are not allowed in this context at line 6, column 16
> install.packages("tidyverse")
trying URL 'https://cran.rstudio.com/bin/macosx/big-sur-arm64/contrib/4.2/tidyverse_1.3.2.tgz'
Content type 'application/x-gzip' length 425892 bytes (415 KB)
downloaded 415 KB

The downloaded binary packages are in
/var/folders/wh/f3ld23jd09n5b_bsk2x3z8h40000gn/T//RtmpV9gWYV/downloaded_packages
> setwd("~/Documents/git/Princeton Classes/DDSSI/R Group Workshops/Workshop 1")
> |
```



# R Scripts and R Markdown

- ▶ R Script (workshop-1.R)
  - ▶ A file that only runs normal R code
- ▶ RMarkdown Script (workshop-1-solutions.Rmd)
  - ▶ A different file type that combines code and text to produce a document that includes both
- ▶ Both a .R and .Rmd file are provided

# Reproducible Analysis




Figure 6: Source: Russo, Righeli, Angelini

## Why you should care

- ▶ It will save you time and make analyses easy to update/run again
- ▶ Eliminates room for mistakes
- ▶ Easily shared and validated by others—especially crucial for analysis informing public policy

# What to keep in mind for our purposes

- ▶ The ideal: someone else (including and especially you, at a later date) should be able to
  - (1) Read your code file and understand what you did and why (code comments are everyone's friend)
  - (2) Re-run your code without making any edits and produce the same results
- ▶ In practice:
  - ▶ Any data cleaning, transformations to the data, edits, analyses, etc. should be documented in an R script
  - ▶ No edits should be made manually!!! (don't edit your data in excel, don't manually enter or copy/paste output, etc.)


# Tidyverse

## Tidyverse



- ▶ A collection of R packages made for data/statistical analysis with the same underlying structure, intuitive syntax and philosophy
- ▶ Great for working with and manipulating a wide variety of datasets
- ▶ We will use tidyverse today

# Tidyverse



Code

# What we will do today

- ▶ Go through and reproduce a shortened version of Project 2 from last semester's 507c class
- ▶ use tidyverse to:
  - ▶ read in data
  - ▶ clean/transform data
  - ▶ generate summary statistics
  - ▶ run a regression model
  - ▶ output results in a summary memo document




## The task: replicate a project assignment

- ▶ You are working for a non-profit organization advocating for safe and healthy lifestyles and you received a request from the director to provide analysis and information on the effect of the minimum legal drinking age on alcohol consumption:
  - ▶ Does crossing the MLDA make it more likely someone will drink?
  - ▶ Is there a jump in consumption in the likelihood of drinking at age 21?
  - ▶ Are there important differences by demographic groups?
  - ▶ Can you something about the jump at age 21 for different levels of alcohol use (ie, heavy drinkers?)?

# Files


- ▶ workshop-1.R
  - ▶ this is just an R script with all the code for your reference later
- ▶ workshop-1-skeleton.Rmd
  - ▶ an RMarkdown code skeleton for you to fill out as we go
- ▶ workshop-1-solutions.Rmd
  - ▶ the same RMarkdown code file as above, but with all the code and solutions

# RMarkdown File Structure: Overview



```
1 ---
2 title: "Project 2"
3 author: "Your Name"
4 date: "2023-02-05"
5 output: html_document
6 ---
7
8 ```{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}
9 library(tidyverse)
10 ```
11
12 ## Overview
13
14 This document provides high-level information on whether the minimum legal drinking age
15 (MLDA) makes any difference in the likelihood of consuming alcohol. It includes:
16
17 + Code to read in and clean data
18
19 + Summary Statistics
20
21 + Regression output
22
23 ```{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}|
24 # read in MLDA data and assign MLDA data
25 mlda <- read_csv("mlda.csv")
26 ```
27
28
29
```

# RMarkdown File Structure: YAML




The screenshot shows the RStudio interface with three tabs: 'Workshop 1.Rmd', 'workshop-1-solutions.Rmd', and 'workshop-1.R'. The 'Source' pane is active, displaying the content of 'workshop-1.R'. The file structure is as follows:

```
1 ---
2 title: "Project 2"
3 author: "Your Name"
4 date: "2023-02-05"
5 output: html_document
6 ---
7
8 ```{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}
9 library(tidyverse)
10 ```
11
12 ## Overview
13
14 This document provides high-level information on whether the minimum legal drinking age
15 (MLDA) makes any difference in the likelihood of consuming alcohol. It includes:
16
17 + Code to read in and clean data
18
19 + Summary Statistics
20
21 + Regression output
22
23 ```{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}
24 # read in MLDA data and assign MLDA data
25 mlda <- read_csv("mlda.csv")
26 ```
27
28
29
```

A green rectangular box highlights the YAML front-matter section (lines 1-6). To the right of the code, there are green annotations: 'YAML' is positioned above 'Some settings for your document', which is above 'You will probably not do much with this beyond what is here'. The RStudio interface includes a toolbar at the top with icons for navigation, saving, and running, and a sidebar on the right with an 'Outline' pane.

# RMarkdown File Structure: Code



The screenshot shows the RStudio interface with three tabs: 'Workshop 1.Rmd', 'workshop-1-solutions.Rmd', and 'workshop-1.R'. The 'Source' tab is active, displaying RMarkdown code. The code is structured as follows:

```
1 ---
2 title: "Project 2"
3 author: "Your Name"
4 date: "2023-02-05"
5 output: html_document
6 ---
7
8 ```{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}
9 library(tidyverse)
10 ```
11
12 ## Overview
13
14 This document provides high-level information on whether the minimum legal drinking age
15 (MLDA) makes any difference in the likelihood of consuming alcohol. It includes:
16
17 + Code to read in and clean data
18
19 + Summary Statistics
20
21 + Regression output
22
23 ```{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}|
24 # read in MLDA data and assign MLDA data
25 mlda <- read_csv("mlda.csv")
26 ```
27
28
29
```


Annotations in the image include:

- CODE CHUNKS** (in red) pointing to the YAML header (lines 2-5).
- All R Code Goes into a CODE CHUNK** (in red) pointing to the code blocks (lines 8-10 and 23-26).

Two code blocks are highlighted with red rectangles:

- Lines 8-10: ````{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}`, `library(tidyverse)`, `````
- Lines 23-26: ````{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}|`, `# read in MLDA data and assign MLDA data`, `mlda <- read_csv("mlda.csv")`, `````

# RMarkdown File Structure: Text



```
1 ---
2 title: "Project 2"
3 author: "Your Name"
4 date: "2023-02-05"
5 output: html_document
6 ---
7
8 ```{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}
9 library(tidyverse)
10 ```
11
12 ## Overview
13
14 This document provides high-level information on whether the minimum legal drinking age
15 (MLDA) makes any difference in the likelihood of consuming alcohol. It includes:
16
17 + Code to read in and clean data
18
19 + Summary Statistics
20
21 + Regression output
22
23 ```{r echo=FALSE, eval=TRUE, warning=FALSE, message=FALSE}
24 # read in MLDA data and assign MLDA data
25 mlda <- read_csv("mlda.csv")
26 ```
27
28
29
```

# Rmarkdown: Output

## Project 2

Your Name

2023-02-05

### Overview

This document provides high-level information on whether the minimum legal drinking age (MLDA) makes any difference in the likelihood of consuming alcohol. It includes:

- Code to read in and clean data
- Summary Statistics
- Regression output

# R Programming Basics

```
# object assignment
# (strings, numbers, dataframes, lists, etc.)
this_is_an_object <- "object"
```

```
# this is how you inspect an object
this_is_an_object
```

```
## [1] "object"
```

```
# another assignment
x <- 2^3
```

```
# another inspection
x
```

```
## [1] 8
```

- ▶ Naming is case sensitive
- ▶ Must start with a letter and have no spaces
- ▶ `i_suggest_using_this_format`
- ▶ `ButSomePeopleDoThis`
- ▶ objects will be loaded into your environment on the right!



## Set Up: Working Directory, Package Loading

```
#set working directory  
setwd("~/Documents/workshop-1")  
  
# you will only need to install packages once  
install.packages("tidyverse")  
install.packages("kableExtra")  
install.packages("stargazer")  
install.packages("knitr")  
install.packages("rddrobrust")  
  
# you will do this whenever  
# you need to load in and use tidyverse  
library(tidyverse)  
library(kableExtra)  
library(stargazer)  
library(knitr)  
library(rddrobrust)
```

# Read in and inspect our data

```
mlda <- read_csv("mlda.csv")  
mlda
```

```
## # A tibble: 61,263 x 11  
##   hs_diploma hispanic white black emplo~1 married male days_21 perc_-2 drink-3  
##   <dbl>      <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>  
## 1         0         1     0     0         1         1     1    1601  0.548     0  
## 2         1         1     0     0         1         0     0    1024  1.10      1  
## 3         1         0     0     1         1         0     0    2455  6.58      1  
## 4         0         1     0     0         1         0     1    -590  0          0  
## 5         0         1     0     0         0         1     0    1815  0          0  
## 6         1         0     0     1         1         1     0    2424  0          0  
## 7         1         0     0     1         1         0     0    1116  3.29      1  
## 8         1         0     0     1         1         0     0    2942  0.548     0  
## 9         1         1     0     0         1         0     0    2516  3.29      1  
## 10        1         0     0     1         1         0     0    2516  57.0      1  
## # ... with 61,253 more rows, 1 more variable: student <dbl>, and abbreviated  
## #   variable names 1: employed, 2: perc_days_drink, 3: drinks_alcohol
```

- Use the viewer to view more of the data (click on it or run code below)

```
View(mlda)
```

# Data Dictionary

## Documentation for MLDA\_507

The data file contains data on over 61,000 individuals drawn from the National Health Interview Sample Audit Files from 1997-2007. The data were collected by Professor Carlos Dobkin of UC Santa Cruz, who has done important research on the minimum legal drinking age.

| Variable Name                     | Description  |
|-----------------------------------|--|
| <i>Age and Drinking Variables</i> |  |
| days_21                           | Days from 21 <sup>st</sup> birthday. (positive values indicate age $\geq$ 21; negative values indicate age $<$ 21) |
| drinks alcohol                    | Binary variable = 1 if person reports that he/she drinks alcohol, 0 otherwise                                      |
| perc_days_drink                   | Percent of days on which he/she reports drinking alcohol   |
| <i>Other Variables</i>            |  |
| HS Diploma                        | Binary variable = 1 if person has a high school diploma, 0 otherwise   |
| Hispanic                          | Binary variable = 1 if person is Hispanic, 0 otherwise   |
| Black                             | Binary variable = 1 if person is Black, 0 otherwise  |
| Employed                          | Binary variable = 1 if person is employed, 0 otherwise   |
| Student                           | Binary variable = 1 if person is a student, 0 otherwise  |
| Male                              | Binary variable = 1 if person is a male, 0 otherwise   |
| Married                           | Binary variable = 1 if person is married, 0 otherwise  |

Note: I eliminated all observations with  $|\text{days\_21}| \leq 21$  to eliminate alcohol consumption associated with someone's 21<sup>st</sup> birthday.

## Some quick data exploration

```
mean(mlda$student)
```

```
## [1] 0.1004848
```

```
mean(mlda$drinks_alcohol)
```

```
## [1] 0.6249449
```

# Transform, explore, and visualize

## Dplyr

The most useful tool in the **tidyverse** is **dplyr**. It's a swiss-army knife for data wrangling. **dplyr** has many handy functions that we recommend incorporating into your analysis:

- `select()` extracts columns and returns a tibble.
- `arrange()` changes the ordering of the rows.
- `filter()` picks cases based on their values.
- `mutate()` adds new variables that are functions of existing variables.
- `rename()` easily changes the name of a column(s)
- `summarise()` reduces multiple values down to a single summary.
- `pull()` extracts a single column as a vector.
- `_join()` group of functions that merge two data frames together, includes (`inner_join()`, `left_join()`, `right_join()`, and `full_join()`).

Figure 7: “Source: [https://hbctraining.github.io/Intro-to-R/lessons/tidyverse\\_data\\_wrangling.html](https://hbctraining.github.io/Intro-to-R/lessons/tidyverse_data_wrangling.html)”

# Tidyverse Function Syntax

Table 1: Useful dplyr functions and syntax

| Function                 | Syntax   |
|--------------------------|--|
| <code>select()</code>    | <code>select(df, var1, var2, ...)</code>           |
| <code>mutate()</code>    | <code>mutate(df, new_var = old_var + 5)</code>     |
| <code>filter()</code>    | <code>filter(df, var1 == value)</code>             |
| <code>rename()</code>    | <code>rename(df, new_name = old_name)</code>       |
| <code>summarise()</code> | <code>summarise(df, mean_var1 = mean(var1))</code> |
| <code>if_else()</code>   | <code>if_else(condition, true, false)</code>       |

# Transform and explore

```
# add a new variable for age in years and a heavy drinker variable if they drink more than 75% of days
mlda <- mutate(mlda,
               age_years = 21 + days_21/365,
               heavy_drinker = if_else(perc_days_drink > 75, 1, 0))

# filter to just underage drinkers
underage <- filter(mlda, days_21 < 0 & drinks_alcohol == 1)

# demographic characteristics of underage drinkers
summ_stats_underage <- summarise(underage,
                                  min_age = min(age_years),
                                  mean_age = mean(age_years),
                                  median_age = median(age_years),
                                  mean_heavy_drinker = mean(heavy_drinker),
                                  mean_white = mean(white),
                                  mean_black = mean(black),
                                  mean_hispanic = mean(hispanic))

summ_stats_underage
```

```
## # A tibble: 1 x 7
##   min_age mean_age median_age mean_heavy_drinker mean_white mean_black mean_hi-1
##   <dbl>    <dbl>    <dbl>          <dbl>        <dbl>    <dbl>    <dbl>
## 1    17.7    19.7    19.8            0.0166      0.661    0.0947    0.203
## # ... with abbreviated variable name 1: mean_hispanic
```

# The Pipe

- ▶ The pipe operator `%>%` takes output from one function and 'pipes' it into another function

```
x <- paste("A", "String")  
print(x)  
  
print(paste("A", "String"))  
  
paste("A", "String") %>%  
  print(.)
```



## Use the pipe operator to combine all of these into one 'dplyr chain'

- The period denotes where the previous output should be the argument in the new function

```
summ_stats <- mutate(mlda,
                      age_years = 21 + days_21/365,
                      heavy_drinker = if_else(perc_days_drink > 75, 1, 0)) %>%
  filter(., days_21 < 0 & drinks_alcohol == 1) %>%
  summarise(., min_age = min(age_years),
            mean_age = mean(age_years),
            median_age = median(age_years),
            mean_perc_days_drink = mean(perc_days_drink),
            median_perc_days_drink = median(perc_days_drink))

summ_stats
```

```
## # A tibble: 1 x 5
##   min_age mean_age median_age mean_perc_days_drink median_perc_days_drink
##   <dbl>    <dbl>    <dbl>          <dbl>          <dbl>
## 1    17.7    19.7    19.8            13.3            6.58
```

# More Summary Statistics

```
# now let's look at summary stats of heavy drinkers vs non heavy drinkers:
```

```
# demographic characteristics of heavy drinkers vs non-heavy drinkers
```

```
summ_stats_heavy <- mlda %>%  
  filter(drinks_alcohol ==1) %>%  
  group_by(heavy_drinker) %>%  
  summarise(min_age = min(age_years),  
            mean_age = mean(age_years),  
            median_age = median(age_years),  
            mean_student = mean(student),  
            n = n())  
summ_stats_heavy
```

```
## # A tibble: 2 x 6
```

```
##   heavy_drinker min_age mean_age median_age mean_student      n  
##         <dbl>   <dbl>   <dbl>     <dbl>     <dbl> <int>  
## 1           0    17.8     24.7      24.9    0.0874 37322  
## 2           1    17.7     25.3      25.7    0.0425  964
```

## Try yourself

- ▶ Create a variable that denotes someone as an underage drinker (they are less than 21 years old and drink alcohol)
- ▶ Use the skeleton code below to calculate the share of underage drinkers that are a student, married, or male

```
summ_stats2 <- mutate(mlda, underage_drinker = if_else()) %>%  
  filter() %>%  
  summarise()
```

# Export as a table

- ▶ use kable to export as a table
- ▶ can make aesthetic changes to the table, add labels, etc.

```
library(kableExtra)


kable(summ_stats_underage,
      digits=2, caption="Drinking Patterns among Underage Drinkers",
      col.names = c("Min Age", "Mean Age", "Med Age", "Heavy Drinker",
                    "White", "Black", "Hispanic"))
```

Table 2: Drinking Patterns among Underage Drinkers

| Min Age | Mean Age | Med Age | Heavy Drinker | White | Black | Hispanic |
|---------|----------|---------|---------------|-------|-------|----------|
| 17.7    | 19.67    | 19.75   | 0.02          | 0.66  | 0.09  | 0.2      |

## Visual: age distribution of drinkers vs non-drinkers?

```
viz <- mlda %>%  
  mutate(drinks_alcohol_string = if_else(drinks_alcohol == 1, "Drinks", "Does Not Drink")) %>%  
  ggplot(aes(x=drinks_alcohol_string, y=age_years)) +  
  geom_boxplot()  
viz
```



# Run a Model

- ▶ Use a linear probability model to predict the effect of age in years on the likelihood of drinking alcohol
- ▶ we can use `lm()`

```
# general form  
lpm1 <- lm(formula = y ~ x_1 + x_2 + ... x_n, data = df)
```

- ▶ `y` is the dependent variable and the `x` variables are the independent variables

# Model our data

```
# lpm of years in age on likelihood of drinking alcohol
lpm1 <- lm(formula = drinks_alcohol ~ age_years, data = mlda )
summary(lpm1)

##
## Call:
## lm(formula = drinks_alcohol ~ age_years, data = mlda)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.7365 -0.5766  0.3128  0.3852  0.4922
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) 0.1999271  0.0140917   14.19  <2e-16 ***
## age_years    0.0173927  0.0005712   30.45  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.4805 on 61261 degrees of freedom
## Multiple R-squared:  0.01491,    Adjusted R-squared:  0.01489
## F-statistic: 927.3 on 1 and 61261 DF,  p-value: < 2.2e-16
```

# Exercise

- ▶ Now, add an age squared and age cubed variable to your dataset and rerun the model

```
mlda2 <- mlda %>%  
  mutate()  
  
lpm2 <- lm(formula = , data = )
```

- ▶ Then add additional demographic controls to your model and rerun the model

```
lpm3 <- lm(formula = drinks_alcohol ~ , data =)
```

- ▶ inspect your results

```
summary(lpm2)  
summary(lpm3)
```



# Use Stargazer to output your results

- ▶ Stargazer is an R package that creates LATEX code, HTML code and ASCII text for well-formatted regression tables, with multiple models side-by-side, and summary stats, etc.; makes changing models and updating tables very easy

```
library(stargazer)
stargazer(lpm1, lpm2, type = "html",
          dep.var.labels = "Probability of Drinking", header=F)
```

Table 3:

|                         | <i>Dependent variable:</i> |                            |
|-------------------------|----------------------------|----------------------------|
|                         | Probability of Drinking    |                            |
|                         | (1)                        | (2)                        |
| age_years               | 0.017***<br>(0.001)        | 1.697***<br>(0.104)        |
| age_sq                  |                            | -0.065***<br>(0.004)       |
| age_cu                  |                            | 0.001***<br>(0.0001)       |
| Constant                | 0.200***<br>(0.014)        | -13.996***<br>(0.817)      |
| Observations            | 61,263                     | 61,263                     |
| R <sup>2</sup>          | 0.015                      | 0.031                      |
| Adjusted R <sup>2</sup> | 0.015                      | 0.031                      |
| Residual Std. Error     | 0.481 (df = 61261)         | 0.476 (df = 61259)         |
| F Statistic             | 927.281*** (df = 1; 61261) | 661.294*** (df = 3; 61259) |

Note:

\* p<0.1; \*\* p<0.05; \*\*\* p<0.01

# Output model results

Table 4:

|                         | <i>Dependent variable:</i>            |                            |                            |
|-------------------------|---------------------------------------|----------------------------|----------------------------|
|                         | Probability of Drinking with Controls |                            |                            |
|                         | (1)                                   | (2)                        | (3)                        |
| age_years               | 0.017***<br>(0.001)                   | 1.697***<br>(0.104)        | 1.710***<br>(0.102)        |
| age_sq                  |                                       | -0.065***<br>(0.004)       | -0.066***<br>(0.004)       |
| age_cu                  |                                       | 0.001***<br>(0.0001)       | 0.001***<br>(0.0001)       |
| student                 |                                       |                            | -0.025***<br>(0.007)       |
| male                    |                                       |                            | 0.179***<br>(0.004)        |
| Constant                | 0.200***<br>(0.014)                   | -13.996***<br>(0.817)      | -14.167***<br>(0.803)      |
| Observations            | 61,263                                | 61,263                     | 61,263                     |
| R <sup>2</sup>          | 0.015                                 | 0.031                      | 0.065                      |
| Adjusted R <sup>2</sup> | 0.015                                 | 0.031                      | 0.065                      |
| Residual Std. Error     | 0.481 (df = 61261)                    | 0.476 (df = 61259)         | 0.468 (df = 61257)         |
| F Statistic             | 927.281*** (df = 1; 61261)            | 661.294*** (df = 3; 61259) | 855.417*** (df = 5; 61257) |

Note:


\* p<0.1; \*\* p<0.05; \*\*\* p<0.01

# Visualize the discontinuity

```
library(rdrobust)
rdplot(mlda$drinks_alcohol,mlda$age_years,c=21)
```

```
## [1] "Mass points detected in the running variable."
```

RD Plot



Wrap up

# Today's workshop

- ▶ We covered a lot!
  - ▶ reproducible research practices
  - ▶ R Markdown
  - ▶ the tidyverse
  - ▶ data transformations
  - ▶ regression
  - ▶ data viz
- ▶ Future events
  - ▶ Workshop from Angela (Maps!)
  - ▶ lightning talks
  - ▶ speaker series
- ▶ Email us with ideas
  - ▶ [kk9870@princeton.edu](mailto:kk9870@princeton.edu)
  - ▶ [al49@princeton.edu](mailto:al49@princeton.edu)

## Citations

## Citations

Russo, Francesco & Righelli, Dario & Angelini, Claudia. (2016). Advantages and Limits in the Adoption of Reproducible Research and R-Tools for the Analysis of Omic Data. Lecture Notes in Computer Science. 9874. 245-258.  
[10.1007/978-3-319-44332-4\\_19](https://doi.org/10.1007/978-3-319-44332-4_19).