

Homework 3-P. Perceptron


Double Click here to edit this cell

- Name: 김동규
- Student ID: 201800615
- Submission date: 2023/05/12

Do this homework on anaconda

Homework Purpose: Learn SGD and Perceptron

Perceptron model



The net input of the perceptron including the bias

$$z = \sum_{i=1}^m w_i x_i + b = \sum_{i=0}^m w_i x_i$$

Remark:

$$\sum_{i=1}^m w_i x_i + b = b + w_1 x_1 + \cdots + w_m x_m = (w_0, w_1, \cdots, w_m) \cdot (1, x_1, \cdots, x_m)$$

where $w_0 = b$

Vector form of the net input


$$z = \mathbf{w}^T \mathbf{x} + b$$

The perceptron fires if and only if the net input is non-negative


$$z = \mathbf{w}^T \mathbf{x} + b \geq 0$$

Perceptron as a Binary Classifier

- A linear classifier uses lines to classify data points—any object on one side of the line is part of one class and any object on the other side is part of the other class.
- A successful linear classifier could use H_1 or H_2 to discriminate between the two classes, whereas H_3 would be a poor decision boundary.
- H_1 or H_2 are called a separating hyperplane




Geometric Interpretation of a separating hyperplane



When a data is misclassified, we move \mathbf{w} to a certain direction

- Which direction? How much should we move? Figure it out



Remark: gradient_descent.py, linear_algebra.py must be in the folder having this notebook file

```
In [1]: # run this cell
from gradient_descent import *
from linear_algebra import *
```

Problem 1 (30 pts)

- We want to implement a simple neural network called `Perceptron`.
- We will use `minimize_stochastic` to optimize the network

The code of SGD

```
def in_random_order(data):
    """generator that returns the elements of data in random order"""
    indexes = [i for i, _ in enumerate(data)] # create a list of
    indexes                                     # indexes
    random.shuffle(indexes)                    # shuffle them
    for i in indexes:                         # return the data in that
    order                                     # order
        yield data[i]

def minimize_stochastic(target_fn, gradient_fn, x, y, theta_0,
alpha_0=0.01):

    data = list(zip(x, y))
    theta = theta_0
    data = list(zip(x, y))
    theta = theta_0 # initial guess
    alpha = alpha_0 # initial step size
    min_theta, min_value = None, float("inf") # the minimum so far
    iterations_with_no_improvement = 0

    # if we ever go 100 iterations with no improvement, stop
    while iterations_with_no_improvement < 100:
        count += 1
```

```

value = sum( target_fn(x_i, y_i, theta) for x_i, y_i in data )

if value < min_value:
    # if we've found a new minimum, remember it
    # and go back to the original step size
    min_theta, min_value = theta, value
    iterations_with_no_improvement = 0
    alpha = alpha_0
else:
    # otherwise we're not improving, so try shrinking the step
size
    iterations_with_no_improvement += 1
    alpha *= 0.9

    # and take a gradient step for each of the data points
    for x_i, y_i in in_random_order(data):
        gradient_i = gradient_fn(x_i, y_i, theta)
        theta = vector_subtract(theta, scalar_multiply(alpha,
gradient_i))

min_theta = theta

return min_theta

```

You should define an error function and a gradient function for perceptron:

Remark: ONE or TWO lines for an error function and a gradient function are enough. If the number of lines > 2, you get a penalty

Define your error function here:

```

In [2]: # YOUR CODE MUST BE HERE

def perceptron_error(x, y, w):
    return np.dot(x[1:], w[1:])+w[0]

```

Define your gradient function here:

```

In [3]: # YOUR CODE MUST BE HERE

def perceptron_error_gradient(x, y, w):
    update=np.array([0.01])*(y-np.where(perceptron_error(x,y,w)>0,1,-1))
    w[1:3]+=update*x[1:3]
    w[0]+=update
    return w[:3]

```

Define a function to shade a decision boundary

- The region of $w_1 \cdot x_1 + w_2 \cdot x_2 + w_0 \geq 0$ are shaded as red; otherwise shaded as blue
- `x_min, x_max, y_min, y_max` defines a shading area

- The resulting shading and plotting must be very similar as shown in the given answer images

```
In [4]: # YOUR CODE MUST BE HERE

def shade_decision_region(X, y, w, x_min, x_max, y_min, y_max):
    xx, yy = np.meshgrid(np.arange(x_min, x_max, 0.001), np.arange(y_min, y_max, 0.001))
    Z = w[1] * (xx) + w[2]*(yy) +w[0] < 0
    i=0
    for x_i in X:
        if(perceptron_error(x_i,y[3],w[:3])>=0):
            plt.scatter(X[i][1], X[i][2], c='red')
        else:
            plt.scatter(X[i][1], X[i][2], c='blue')
        i+=1
    plt.contourf(xx, yy, Z, cmap=plt.cm.RdBu, alpha=0.8)
    plt.xlim(x_min, x_max)
    plt.ylim(y_min, y_max)
    plt.show()
```

Test Case 1: OR

```
In [5]: # DO NOT EDIT THIS CELL
# RUN THIS CELL


import matplotlib.pyplot as plt
import numpy as np

X = [[1,0,0], [1,0,1], [1,1,0], [1,1,1]]
y = [-1, 1, 1, 1]


random.seed(2)
theta = [1, random.random(),random.random()]

w = minimize_stochastic(perceptron_error,
                        perceptron_error_gradient,
                        X,
                        y,
                        theta,
                        0.1)

shade_decision_region(X, y, w, x_min=-1, x_max=2, y_min=-1, y_max=2)
```



Your output must be similar to the following:



Test Case 2: AND

```
In [6]: # DO NOT EDIT THIS CELL
# RUN THIS CELL

import matplotlib.pyplot as plt
import numpy as np

X = [[1,0,0], [1,0,1], [1,1,0], [1,1,1]]
y = [-1, -1, -1, 1]

# choose random value to start
random.seed(2)
theta = [1, random.random(), random.random()]


w = minimize_stochastic(perceptron_error,
```

```


        perceptron_error_gradient,
        X,
        y,
        theta,
        0.1)

shade_decision_region(X, y, w, x_min=-1, x_max=2, y_min=-1, y_max=2)

```



Your output must be similar to the following:



Test Case 3: XOR

```

In [7]: # DO NOT EDIT THIS CELL
        # RUN THIS CELL

import matplotlib.pyplot as plt
import numpy as np

X = [[1,0,0], [1,0,1], [1,1,0], [1,1,1]]

```

```


y = [-1, 1, 1, -1]

# choose random value to start
random.seed(2)
theta = [1, random.random(), random.random()]


w = minimize_stochastic(perceptron_error,
                        perceptron_error_gradient,
                        X,
                        y,
                        theta,
                        0.1)

shade_decision_region(X, y, w, x_min=-1, x_max=2, y_min=-1, y_max=2)

```



Your output must be similar to the following:



Test Case 4: Right


```

In [8]: # DO NOT EDIT THIS CELL
# RUN THIS CELL

import matplotlib.pyplot as plt
import numpy as np


X = [[1,0,0], [1,0,1], [1,1,0], [1,1,1]]
y = [-1, -1, 1, 1]

# choose random value to start
random.seed(2)
theta = [1, random.random(), random.random()]


w = minimize_stochastic(perceptron_error,
                        perceptron_error_gradient,
                        X,
                        y,
                        theta,
                        0.1)

shade_decision_region(X, y, w, x_min=-1, x_max=2, y_min=-1, y_max=2)

```



Your output must be similar to the following:



Test Case 5: Upper

```
In [9]: # DO NOT EDIT THIS CELL
# RUN THIS CELL


import matplotlib.pyplot as plt
import numpy as np

X = [[1,0,0], [1,0,1], [1,1,0], [1,1,1]]
y = [-1, 1, -1, 1]


# choose random value to start
random.seed(2)
theta = [1, random.random(), random.random()]

w = minimize_stochastic(perceptron_error,
                        perceptron_error_gradient,
                        X,
                        y,
                        theta,
                        0.1)

shade_decision_region(X, y, w, x_min=-1, x_max=2, y_min=-1, y_max=2)
```



Your output must be similar to the following:



Test Case 6: Two Clusters

```
In [10]: # DO NOT EDIT THIS CELL
# RUN THIS CELL

import matplotlib.pyplot as plt
from sklearn.datasets import make_blobs
import random

Xs, ys = make_blobs(n_samples=1000, n_features=2, centers=2, cluster_std=0.5, random_state=42)
Xs1 = np.hstack((np.ones((Xs.shape[0],1)), Xs))

# choose random value to start
random.seed(2)
theta = [1, random.random(), random.random()]
```


```

X = Xs1.tolist()
y = (np.where(ys == 1, 1, -1)).tolist()


w = minimize_stochastic(perceptron_error,
                        perceptron_error_gradient,
                        X,
                        y,
                        theta,
                        0.1)

shade_decision_region(X, y, w, x_min=-3, x_max=7, y_min=-3, y_max=7)

```



Your output must be similar to the following:



Test Case 7: Two Big Clusters

```

In [ ]: # DO NOT EDIT THIS CELL
        # RUN THIS CELL

```

```

import matplotlib.pyplot as plt
from sklearn.datasets import make_blobs
import random
import time

Xs, ys = make_blobs(n_samples=100000, n_features=2, centers=2, cluster_std=0.5, random_state=1)
Xs1 = np.hstack((np.ones((Xs.shape[0],1)), Xs))

# choose random value to start
random.seed(2)
theta = [1, random.random(), random.random()]

X = Xs1.tolist()
y = (np.where(ys == 1, 1, -1)).tolist()

start = time.time()
w = minimize_stochastic(perceptron_error,
                        perceptron_error_gradient,
                        X,
                        y,
                        theta,
                        0.1)


end = time.time()

shade_decision_region(X, y, w, x_min=-3, x_max=7, y_min=-3, y_max=7)

lapse = end - start
total = 10
weight = 1.5
grace = 100.0
my_point = int(total / (weight ** (lapse // grace)))
print(f'Total time taken : {lapse} seconds')
print(f'My point is {my_point}')

```

Your output must be similar to the following:



```

Total time taken : 71.98880887031555 seconds
My point is 10

```

Ethics:

If you cheat, you will get negative of the total points. If the homework total is 22 and you cheat, you get -22.

What to submit

- Run **all cells** after restarting the kernel
- Goto "File -> Print Preview"
- Print the page as pdf
- Pdf file name must be in a form of: homework_3_홍길동_202200001.pdf
- Submit the pdf file in google classroom
- No late homeworks will be accepted
- Your homework will be graded on the basis of correctness, performance, and programming skills