

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

### SECTION 1. IDENTIFICATION

Product name : PETROGLIDE™/MC 100

Synonyms : PETROGLIDE PREMIUM SAW GUIDE OIL 100

Product code : GLID100CBE, GLID100IBC, GLID100DRM, GLID100DCT, GLID100, GLID100BLK

#### Manufacturer or supplier's details

Petro-Canada America Lubricants LLC  
2828 N. Harwood St., Suite 1300  
Dallas TX 75201  
United States  
Telephone : 1-214-871-3555

#### Emergency telephone number

Emergency telephone number : CHEMTREC: 1-800-424-9300;  
Poison Control Centre: Consult local telephone directory for emergency number(s).

#### Recommended use of the chemical and restrictions on use

Recommended use : Petroglide oils are designed to lubricate saw blades of multi-blade, gang saws and edgers.

Prepared by : Product Safety: +1 905-491-0565

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitisation : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : May cause an allergic skin reaction.

Precautionary statements : **Prevention:**  
Avoid breathing mist or vapours.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves.

**Response:**  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/ attention.

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

Wash contaminated clothing before reuse.

### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

| Chemical name   | CAS-No.    | Concentration (% w/w) |
|---|------------|-----------------------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified | 72623-87-1 | 50 - 70               |
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified               | 64742-54-7 | 50 - 70               |
| Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified                   | 64742-70-7 | 30 - 50               |
| Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified                           | 64742-62-7 | 30 - 50               |
| 2,5-bis(octyldithio)-1,3,4-thiadiazole  | 13539-13-4 | 0.1 - 1               |

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Wash clothing before reuse.

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

|   |   |
|---|---|
|   | Seek medical advice.  |
| In case of eye contact                                      | : Remove contact lenses.<br>Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.<br>Obtain medical attention.   |
| If swallowed  | : Rinse mouth with water.<br>DO NOT induce vomiting unless directed to do so by a physician or poison control center.<br>Never give anything by mouth to an unconscious person.<br>Seek medical advice. |
| Most important symptoms and effects, both acute and delayed | : First aider needs to protect himself.<br>May cause an allergic skin reaction.   |
| Notes to physician  | : Treat symptomatically.  |

### SECTION 5. FIREFIGHTING MEASURES

|                                      |  |
|--------------------------------------|--|
| Suitable extinguishing media         | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  |
| Unsuitable extinguishing media       | : No information available.  |
| Specific hazards during firefighting | : Cool closed containers exposed to fire with water spray.   |
| Hazardous combustion products        | : Carbon oxides (CO, CO <sub>2</sub> ), sulphur oxides (SO <sub>x</sub> ), sulphur compounds (H <sub>2</sub> S), silicon oxides (SiO <sub>x</sub> ), hydrocarbons, metal oxides, alkyl mercaptans, sulfides, aldehydes, smoke and irritating vapours as products of incomplete combustion. |
| Further information                  | : Prevent fire extinguishing water from contaminating surface water or the ground water system.  |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

|   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Ensure adequate ventilation.<br>Evacuate personnel to safe areas.<br>Material can create slippery conditions.<br>Mark the contaminated area with signs and prevent access to unauthorized personnel.<br>Only qualified personnel equipped with suitable protective equipment may intervene. |
| Environmental precautions   | : Do not allow uncontrolled discharge of product into the environment.<br>If the product contaminates rivers and lakes or drains inform respective authorities.   |

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : None known.

Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.

Conditions for safe storage : Store in original container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

| Components  | CAS-No.    | Value type<br>(Form of exposure)   | Control parameters /<br>Permissible concentration | Basis     |
|---|------------|------------------------------------|---|-----------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified | 72623-87-1 | TWA (Mist)                         | 5 mg/m3   | OSHA Z-1  |
|   |            | TWA (Inhalable particulate matter) | 5 mg/m3   | ACGIH     |
|   |            | TWA (Mist)                         | 5 mg/m3   | OSHA P0   |
|   |            | TWA (Mist)                         | 5 mg/m3   | NIOSH REL |
|   |            | ST (Mist)                          | 10 mg/m3  | NIOSH REL |
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified               | 64742-54-7 | TWA (Mist)                         | 5 mg/m3   | OSHA Z-1  |
|   |            | TWA (Inhalable particulate)        | 5 mg/m3   | ACGIH     |

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

|   |            |   |          |           |
|---|------------|---|----------|-----------|
|   |            | matter)                                     |          |           |
|   |            | TWA (Mist)                                  | 5 mg/m3  | OSHA P0   |
|   |            | TWA (Mist)                                  | 5 mg/m3  | NIOSH REL |
|   |            | ST (Mist)                                   | 10 mg/m3 | NIOSH REL |
| Paraffin oils (petroleum),<br>catalytic dewaxed heavy;<br>Baseoil — unspecified | 64742-70-7 | TWA (Mist)                                  | 5 mg/m3  | OSHA Z-1  |
|   |            | TWA (Mist)                                  | 5 mg/m3  | OSHA P0   |
|   |            | TWA (Mist)                                  | 5 mg/m3  | NIOSH REL |
|   |            | ST (Mist)                                   | 10 mg/m3 | NIOSH REL |
| Residual oils (petroleum),<br>solvent-dewaxed; Baseoil —<br>unspecified         | 64742-62-7 | TWA (Mist)                                  | 5 mg/m3  | OSHA Z-1  |
|   |            | TWA<br>(Inhalable<br>particulate<br>matter) | 5 mg/m3  | ACGIH     |
|   |            | TWA (Mist)                                  | 5 mg/m3  | OSHA P0   |
|   |            | TWA (Mist)                                  | 5 mg/m3  | NIOSH REL |
|   |            | ST (Mist)                                   | 10 mg/m3 | NIOSH REL |

**Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Personal protective equipment

**Respiratory protection** : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Filter type** : organic vapour filter

### Hand protection

**Material** : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

**Remarks** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Protective measures** : Wash contaminated clothing before re-use.

**Hygiene measures** : Remove and wash contaminated clothing and gloves, including the inside, before re-use.  
Wash face, hands and any exposed skin thoroughly after handling.

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|  |  |
|--|--|
| Appearance                                       | : viscous liquid   |
| Colour   | : dark amber   |
| Odour  | : Mild petroleum oil like.   |
| Odour Threshold                                  | : No data available  |
| pH   | : No data available  |
| Pour point                                       | : -36 °C (-33 °F)  |
| Boiling point/boiling range                      | : No data available  |
| Flash point                                      | : 277 °C (531 °F)<br>Method: Cleveland open cup                                      |
| Fire Point                                       | : No data available  |
| Evaporation rate                                 | : No data available  |
| Flammability                                     | : Remarks: Low fire hazard. This material must be heated before ignition will occur. |
| Auto-Ignition Temperature                        | : No data available  |
| Upper explosion limit / Upper flammability limit | : No data available  |
| Lower explosion limit / Lower flammability limit | : No data available  |
| Vapour pressure                                  | : No data available  |
| Relative vapour density                          | : No data available  |
| Relative density                                 | : No data available  |
| Density  | : 0.8593 kg/l (59 °F / 15 °C)  |
| Solubility(ies)<br>Water solubility              | : insoluble  |
| Partition coefficient: n-octanol/water           | : No data available  |
| Viscosity<br>Viscosity, kinematic                | : 108.1 cSt (104 °F / 40 °C)<br>14.1 cSt (212 °F / 100 °C)                           |
| Explosive properties                             | : Do not pressurize, cut, weld, braze, solder, drill, grind or                       |

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

expose containers to heat or sources of ignition.

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |   |
|------------------------------------|---|---|
| Reactivity                         | : | No dangerous reaction known under conditions of normal use.   |
| Chemical stability                 | : | Stable under normal conditions.   |
| Possibility of hazardous reactions | : | Hazardous polymerisation does not occur.<br>Stable under normal conditions.   |
| Conditions to avoid                | : | No data available   |
| Incompatible materials             | : | Reactive with oxidising agents, acids, alkalis and reducing agents.   |
| Hazardous decomposition products   | : | May release COx, SOx, H2S, sulfides, hydrocarbons, alkyl mercaptans, formaldehyde, methacrylate monomers, asphyxiants, smoke and irritating vapours when heated to decomposition. |

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact  
Ingestion  
Inhalation  
Skin contact

#### Acute toxicity

Not classified due to lack of data.

#### Product:

|                           |   |   |
|---------------------------|---|---|
| Acute oral toxicity       | : | Remarks: No data available  |
| Acute inhalation toxicity | : | Assessment: The substance or mixture has no acute inhalation toxicity<br>Remarks: No data available |
| Acute dermal toxicity     | : | Assessment: The substance or mixture has no acute dermal toxicity<br>Remarks: No data available     |

#### Components:

#### **Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified:**

|                           |   |  |
|---------------------------|---|--|
| Acute oral toxicity       | : | LD50 (Rat): > 5,000 mg/kg,   |
| Acute inhalation toxicity | : | LC50 (Rat): > 5.2 mg/l<br>Exposure time: 4 h<br>Test atmosphere: dust/mist |
| Acute dermal toxicity     | : | LD50 (Rabbit): > 2,000 mg/kg,  |

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

### **Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

### **Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg,

### **Skin corrosion/irritation**

Not classified due to lack of data.

### **Product:**

Remarks : No data available

### **Serious eye damage/eye irritation**

Not classified due to lack of data.

### **Product:**

Remarks : No data available

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified due to lack of data.

#### **Germ cell mutagenicity**

Not classified due to lack of data.

#### **Carcinogenicity**

Not classified due to lack of data.

#### **Reproductive toxicity**

Not classified due to lack of data.

#### **STOT - single exposure**

Not classified due to lack of data.

#### **STOT - repeated exposure**

Not classified due to lack of data.

#### **Aspiration toxicity**

Not classified due to lack of data.



# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413

Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16



### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

##### Components:

##### **Residual oils (petroleum), solvent-dewaxed; Baseoil — unspecified :**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): > 100 mg/l  
Exposure time: 72 h

#### Persistence and degradability

##### Product:

Biodegradability : Remarks: No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413

Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16



### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### National Regulations

##### 49 CFR

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

#### California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). The chemicals include:

1-chloro-2,3-epoxypropane 106-89-8

#### The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

### SECTION 16. OTHER INFORMATION

#### Further information

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413




Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

### NFPA 704:



### HMIS® IV:

|                 |   |
|-----------------|---|
| HEALTH          | 2 |
| FLAMMABILITY    | 1 |
| PHYSICAL HAZARD | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

|                 |   |
|-----------------|---|
| ACGIH           | : USA. ACGIH Threshold Limit Values (TLV)   |
| NIOSH REL       | : USA. NIOSH Recommended Exposure Limits  |
| OSHA P0         | : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)                        |
| OSHA Z-1        | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants          |
| ACGIH / TWA     | : 8-hour, time-weighted average   |
| NIOSH REL / TWA | : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| NIOSH REL / ST  | : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday    |
| OSHA P0 / TWA   | : 8-hour time weighted average  |
| OSHA Z-1 / TWA  | : 8-hour time weighted average  |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect

# SAFETY DATA SHEET

## PETROGLIDE™/MC 100

000003000413



Version 4.1

Revision Date 2024/01/16

Print Date 2024/01/16

Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS : Internet: [www.petrocanadalubricants.com/sds](http://www.petrocanadalubricants.com/sds)  
United States, telephone: 1-800-268-5850; fax: 1-800-201-6285  
For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2024/01/16  
Date format : yyyy/mm/dd

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN