according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

SECTION 1. IDENTIFICATION

Product name PC HEAVY DUTY SUSPENSION FLUID

Product code HDSFBLK, HDSFDCT, HDSFIBC, HDSF

Manufacturer or supplier's details

Petro-Canada America Lubricants LLC

2323 Victory Ave., Suite 1400

Dallas TX 75219 **United States**

1-214-871-3555 Telephone:

Emergency telephone number

Emergency telephone : CHEMTREC: 1-800-424-9300;

Poison Control Centre: Consult local telephone directory for number

emergency number(s).

Recommended use of the chemical and restrictions on use

Recommended use This product is a blend of Friction Modifier additive (6 % vol.)

> and SAE 5W-40 Heavy Duty Diesel Engine Oil (94 % vol.), as specified by Komatsu, specifically for use in Komatsu heavy equipment suspension systems of electric drive dump trucks.

Product Safety: +1 905-491-0565 Prepared by

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

Other hazards

None known.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s)

required.

IARC No component of this product present at levels greater than

or equal to 0.1% is identified as probable, possible or

confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lubricating oils (petroleum), C15-30,	72623-86-0	50 - 70
hydrotreated neutral oil-based;		
Baseoil — unspecified		
Distillates (petroleum), hydrotreated	64742-54-7	50 - 70
heavy paraffinic; Baseoil —		
unspecified		
Dec-1-ene, oligomers, hydrogenated	68037-01-4	5 - 10
Lubricating oils (petroleum), C20-50,	72623-87-1	5 - 10
hydrotreated neutral oil-based;		
Baseoil — unspecified		
Distillates (petroleum), solvent-	64742-65-0	1 - 5
dewaxed heavy paraffinic; Baseoil —		
unspecified		
Phenol, tetrapropylene-, sulfurized,	122384-87-6	1 - 5
carbonates, calcium salts, overbased		
bis(nonylphenyl)amine	36878-20-3	1 - 5
Distillates (petroleum), solvent-	64742-56-9	1 - 5
dewaxed light paraffinic; Baseoil —		
unspecified		
Zinc alkyldithiophosphate	113706-15-3	1 - 5

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and delayed

First aider needs to protect himself.

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

No information available.

Specific hazards during

firefighting

Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), sulphur compounds (H2S), zinc oxides (ZnOx), metal oxides, hydrocarbons, smoke and irritating vapours as products of incomplete

combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow uncontrolled discharge of product into the

environment.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation.

Osstantilla assault and a discontinuous

Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

Advice on protection against :

fire and explosion

None known.

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct

sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters/ Permissible concentration	Basis
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil — unspecified	72623-86-0	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil — unspecified	72623-87-1	TWA (Mist)	5 mg/m3	OSHA Z-1

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	ACGIH
		(Inhalable		
		particulate		
		matter)		
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Distillates (petroleum), solvent- dewaxed light paraffinic; Baseoil — unspecified	64742-56-9	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

concentration and amount of dangerous substances, and to

the specific work-place.

Protective measures : Wash contaminated clothing before re-use.

Hygiene measures : Remove and wash contaminated clothing and gloves,

including the inside, before re-use.

Wash face, hands and any exposed skin thoroughly after

handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Colour : amber

Odour : Mild petroleum oil like.

Odour Threshold : No data available

pH : No data available

Pour point : -42 °C (-44 °F)

Boiling point/boiling range : No data available

Flash point : 219 °C (426 °F)

Method: Cleveland open cup

Fire Point : No data available

Evaporation rate : No data available

Flammability : Remarks: Low fire hazard. This material must be heated

before ignition will occur.

Auto-Ignition Temperature : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.8600 kg/l (59 °F / 15 °C)

Solubility(ies)

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 92.9 cSt (104 °F / 40 °C)

14.8 cSt (212 °F / 100 °C)

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerisation does not occur.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents, acids and alkalis.

Hazardous decomposition

products

May release COx, H2S, methacrylate monomers, smoke and

irritating vapours when heated to decomposition.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Eye contact Inhalation Ingestion

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

Components:

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil —

unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil —

unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg,

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Remarks: No data available Toxicity to microorganisms

Persistence and degradability

Product:

: Remarks: No data available Biodegradability

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

California Prop. 65 This product contains chemical(s) known to the State of

California to cause cancer and/or to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. The chemicals include:

benzene 71-43-2

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the


TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA PO : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

For Copy of SDS : Internet: www.petrocanadalubricants.com/sds

United States, telephone: 1-800-268-5850; fax: 1-800-201-

6285

For Product Safety Information: 1 905-491-0565

Prepared by : Product Safety: +1 905-491-0565

Revision Date : 2025/06/19 Date format : yyyy/mm/dd

Internet: www.petrocanadalubricants.com/sds Trademarks are owned or used under license.

according to the OSHA Hazard Communication Standard



PC HEAVY DUTY SUSPENSION FLUID

000003008245

Version 4.0 Revision Date 2025/06/19 Print Date 2025/06/19

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN