

SUNISOTM 4SA

WORLD-LEADING REFRIGERATION LUBRICANTS



Introduction

Suniso[®] 4SA is a highly refined naphthenic refrigeration lubricant designed to lubricate refrigeration compressors using ammonia (R-717) refrigerant. Suniso 4SA offers low wax content and a low pour point delivering excellent low temperature performance with no wax deposits to plug the system.

Application

Suniso 4SA is designed for use in commercial and industrial refrigeration systems charged with ammonia (R-717) refrigerant. Suniso 4SA is ideally suited for low-temperature systems where evaporator temperatures are as low as -36°C/-33°F. Suniso 4SA is based on naphthenic base oils which provide mild seal swell.

FEATURES & BENEFITS



LOW WAX CONTENT & LOW POUR POINT

Excellent low-temperature performance with no wax deposits to plug the system.



EXCELLENT CHEMICAL STABILITY

Does not react with ammonia refrigerant or metal components in the system, extending machine service life and reducing maintenance costs.



HIGH THERMAL STABILITY

Cleaner operation of the compressor with minimal deposits and failures due to valve sticking.



SEAL COMPATIBILITY

Suniso 4SA is based on naphthenic base oils which provide mild seal swell.

Typical Performance Data

Property	ASTM Method	Suniso 4SA
Density @ 15°C, kg/L	D4052	0.91
Viscosity @ 40°C, cSt	D445	56
Viscosity @ 100°C, cSt	D445	6.4
Flash Point, °C / °F	D92	180 / 356
Pour Point, °C / °F	D5950	-39 / -38
Minimum Evaporator Temperature °C / °F		-36 / -33

The values quoted above are typical of normal production. They do not constitute a specification.



Committed to the disciplined operation of our business.

CERTIFIED

ISO 9001: 2015

ISO 14001: 2015

IAFT 16949: 2016



SUNISO™

Learn more about us: sunisolubricants.com

Petro-Canada Lubricants Inc.

2310 Lakeshore Road West, Mississauga, ON, Canada L5J 1K2

petrocanadalubricants.com

Petro-Canada Lubricants is an HF Sinclair Brand.

Trademarks are owned or used under license.

IM-8248E (2025.09)