

# EDGE™ MTP® Trunk 50 µm multimode (OM3), MTP® Connector to MTP Connector, 24 F, with 33/ 33 inch legs, pulling grip one side, 130 ft

CORNING

**Part Number:**  
**G757524TPNDDU130F**

EDGE™ MTP® trunks provide the backbone of the EDGE solution. With non-pinned MTP connectors on both ends, these fiber trunk cable assemblies are designed to interface with the EDGE solutions or Plug & Play™ systems modules. All MTP trunks are manufactured with Corning® CleanAdvantage™, MTP trunk cables are shipped with strain-relief clips to allow easy tool-less installation.

## Features and Benefits

### **Snap-in strain-relief clips**

Provide easier cable management

### **Small outer diameter**

Improves cable tray fill ratio and allows for imported airflow

### **Low-loss connectivity**

Enables system design flexibility

### **Bend-improved fiber**

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

### **Fiber optic trunk cable manufactured with Corning® CleanAdvantage™ technology and optimized dust cap**

Eliminates the need for scoping and cleaning prior to initial field connection

### **Non-pinned MTP connectors on both ends**

Fiber optic trunks designed to interface with the EDGE solutions or Plug & Play™ systems modules



EDGE™ Solutions Trunk Cable, 50 µm multimode (OM3), MTP® Connector to MTP Connector, 24 F, with 33/33 inch legs, pulling grip one side, 130 ft

# EDGE™ MTP® Trunk 50 µm multimode (OM3), MTP® Connector to MTP Connector, 24 F, with 33/ 33 inch legs, pulling grip one side, 130 ft

CORNING

## Specifications

### General Specifications

|                         |                |
|-------------------------|----------------|
| Flame Rating            | Plenum (OFNP)  |
| Fiber Category          | 50 µm MM (OM3) |
| Cable Assembly Type     | EDGE™ Trunk    |
| Environment             | Indoor         |
| Application             | Data Center    |
| Pulling grip            | Yes            |
| Connector Assembly Type | MTP to MTP     |

### Standards

|                          |                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Fiber Standards          | IEC 60793-2-10 for A1a class 50/125 multimode fibers; TIA/EIA 492AAAC-A (OM3); ITU-T Recommendation G.651; ISO/IEC 11801 Ed.2.2 Grade OM3 |
| Reaction to Fire         | Cca, s1b, d1, a1                                                                                                                          |
| RoHS                     | Free of hazardous substances according to RoHS 2011/65/EU                                                                                 |
| Approvals and Listings   | NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6                                                                                |
| Design and Test Criteria | ANSI/ICEA S-83-596                                                                                                                        |

### Environmental Conditions

|                              |                                    |
|------------------------------|------------------------------------|
| Temperature Range, Operation | -10 °C to 60 °C (14 °F to 140 °F ) |
|------------------------------|------------------------------------|

### Design

|                            |                           |
|----------------------------|---------------------------|
| Fiber Count                | 24                        |
| Polarity                   | Universal, TIA-568 Type-B |
| Strain-Relief Bracket Type | 1                         |
| Fiber Type                 | Multimode                 |

# EDGE™ MTP® Trunk 50 µm multimode (OM3), MTP® Connector to MTP Connector, 24 F, with 33/ 33 inch legs, pulling grip one side, 130 ft

CORNING

## Mechanical Specifications

|                                        |                                  |
|----------------------------------------|----------------------------------|
| Nominal Outer Diameter                 | 7.7 mm ± 0.3mm (0.3 in ± 0.01in) |
| Max. Tensile Strength for Installation | 660 N (148.37 lbf)               |
| Min. Bend Radius Installation          | 115.5 mm (4.55 in)               |
| Min. Bend Radius Operation             | 38.5 mm (1.52 in)                |
| Minimum Conduit Size with 18-in Elbow  | 63.5 mm (2.5 in)                 |

## Optical Characteristics

|                                         |                          |
|-----------------------------------------|--------------------------|
| Fiber Code                              | T                        |
| Performance Option Code                 | 80                       |
| Fiber Category                          | OM3                      |
| Fiber Type                              | Multimode                |
| Fiber Name                              | 50 µm MM (OM3)           |
| Maximum Attenuation                     | 2.8 dB/km / 1.0 dB/km    |
| Wavelengths                             | 850 nm / 1300 nm         |
| Fiber Compliance                        | IEC 60793-2-10           |
| Fiber Core Diameter                     | 50 µm                    |
| Serial 1 Gigabit Ethernet               | 1000 m / 600 m           |
| Serial 10 Gigabit Ethernet              | 300 m / -                |
| Minimum Effective Modal Bandwidth (EMB) | 2000 MHz*km / -          |
| Min. Overfilled Launch (OFL) Bandwidth  | 1500 MHz*km / 500 MHz*km |

## Specifications - Connector A

|                      |                   |
|----------------------|-------------------|
| Insertion Loss, Max. | 0.25 dB           |
| Connector Type       | MTP® (non-pinned) |
| Ferrule Material     | Composite         |
| Reflectance          | < -20 dB          |

**EDGE™ MTP® Trunk 50 µm multimode (OM3),  
MTP® Connector to MTP Connector, 24 F, with 33/  
33 inch legs, pulling grip one side, 130 ft**

CORNING

**Specifications - Connector B**

|                      |                   |
|----------------------|-------------------|
| Insertion Loss, Max. | 0.25 dB           |
| Connector Type       | MTP® (non-pinned) |
| Ferrule Material     | Composite         |
| Reflectance          | < -20 dB          |

**Pulling Grip - Connector A**

|                     |                   |
|---------------------|-------------------|
| Pulling grip        | Yes               |
| Tensile Strength    | 440 N (98.92 lbf) |
| Grip Outer Diameter | 41 mm (1.61 in)   |

**Pulling Grip - Connector B**

|                         |                 |
|-------------------------|-----------------|
| Min. Duct Size Diameter | 64 mm (2.52 in) |
|-------------------------|-----------------|

**Dimensions**

|              |                            |
|--------------|----------------------------|
| Length       | 130 ft                     |
| Cable Weight | 50 kg/km (33.6 lb/1000 ft) |

**Ordering Information**

|                    |                   |
|--------------------|-------------------|
| Product Number     | G757524TPNDDU130F |
| Reel Diameter      | 23.5 in           |
| Reel Width         | 5 in              |
| Units per Delivery | 1/1               |

**Furcation - Connector A**

|                |                                            |
|----------------|--------------------------------------------|
| Leg Length     | 838 mm -0 / +76mm (32.99 in -0 / +2.99in)  |
| Furcation Type | EDGE™ Size 1, 14.7 mm x 14.7 mm x 108.6 mm |

**EDGE™ MTP® Trunk 50 µm multimode (OM3),  
MTP® Connector to MTP Connector, 24 F, with 33/  
33 inch legs, pulling grip one side, 130 ft**

CORNING

**Furcation - Connector A**

|              |                |
|--------------|----------------|
| Leg Color    | Aqua           |
| Leg Diameter | 2 mm (0.08 in) |

**Furcation - Connector B**

|                |                                            |
|----------------|--------------------------------------------|
| Furcation Type | EDGE™ Size 1, 14.7 mm x 14.7 mm x 108.6 mm |
| Leg Diameter   | 2 mm (0.08 in)                             |
| Leg Length     | 838 mm (32.99 in)                          |



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.