

EDGE™ Adapter Panel, MTP® 48 F, single-mode (OS2)

CORNING

Part Number:
EDGE-CP48-90

EDGE™ MTP® adapter panels provide a simple interface to mate MTP Connectors. This occurs when connecting MTP trunks to MTP extended trunks, MTP trunks to trunk harnesses and, in 40G multimode networks, connecting MTP trunks to 40G patch cords.

Features and Benefits

Provide MTP connection points

Between trunks and harnesses or extender trunks

Installation


Can be installed or removed from the front or rear of a housing

Network upgrades


Facilitate simple upgrades to parallel optics

Packaging

Packaged in easy-open containers



EDGE™ Panel, 48 F, 4X MTP® Adapter Panel, shuttered, single-mode (OS2)



EDGE™ Panel, 48 F, 4X MTP® Adapter Panel, shuttered, single-mode (OS2)

EDGE™ Adapter Panel, MTP® 48 F, single-mode (OS2)



EDGE™ Panel, 48 F, 4X MTP® Adapter Panel, shuttered, single-mode (OS2)



EDGE™ Panel, 48 F, 4X MTP® Adapter Panel, shuttered, single-mode (OS2)

Specifications

General Specifications	
Fiber Category	Single-mode (OS2)
Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Design	
Number of Adapters per Panel	4
Fiber Count	48
Adapter Type Back	MTP®
Adapter Color Back	Black
Adapter Type Master Level	MTP®/MPO
Adapter Color Front	Black
Number of Adapters	2

EDGE™ Adapter Panel, MTP® 48 F, single-mode (OS2)

CORNING

Design - Adapter

Housing Color	Black
Housing Material	Composite
Adapter Style	Standard
Adapter Type	MTP®

Dimensions

Height	9 mm (0.35 in)
Width	100 mm (3.94 in)
Depth	125 mm (4.92 in)
Weight	35 g

Ordering Information

Product Number	EDGE-CP48-90
Shipping Weight	230 g
Shipping Height	200 mm (7.87 in)
Shipping Width	250 mm (9.84 in)
Shipping Depth	130 mm (5.12 in)
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.