

EDGE™ Panels 72F, 6X MTP Adapter Panel, shuttered, multimode (OM3/OM4)

CORNING

Part Number:
EDGE-CP72-U3

EDGE™ Panels are a pass-through patch panel with a single row of MTP® adapters. The link's backbone trunks connect at the rear of the adapters. EDGE Panels are available with six 12-fiber MTP adapters. Each panel features translucent shuttered adapters with translucent shuttered MTP reversible adapters at the front of the panel.

Features and Benefits

Reversible MTP adapters allow on-site polarity changes

Reduced risk of installation delays or errors during commissioning of new devices

Utilises existing EDGE Solutions hardware and backbone cabling

Higher return on investment and reduced capitalisation and installation costs

Corning® ClearCurve® fiber-enabled components create smaller form factor, more rugged cabling

Reduced congestion within and between racks for improved airflow; less risk of downtime due to pinched or bent cables

MTP adapter panels

Facilitate simple upgrades to parallel optics

No need for dust caps

Provide reliable dust protection

Translucent shutters

Diffuse VFL light and allows fiber identification for 6 port MTP and LC panels



EDGE™ Panel, 72F, 6X MTP® Adapter Panel, shuttered, multimode (OM3/OM4)

EDGE™ Panels 72F, 6X MTP Adapter Panel, shuttered, multimode (OM3/OM4)

CORNING

Specifications

General Specifications

Fiber Category	50 µm MM (OM3/OM4/OM5)
----------------	------------------------

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Design

Number of Adapters per Panel	6
Fiber Count	72
Adapter Type Back	MTP®
Adapter Color Back	Aqua
Adapter Type Master Level	MTP®/MPO
Adapter Color Front	Aqua
Adapter Type Front	Shuttered MTP

Design - Adapter

Housing Color	Aqua
---------------	------

Dimensions

Depth	14.43 mm (0.57 in)
Weight	11 kg

Ordering Information

Product Number	EDGE-CP72-U3
Units per Delivery	1/1

EDGE™ Panels 72F, 6X MTP Adapter Panel, shuttered, multimode (OM3/OM4)

The Corning logo consists of the word "CORNING" in a white, serif, all-caps font, centered within a solid blue square.

Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.