

# SOLO® ADSS Medium-Span, Loose Tube, Gel-Filled Cable 72 F, Single-mode (OS2)

CORNING

## Part Number: 072EN4-T4M01A20

Corning SOLO® ADSS medium-span cables are all-dielectric, self-supporting (ADSS) cables designed for easy and economical one-step installation in campus backbones with self-supporting installations where metallic messengers cannot be used. The loose tube design provides stable performance over a wide temperature range and is compatible with any telecommunications-grade optical fiber. The economical single-jacket design can span distances of 800 ft in NESC light conditions, 650 ft in NESC medium conditions and 450 ft in NESC heavy conditions. This cable incorporates innovative waterblocking materials, eliminating the need for traditional flooding compound and providing efficient and craft-friendly cable preparation. While the concentric, self-supporting cable design allows easy, one-step installation using standard hardware and installation methods, the SZ-stranded, loose tube design isolates optical fibers from installation and environmental rigors and facilitates mid-span access. The ADSS optical cables are also available with a proprietary track-resistant polyethylene (TRPE) jacket suitable for installation in electric field potentials up to 25 kV.

## Features and Benefits

### Loose tube design

Stable performance and compatibility with all common fiber types

### Self-supporting


Easy, one-step installation

### Track-resistant jacket available


Suitable for installations up to 25 kV electric field potential

### Innovative waterblocking cable core

Provides efficient and craft-friendly cable preparation



SOLO® ADSS Medium-Span, Loose Tube, Gel-Filled Cable, 72 F, Single-mode (OS2)



SOLO® ADSS Medium-Span, Loose Tube, Gel-Filled Cable, 72 F, Single-mode (OS2)

# SOLO® ADSS Medium-Span, Loose Tube, Gel-Filled Cable 72 F, Single-mode (OS2)

CORNING

## Specifications

### General Specifications

|                |                       |
|----------------|-----------------------|
| Cable Type     | Loose Tube            |
| Environment    | Outdoor               |
| Product Type   | Self-Supporting, ADSS |
| Fiber Category | Single-mode (OS2)     |
| Cable geometry | Other                 |

### Standards

|                          |                                                           |
|--------------------------|-----------------------------------------------------------|
| RoHS                     | Free of hazardous substances according to RoHS 2011/65/EU |
| Approvals and Listings   | USDA Rural Development Programs                           |
| Common Installations     | Outdoor self-supporting aerial                            |
| Design and Test Criteria | ANSI/ICEA S-87-640                                        |

### Environmental Conditions

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Temperature Range, Installation | -30 °C to 70 °C (-22 °F to 158 °F ) |
| Temperature Range, Operation    | -40 °C to 70 °C (-40 °F to 158 °F ) |
| Temperature Range, Storage      | -40 °C to 70 °C (-40 °F to 158 °F ) |

### Cable Design

|                                                     |                                          |
|-----------------------------------------------------|------------------------------------------|
| Central Element                                     | Dielectric                               |
| Fiber Count                                         | 72                                       |
| Number of Ripcords                                  | 1                                        |
| Outer Jacket Color                                  | Black                                    |
| Outer Jacket Material                               | Polyethylene (PE)                        |
| Tensile Strength Elements and/or Armoring - Layer 1 | Dielectric strength members              |
| Buffer Tube Color                                   | Blue, Orange, Green, Brown, Slate, White |
| Buffer Tube Diameter                                | 2.5 mm (0.1 in)                          |

# SOLO® ADSS Medium-Span, Loose Tube, Gel-Filled Cable 72 F, Single-mode (OS2)

CORNING

## Cable Design

|                          |                                                                                  |
|--------------------------|----------------------------------------------------------------------------------|
| Number of Active Tubes   | 6                                                                                |
| Number of Tube Positions | 6                                                                                |
| Tape                     | Water-swellaable                                                                 |
| Fiber Coloring           | Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua |
| Fibers per Tube          | 12                                                                               |
| Color Code Standards     | Telcordia                                                                        |

## Mechanical Specifications

|                                 |                    |
|---------------------------------|--------------------|
| Nominal Outer Diameter          | 11.3 mm (0.44 in ) |
| Min. Bend Diameter Installation | 340 mm (13.39 in)  |
| Min. Bend Diameter Operation    | 226 mm (8.9 in)    |

## Optical Characteristics

|                         |                                   |
|-------------------------|-----------------------------------|
| Fiber Code              | E                                 |
| Performance Option Code | 01                                |
| Fiber Category          | OS2                               |
| Fiber Type              | Single-mode (OS2) / 250 µm        |
| Fiber Name              | Single-mode (OS2)                 |
| Maximum Attenuation     | 0.4 dB/km / 0.4 dB/km / 0.3 dB/km |
| Wavelengths             | 1310 nm / 1383 nm / 1550 nm       |
| Fiber Compliance        | ITU-T G.652.D                     |

## Dimensions

|              |                             |
|--------------|-----------------------------|
| Cable Weight | 97 kg/km (65.18 lb/1000 ft) |
|--------------|-----------------------------|

# SOLO® ADSS Medium-Span, Loose Tube, Gel-Filled Cable 72 F, Single-mode (OS2)

CORNING

| Installation Characteristics |                      |                     |            |                     |             |                       |            |                       |
|------------------------------|----------------------|---------------------|------------|---------------------|-------------|-----------------------|------------|-----------------------|
|                              | Initial Installation |                     | NESC Light |                     | NESC Medium |                       | NESC Heavy |                       |
| Span                         | SAG                  | Tension             | SAG        | Tension             | SAG         | Tension               | SAG        | Tension               |
| Fiber Count 72               |                      |                     |            |                     |             |                       |            |                       |
| 15 m (49.2 ft)               | 1 %                  | 181 N (40.7 lbf)    | 0.4 %      | 495 N (111.3 lbf)   | 1.6 %       | 717 N (161.2 lbf)     | 2.3 %      | 1,092 N (245.5 lbf)   |
| 30 m (98.4 ft)               | 1 %                  | 362 N (81.4 lbf)    | 0.5 %      | 893 N (200.8 lbf)   | 1.9 %       | 1,256 N (282.4 lbf)   | 2.7 %      | 1,862 N (418.6 lbf)   |
| 46 m (150.9 ft)              | 1 %                  | 543 N (122.1 lbf)   | 0.5 %      | 1,249 N (280.8 lbf) | 2.1 %       | 1,728 N (388.5 lbf)   | 2.9 %      | 2,527 N (568.1 lbf)   |
| 61 m (200.1 ft)              | 1 %                  | 725 N (163 lbf)     | 0.5 %      | 1,580 N (355.2 lbf) | 2.2 %       | 2,162 N (486 lbf)     | 3.2 %      | 3,133 N (704.3 lbf)   |
| 76 m (249.3 ft)              | 1 %                  | 906 N (203.7 lbf)   | 0.6 %      | 1,894 N (425.8 lbf) | 2.3 %       | 2,569 N (577.5 lbf)   | 3.4 %      | 3,698 N (831.3 lbf)   |
| 91 m (298.5 ft)              | 1 %                  | 1,087 N (244.4 lbf) | 0.6 %      | 2,195 N (493.5 lbf) | 2.4 %       | 2,956 N (664.5 lbf)   | 3.5 %      | 4,233 N (951.6 lbf)   |
| 107 m (351 ft)               | 1 %                  | 1,268 N (285.1 lbf) | 0.6 %      | 2,485 N (558.6 lbf) | 2.5 %       | 3,328 N (748.2 lbf)   | 3.7 %      | 4,745 N (1,066.7 lbf) |
| 122 m (400.2 ft)             | 1 %                  | 1,449 N (325.8 lbf) | 0.6 %      | 2,768 N (622.3 lbf) | 2.6 %       | 3,688 N (829.1 lbf)   | 3.8 %      | 5,238 N (1,177.5 lbf) |
| 137 m (449.4 ft)             | 1 %                  | 1,630 N (366.4 lbf) | 0.6 %      | 3,043 N (684.1 lbf) | 2.7 %       | 4,037 N (907.5 lbf)   | 3.9 %      | 5,715 N (1,284.8 lbf) |
| 152 m (498.6 ft)             | 1 %                  | 1,811 N (407.1 lbf) | 0.6 %      | 3,313 N (744.8 lbf) | 2.7 %       | 4,377 N (984 lbf)     | 4.1 %      | 6,179 N (1,389.1 lbf) |
| 168 m (551 ft)               | 1 %                  | 1,992 N (447.8 lbf) | 0.6 %      | 3,577 N (804.1 lbf) | 2.8 %       | 4,710 N (1,058.8 lbf) | 4.2 %      | 6,631 N (1,490.7 lbf) |
| 183 m (600.2 ft)             | 1 %                  | 2,174 N (488.7 lbf) | 0.7 %      | 3,837 N (862.6 lbf) | 2.8 %       | 5,036 N (1,132.1 lbf) | 4.3 %      | 7,073 N (1,590.1 lbf) |
| 198 m (649.4 ft)             | 1 %                  | 2,355 N (529.4 lbf) | 0.7 %      | 4,093 N (920.1 lbf) | 2.9 %       | 5,355 N (1,203.8 lbf) | 4.4 %      | 7,506 N (1,687.4 lbf) |
| 213 m (698.6 ft)             | 1 %                  | 2,536 N (570.1 lbf) | 0.7 %      | 4,346 N (977 lbf)   | 2.9 %       | 5,670 N (1,274.7 lbf) | 4.4 %      | 7,931 N (1,783 lbf)   |

# SOLO® ADSS Medium-Span, Loose Tube, Gel-Filled Cable 72 F, Single-mode (OS2)

CORNING

| Installation Characteristics |                      |                       |            |                       |             |                       |            |         |
|------------------------------|----------------------|-----------------------|------------|-----------------------|-------------|-----------------------|------------|---------|
|                              | Initial Installation |                       | NESC Light |                       | NESC Medium |                       | NESC Heavy |         |
| Span                         | SAG                  | Tension               | SAG        | Tension               | SAG         | Tension               | SAG        | Tension |
| 229 m (751.1 ft)             | 1 %                  | 2,717 N (610.8 lbf)   | 0.7 %      | 4,595 N (1,033 lbf)   | 3 %         | 5,980 N (1,344.4 lbf) |            |         |
| 244 m (800.3 ft)             | 1 %                  | 2,898 N (651.5 lbf)   | 0.7 %      | 4,842 N (1,088.5 lbf) | 3 %         | 6,285 N (1,412.9 lbf) |            |         |
| 259 m (849.5 ft)             | 1 %                  | 3,079 N (692.2 lbf)   | 0.7 %      | 5,086 N (1,143.4 lbf) | 3.1 %       | 6,586 N (1,480.6 lbf) |            |         |
| 274 m (898.7 ft)             | 1 %                  | 3,260 N (732.9 lbf)   | 0.7 %      | 5,328 N (1,197.8 lbf) | 3.1 %       | 6,884 N (1,547.6 lbf) |            |         |
| 290 m (951.2 ft)             | 1 %                  | 3,441 N (773.6 lbf)   | 0.7 %      | 5,567 N (1,251.5 lbf) | 3.2 %       | 7,178 N (1,613.7 lbf) |            |         |
| 305 m (1,000.4 ft)           | 1 %                  | 3,623 N (814.5 lbf)   | 0.7 %      | 5,804 N (1,304.8 lbf) | 3.2 %       | 7,469 N (1,679.1 lbf) |            |         |
| 320 m (1,049.6 ft)           | 1 %                  | 3,804 N (855.2 lbf)   | 0.7 %      | 6,040 N (1,357.8 lbf) | 3.2 %       | 7,757 N (1,743.8 lbf) |            |         |
| 335 m (1,098.8 ft)           | 1 %                  | 3,985 N (895.9 lbf)   | 0.7 %      | 6,274 N (1,410.5 lbf) | 3.3 %       | 8,043 N (1,808.1 lbf) |            |         |
| 351 m (1,151.3 ft)           | 1 %                  | 4,166 N (936.5 lbf)   | 0.7 %      | 6,506 N (1,462.6 lbf) |             |                       |            |         |
| 366 m (1,200.5 ft)           | 1 %                  | 4,347 N (977.2 lbf)   | 0.8 %      | 6,737 N (1,514.5 lbf) |             |                       |            |         |
| 381 m (1,249.7 ft)           | 1 %                  | 4,528 N (1,017.9 lbf) | 0.8 %      | 6,966 N (1,566 lbf)   |             |                       |            |         |
| 396 m (1,298.9 ft)           | 1 %                  | 4,709 N (1,058.6 lbf) | 0.8 %      | 7,194 N (1,617.3 lbf) |             |                       |            |         |
| 411 m (1,348.1 ft)           | 1 %                  | 4,891 N (1,099.5 lbf) | 0.8 %      | 7,421 N (1,668.3 lbf) |             |                       |            |         |
| 427 m (1,400.6 ft)           | 1 %                  | 5,072 N (1,140.2 lbf) | 0.8 %      | 7,646 N (1,718.9 lbf) |             |                       |            |         |

# SOLO® ADSS Medium-Span, Loose Tube, Gel-Filled Cable 72 F, Single-mode (OS2)

CORNING

| Installation Characteristics |                      |                          |            |                          |             |         |            |         |
|------------------------------|----------------------|--------------------------|------------|--------------------------|-------------|---------|------------|---------|
|                              | Initial Installation |                          | NESC Light |                          | NESC Medium |         | NESC Heavy |         |
| Span                         | SAG                  | Tension                  | SAG        | Tension                  | SAG         | Tension | SAG        | Tension |
| 442 m<br>(1,449.8 ft)        | 1 %                  | 5,253 N<br>(1,180.9 lbf) | 0.8 %      | 7,871 N<br>(1,769.5 lbf) |             |         |            |         |
| 457 m (1,499 ft)             | 1 %                  | 5,434 N<br>(1,221.6 lbf) | 0.8 %      | 8,094 N<br>(1,819.6 lbf) |             |         |            |         |



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.