

# 12-Fiber MTP® PRO Jumper 12F, 50 μm multimode (OM4), 10 ft



**Part Number:**  
**J939312QE8-NB010F**

EDGE™ MTP® PRO patch cords are used to create a connection between MTP adapter panels, conversion modules, and electronics, typically providing connectivity within the rack or the row. These cable assemblies feature a smaller (2.0 mm) outside diameter than traditional 12-fiber patch cords to improve finger access and reduce congestion and increase airflow in the horizontal and vertical rack space. EDGE 12-fiber MTP patch cords have the same connector size and cable footprint as LC duplex patch cords used today. The density, airflow, and cable management advantages of EDGE solutions was preserved as you migrate to higher data rates. These patch cords are manufactured using Corning® CleanAdvantage™ technology and shipped with optimized dust caps, eliminating the need for cleaning and scoping prior to the initial field connection. They are built with MTP PRO push-pull connectors, allowing for a simple one-step color-coded polarity change without removing the connector housing. The connector also provides the capability for field-friendly pinning configuration changes with safe handling of pins and easy color identification while maintaining product integrity.



## Features and Benefits

- Slim round 2-fiber interconnect cable**  
Improves airflow and reduces congestion
- MTP® PRO connectors**  
Allows for pinning and polarity changes in the field
- Bend-improved fiber**  
Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables
- Corning® CleanAdvantage™ technology and optimized dust cap**  
Eliminates the need for scoping and cleaning prior to initial field connection



# 12-Fiber MTP® PRO Jumper 12F, 50 µm multimode (OM4), 10 ft

CORNING

## Specifications

### General Specifications

|                         |                                                                |
|-------------------------|----------------------------------------------------------------|
| Flame Rating            | NFPA 262 (for plenum, riser and general building applications) |
| Fiber Category          | 50 µm MM (OM4)                                                 |
| Cable Assembly Type     | EDGE™ Jumper                                                   |
| Environment             | Indoor                                                         |
| Cable Type              | Interconnect                                                   |
| Assembly Insertion Loss | ≤ 0.5 dB                                                       |
| Connector Assembly Type | MTP to MTP                                                     |

### Standards

|                 |                                                                                                                                                                       |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fiber Standards | TIA/EIA-492AAAC-A, Tested with minEMBc method to TIA/EIA-455-220, IEC 60793-2-10 Type A1a.2 Ed.2.0, IEC 60793-1-49 Ed.2.0, ITU-T G.651, ISO/IEC 11801 Ed.2.2 Cat. OM3 |
| RoHS            | Free of hazardous substances according to RoHS 2011/65/EU                                                                                                             |

### Environmental Conditions

|                                 |                                    |
|---------------------------------|------------------------------------|
| Temperature Range, Installation | 0 °C to 50 °C (32 °F to 122 °F )   |
| Temperature Range, Operation    | -10 °C to 60 °C (14 °F to 140 °F ) |

### Design

|             |                |
|-------------|----------------|
| Fiber Count | 12             |
| Polarity    | TIA-568 Type-B |
| Fiber Type  | Multimode      |

### Mechanical Specifications

|                                        |                   |
|----------------------------------------|-------------------|
| Nominal Outer Diameter                 | 2 mm (0.08 in )   |
| Max. Tensile Strength for Installation | 220 N (49.46 lbf) |

# 12-Fiber MTP® PRO Jumper 12F, 50 µm multimode (OM4), 10 ft

CORNING

## Mechanical Specifications

|                               |                             |
|-------------------------------|-----------------------------|
| Min. Bend Radius Installation | 30 mm (1.18 in)             |
| Min. Bend Radius Operation    | 10 mm (0.39 in)             |
| Weight                        | 3.5 kg/km (2.35 lb/1000 ft) |

## Optical Characteristics

|                                         |                          |
|-----------------------------------------|--------------------------|
| Fiber Code                              | T                        |
| Performance Option Code                 | 90                       |
| Fiber Category                          | OM4                      |
| Fiber Type                              | Multimode                |
| Fiber Name                              | 50 µm MM (OM4)           |
| Maximum Attenuation                     | 2.8 dB/km / 1.0 dB/km    |
| Wavelengths                             | 850 nm / 1300 nm         |
| Fiber Compliance                        | IEC 60793-2-10           |
| Fiber Core Diameter                     | 50 µm                    |
| Serial 1 Gigabit Ethernet               | 1000 m / 600 m           |
| Serial 10 Gigabit Ethernet              | 550 m / -                |
| Minimum Effective Modal Bandwidth (EMB) | 4700 MHz*km / -          |
| Min. Overfilled Launch (OFL) Bandwidth  | 3500 MHz*km / 500 MHz*km |

## Specifications - Connector A

|                      |                   |
|----------------------|-------------------|
| Polish               | PC                |
| Insertion Loss, Max. | 0.25 dB           |
| Boot Color           | Black             |
| Connector Type       | MTP® PRO (pinned) |
| Ferrule Material     | Composite         |
| Boot Type            | Simplex           |
| Reflectance          | < -20 dB          |

# 12-Fiber MTP® PRO Jumper 12F, 50 µm multimode (OM4), 10 ft

CORNING

## Specifications - Connector B

|                      |                   |
|----------------------|-------------------|
| Polish               | PC                |
| Insertion Loss, Max. | 0.25 dB           |
| Boot Color           | Black             |
| Connector Type       | MTP® PRO (pinned) |
| Ferrule Material     | Composite         |
| Boot Type            | Simplex           |
| Reflectance          | < -20 dB          |

## Dimensions

|              |                             |
|--------------|-----------------------------|
| Length       | 10 ft                       |
| Cable Weight | 3.5 kg/km (2.35 lb/1000 ft) |

## Ordering Information

|                    |                   |
|--------------------|-------------------|
| Product Number     | J939312QE8-NB010F |
| Units per Delivery | 1/1               |

## Cable Material

|                 |              |
|-----------------|--------------|
| Fiber Count     | 12           |
| Fiber Type      | OM4 MM       |
| Outer Diameter  | Standard     |
| Flame Rating    | Plenum       |
| Armor           | Non-armored  |
| Length          | 10           |
| Unit of Measure | Feet         |
| Cable Type      | Interconnect |
| Fiber Mode      | Multimode    |

# 12-Fiber MTP® PRO Jumper 12F, 50 µm multimode (OM4), 10 ft

CORNING

## CONNECTOR\_A\_1 Material

|                   |                 |
|-------------------|-----------------|
| Connector         | MTP® 12F Pinned |
| Connector Keying  | Non-Keyed       |
| Connector Loss    | Low Loss        |
| Connector Pinning | Pinned          |

## CONNECTOR\_B Material

|                   |                 |
|-------------------|-----------------|
| Connector         | MTP® 12F Pinned |
| Connector Keying  | Non-Keyed       |
| Connector Pinning | Pinned          |
| Connector Loss    | Low Loss        |



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.