

# ALTOS® Lite Loose Tube, Gel-Free, Single-Jacket, Single-Armored Cable 72 F, 62.5 µm multimode (OM1)

CORNING

**Part Number:**  
**072KUC-T4130D20**

Corning ALTOS® Lite gel-free, single-jacket, single-armored cables are designed for campus backbones in direct-buried installations. The loose tube design provides stable and highly reliable transmission parameters for a variety of voice, data, video and imaging applications. These cables also provide high-fiber density within a given cable diameter while allowing flexibility to suit many system configurations. The single armored construction provides additional crush and rodent protection with a high-strength ripcord under the armor for easy stripping. Gel-free means the cables are fully waterblocked using craft-friendly, water-swappable materials which make cable access simple and require no clean up. The flexible, craft-friendly buffer tubes are easy to route in closures, and the SZ-stranded, loose tube design isolates fibers from installation and environmental rigors while allowing easy mid-span access. These cables have a medium density polyethylene jacket that is rugged, durable and easy to strip.

## Features and Benefits

### Gel-free waterblocking technology


Craft-friendly cable preparation

### Polyethylene jacket


Rugged, durable and easy to strip (while providing superior protection against UV radiation, fungus, abrasion and other environmental factors)

### Corrugated steel tape armor

Provides rodent resistance for direct-buried applications



ALTOS® Lite Loose Tube, Gel-Free, Single-Jacket, Single-Armored Cable, 72 F, 62.5 µm multimode (OM1)



ALTOS® Lite Loose Tube, Gel-Free, Single-Jacket, Single-Armored Cable, 72 F, 62.5 µm multimode (OM1)

# ALTOS® Lite Loose Tube, Gel-Free, Single-Jacket, Single-Armored Cable 72 F, 62.5 µm multimode (OM1)

CORNING

## Specifications

### General Specifications

|                      |                             |
|----------------------|-----------------------------|
| Installation Methods | Aerial, Direct Buried, Duct |
| Cable Type           | Loose Tube                  |
| Environment          | Outdoor                     |
| Product Type         | Steel Tape Armor            |
| Fiber Category       | 62.5 µm MM (OM1)            |
| Cable geometry       | Round                       |

### Standards

|                          |                                                                                                                                |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| RoHS                     | Free of hazardous substances according to RoHS 2011/65/EU                                                                      |
| Common Installations     | Outdoor lashed aerial, duct and direct-buried, indoor when installed according to National Electrical Code® (NEC®) Article 770 |
| Design and Test Criteria | ANSI/ICEA S-87-640                                                                                                             |

### Environmental Conditions

|                                 |                                                                                                                                                                                                                |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes                           | Corning recommends storing cable in a proper temperature environment prior to installation to allow the cable temperature to meet installation temperature range specifications for best installation results. |
| Temperature Range, Installation | -30 °C to 70 °C (-22 °F to 158 °F )                                                                                                                                                                            |
| Temperature Range, Operation    | -40 °C to 70 °C (-40 °F to 158 °F )                                                                                                                                                                            |
| Temperature Range, Storage      | -40 °C to 70 °C (-40 °F to 158 °F )                                                                                                                                                                            |

### Cable Design

|                    |            |
|--------------------|------------|
| Central Element    | Dielectric |
| Fiber Count        | 72         |
| Number of Ripcords | 2          |
| Outer Jacket Color | Black      |

# ALTOS® Lite Loose Tube, Gel-Free, Single-Jacket, Single-Armored Cable 72 F, 62.5 µm multimode (OM1)

CORNING

## Cable Design

|                                                     |                                                                                  |
|-----------------------------------------------------|----------------------------------------------------------------------------------|
| Outer Jacket Material                               | Polyethylene (PE)                                                                |
| Tensile Strength Elements and/or Armoring - Layer 1 | Corrugated steel tape armor                                                      |
| Buffer Tube Color                                   | Blue, Orange, Green, Brown, Slate, White                                         |
| Buffer Tube Diameter                                | 2.5 mm (0.1 in)                                                                  |
| Number of Active Tubes                              | 6                                                                                |
| Number of Tube Positions                            | 6                                                                                |
| Tape                                                | Water-swellable                                                                  |
| Fiber Coloring                                      | Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua |
| Fibers per Tube                                     | 12                                                                               |
| Color Code Standards                                | Telcordia                                                                        |

## Mechanical Specifications

|                                   |                     |
|-----------------------------------|---------------------|
| Max. Tensile Strength, Long-Term  | 890 N (200.08 lbf)  |
| Max. Tensile Strength, Short-Term | 2700 N (606.98 lbf) |
| Nominal Outer Diameter            | 12.1 mm (0.48 in )  |
| Min. Bend Diameter Installation   | 364 mm (14.33 in)   |
| Min. Bend Diameter Operation      | 242 mm (9.53 in)    |

## Optical Characteristics

|                         |                       |
|-------------------------|-----------------------|
| Fiber Code              | K                     |
| Performance Option Code | 30                    |
| Fiber Category          | OM1                   |
| Fiber Type              | Multimode             |
| Fiber Name              | 62.5 µm MM (OM1)      |
| Maximum Attenuation     | 3.4 dB/km / 1.0 dB/km |
| Wavelengths             | 850 nm / 1300 nm      |
| Fiber Compliance        | ISO/IEC 11801         |
| Fiber Core Diameter     | 62.5 µm               |

# ALTOS® Lite Loose Tube, Gel-Free, Single-Jacket, Single-Armored Cable 72 F, 62.5 µm multimode (OM1)

CORNING

## Optical Characteristics

|                                         |                         |
|-----------------------------------------|-------------------------|
| Coating diameter                        | 242 µm                  |
| Serial 1 Gigabit Ethernet               | 300 m / 550 m           |
| Serial 10 Gigabit Ethernet              | 33 m / -                |
| Minimum Effective Modal Bandwidth (EMB) | 220 MHz*km / -          |
| Min. Overfilled Launch (OFL) Bandwidth  | 200 MHz*km / 500 MHz*km |

## Dimensions

|              |                              |
|--------------|------------------------------|
| Cable Weight | 129 kg/km (86.68 lb/1000 ft) |
|--------------|------------------------------|



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.