

EDGE™ Armored Trunk 50 µm multimode (OM3), MTP® (non-pinned) to MTP (non-pinned) 36 F, with 33/33 in legs, pulling grip one side, 100 ft

CORNING

Part Number:
G757536TADDDU100F

EDGE™ MTP® trunks provide the backbone of the EDGE Solution. With non-pinned MTP connectors on both ends of the cable, the trunks are designed to interface with EDGE or Plug & Play™ modules. All trunks are shipped with strain-relief clips that allow for tool-less installation in both EDGE and Plug & Play housings. The trunks conform to TIA-568 Type-B polarity.

Features and Benefits

Snap-in strain-relief clips

Provide easier cable management

Small outer diameter

Improves the cable tray fill ratio and allows for improved airflow

Low-loss connectivity


Enables system design flexibility

Bend-improved fiber

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

Corning® CleanAdvantage™ technology and optimized dust cap

Eliminates the need for scoping and cleaning prior to initial field connection



EDGE™ Armored Trunk, 50 µm multimode (OM3), MTP® (non-pinned) to MTP (non-pinned) 36 F, with 33/33 in legs, pulling grip one side, 100 ft

EDGE™ Armored Trunk 50 µm multimode (OM3), MTP® (non-pinned) to MTP (non-pinned) 36 F, with 33/33 in legs, pulling grip one side, 100 ft

CORNING

Specifications

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Moisture Resistance	MIL-STD-202, Method 106, except Step 7B
---------------------	---

Design

Polarity	Universal, TIA-568 Type-B
----------	---------------------------

Optical Characteristics

Fiber Code	T
Performance Option Code	80
Fiber Category	OM3
Fiber Type	Multimode
Fiber Name	50 µm MM (OM3)
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fiber Compliance	IEC 60793-2-10
Fiber Core Diameter	50 µm
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	300 m / -
Minimum Effective Modal Bandwidth (EMB)	2000 MHz*km / -
Min. Overfilled Launch (OFL) Bandwidth	1500 MHz*km / 500 MHz*km

Dimensions

Length	100 ft
--------	--------

**EDGE™ Armored Trunk 50 µm multimode (OM3),
MTP® (non-pinned) to MTP (non-pinned) 36 F, with
33/33 in legs, pulling grip one side, 100 ft**

CORNING



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.