

EDGE™ Armored Trunk Bend-improved Single-mode (OS2), MTP® (non-pinned) to MTP (non-pinned), 144 F, with 33/33 in legs, pulling grip one side, 100 ft

CORNING

Part Number:
G9090E4GADDDU100F

EDGE™ MTP® trunks provide the backbone of the EDGE Solution. With non-pinned MTP connectors on both ends of the cable, the trunks are designed to interface with EDGE or Plug & Play™ modules. All trunks are shipped with strain-relief clips that allow for tool-less installation in both EDGE and Plug & Play housings. The trunks conform to TIA-568 Type-B polarity.

Features and Benefits

Snap-in strain-relief clips

Provide easier cable management

Small outer diameter

Improves the cable tray fill ratio and allows for improved airflow

Low-loss connectivity


Enables system design flexibility

Bend-improved fiber

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

Corning® CleanAdvantage™ technology and optimized dust cap

Eliminates the need for scoping and cleaning prior to initial field connection



EDGE™ Armored Trunk, Bend-improved Single-mode (OS2), MTP® (non-pinned) to MTP (non-pinned), 144 F, with 33/33 in legs, pulling grip one side, 100 ft

EDGE™ Armored Trunk Bend-improved Single-mode (OS2), MTP® (non-pinned) to MTP (non-pinned), 144 F, with 33/33 in legs, pulling grip one side, 100 ft

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	Bend-improved SM (OS2)
Cable Assembly Type	EDGE™ Trunk
Environment	Indoor
Application	Data Center
Cable Type	Indoor: ANSI/ICEA S-83-596

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Temperature Range, Installation	0 °C to 50 °C (32 °F to 122 °F)
Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)

Design

Fiber Count	144
Polarity	Universal, TIA-568 Type-B

Mechanical Specifications

Nominal Outer Diameter	18.8 mm (0.74 in)
Min. Bend Radius Installation	282 mm (11.1 in)
Min. Bend Radius Operation	94 mm (3.7 in)

Optical Characteristics

Fiber Code	E
------------	---

EDGE™ Armored Trunk Bend-improved Single-mode (OS2), MTP® (non-pinned) to MTP (non-pinned), 144 F, with 33/33 in legs, pulling grip one side, 100 ft

CORNING

Optical Characteristics

Performance Option Code	31
Fiber Category	OS2
Fiber Type	Single-mode (OS2) / 250 µm
Fiber Name	Single-mode (OS2)
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.4 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Compliance	ITU-T G.652.D

Specifications - Connector A

Insertion Loss, Max.	0.35 dB
Boot Color	Black
Connector Type	MTP® (non-pinned)
Ferrule Material	Composite
Reflectance	≤ -55 dB

Specifications - Connector B

Insertion Loss, Max.	0.35 dB
Boot Color	Black
Connector Type	MTP® (non-pinned)
Ferrule Material	Composite
Reflectance	≤ -55 dB

Pulling Grip - Connector A

Pulling grip	Yes
Grip Outer Diameter	51 mm (2.01 in)

EDGE™ Armored Trunk Bend-improved Single-mode (OS2), MTP® (non-pinned) to MTP (non-pinned), 144 F, with 33/33 in legs, pulling grip one side, 100 ft

CORNING

Dimensions

Length	100 ft
Weight	78 kg

Ordering Information

Product Number	G9090E4GADDDU100F
Packaging Method	Plastic reel
Units per Delivery	1/1

Cable Material

Fiber Count	144
Fiber Type	OS2 Bend-improved SM
Outer Diameter	Standard
Flame Rating	Plenum
Aarmor	Armored
Length	100
Unit of Measure	Feet
Cable Type	Distribution
Fiber Mode	Single-Mode

CONNECTOR_A_1 Material

Connector	MTP® 12F Non-pinned
Connector Keying	Non-Keyed
Connector Loss	Standard Loss
Connector Pinning	Non-Pinned

CONNECTOR_B Material

Connector	MTP® 12F Non-pinned
-----------	---------------------

EDGE™ Armored Trunk Bend-improved Single-mode (OS2), MTP® (non-pinned) to MTP (non-pinned), 144 F, with 33/33 in legs, pulling grip one side, 100 ft

CORNING

CONNECTOR_B Material

Connector Keying	Non-Keyed
Connector Pinning	Non-Pinned
Connector Loss	Standard Loss

Furcation A Material

Leg Length	33 in
Leg Length	840 mm (33.07 in)
Furcation Type	Size 1
Leg Color	Yellow
Leg Diameter	2 mm (0.08 in)
Leg Count	12

Furcation - Connector B

Leg Color	Yellow
Furcation Type	Size 1
Leg Diameter	2 mm (0.08 in)
Leg Length	840 mm (33.07 in)
Leg Count	12
Leg Length	33 in



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.