

EDGE™ MTP® Extender Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Part Number:
G8990E4GPNCDX100F

The EDGE™ MTP® Extender Trunks provide additional distance for the backbone of the EDGE Solution. With a non-pinned MTP on one end of the cable, a pinned MTP on the other and a TIA-568 Type-A polarity, these trunks are designed to interface with a EDGE or Plug & Play™ module and an MTP trunk. All trunks are shipped with strain-relief clips that allow for the tool-less installation in both EDGE and Plug & Play housings. Most often these extender trunks will be used in a Zone Distribution Area (ZDA).

Features and Benefits

Snap-in strain-relief clips

Provide easier cable management

Small outer diameter

Improves cable tray fill ratio and allows for imported airflow

Low-loss connectivity


Enables system design flexibility

Bend-improved fiber

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

Corning® CleanAdvantage™ technology and optimized dust cap

Eliminates the need for scoping and cleaning prior to initial field connection



EDGE™ Solutions Extender Trunk, Bend-improved Single-mode (OS2), MTP® Connector to MTP Connector, 144 F, with 33/60 inch legs, pulling grip one side, 100 ft

EDGE™ MTP® Extender Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	Bend-improved SM (OS2)
Cable Assembly Type	EDGE™ Trunk
Environment	Indoor
Pulling grip	Yes
Connector Assembly Type	MTP to MTP

Standards

Fiber Standards	ITU-T G.652.D and ITU-T G.657.A1
Reaction to Fire	Cca, s1b, d1, a1
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6
Design and Test Criteria	ANSI/ICEA S-83-596

Environmental Conditions

Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)
------------------------------	------------------------------------

Design

Fiber Count	144
Polarity	Extender, TIA-568 Type-A
Fiber Type	Single-mode

Mechanical Specifications

Nominal Outer Diameter	12.5 mm (0.49 in)
Max. Tensile Strength for Installation	660 N (148.37 lbf)

EDGE™ MTP® Extender Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Mechanical Specifications

Min. Bend Radius Installation	187.5 mm (7.38 in)
Min. Bend Radius Operation	62.5 mm (2.46 in)
Minimum Conduit Size with 18-in Elbow	77 mm (3.03 in)

Optical Characteristics

Fiber Code	Z
Performance Option Code	01
Fiber Category	OS2
Fiber Type	Single-mode (OS2) / 250 µm
Fiber Name	Bend-Improved Single-mode (OS2)
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Compliance	ITU-T G.652.D and ITU-T G.657.A1

Specifications - Connector A

Insertion Loss, Max.	0.35 dB
Boot Color	Black
Connector Type	MTP® (pinned)
Ferrule Material	Composite
Reflectance	< -65 dB

Specifications - Connector B

Insertion Loss, Max.	0.35 dB
Boot Color	Black
Connector Type	MTP® (non-pinned)
Ferrule Material	Composite
Reflectance	< -65 dB

EDGE™ MTP® Extender Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Pulling Grip - Connector A

Pulling grip	Yes
Tensile Strength	440 N (98.92 lbf)
Grip Outer Diameter	56 mm (2.2 in)

Pulling Grip - Connector B

Min. Duct Size Diameter	89 mm (3.5 in)
-------------------------	----------------

Dimensions

Length	100 ft
Cable Weight	122 kg/km (81.98 lb/1000 ft)

Ordering Information

Product Number	G8990E4GPNCDX100F
Packaging Method	Plastic reel
Reel Diameter	23.5 in
Reel Width	5 in
Units per Delivery	1/1

Furcation - Connector A

Leg Length	1524 mm -0 / +76mm (60 in -0 / +2.99in)
Furcation Type	EDGE™ Size 2, 20 mm x 20 mm x 108.6 mm
Leg Color	Yellow
Leg Diameter	2 mm (0.08 in)
Leg Count	12

EDGE™ MTP® Extender Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Furcation - Connector B	
Leg Color	Yellow
Furcation Type	EDGE™ Size 2, 20 mm x 20 mm x 108.6 mm
Leg Diameter	2 mm (0.08 in)
Leg Length	838 mm -0 / +76mm (32.99 in -0 / +2.99in)
Leg Count	12



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.