

EDGE™ MTP® Extender Trunk 576F, 50 µm multimode (OM4), 100 ft

CORNING

Part Number:
G9375AZQPNCDX100F

The EDGE™ MTP® Extender Trunks provide additional distance for the backbone of the EDGE Solution. With a non-pinned MTP on one end of the cable, a pinned MTP on the other and a TIA-568 Type-A polarity, these trunks are designed to interface with a EDGE or Plug & Play™ module and an MTP trunk. All trunks are shipped with strain-relief clips that allow for the tool-less installation in both EDGE and Plug & Play housings. Most often these extender trunks will be used in a Zone Distribution Area (ZDA).

Features and Benefits

Snap-in strain-relief clips

Provide easier cable management

Small outer diameter

Improves cable tray fill ratio and allows for imported airflow

Low-loss connectivity


Enables system design flexibility

Bend-improved fiber

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

Corning® CleanAdvantage™ technology and optimized dust cap

Eliminates the need for scoping and cleaning prior to initial field connection



EDGE™ MTP® Extender Trunk, 576F, MTP (pinned) to MTP (non-pinned) with 60 inch/33 inch legs, 50 µm multimode (OM4), pulling grip on one end, 100 ft

EDGE™ MTP® Extender Trunk 576F, 50 µm multimode (OM4), 100 ft

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	50 µm MM (OM4)
Cable Assembly Type	EDGE™ Trunk
Environment	Indoor
Cable Type	Indoor: ANSI/ICEA S-83-596
Pulling grip	Yes
Connector Assembly Type	MTP to MTP

Standards

Fiber Standards	IEC 60793-2-10 for A1a class 50/125 multimode fibers; TIA/EIA 492AAAD (OM4); ITU-T Recommendation G.651; ISO/IEC 11801 Ed.2.2 Grade OM4
Reaction to Fire	Cca, s1b, d1, a1
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6

Environmental Conditions

Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)
------------------------------	------------------------------------

Design

Fiber Count	576
Polarity	Extender, TIA-568 Type-A
Fiber Type	Multimode

Mechanical Specifications

Nominal Outer Diameter	24.5 mm (0.96 in)
------------------------	--------------------

EDGE™ MTP® Extender Trunk 576F, 50 µm multimode (OM4), 100 ft

CORNING

Mechanical Specifications

Max. Tensile Strength for Installation	440 N (98.92 lbf)
Min. Bend Radius Installation	367.5 mm (14.47 in)
Min. Bend Radius Operation	122.5 mm (4.82 in)
Minimum Conduit Size with 18-in Elbow	64 mm (2.52 in)

Optical Characteristics

Fiber Code	T
Performance Option Code	90
Fiber Category	OM4
Fiber Type	Multimode
Fiber Name	50 µm MM (OM4)
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fiber Compliance	IEC 60793-2-10
Fiber Core Diameter	50 µm
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	550 m / -
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km

Specifications - Connector A

Insertion Loss, Max.	0.25 dB
Boot Color	Black
Connector Type	MTP® (pinned)
Ferrule Material	Composite
Reflectance	< -20 dB

EDGE™ MTP® Extender Trunk 576F, 50 µm multimode (OM4), 100 ft

CORNING

Specifications - Connector B

Insertion Loss, Max.	0.25 dB
Boot Color	Black
Connector Type	MTP® (non-pinned)
Ferrule Material	Composite
Reflectance	< -20 dB

Pulling Grip - Connector A

Pulling grip	Yes
Tensile Strength	440 N (98.92 lbf)
Grip Outer Diameter	48 mm (1.89 in)

Pulling Grip - Connector B

Min. Duct Size Diameter	50 mm (1.97 in)
-------------------------	-----------------

Dimensions

Length	100 ft
Cable Weight	469.4 kg/km (315.42 lb/1000 ft)

Ordering Information

Product Number	G9375AZQPNCDX100F
Packaging Method	plywood-reel
Units per Delivery	1/1

Furcation - Connector A

Leg Length	1524 mm -0 / +76mm (60 in -0 / +2.99in)
Furcation Type	Heat-shrink with strain-relief

EDGE™ MTP® Extender Trunk 576F, 50 µm multimode (OM4), 100 ft

CORNING

Furcation - Connector A

Leg Color	Aqua
Leg Diameter	2 mm (0.08 in)
Leg Count	48

Furcation - Connector B

Leg Color	Aqua
Furcation Type	Heat-shrink with strain-relief
Leg Diameter	2 mm (0.08 in)
Leg Length	838 mm -0 / +76mm (32.99 in -0 / +2.99in)
Leg Count	48



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.