

# EDGE™ MTP® Extender Trunk 288F, 50 µm multimode (OM4), 100 ft

CORNING

**Part Number:**  
**G9375U8QPNC DX100F**

The EDGE™ MTP® Extender Trunks provide additional distance for the backbone of the EDGE Solution. With a non-pinned MTP on one end of the cable, a pinned MTP on the other and a TIA-568 Type-A polarity, these trunks are designed to interface with a EDGE or Plug & Play™ module and an MTP trunk. All trunks are shipped with strain-relief clips that allow for the tool-less installation in both EDGE and Plug & Play housings. Most often these extender trunks will be used in a Zone Distribution Area (ZDA).

## Features and Benefits

### **Snap-in strain-relief clips**

Provide easier cable management

### **Small outer diameter**

Improves cable tray fill ratio and allows for imported airflow

### **Low-loss connectivity**


Enables system design flexibility

### **Bend-improved fiber**

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

### **Corning® CleanAdvantage™ technology and optimized dust cap**

Eliminates the need for scoping and cleaning prior to initial field connection



EDGE™ MTP® Extender Trunk, 288F, MTP (pinned) to MTP (non-pinned) with 60 inch/33 inch legs, 50 µm multimode (OM4), pulling grip on one end, 100 ft

# EDGE™ MTP® Extender Trunk 288F, 50 µm multimode (OM4), 100 ft

CORNING

## Specifications

### General Specifications

|                         |                            |
|-------------------------|----------------------------|
| Flame Rating            | Plenum (OFNP)              |
| Fiber Category          | 50 µm MM (OM4)             |
| Cable Assembly Type     | EDGE™ Trunk                |
| Environment             | Indoor                     |
| Cable Type              | Indoor: ANSI/ICEA S-83-596 |
| Pulling grip            | Yes                        |
| Connector Assembly Type | MTP to MTP                 |

### Standards

|                        |                                                                                                                                         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Fiber Standards        | IEC 60793-2-10 for A1a class 50/125 multimode fibers; TIA/EIA 492AAAD (OM4); ITU-T Recommendation G.651; ISO/IEC 11801 Ed.2.2 Grade OM4 |
| Reaction to Fire       | Cca, s1b, d1, a1                                                                                                                        |
| RoHS                   | Free of hazardous substances according to RoHS 2011/65/EU                                                                               |
| Approvals and Listings | NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6                                                                              |

### Environmental Conditions

|                              |                                    |
|------------------------------|------------------------------------|
| Temperature Range, Operation | -10 °C to 60 °C (14 °F to 140 °F ) |
|------------------------------|------------------------------------|

### Design

|             |                          |
|-------------|--------------------------|
| Fiber Count | 288                      |
| Polarity    | Extender, TIA-568 Type-A |
| Fiber Type  | Multimode                |

### Mechanical Specifications

|                        |                  |
|------------------------|------------------|
| Nominal Outer Diameter | 16 mm (0.63 in ) |
|------------------------|------------------|

# EDGE™ MTP® Extender Trunk 288F, 50 µm multimode (OM4), 100 ft

CORNING

## Mechanical Specifications

|                                        |                   |
|----------------------------------------|-------------------|
| Max. Tensile Strength for Installation | 440 N (98.92 lbf) |
| Min. Bend Radius Installation          | 250 mm (9.84 in)  |
| Min. Bend Radius Operation             | 80 mm (3.15 in)   |
| Minimum Conduit Size with 18-in Elbow  | 51 mm (2.01 in)   |

## Optical Characteristics

|                                         |                          |
|-----------------------------------------|--------------------------|
| Fiber Code                              | T                        |
| Performance Option Code                 | 90                       |
| Fiber Category                          | OM4                      |
| Fiber Type                              | Multimode                |
| Fiber Name                              | 50 µm MM (OM4)           |
| Maximum Attenuation                     | 2.8 dB/km / 1.0 dB/km    |
| Wavelengths                             | 850 nm / 1300 nm         |
| Fiber Compliance                        | IEC 60793-2-10           |
| Fiber Core Diameter                     | 50 µm                    |
| Serial 1 Gigabit Ethernet               | 1000 m / 600 m           |
| Serial 10 Gigabit Ethernet              | 550 m / -                |
| Minimum Effective Modal Bandwidth (EMB) | 4700 MHz*km / -          |
| Min. Overfilled Launch (OFL) Bandwidth  | 3500 MHz*km / 500 MHz*km |

## Specifications - Connector A

|                      |               |
|----------------------|---------------|
| Insertion Loss, Max. | 0.25 dB       |
| Boot Color           | Black         |
| Connector Type       | MTP® (pinned) |
| Ferrule Material     | Composite     |
| Reflectance          | < -20 dB      |

# EDGE™ MTP® Extender Trunk 288F, 50 µm multimode (OM4), 100 ft

CORNING

## Specifications - Connector B

|                      |                   |
|----------------------|-------------------|
| Insertion Loss, Max. | 0.25 dB           |
| Boot Color           | Black             |
| Connector Type       | MTP® (non-pinned) |
| Ferrule Material     | Composite         |
| Reflectance          | < -20 dB          |

## Pulling Grip - Connector A

|                     |                   |
|---------------------|-------------------|
| Pulling grip        | Yes               |
| Tensile Strength    | 440 N (98.92 lbf) |
| Grip Outer Diameter | 38.1 mm (1.5 in)  |

## Pulling Grip - Connector B

|                         |                 |
|-------------------------|-----------------|
| Min. Duct Size Diameter | 50 mm (1.97 in) |
|-------------------------|-----------------|

## Dimensions

|              |                                 |
|--------------|---------------------------------|
| Length       | 100 ft                          |
| Cable Weight | 237.7 kg/km (159.73 lb/1000 ft) |

## Ordering Information

|                    |                    |
|--------------------|--------------------|
| Product Number     | G9375U8QPNC DX100F |
| Packaging Method   | corrugated-box     |
| Units per Delivery | 1/1                |

## Furcation - Connector A

|                |                                         |
|----------------|-----------------------------------------|
| Leg Length     | 1524 mm -0 / +76mm (60 in -0 / +2.99in) |
| Furcation Type | Heat-shrink with strain-relief          |

# EDGE™ MTP® Extender Trunk 288F, 50 µm multimode (OM4), 100 ft

CORNING

## Furcation - Connector A

|              |                |
|--------------|----------------|
| Leg Color    | Aqua           |
| Leg Diameter | 2 mm (0.08 in) |
| Leg Count    | 24             |

## Furcation - Connector B

|                |                                           |
|----------------|-------------------------------------------|
| Leg Color      | Aqua                                      |
| Furcation Type | Heat-shrink with strain-relief            |
| Leg Diameter   | 2 mm (0.08 in)                            |
| Leg Length     | 838 mm -0 / +76mm (32.99 in -0 / +2.99in) |
| Leg Count      | 24                                        |



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.