

EDGE™ Bidi Tap Module 50 μm MM (OM4), 50/50 split ratio (live/tap), two red LC duplex adapters labeled TAP, two aqua LC duplex adapters labeled LIVE, supports Cisco's Bi-directional transceivers only

CORNING

Part Number:
ETM-5A-Q-BD

EDGE™ Bidi tap modules, part of EDGE solutions for data centers and storage area networks (SAN), enable passive optical tapping of Cisco's 40G multimode BiDi links while reducing downtime and link loss and increasing rack space utilization and density compared to other optical tap options.

EDGE Bidi tap modules use an advanced splitter technology for multimode to reduce insertion loss compared to traditional splitter technology.



EDGE™ Bidirectional Tap Module, 50 μm MM (OM4), 50/50 split ratio (live/tap), two red LC duplex adapters labeled TAP, two aqua LC duplex adapters labeled LIVE, supports Cisco's Bi-directional transceivers only



EDGE™ Bidirectional Tap Module, 50 μm MM (OM4), 50/50 split ratio (live/tap), two red LC duplex adapters labeled TAP, two aqua LC duplex adapters labeled LIVE, supports Cisco's Bi-directional transceivers only

EDGE™ Bidi Tap Module 50 µm MM (OM4), 50/50 split ratio (live/tap), two red LC duplex adapters labeled TAP, two aqua LC duplex adapters labeled LIVE, supports Cisco's Bi-directional transceivers only

CORNING

Specifications

General Specifications

Product Type	Panels and Modules
Fiber Category	50 µm MM (OM4)
Application	Data Center

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Temperature Range, Operation	-5 °C to 70 °C (23 °F to 158 °F)
Temperature Range, Storage	-40 °C to 85 °C (-40 °F to 185 °F)

Design

Fiber Count	8
Adapter Type Master Level	MTP®/MPO
Adapter Color Front	Aqua / Red
Adapter Type Front	Shuttered LC
Housing Type	Panels and Modules
Number of Adapters per Panel	4

Cable Design

Polarity	Straight-Through, TIA-568 Type-A
----------	----------------------------------

Optical Specification - Hardware

Split Ratio Live/Tap	50/50
Splitter Loss for Tap Modules	3.8 dB LIVE / 3.8 dB TAP

EDGE™ Bidi Tap Module 50 µm MM (OM4), 50/50 split ratio (live/tap), two red LC duplex adapters labeled TAP, two aqua LC duplex adapters labeled LIVE, supports Cisco's Bi-directional transceivers only

CORNING

Optical Specification - Hardware

Wavelengths	850 nm / 900 nm
Fiber Category	50 µm MM (OM4)

Specifications - Connector A

Connector Type	LC duplex
Ferrule Material	Composite

Specifications - Connector B

Connector Type	LC duplex
Ferrule Material	Composite

Dimensions

Weight	1 kg
--------	------

Ordering Information

Product Number	ETM-5A-Q-BD
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.