

EDGE™ Module, Ultra Low Loss 12F, 50 µm multimode (OM4), Shuttered LC PC Duplex Multimode to MTP® pinned MM

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font.

Part Number:
ECM-UM12-05-93Q-ULL-VI

EDGE™ modules provide the interface between the MTP® connector on the trunk and the LC duplex patch cords that will then connect directly into the electronics or as a crossconnect in the main distribution area (MDA). These modules feature VFL-compatible LC shuttered adapters and are manufactured with Corning® CleanAdvantage™ Technology, an innovative factory cleaning and sealing process that minimizes debris transfer and allows you to connect with confidence.

The ultra-low-loss modules allow for extended-reach capabilities in high-speed serial duplex transmission. OM3/OM4/OM5 EDGE ultra-low-loss modules are specified to 0.35 dB compared to 0.5 dB for the low-loss EDGE module. The OS2 EDGE ultra-low-loss modules are specified to 0.60 dB compared to 1.0 dB for the standard EDGE module.

EDGE™ Module, Ultra Low Loss 12F, 50 µm multimode (OM4), Shuttered LC PC Duplex Multimode to MTP® pinned MM

CORNING

Specifications

General Specifications

Product Type	Panels and Modules
Application	Data Center

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Design

Fiber Count	12
Adapter Type Back	MTP®
Adapter Color Back	Violet
Adapter Color Front	Violet
Adapter Type Front	Shuttered LC
Housing Type	Modules
Color	Black
Panel or Module Type	EDGE
Number of Adapters per Panel	1

Cable Design

Polarity	TIA-568 Type-B
----------	----------------

Optical Specification - Hardware

Module Insertion Loss, Max	0.35 dB
----------------------------	---------

Specifications - Connector A

Connector Type	LC Uniboot
----------------	------------

EDGE™ Module, Ultra Low Loss 12F, 50 µm multimode (OM4), Shuttered LC PC Duplex Multimode to MTP® pinned MM

CORNING

Specifications - Connector A

Polish	PC
Ferrule Material	Composite
Insertion Loss, Max.	≤ 0.25 dB

Specifications - Connector B

Connector Type	MTP® (pinned)
Ferrule Material	Ceramic
Insertion Loss, Max.	≤ 0.10 dB

Dimensions

Width	90 mm (3.54 in)
Depth	124 mm (4.88 in)

Ordering Information

Product Number	ECM-UM12-05-93Q-ULL-VI
Packaging Method	Individual Blister Packs
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.