

EDGE™ Hybrid Trunk 36F, 50 µm multimode (OM4), 100 ft

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font.

Part Number:
G757936QPNDLW100F

EDGE™ MTP® to LC uniboot hybrid trunks combine non-pinned MTP connectors, which connect to EDGE modules, and LC uniboot connectors, which connect directly to the electronics. These trunks enable additional options for cabling of data centers. All hybrid trunks are manufactured with Corning® CleanAdvantage™ technology and shipped with strain-relief clips to allow easy tool-less installation.

Features and Benefits

Snap-in strain-relief clips

Provide easier cable management

Small outer diameter

Improves cable tray fill ratio and allows for imported airflow

Low-loss connectivity

Enables system design flexibility

Bend-improved fiber

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

Corning® CleanAdvantage™ technology and optimized dust cap

Eliminates the need for scoping and cleaning prior to initial field connection

EDGE™ Hybrid Trunk 36F, 50 µm multimode (OM4), 100 ft

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	50 µm MM (OM4)
Cable Assembly Type	EDGE™ Trunk
Environment	Indoor
Cable Type	Indoor: ANSI/ICEA S-83-596
Connector Assembly Type	MTP to LC

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6

Environmental Conditions

Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)
------------------------------	------------------------------------

Design

Fiber Count	36
Polarity	Universal hybrid
Fiber Type	Multimode

Mechanical Specifications

Nominal Outer Diameter	8 mm (0.31 in)
Weight	56 kg/km (37.63 lb/1000 ft)
Minimum Conduit Size with 18-in Elbow	64 mm (2.52 in)

EDGE™ Hybrid Trunk 36F, 50 µm multimode (OM4), 100 ft

CORNING

Specifications - Connector A

Insertion Loss, Max.	0.25 dB
Boot Color	Black
Connector Type	MTP® (non-pinned)
Ferrule Material	Composite
Reflectance	< -20 dB

Specifications - Connector B

Insertion Loss, Max.	0.15 dB
Boot Color	Aqua
Connector Type	LC Uniboot
Ferrule Material	Ceramic
Reflectance	< -20 dB

Pulling Grip - Connector A

Pulling grip	Yes
Tensile Strength	440 N (98.92 lbf)

Dimensions

Length	100 ft
Cable Weight	56 kg/km (37.63 lb/1000 ft)

Ordering Information

Product Number	G757936QPNDLW100F
Packaging Method	Plastic reel

EDGE™ Hybrid Trunk 36F, 50 µm multimode (OM4), 100 ft

CORNING

Furcation - Connector A

Leg Length	838 mm (32.99 in)
Furcation Type	EDGE™ Size 1, 14.7 mm x 14.7 mm x 108.6 mm
Leg Color	Aqua
Leg Diameter	2 mm (0.08 in)
Leg Count	3

Furcation - Connector B

Leg Color	Aqua
Furcation Type	EDGE™ Size 2, 20 mm x 20 mm x 108.6 mm
Leg Diameter	2 mm (0.08 in)
Leg Length	914 mm (35.98 in)
Leg Count	18



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.