

EDGE™ Hybrid Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Part Number:
G9078E4GPNDLW100F

EDGE™ MTP® to LC uniboot hybrid trunks combine non-pinned MTP connectors, which connect to EDGE modules, and LC uniboot connectors, which connect directly to the electronics. These trunks enable additional options for cabling of data centers. All hybrid trunks are manufactured with Corning® CleanAdvantage™ technology and shipped with strain-relief clips to allow easy tool-less installation.

Features and Benefits

Snap-in strain-relief clips

Provide easier cable management

Small outer diameter

Improves cable tray fill ratio and allows for imported airflow

Low-loss connectivity


Enables system design flexibility

Bend-improved fiber

Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

Corning® CleanAdvantage™ technology and optimized dust cap

Eliminates the need for scoping and cleaning prior to initial field connection



EDGE™ Solutions Hybrid Trunk Cable, 144 F, MTP® (non-pinned) Connector to LC Duplex Uniboot, with 33/36 inch legs, pulling grip one side, Single-mode (OS2), 100 ft

EDGE™ Hybrid Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	Bend-improved SM (OS2)
Cable Assembly Type	EDGE™ Trunk
Environment	Indoor
Cable Type	Indoor: ANSI/ICEA S-83-596
Pulling grip	Yes
Connector Assembly Type	MTP to LC

Standards

Fiber Standards	ITU-T G.652.D and ITU-T G.657.A1
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6

Environmental Conditions

Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)
------------------------------	------------------------------------

Design

Fiber Count	144
Polarity	Universal hybrid
Fiber Type	Single-mode

Mechanical Specifications

Nominal Outer Diameter	12.5 mm (0.49 in)
Max. Tensile Strength for Installation	445 N (100.04 lbf)
Min. Bend Radius Installation	187.45 mm (7.38 in)

EDGE™ Hybrid Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Mechanical Specifications

Min. Bend Radius Operation	62.48 mm (2.46 in)
Weight	130 kg/km (87.36 lb/1000 ft)
Minimum Conduit Size with 18-in Elbow	76 mm (2.99 in)

Optical Characteristics

Fiber Code	Z
Performance Option Code	01
Fiber Category	OS2
Fiber Type	Single-mode (OS2) / 250 µm
Fiber Name	Bend-Improved Single-mode (OS2)
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Compliance	ITU-T G.652.D and ITU-T G.657.A1

Specifications - Connector A

Insertion Loss, Max.	0.35 dB
Boot Color	Black
Connector Type	MTP® (non-pinned)
Ferrule Material	Composite
Reflectance	< -65 dB

Specifications - Connector B

Insertion Loss, Max.	0.25 dB
Boot Color	Blue
Connector Type	LC Uniboot
Ferrule Material	Ceramic
Reflectance	< -55 dB

EDGE™ Hybrid Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Pulling Grip - Connector A

Pulling grip	Yes
Tensile Strength	440 N (98.92 lbf)
Grip Outer Diameter	56 mm (2.2 in)

Pulling Grip - Connector B

Min. Duct Size Diameter	76 mm (2.99 in)
-------------------------	-----------------

Dimensions

Length	100 ft
Cable Weight	130 kg/km (87.36 lb/1000 ft)

Ordering Information

Product Number	G9078E4GPNDLW100F
Packaging Method	Plastic reel
Reel Diameter	23.5 in
Reel Width	5 in
Units per Delivery	1/1

Furcation - Connector A

Leg Length	838 mm -0 / +76mm (32.99 in -0 / +2.99in)
Furcation Type	EDGE™ Size 2, 20 mm x 20 mm x 108.6 mm
Leg Color	Yellow
Leg Diameter	2 mm (0.08 in)
Leg Count	12

EDGE™ Hybrid Trunk 144F, Bend-Improved single-mode (OS2), 100 ft

CORNING

Furcation - Connector B	
Leg Color	Yellow
Furcation Type	Plug & Play™ Size 2, 82.5 mm x 43.2 mm x 38.1 mm
Leg Diameter	2 mm (0.08 in)
Leg Length	914 mm (35.98 in)
Leg Count	72



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.