

# ALTOS® Loose Tube, Gel-Free, All-Dielectric Cable with FastAccess® Technology 6 F, 50 $\mu$ m multimode (OM4)

CORNING

**Part Number:**  
**006TU4-T4790D20**

Corning ALTOS® cable with FastAccess® technology is an all-dielectric gel-free cable designed for outdoor and limited indoor use for campus backbones in lashed aerial and duct installations. The innovative FastAccess technology feature combined with the all-dielectric gel-free loose tube design simplifies removal of the cable jacket reducing cable end access time by at least 50 percent. Equally important is the overall reduction in risk of inadvertent fiber damage and risk to installers from sharp cable access tools. The cable is fully waterblocked using craft-friendly, water-swallowable materials, which means no clean up is required. The flexible buffer tubes are easy to route in closures, and the SZ-stranded, loose tube design isolates fibers from installation and environmental rigors while allowing easy mid-span access. The all-dielectric gel-free cable construction requires no bonding or grounding, and these cables have a medium-density polyethylene jacket that is rugged, durable and easy to handle. A variety of fiber types are available including 62.5  $\mu$ m and 50  $\mu$ m, single-mode and hybrid versions, as well as fibers with Gigabit and 10 Gigabit Ethernet performance.

## Features and Benefits

### Contains FastAccess® technology

Innovative cable jacket feature reduces cable end access time, reduces overall risk of inadvertent fiber damage, as well as, risk to installers from sharp cable access tools

### Polyethylene jacket

Rugged, durable and easy to strip (while providing superior protection against UV radiation, fungus, abrasion and other environmental factors)

### Fully waterblocked loose tube all-dielectric gel-free design



Simple access and no clean up

### Industry-standard performance

Meets the requirements of Telcordia GR-20, Issue 3 and ICEA S-87-640

### Available in 62.5 $\mu$ m, 50 $\mu$ m, single-mode and hybrid versions

Ready for any application including Gigabit Ethernet and 10 Gigabit Ethernet



# ALTOS® Loose Tube, Gel-Free, All-Dielectric Cable with FastAccess® Technology 6 F, 50 µm multimode (OM4)

CORNING

## Specifications

### General Specifications

|                      |                |
|----------------------|----------------|
| Installation Methods | Aerial, Duct   |
| Cable Type           | Loose Tube     |
| Environment          | Outdoor        |
| Product Type         | Dielectric     |
| Fiber Category       | 50 µm MM (OM4) |
| Cable geometry       | Round          |

### Standards

|                          |                                                                                                                 |
|--------------------------|-----------------------------------------------------------------------------------------------------------------|
| RoHS                     | Free of hazardous substances according to RoHS 2011/65/EU                                                       |
| Common Installations     | Outdoor lashed aerial and duct, indoor when installed according to National Electrical Code® (NEC®) Article 770 |
| Design and Test Criteria | ANSI/ICEA S-87-640                                                                                              |

### Environmental Conditions

|                                 |                                                                                                                                                                                                                |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes                           | Corning recommends storing cable in a proper temperature environment prior to installation to allow the cable temperature to meet installation temperature range specifications for best installation results. |
| Temperature Range, Installation | -30 °C to 70 °C (-22 °F to 158 °F )                                                                                                                                                                            |
| Temperature Range, Operation    | -40 °C to 70 °C (-40 °F to 158 °F )                                                                                                                                                                            |
| Temperature Range, Storage      | -40 °C to 70 °C (-40 °F to 158 °F )                                                                                                                                                                            |

### Cable Design

|                       |                   |
|-----------------------|-------------------|
| Central Element       | Dielectric        |
| Fiber Count           | 6                 |
| Outer Jacket Color    | Black             |
| Outer Jacket Material | Polyethylene (PE) |
| Buffer Tube Color     | Blue              |

# ALTOS® Loose Tube, Gel-Free, All-Dielectric Cable with FastAccess® Technology 6 F, 50 µm multimode (OM4)

CORNING

## Cable Design

|                            |                                          |
|----------------------------|------------------------------------------|
| Buffer Tube Diameter       | 2.5 mm (0.1 in)                          |
| Number of Active Tubes     | 1                                        |
| Number of Filling Elements | 5                                        |
| Number of Tube Positions   | 6                                        |
| Tape                       | Water-swellaable                         |
| Fiber Coloring             | Blue, Orange, Green, Brown, Slate, White |
| Fibers per Tube            | 6                                        |
| Color Code Standards       | Telcordia                                |

## Mechanical Specifications

|                                   |                     |
|-----------------------------------|---------------------|
| Max. Tensile Strength, Long-Term  | 890 N (200.08 lbf)  |
| Max. Tensile Strength, Short-Term | 2700 N (606.98 lbf) |
| Nominal Outer Diameter            | 10.5 mm (0.41 in )  |
| Min. Bend Diameter Installation   | 316 mm (12.44 in)   |
| Min. Bend Diameter Operation      | 210 mm (8.27 in)    |

## Optical Characteristics

|                            |                       |
|----------------------------|-----------------------|
| Fiber Code                 | T                     |
| Performance Option Code    | 90                    |
| Fiber Category             | OM4                   |
| Fiber Type                 | Multimode             |
| Fiber Name                 | 50 µm MM (OM4)        |
| Maximum Attenuation        | 3.0 dB/km / 1.0 dB/km |
| Wavelengths                | 850 nm / 1300 nm      |
| Fiber Compliance           | IEC 60793-2-10        |
| Fiber Core Diameter        | 50 µm                 |
| Serial 1 Gigabit Ethernet  | 1000 m / 600 m        |
| Serial 10 Gigabit Ethernet | 550 m / -             |

# ALTOS® Loose Tube, Gel-Free, All-Dielectric Cable with FastAccess® Technology 6 F, 50 µm multimode (OM4)

CORNING

## Optical Characteristics

|                                         |                          |
|-----------------------------------------|--------------------------|
| Minimum Effective Modal Bandwidth (EMB) | 4700 MHz*km / -          |
| Min. Overfilled Launch (OFL) Bandwidth  | 3500 MHz*km / 500 MHz*km |

## Dimensions

|              |                             |
|--------------|-----------------------------|
| Cable Weight | 73 kg/km (49.05 lb/1000 ft) |
|--------------|-----------------------------|



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.