

EDGE™ Solutions Jumper, 2 F, LC Uniboot to SC Duplex, Interconnect Cable, Riser 50 µm multimode (OM4), 3 m

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font.

Part Number:
577902QD120003M

EDGE™ Solutions jumpers are integrated reverse-polarity uniboot duplex assemblies that meet the high-density space requirements of the MDA and EDA and provide a 50-percent reduction in bulk cabling when compared to traditional duplex jumpers. The highly flexible, 2-fiber interconnect cable reduces cable congestion, improves jumper management and routing and improves air circulation.

Enabled by Corning® ClearCurve® multimode optical fiber, EDGE™ Solutions jumpers feature ultra-bendable performance and accommodate a minimum bend-radius of 10 mm with minimal bend-induced attenuation loss. With this bend performance, EDGE Solutions jumpers can greatly reduce outages and degradation in systems caused by severe bending problems.

Additional detailed furcation images are available in the Cable Assembly Family Specification Sheet.

EDGE™ Solutions Jumper, 2 F, LC Uniboot to SC Duplex, Interconnect Cable, Riser 50 µm multimode (OM4), 3 m

CORNING

Specifications

General Specifications

Flame Rating	Riser (OFNR)
Fiber Category	50 µm MM (OM4)
Product Category	Core Product
Cable Assembly Type	Two Fiber
Application	Data Center
Cable Type	Tight-Buffered
Installation Methods	General Building Applications, Riser

Standards

Fiber Standards	TIA/EIA-492AAAC-A, Tested with minEMBc method to TIA/EIA-455-220, IEC 60793-2-10 Type A1a.2 Ed.2.0, IEC 60793-1-49 Ed.2.0, ITU-T G.651, ISO/IEC 11801 Ed.2.2 Cat. OM3
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design

Fiber Count	2
Outer Jacket Color	Aqua
Fiber Type	Multimode

Mechanical Specifications

Minimum Bend Radius	10 mm (0.39 in)
Nominal Outer Diameter	3.3 mm (0.13 in)
Max. Tensile Strength, Short-Term	890 N (200.08 lbf)
Max. Tensile Strength for Installation	2700 N (606.98 lbf)

EDGE™ Solutions Jumper, 2 F, LC Uniboot to SC Duplex, Interconnect Cable, Riser 50 µm multimode (OM4), 3 m

CORNING

Optical Characteristics

Fiber Code	T
Performance Option Code	90
Fiber Category	OM4
Fiber Type	Multimode
Fiber Name	50 µm MM (OM4)
Maximum Attenuation	3.0 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fiber Compliance	IEC 60793-2-10
Fiber Core Diameter	50 µm
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	550 m / -
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km

Specifications - Connector A

Boot Color	Aqua
Connector Type	LC Uniboot
Ferrule Material	Ceramic
Housing Color	Black
Housing Material	Composite

Specifications - Connector B

Boot Color	Aqua
Connector Type	SC Duplex
Ferrule Material	Ceramic
Housing Color	Black

EDGE™ Solutions Jumper, 2 F, LC Uniboot to SC Duplex, Interconnect Cable, Riser 50 μm multimode (OM4), 3 m



Dimensions	
Length	3 m (9.84 ft)

Ordering Information	
Product Number	577902QD120003M
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.