

EDGE™ Conversion Harness 50 µm multimode (OM4), 10 ft, two 12 F 24-in pinned MTP® legs, three 8 F 36-in non-pinned MTP legs

The Corning logo is a solid blue square with the word "CORNING" in white, uppercase, sans-serif font centered within it.

Part Number:
H937524QPH-KLA010F

EDGE™ conversion harness is a LS0H-rated preterminated harness that, like the EDGE module, provides the conversion from 12- to 8-fiber connectivity for full-fiber utilization. It is offered as a 2x3 MTP® harness (two 12-fiber MTP connectors on one end, three 8-fiber MTP connectors on the other) for connection to electronics with MPO-style ports.

EDGE harnesses are a TIA-568 Type-A component.

EDGE™ Conversion Harness 50 µm multimode (OM4), 10 ft, two 12 F 24-in pinned MTP® legs, three 8 F 36-in non-pinned MTP legs

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	50 µm MM (OM4)
Cable Assembly Type	EDGE™ Harness
Cable Type	Indoor: ANSI/ICEA S-83-596
Connector Assembly Type	MTP to MTP

Standards

Fiber Standards	IEC 60793-2-10 for A1a class 50/125 multimode fibers; TIA/EIA 492AAAD (OM4); ITU-T Recommendation G.651; ISO/IEC 11801 Ed.2.2 Grade OM4
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Environmental Conditions

Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)
------------------------------	------------------------------------

Design

Fiber Count	8
Polarity	TIA-568 Type-A

Mechanical Specifications

Nominal Outer Diameter	2 mm (0.08 in)
Max. Tensile Strength for Installation	220 N (49.46 lbf)
Min. Bend Radius Installation	30 mm (1.18 in)
Min. Bend Radius Operation	10 mm (0.39 in)

EDGE™ Conversion Harness 50 µm multimode (OM4), 10 ft, two 12 F 24-in pinned MTP® legs, three 8 F 36-in non-pinned MTP legs

CORNING

Optical Characteristics

Fiber Code	T
Performance Option Code	90
Fiber Category	OM4
Fiber Type	Multimode
Fiber Name	50 µm MM (OM4)
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fiber Compliance	IEC 60793-2-10
Fiber Core Diameter	50 µm
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	550 m / -
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km

Specifications - Connector A

Reflectance, Typical	< -20 dB
Insertion Loss, Max.	0.35 dB
Connector Type	MTP® (pinned)
Ferrule Material	Composite

Specifications - Connector B

Reflectance, Typical	< -20 dB
Insertion Loss, Max.	0.25 dB
Connector Type	MTP® (non-pinned)
Ferrule Material	Ceramic

Dimensions

Length	10 ft
--------	-------

EDGE™ Conversion Harness 50 µm multimode (OM4), 10 ft, two 12 F 24-in pinned MTP® legs, three 8 F 36-in non-pinned MTP legs

CORNING

Dimensions

Cable Weight	4.6 kg/km (3.09 lb/1000 ft)
--------------	-----------------------------

Ordering Information

Product Number	H937524QPH-KLA010F
Units per Delivery	1/1

Furcation - Connector A

Leg Length	914.4 mm -0 / +76.2mm (36 in -0 / +3in)
Furcation Type	EDGE™ Harness Plug
Leg Color	Aqua
Leg Diameter	2 mm (0.08 in)



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.