

EDGE™ MTP® Trunk Bend-improved Single-mode (OS2), MTP® Connector to MTP Connector, 96 F, with 33/33 inch legs, pulling grip one side, 100 ft

CORNING

Part Number:
G909096GPNDDU100F

EDGE™ MTP® trunks provide the backbone of the EDGE solution. With non-pinned MTP connectors on both ends, these fiber trunk cable assemblies are designed to interface with the EDGE solutions or Plug & Play™ systems modules. All MTP trunks are manufactured with Corning® CleanAdvantage™, MTP trunk cables are shipped with strain-relief clips to allow easy tool-less installation.

Features and Benefits

Snap-in strain-relief clips

Provide easier cable management

Small outer diameter

Improves cable tray fill ratio and allows for imported airflow

Low-loss connectivity

Enables system design flexibility

Bend-improved fiber


Allows tighter cable bends for slack storage and routing, less risk of downtime due to pinched or bent cables

Fiber optic trunk cable manufactured with Corning® CleanAdvantage™ technology and optimized dust cap

Eliminates the need for scoping and cleaning prior to initial field connection

Non-pinned MTP connectors on both ends

Fiber optic trunks designed to interface with the EDGE solutions or Plug & Play™ systems modules



EDGE™ MTP® Trunk Bend-improved Single-mode (OS2), MTP® Connector to MTP Connector, 96 F, with 33/33 inch legs, pulling grip one side, 100 ft

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	Bend-improved SM (OS2)
Cable Assembly Type	EDGE™ Trunk
Environment	Indoor
Application	Data Center
Pulling grip	Yes
Connector Assembly Type	MTP to MTP

Standards

Fiber Standards	ITU-T G.652.D and ITU-T G.657.A1
Reaction to Fire	Cca, s1b, d1, a1
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	NFPA 262, National Electrical Code® (NEC®), OFNP, CSA FT-6
Design and Test Criteria	ANSI/ICEA S-83-596

Environmental Conditions

Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)
------------------------------	------------------------------------

Design

Fiber Count	96
Polarity	Universal, TIA-568 Type-B
Strain-Relief Bracket Type	2
Fiber Type	Single-mode

EDGE™ MTP® Trunk Bend-improved Single-mode (OS2), MTP® Connector to MTP Connector, 96 F, with 33/33 inch legs, pulling grip one side, 100 ft

CORNING

Mechanical Specifications

Nominal Outer Diameter	11.9 mm ± 0.3mm (0.47 in ± 0.01in)
Max. Tensile Strength for Installation	660 N (148.37 lbf)
Min. Bend Radius Installation	178.5 mm (7.03 in)
Min. Bend Radius Operation	59.5 mm (2.34 in)
Weight	111 kg/km (74.59 lb/1000 ft)
Minimum Conduit Size with 18-in Elbow	77 mm (3.03 in)

Optical Characteristics

Fiber Code	Z
Performance Option Code	01
Fiber Category	OS2
Fiber Type	Single-mode (OS2) / 250 µm
Fiber Name	Bend-Improved Single-mode (OS2)
Maximum Attenuation	0.4 dB/km / 0.4 dB/km / 0.3 dB/km
Wavelengths	1310 nm / 1383 nm / 1550 nm
Fiber Compliance	ITU-T G.652.D and ITU-T G.657.A1

Specifications - Connector A

Insertion Loss, Max.	0.35 dB
Boot Color	Black
Connector Type	MTP® (non-pinned)
Ferrule Material	Composite
Reflectance	< -65 dB

Specifications - Connector B

Insertion Loss, Max.	0.35 dB
Boot Color	Black
Connector Type	MTP® (non-pinned)

EDGE™ MTP® Trunk Bend-improved Single-mode (OS2), MTP® Connector to MTP Connector, 96 F, with 33/33 inch legs, pulling grip one side, 100 ft

CORNING

Specifications - Connector B

Ferrule Material	Composite
Reflectance	< -65 dB

Pulling Grip - Connector A

Pulling grip	Yes
Tensile Strength	440 N (98.92 lbf)
Grip Outer Diameter	56 mm (2.2 in)

Pulling Grip - Connector B

Min. Duct Size Diameter	89 mm (3.5 in)
-------------------------	----------------

Dimensions

Length	100 ft
Cable Weight	111 kg/km (74.59 lb/1000 ft)

Ordering Information

Product Number	G909096GPNDU100F
Packaging Method	Plastic reel
Reel Diameter	23.5 in
Reel Width	5 in
Units per Delivery	1/1

Furcation - Connector A

Leg Length	838 mm -0 / +76mm (32.99 in -0 / +2.99in)
Furcation Type	EDGE™ Size 2, 20 mm x 20 mm x 108.6 mm
Leg Color	Yellow

EDGE™ MTP® Trunk Bend-improved Single-mode (OS2), MTP® Connector to MTP Connector, 96 F, with 33/33 inch legs, pulling grip one side, 100 ft

CORNING

Furcation - Connector A

Leg Diameter	2 mm (0.08 in)
Leg Count	8

Furcation - Connector B

Leg Color	Yellow
Furcation Type	EDGE™ Size 2, 20 mm x 20 mm x 108.6 mm
Leg Diameter	2 mm (0.08 in)
Leg Length	838 mm -0 / +76mm (32.99 in -0 / +2.99in)
Leg Count	8



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.