

# EDGE™ Module 12 Fiber, OS2, LC Duplex to MTP (pinned), Universal Polarity, 4-pack

CORNING

**Part Number:**  
**ECM-UM12-04-89G-Z**

EDGE™ low-loss modules provide an interface between the MTP® connector on an MTP trunk and the LC duplex jumpers that connect directly to the electronics. These modules feature VFL-compatible LC shuttered adapters and are manufactured with Corning® CleanAdvantage™ Technology, an innovative factory cleaning and sealing process that minimizes debris transfer and allows you to connect with confidence.

All EDGE modules meet RoHS standards and are ideal for data center, local area network (LAN), and storage area network (SAN) applications.



# EDGE™ Module 12 Fiber, OS2, LC Duplex to MTP (pinned), Universal Polarity, 4-pack

CORNING

## Specifications

### General Specifications

|                |                        |
|----------------|------------------------|
| Product Type   | Module                 |
| Fiber Category | Bend-improved SM (OS2) |
| Application    | Data Center            |

### Standards

|      |                                                           |
|------|-----------------------------------------------------------|
| RoHS | Free of hazardous substances according to RoHS 2011/65/EU |
|------|-----------------------------------------------------------|

### Design

|                     |                     |
|---------------------|---------------------|
| Fiber Count         | 12                  |
| Adapter Type Back   | MTP®                |
| Adapter Color Back  | Black               |
| Adapter Color Front | Blue                |
| Adapter Type Front  | Shuttered LC Duplex |
| Color               | Black               |
| Product Family      | EDGE                |

### Cable Design

|          |           |
|----------|-----------|
| Polarity | Universal |
|----------|-----------|

### Optical Specification - Hardware

|                            |      |
|----------------------------|------|
| Module Insertion Loss, Max | 1 dB |
|----------------------------|------|

### Specifications - Connector A

|                |           |
|----------------|-----------|
| Connector Type | LC duplex |
| Polish         | UPC       |

# EDGE™ Module 12 Fiber, OS2, LC Duplex to MTP (pinned), Universal Polarity, 4-pack

CORNING

## Specifications - Connector A

|              |     |
|--------------|-----|
| Endface Type | UPC |
|--------------|-----|

## Specifications - Connector B

|                  |               |
|------------------|---------------|
| Connector Type   | MTP® (pinned) |
| Polish           | APC           |
| Housing Material | Ceramic       |
| Ferrule Material | Composite     |

## Dimensions

|        |                    |
|--------|--------------------|
| Length | 231 mm (9.09 in)   |
| Height | 28.58 mm (1.13 in) |
| Width  | 165 mm (6.5 in)    |
| Weight | 0.57 kg            |

## Ordering Information

|                    |                                 |
|--------------------|---------------------------------|
| Product Number     | ECM-UM12-04-89G-Z               |
| Packaging Method   | Bulk Pack                       |
| Package Contents   | 4 EDGE modules per blister pack |
| Units per Delivery | 1/1                             |



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States  
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.