

EDGE™ Module 12 F, LC Duplex, PC to MTP® Connector, 50 µm multimode (OM4)

The Corning logo is a solid blue square with the word "CORNING" in white, uppercase, sans-serif font centered within it.

Part Number:
ECM-UM12-05-93Q-VI

EDGE™ low-loss modules provide an interface between the MTP® connector on an MTP trunk and the LC duplex jumpers that connect directly to the electronics. These modules feature VFL-compatible LC shuttered adapters and are manufactured with Corning® CleanAdvantage™ Technology, an innovative factory cleaning and sealing process that minimizes debris transfer and allows you to connect with confidence.

All EDGE modules meet RoHS standards and are ideal for data center, local area network (LAN), and storage area network (SAN) applications.

EDGE™ Module 12 F, LC Duplex, PC to MTP® Connector, 50 µm multimode (OM4)

CORNING

Specifications

General Specifications

Product Type	Panels and Modules
Fiber Category	50 µm MM (OM4)
Application	Data Center

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Design

Fiber Count	12
Adapter Type Back	MTP®
Adapter Color Back	Violet
Adapter Color Front	Violet
Adapter Type Front	Shuttered LC
Housing Type	Modules
Color	Black
Panel or Module Type	EDGE
Product Family	EDGE
Number of Adapters per Panel	1

Cable Design

Polarity	TIA-568 Type-B
----------	----------------

Optical Specification - Hardware

Module Insertion Loss, Max	0.5 dB
----------------------------	--------

EDGE™ Module 12 F, LC Duplex, PC to MTP® Connector, 50 µm multimode (OM4)

CORNING

Specifications - Connector A

Connector Type	LC duplex
Polish	PC
Ferrule Material	Composite
Endface Type	PC
Insertion Loss, Max.	0.35 dB

Specifications - Connector B

Connector Type	MTP® (pinned)
Polish	PC
Ferrule Material	Ceramic
Insertion Loss, Max.	0.15 dB

Dimensions

Width	113 mm (4.45 in)
Depth	124 mm (4.88 in)

Ordering Information

Product Number	ECM-UM12-05-93Q-VI
Packaging Method	Individual Blister Packs
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.