

EDGE™ Module 12 Fiber, OM4, LC Duplex to MTP (pinned), Universal Polarity, 4-pack

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font.

Part Number:
ECM-UM12-05-93Q-Z

EDGE™ low-loss modules provide an interface between the MTP® connector on an MTP trunk and the LC duplex jumpers that connect directly to the electronics. These modules feature VFL-compatible LC shuttered adapters and are manufactured with Corning® CleanAdvantage™ Technology, an innovative factory cleaning and sealing process that minimizes debris transfer and allows you to connect with confidence.

All EDGE modules meet RoHS standards and are ideal for data center, local area network (LAN), and storage area network (SAN) applications.

EDGE™ Module 12 Fiber, OM4, LC Duplex to MTP (pinned), Universal Polarity, 4-pack

CORNING

Specifications

General Specifications

Product Type	Module
Fiber Category	50 µm MM (OM4)
Application	Data Center

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Design

Fiber Count	12
Adapter Type Back	MTP®
Adapter Color Back	Aqua
Adapter Color Front	Aqua
Adapter Type Front	Shuttered LC Duplex
Color	Black
Product Family	EDGE

Cable Design

Polarity	Universal
----------	-----------

Optical Specification - Hardware

Module Insertion Loss, Max	1 dB
----------------------------	------

Specifications - Connector A

Connector Type	LC duplex
Polish	PC

EDGE™ Module 12 Fiber, OM4, LC Duplex to MTP (pinned), Universal Polarity, 4-pack

CORNING

Specifications - Connector A

Endface Type	PC
--------------	----

Specifications - Connector B

Connector Type	MTP® (pinned)
Polish	PC
Housing Material	Ceramic
Ferrule Material	Composite

Dimensions

Length	231 mm (9.09 in)
Height	28.58 mm (1.13 in)
Width	165 mm (6.5 in)
Weight	0.57 kg

Ordering Information

Product Number	ECM-UM12-05-93Q-Z
Packaging Method	Bulk Pack
Package Contents	4 EDGE modules per blister pack
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.