

ALTOS® Figure-8 Loose Tube, Gel-Free Cable 72 F, 50 µm multimode (OM2)

CORNING

Part Number:
072TUB-T4131D20

Corning ALTOS® figure-8 gel-free cables are self-supporting aerial cables designed for easy and economical one-step installation. The loose tube design provides stable performance over a wide temperature range and is compatible with any telecommunications-grade optical fiber. The gel-free design is fully waterblocked using craft-friendly water-swellaable materials, making cable access simple and requiring no clean up. While the flexible, craft-friendly buffer tubes are easy to route in closures, the SZ-stranded, loose tube design isolates optical fibers from installation and environmental rigors and facilitates mid-span access. The figure-8 cable design allows easy, one-step installation, using standard hardware and installation methods. These cables have a medium density polyethylene jacket that is rugged, durable and easy to strip.

Features and Benefits

Gel-free waterblocking technology


Craft-friendly cable preparation

Polyethylene jacket


Rugged, durable and easy to strip (while providing superior protection against UV radiation, fungus, abrasion and other environmental factors)

Figure-8 cable design

Easy, one-step installation



ALTOS® Figure-8 Loose Tube, Gel-Free Armored Cable, 72 F, 50 µm multimode (OM2)



ALTOS® Figure-8 Loose Tube, Gel-Free Armored Cable, 72 F, 50 µm multimode (OM2)

ALTOS® Figure-8 Loose Tube, Gel-Free Cable 72 F, 50 µm multimode (OM2)

CORNING

Specifications

General Specifications

Installation Methods	Aerial
Cable Type	Loose Tube
Environment	Outdoor
Product Type	Self-Supporting, Figure-8
Fiber Category	50 µm MM (OM2)
Cable geometry	Other

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Common Installations	Outdoor self-supporting aerial
Design and Test Criteria	ANSI/ICEA S-87-640

Environmental Conditions

Notes	Corning recommends storing cable in a proper temperature environment prior to installation to allow the cable temperature to meet installation temperature range specifications for best installation results.
Temperature Range, Installation	-30 °C to 70 °C (-22 °F to 158 °F)
Temperature Range, Operation	-40 °C to 70 °C (-40 °F to 158 °F)
Temperature Range, Storage	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design

Central Element	Dielectric
Fiber Count	72
Number of Ripcords	3
Outer Jacket Color	Black
Outer Jacket Material	Polyethylene (PE)

ALTOS® Figure-8 Loose Tube, Gel-Free Cable 72 F, 50 µm multimode (OM2)

CORNING

Cable Design

Tensile Strength Elements and/or Armoring - Layer 1	Corrugated steel tape armor
Buffer Tube Color	Blue, Orange, Green, Brown, Slate, White
Buffer Tube Diameter	2.5 mm (0.1 in)
Inner Jacket Material	Polyethylene (PE)
Messenger	Stranded steel
Number of Active Tubes	6
Number of Tube Positions	6
Tape	Water-swellable
Fiber Coloring	Blue, Orange, Green, Brown, Slate, White, Red, Black, Yellow, Violet, Rose, Aqua
Fibers per Tube	12
Color Code Standards	Telcordia

Mechanical Specifications

Nominal Cable Height	25.9 mm (1.02 in)
Nominal Outer Diameter	14.3 mm (0.56 in)
Min. Bend Diameter Installation	430 mm (16.93 in)
Min. Bend Diameter Operation	286 mm (11.26 in)

Optical Characteristics

Fiber Code	T
Performance Option Code	31
Fiber Category	OM2
Fiber Type	Multimode
Fiber Name	50 µm MM (OM2)
Maximum Attenuation	3.0 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fiber Compliance	IEC 60793-2-10
Fiber Core Diameter	50 µm

ALTOS® Figure-8 Loose Tube, Gel-Free Cable 72 F, 50 µm multimode (OM2)

CORNING

Optical Characteristics

Serial 1 Gigabit Ethernet	750 m / 600 m
Serial 10 Gigabit Ethernet	150 m / -
Minimum Effective Modal Bandwidth (EMB)	950 MHz*km / -
Min. Overfilled Launch (OFL) Bandwidth	700 MHz*km / 500 MHz*km

Dimensions

Cable Weight	396 kg/km (266.1 lb/1000 ft)
--------------	------------------------------



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.