

EDGE™ Solutions 24 F Y Harness 24 F MTP® (non-pinned) to 12 F MTP (pinned) MTP, Plenum, OM4, Type-6 polarity, 12 F leg length of 36 in (L), 10 ft

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font centered within it.

CORNING

Part Number:
HA69324QPH-L6010F

EDGE™ Solutions 24-fiber Y jumper is a preterminated assembly that provides the conversion from 24- to 12-fiber connectivity for full-fiber utilization of an existing Base-12 backbone. It is offered as a 1x2 MTP® assembly (one 24-fiber MTP connector on one end, two 12 F MTP connectors on the other), creating the connection from the patch panel to 100G switch port (Base-24).

EDGE™ Solutions 24 F Y Harness 24 F MTP® (non-pinned) to 12 F MTP (pinned) MTP, Plenum, OM4, Type-6 polarity, 12 F leg length of 36 in (L), 10 ft

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	50 µm MM (OM4)
Cable Assembly Type	EDGE™ Harness
Application	Data Center, High-density Field Switches
Solution	EDGE
Connector Assembly Type	MTP to MTP

Standards

Fiber Standards	TIA/EIA-492AAAC-A, Tested with minEMBc method to TIA/EIA-455-220, IEC 60793-2-10 Type A1a.2 Ed.2.0, IEC 60793-1-49 Ed.2.0, ITU-T G.651, ISO/IEC 11801 Ed.2.2 Cat. OM3
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Design and Test Criteria	ANSI/ICEA S-83-596

Environmental Conditions

Temperature Range, Installation	0 °C to 50 °C (32 °F to 122 °F)
Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)

Design

Fiber Count	24
Outer Jacket Material	Flame-retardant
Polarity	Refer to AE Note 150

Mechanical Specifications

Nominal Outer Diameter	3.1 mm (0.12 in)
Max. Tensile Strength for Installation	220 N (49.46 lbf)

EDGE™ Solutions 24 F Y Harness 24 F MTP® (non-pinned) to 12 F MTP (pinned) MTP, Plenum, OM4, Type-6 polarity, 12 F leg length of 36 in (L), 10 ft

CORNING

Mechanical Specifications

Min. Bend Radius Installation	32 mm (1.26 in)
Min. Bend Radius Operation	54 mm (2.13 in)

Optical Characteristics

Fiber Code	T
Performance Option Code	90
Fiber Category	OM4
Fiber Type	Multimode
Fiber Name	50 µm MM (OM4)
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fiber Compliance	IEC 60793-2-10
Fiber Core Diameter	50 µm
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	550 m / -
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km

Specifications - Connector A

Insertion Loss, Max.	0.5 dB
Boot Color	Red
Connector Type	24 F MTP® (non-pinned)
Ferrule Material	Composite

Specifications - Connector B

Insertion Loss, Max.	0.25 dB
Boot Color	Aqua
Connector Type	12 F MTP® (pinned)

**EDGE™ Solutions 24 F Y Harness 24 F MTP®
(non-pinned) to 12 F MTP (pinned) MTP, Plenum,
OM4, Type-6 polarity, 12 F leg length of 36 in (L),
10 ft**

CORNING

Specifications - Connector B

Ferrule Material	Composite
------------------	-----------

Furcation - Connector A

Furcation Type	EDGE™ Harness Plug
----------------	--------------------

Dimensions

Length	10 ft -0 / +0.08m
--------	-------------------

Ordering Information

Product Number	HA69324QPH-L6010F
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.