

EDGE™ Solutions 24 F Y Harness 24 F MTP® (non-pinned) to 12 F MTP (pinned) MTP, Plenum, OM4, Type-8 polarity, 12 F leg length of 36 in (L), 10 ft

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font.

Part Number:
HA69324QPH-L8010F

EDGE™ Solutions 24-fiber Y jumper is a preterminated assembly that provides the conversion from 24- to 12-fiber connectivity for full-fiber utilization of an existing Base-12 backbone. It is offered as a 1x2 MTP® assembly (one 24-fiber MTP connector on one end, two 12 F MTP connectors on the other), creating the connection from the patch panel to 100G switch port (Base-24).

EDGE™ Solutions 24 F Y Harness 24 F MTP® (non-pinned) to 12 F MTP (pinned) MTP, Plenum, OM4, Type-8 polarity, 12 F leg length of 36 in (L), 10 ft

CORNING

Specifications

General Specifications

Flame Rating	Plenum (OFNP)
Fiber Category	50 µm MM (OM4)
Cable Assembly Type	EDGE™ Harness
Application	Data Center, High-density Field Switches
Solution	EDGE
Connector Assembly Type	MTP to MTP

Standards

Fiber Standards	TIA/EIA-492AAAC-A, Tested with minEMBc method to TIA/EIA-455-220, IEC 60793-2-10 Type A1a.2 Ed.2.0, IEC 60793-1-49 Ed.2.0, ITU-T G.651, ISO/IEC 11801 Ed.2.2 Cat. OM3
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Design and Test Criteria	ANSI/ICEA S-83-596

Environmental Conditions

Temperature Range, Installation	0 °C to 50 °C (32 °F to 122 °F)
Temperature Range, Operation	-10 °C to 60 °C (14 °F to 140 °F)

Design

Fiber Count	24
Outer Jacket Material	Flame-retardant
Polarity	Refer to AE Note 150

Mechanical Specifications

Nominal Outer Diameter	3.1 mm (0.12 in)
Max. Tensile Strength for Installation	220 N (49.46 lbf)

**EDGE™ Solutions 24 F Y Harness 24 F MTP®
(non-pinned) to 12 F MTP (pinned) MTP, Plenum,
OM4, Type-8 polarity, 12 F leg length of 36 in (L),
10 ft**

CORNING

Mechanical Specifications

Min. Bend Radius Installation	32 mm (1.26 in)
Min. Bend Radius Operation	54 mm (2.13 in)

Optical Characteristics

Fiber Code	T
Performance Option Code	90
Fiber Category	OM4
Fiber Type	Multimode
Fiber Name	50 µm MM (OM4)
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Wavelengths	850 nm / 1300 nm
Fiber Compliance	IEC 60793-2-10
Fiber Core Diameter	50 µm
Serial 1 Gigabit Ethernet	1000 m / 600 m
Serial 10 Gigabit Ethernet	550 m / -
Minimum Effective Modal Bandwidth (EMB)	4700 MHz*km / -
Min. Overfilled Launch (OFL) Bandwidth	3500 MHz*km / 500 MHz*km

Specifications - Connector A

Insertion Loss, Max.	0.5 dB
Boot Color	Red
Connector Type	24 F MTP® (non-pinned)
Ferrule Material	Composite

Specifications - Connector B

Insertion Loss, Max.	0.25 dB
Boot Color	Aqua
Connector Type	12 F MTP® (pinned)

EDGE™ Solutions 24 F Y Harness 24 F MTP® (non-pinned) to 12 F MTP (pinned) MTP, Plenum, OM4, Type-8 polarity, 12 F leg length of 36 in (L), 10 ft

CORNING

Specifications - Connector B

Ferrule Material	Composite
------------------	-----------

Dimensions

Length	10 ft -0 / +0.08m
--------	-------------------

Ordering Information

Product Number	HA69324QPH-L8010F
Units per Delivery	1/1

Furcation - Connector A

Furcation Type	EDGE™ Harness Plug
----------------	--------------------



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.