



# Data Structure and Algorithms [CO2003]

## Chapter 5 - Stack and Queue

---

Lecturer: Vuong Ba Thinh

Contact: [vbthinh@hcmut.edu.vn](mailto:vbthinh@hcmut.edu.vn)

Faculty of Computer Science and Engineering  
Hochiminh city University of Technology

1. Basic operations of Stacks

2. Implementation of Stacks

3. Applications of Stack

4. Basic operations of Queues

5. Implementation of Queue

6. Applications of Queue

- **L.O.2.1** - Depict the following concepts: (a) array list and linked list, including single link and double links, and multiple links; (b) stack; and (c) queue and circular queue.
- **L.O.2.2** - Describe storage structures by using pseudocode for: (a) array list and linked list, including single link and double links, and multiple links; (b) stack; and (c) queue and circular queue.
- **L.O.2.3** - List necessary methods supplied for list, stack, and queue, and describe them using pseudocode.
- **L.O.2.4** - Implement list, stack, and queue using C/C++.

- **L.O.2.5** - Use list, stack, and queue for problems in real-life, and choose an appropriate implementation type (array vs. link).
- **L.O.2.6** - Analyze the complexity and develop experiment (program) to evaluate the efficiency of methods supplied for list, stack, and queue.
- **L.O.8.4** - Develop recursive implementations for methods supplied for the following structures: list, tree, heap, searching, and graphs.
- **L.O.1.2** - Analyze algorithms and use Big-O notation to characterize the computational complexity of algorithms composed by using the following control structures: sequence, branching, and iteration (not recursion).

The background of the slide is a repeating pattern of various geometric shapes, including cubes, octahedrons, and other polyhedrons, rendered in a light blue and white color scheme. These shapes are arranged in a grid-like fashion, creating a complex, crystalline texture.

## Basic operations of Stacks


---

## General list:

- No restrictions on which operation can be used on the list.
- No restrictions on where data can be inserted/deleted.

## Restricted list:

- Only some operations can be used on the list.
- Data can be inserted/deleted **only at the ends** of the list.



## Definition

A **stack** of elements of type  $T$  is a finite sequence of elements of  $T$ , in which all insertions and deletions are restricted to one end, called the **top**.

Stack is a Last In - First Out (**LIFO**) data structure.

**LIFO**: The last item put on the stack is the first item that can be taken off.





## Basic operations:

- Construct a stack, leaving it empty.
- Push an element: put a new element on to the top of the stack.
- Pop an element: remove the top element from the top of the stack.
- Top an element: retrieve the top element.

## Extended operations:

- Determine whether the stack is empty or not.
- Determine whether the stack is full or not.
- Find the size of the stack.
- Clear the stack to make it empty.





Figure 1: Successful Push operation



**Figure 2:** Unsuccessful Push operation. Stack remains unchanged.





Figure 3: Successful Pop operation



**Figure 4:** Unsuccessful Pop operation. Stack remains unchanged.





Figure 5: Successful Top operation. Stack remains unchanged.




**Figure 6:** Unsuccessful Top operation. Stack remains unchanged.




# Implementation of Stacks

---



## Stack structure



```
stack  
  count <integer>  
  top <node pointer>  
end stack
```


## Stack node structure



```
node  
  data <dataType>  
  next <node pointer>  
end node
```


# Create an empty Linked Stack

Before



(no stack)

After



(empty stack)

**Algorithm** createStack(ref stack <metadata>)

Initializes the metadata of a stack

**Pre:** stack is a metadata structure of a stack

**Post:** metadata initialized


stack.count = 0

stack.top = null


return

**End** createStack

Before



After



1. Allocate memory for the new node and set up data.
2. Update pointers:
  - Point the new node to the top node (before adding the new node).
  - Point top to the new node.
3. Update count

**Algorithm** `pushStack(ref stack <metadata>, val data <dataType>)`

Inserts (pushes) one item into the stack

**Pre:** stack is a metadata structure to a valid stack  
data contains value to be pushed into the stack

**Post:** data have been pushed in stack

**Return** true if successful; false if memory overflow

# Push data into a Linked Stack



**if** *stack full* **then**

| success = false

**else**

| allocate (pNew)

| pNew -> data = data

| pNew -> next = stack.top

| stack.top = pNew

| stack.count = stack.count + 1

| success = true

**end**


return success

**End** pushStack




- Push is successful when allocation memory for the new node is successful.
- There is **no difference** between push data into **a stack having elements** and push data into **an empty stack** (top having NULL value is assigned to pNew->next: that's corresponding to a list having only one element).

Before



After



1. `dltPtr` holds the element on the top of the stack.
2. `top` points to the next element.
3. Recycle `dltPtr`. Decrease count by 1.

**Algorithm** popStack(ref stack <metadata>, ref dataOut <dataType>)

Pops the item on the top of the stack and returns it to caller

**Pre:** stack is a metadata structure to a valid stack  
dataOut is to receive the popped data

**Post:** data have been returned to caller

**Return** true if successful; false if stack is empty

```
if stack empty then
  | success = false
else
  dltPtr = stack.top
  dataOut = stack.top -> data
  stack.top = stack.top -> next
  stack.count = stack.count - 1
  recycle(dltPtr)
  success = true
end
return success
End popStack
```

- Pop is successful when the stack is not empty.
- There is **no difference** between pop an element from **a stack having elements** and pop the **only-one element** in the stack (`dltPtr->next` having NULL value is assigned to top: that's corresponding to an empty stack).

**Algorithm** `stackTop(ref stack <metadata>, ref dataOut <dataType>)`

Retrieves the data from the top of the stack without changing the stack

**Pre:** stack is a metadata structure to a valid stack  
dataOut is to receive top stack data

**Post:** data have been returned to caller

**Return** true if successful; false if stack is empty

```
if stack empty then
```

```
    | success = false
```

```
else
```

```
    | dataOut = stack.top -> data
```

```
    | success = true
```

```
end
```

```
return success
```

```
End stackTop
```

**Algorithm** `destroyStack(ref stack <metadata>)`

Releases all nodes back to memory

**Pre:** stack is a metadata structure to a valid stack

**Post:** stack empty and all nodes recycled



```
if stack not empty then
    while stack.top not null do
        temp = stack.top
        stack.top = stack.top -> next
        recycle(temp)
    end
end
stack.count = 0
return
End destroyStack
```

**Algorithm** isEmpty(ref stack <metadata>)

Determines if the stack is empty

**Pre:** stack is a metadata structure to a valid stack

**Post:** return stack status

**Return** true if the stack is empty, false otherwise

**if** *count* = 0 **then**

**Return** true

**else**

**Return** false

**end**

**End** isEmpty



## Applications of Stack

---

- Reversing data items
  - Reverse a list
  - Convert Decimal to Binary
- Parsing
  - Brackets Parse
- Postponement of processing data items
  - Infix to Postfix Transformation
  - Evaluate a Postfix Expression
- Backtracking
  - Goal Seeking Problem
  - Knight's Tour
  - Exiting a Maze
  - Eight Queens Problem

# Basic operations of Queues

---

## Definition

A **queue** of elements of type  $T$  is a finite sequence of elements of  $T$ , in which data can only be inserted at one end called the **rear**, and deleted from the other end called the **front**.


Queue is a First In - First Out (**FIFO**) data structure.

**FIFO**: The first item stored in the queue is the first item that can be taken out.




## Basic operations:

- Construct a queue, leaving it empty.
- Enqueue: put a new element in to the rear of the queue.
- Dequeue: remove the first element from the front of the queue.
- Queue Front: retrieve the front element.
- Queue Rear: retrieve the rear element.





# Basic operations of Queues: Enqueue






# Basic operations of Queues: Dequeue









# Implementation of Queue


---

## Conceptual



## Physical

## Queue structure



queue

```
count <integer>  
front <node pointer>  
rear <node pointer>
```

enqueue

## Queue node structure




node

```
data <dataType>  
next <node pointer>  
end node
```

Before


queue



(no queue)

After

queue



(empty queue)

**Algorithm** createQueue(ref queue <metadata>)

Initializes the metadata of a queue

**Pre:** queue is a metadata structure of a queue

**Post:** metadata initialized

queue.count = 0

queue.front = null

queue.rear = null

return

**End** createQueue



# Enqueue: Insert into an empty queue




Figure 7: Insert into an empty queue

# Enqueue: Insert into a queue with data




Figure 8: Insert into a queue with data

**Algorithm** enqueue(ref queue <metadata>, val data <dataType>)

Inserts one item at the rear of the queue

**Pre:** queue is a metadata structure of a valid queue  
data contains data to be inserted into queue

**Post:** data have been inserted in queue

**Return** true if successful, false if memory overflow

```
if queue full then
| return false
end
allocate (newPtr)
newPtr -> data = data
newPtr -> next = null
if queue.count = 0 then
| queue.front = newPtr // Insert into an empty queue
else
| queue.rear -> next = newPtr // Insert into a queue with data
end
queue.rear = newPtr
queue.count = queue.count + 1
return true
```

# Deque: Delete data in a queue with only one item




Figure 9: Delete data in a queue with **only one item**

# Dequeue: Delete data in a queue with more than one item




Figure 10: Delete data in a queue with more than one item

**Algorithm** dequeue(ref queue <metadata>, ref dataOut <dataType>)

Deletes one item at the front of the queue and returns its data to caller

**Pre:** queue is a metadata structure of a valid queue  
dataOut is to receive dequeued data

**Post:** front data have been returned to caller

**Return** true if successful, false if memory overflow

```
if queue.empty then
    return false
end
dataOut = queue.front -> data
dltPtr = queue.front
if queue.count = 1 then
    // Delete data in a queue with only one item
    queue.rear = NULL
end
queue.front = queue.front -> next
queue.count = queue.count - 1
recycle (dltPtr)
return true
End dequeue
```



# Applications of Queue

---

# Applications of Queue

- Polynomial Arithmetic
- Categorizing Data
- Evaluate a Prefix Expression
- Radix Sort
- Queue Simulation