



Data Structure and Algorithms [CO2003]

Chapter 3 - Recursion


Lecturer: Vuong Ba Thinh

Contact: vbthinh@hcmut.edu.vn

Faculty of Computer Science and Engineering
Hochiminh city University of Technology

1. Recursion and the basic components of recursive algorithms
2. Properties of recursion
3. Designing recursive algorithms
4. Recursion and backtracking

- **L.O.8.1** - Describe the basic components of recursive algorithms (functions).
- **L.O.8.2** - Draw trees to illustrate callings and the value of parameters passed to them for recursive algorithms.
- **L.O.8.3** - Give examples for recursive functions written in C/C++.
- **L.O.8.5** - Develop experiment (program) to compare the recursive and the iterative approach.
- **L.O.8.6** - Give examples to relate recursion to backtracking technique.



Recursion and the basic components of recursive algorithms

Definition

Recursion is a **repetitive process** in which an algorithm **calls itself**.

- Direct : $A \rightarrow A$
- Indirect : $A \rightarrow B \rightarrow A$

Example Factorial

$$Factorial(n) = \begin{cases} 1 & \text{if } n = 0 \\ n \times (n - 1) \times (n - 2) \times \dots \times 3 \times 2 \times 1 & \text{if } n > 0 \end{cases}$$

Using recursion:

$$Factorial(n) = \begin{cases} 1 & \text{if } n = 0 \\ n \times Factorial(n - 1) & \text{if } n > 0 \end{cases}$$

Two main components of a Recursive Algorithm

1. Base case (i.e. stopping case)
2. General case (i.e. recursive case)

Example Factorial

$$Factorial(n) = \begin{cases} 1 & \text{if } n = 0 \quad \text{base case} \\ n \times Factorial(n - 1) & \text{if } n > 0 \quad \text{general case} \end{cases}$$




Figure 1: Factorial (3) Recursively (source: Data Structure - A pseudocode Approach with C++)

Factorial: Iterative Solution

Algorithm iterativeFactorial(n)

Calculates the factorial of a number using a loop.

Pre: n is the number to be raised factorially

Post: $n!$ is returned - result in **factoN**

```
i = 1
factoN = 1
while i <= n do
    factoN = factoN * i
    i = i + 1
end
return factoN
End iterativeFactorial
```


Factorial: Recursive Solution

Algorithm recursiveFactorial(n)

Calculates the factorial of a number using a recursion.

Pre: n is the number to be raised factorially

Post: $n!$ is returned

```
if  $n = 0$  then
    return 1
else
    return  $n * \text{recursiveFactorial}(n-1)$ 
end
End recursiveFactorial
```




Figure 2: Calling a Recursive Algorithm (source: Data Structure - A



Properties of recursion

- A recursive algorithm solves the large problem by using its solution to a simpler sub-problem
- Eventually the sub-problem is simple enough that it can be solved without applying the algorithm to it recursively.
→ This is called the **base case**.



Designing recursive algorithms

Every recursive call must either **solve a part** of the problem or **reduce the size** of the problem.

Rules for designing a recursive algorithm

1. Determine the **base case (stopping case)**.
2. Then determine the **general case (recursive case)**.
3. **Combine** the base case and the general cases into an algorithm.


- A recursive algorithm generally runs **more slowly** than its nonrecursive implementation.
- BUT, the recursive solution **shorter** and **more understandable**.

Print List in Reverse



26 8 19 93

Print List in Reverse



Algorithm printReverse(list)

Prints a linked list in reverse.

Pre: list has been built

Post: list printed in reverse

if *list is null* **then**

 return

end

 printReverse (list -> next)

 print (list -> data)

End printReverse

Definition

$$\gcd(a, b) = \begin{cases} a & \text{if } b = 0 \\ b & \text{if } a = 0 \\ \gcd(b, a \bmod b) & \text{otherwise} \end{cases}$$

Example

$$\gcd(12, 18) = 6$$

$$\gcd(5, 20) = 5$$

Algorithm gcd(a , b)

Calculates greatest common divisor using the Euclidean algorithm.

Pre: a and b are integers

Post: greatest common divisor returned

if $b = 0$ **then**

 | return a

end

if $a = 0$ **then**

 | return b


end


return gcd(b , $a \bmod b$)

End gcd

Definition

$$Fibonacci(n) = \begin{cases} 0 & \text{if } n = 0 \\ 1 & \text{if } n = 1 \\ Fibonacci(n-1) + Fibonacci(n-2) & \text{otherwise} \end{cases}$$





Result

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, ...

Algorithm fib(n)

Calculates the n^{th} Fibonacci number.

Pre: n is positive integer

Post: the n^{th} Fibonacci number returned

if $n = 0$ or $n = 1$ **then**

 return n

end


return $\text{fib}(n-1) + \text{fib}(n-2)$

End fib


No	Calls	Time	No	Calls	Time
1	1	< 1 sec.	11	287	< 1 sec.
2	3	< 1 sec.	12	465	< 1 sec.
3	5	< 1 sec.	13	753	< 1 sec.
4	9	< 1 sec.	14	1,219	< 1 sec.
5	15	< 1 sec.	15	1,973	< 1 sec.
6	25	< 1 sec.	20	21,891	< 1 sec.
7	41	< 1 sec.	25	242,785	1 sec.
8	67	< 1 sec.	30	2,692,573	7 sec.
9	109	< 1 sec.	35	29,860,703	1 min.
10	177	< 1 sec.	40	331,160,281	13 min.

Move disks from Source to Destination using Auxiliary:

1. Only one disk could be moved at a time.
2. A larger disk must never be stacked above a smaller one.
3. Only one auxiliary needle could be used for the intermediate storage of disks.



Source



Auxiliary



Destination

The Towers of Hanoi




Moved disc from pole 1 to pole 3.

The Towers of Hanoi




Moved disc from pole 1 to pole 2.

The Towers of Hanoi



Moved disc from pole 3 to pole 2.

The Towers of Hanoi



Moved disc from pole 1 to pole 3.

The Towers of Hanoi



Moved disc from pole 2 to pole 1.

The Towers of Hanoi




Moved disc from pole 2 to pole 3.


The Towers of Hanoi



Moved disc from pole 1 to pole 3.

The Towers of Hanoi





Complexity

$$T(n) = 1 + 2T(n - 1)$$

Complexity

$$T(n) = 1 + 2T(n-1)$$

$$\Rightarrow T(n) = 1 + 2 + 2^2 + \dots + 2^{n-1}$$

$$\Rightarrow T(n) = 2^n - 1$$

$$\Rightarrow T(n) = O(2^n)$$

- With 64 disks, total number of moves:

$$2^{64} - 1 \approx 2^4 \times 2^{60} \approx 2^4 \times 10^{18} = 1.6 \times 10^{19}$$

- If one move takes 1s, 2^{64} moves take about 5×10^{11} years (500 billions years).

Algorithm move(val disks <integer>, val source <character>, val destination <character>, val auxiliary <character>)

Move disks from source to destination.

Pre: disks is the number of disks to be moved

Post: steps for moves printed

print("Towers: ", disks, source, destination, auxiliary)

if *disks* = 1 **then**

| print ("Move from", source, "to", destination)

else

| move(disks - 1, source, auxiliary, destination)

| move(1, source, destination, auxiliary)

| move(disks - 1, auxiliary, destination, source)

end

return

End move



Recursion and backtracking

Definition

A process to go **back to previous steps** to **try unexplored alternatives**.






Figure 3: Goal seeking

Eight Queens Problem



- Place eight queens on the chess board in such a way that no queen can capture another.



Algorithm putQueen(ref board <array>, val r <integer>)

Place remaining queens safely from a row of a chess board.

Pre: board is nxn array representing a chess board

r is the row to place queens onwards

Post: all the remaining queens are safely placed on the board; or
backtracking to the previous rows is required

Eight Queens Problem



for every column c on the same row r **do**

if cell r, c is safe **then**

 place the next queen in cell r, c

if $r < n-1$ **then**

 | putQueen (board, $r + 1$)

else

 | output successful placement

end

 remove the queen from cell r, c

end

end

return

End putQueen

Eight Queens Problem



	1	2	3	4
1	Q			
2				
3				
4				

	1	2	3	4
1	Q			
2			Q	
3				
4				

	1	2	3	4
1	Q			
2				Q
3				
4				

	1	2	3	4
1	Q			
2				Q
3		Q		
4				

	1	2	3	4
1		Q		
2				
3				
4				

	1	2	3	4
1		Q		
2				Q
3				
4				

	1	2	3	4
1		Q		
2				Q
3	Q			
4				

	1	2	3	4
1		Q		
2				Q
3	Q			
4			Q	