## Product Screening Form – auxiliaries, dyestuffs and finishing agents

The "Product Screening Form" PSF is a tool for data collection which must be completed by the supplier of the chemical product. In combination with "Material Safety Data Sheet" MSDS and the "Technical Data Sheet" TDS it is the basis for an EHS-assessment of the product by bluesign technologies.

A duly filled PSF is a prerequisite for tolerating this product for temporary usage at the requesting company. Certification of the product as "bluesign® approved" requires a bluesign® system partnership.

All information will be handled with absolute confidentiality. On request, a confidentiality agreement can be signed prior to completing the PSF.

Please separately enclose MSDS and TDS in English. The information provided in the PSF and in the MSDS must be based on GHS or European Regulations concerning classification/ labelling.

Please name the files as follows:

Chemical tradename\_MSDS|PSF|TDS\_date (yyyy.mmm.dd)



Revised documents must be marked with the revision number. e.g. Disperse Black ABC\_PSF\_1\_2012.06.15

Send back directly to "psf@bluesign.com"

The attached "bluesign® system substances list - BSSL" is the reference document for evaluation.



Click here for the link to the bluesign® system substances list

Please process the PSF-worksheet as follows:

- PSF must be filled and signed by the supplier of the chemical product
- For each product a separate PSF worksheet in English must be provided
- Part "3. Substances listed in the bluesign® standard substances list"

  Table must be filled only if product contains/ might contain any component which is listed in the BSSL or other critical substances.
- Send back directly to "psf@bluesign.com"

For any question please contact bluesign technologies ag | +41 71 2722990 | psf@bluesign.com.

#### 1. General Information

Product name:	HUNTEX DMC-KO2					
Product supplier:	HUNG XUONG CHEMICAL CO., LTD.					
Contact details						
Name:	THAI KIEM LINH					
Title/Position:	Supporter Manager					
Email:	phongvattu@hungxuong.com.vn					
Phone:	84-028-39610618/28 Ext: 108					
Identification No.a:	CNMKO-02					
Type of chemical:	☐ Pretreatment agents ☐ Finishing agents					
	☐ Dyestuffs and Pigments ☐ Water based coating agents					
	☐ Dyeing/ Printing auxilliaries					
	$\square$ Aftertreatment agents (to be fixed on the fibre)					
	🛮 others, pls specify					
Group according to	7.5					
bluesign <sup>®</sup> product groups*						
Chemical description <sup>b</sup>	Lauryl alcohol ethoxylate (9002-92-0) 24%; Butyl carbitol(112-					
and CAS number:	34-5) 66%; Polyoxyethylene styrenated aryl sulfate ammonium					
	salt( 119432-41-6) 9%;Tristyrylphenol ethoxylates (70559-25-					
	0 ) 0.5%; Isopropyl alcohol(67-63-0) 0.3%.					
Colour Index (C.I.)						
and CAS number						
(for dyestuffs and Pigments only)						
Standardization agents						
and CAS number						
(for dyestuffs and Pigments only)						
Application process:	☑ Exhaust					
	☐ Coat					
	⊠ others, pls specify					
Description of use <sup>c</sup> :	Machine cleaning agent					
Product using company						

Please click here for the list: <u>bluesign-Groups.pdf</u>

a Use the individual product key, article code, material number

b Enter type of chemistry the product is based on, e.g. fatty alcohol ether, silicone

c Describe for what purpose the product is mainly used, e.g. bleaching, levelling agent

<sup>\*</sup> The bluesign® product groups are based on TEGEWA nomenclature

#### 2. **Specifications – Wastewater | Toxicology | Air Emission**

#### 2.1. **Wastewater Parameters**

Wastewater Parameters	Method	Value	Unit	S <sup>d</sup>			
					Comment		
Biodegradability							
standard method	OECD 302 B	14	%	С			
or alternative	OECD 301 A-F, 303 A, 310		%				
	specify method used						
COD	DIN 38409-41	9936	mg/g	m	Cuvette test,		
	also cuvette test if reliable				dichromate, USEPA 410.4		
or TOC	DIN EN 1484		mg/g				
BOD <sub>5</sub>	DIN EN 1899-1	1340	mg/g	m	SMEWW		
					5210B:2012		
Aquatic toxicity							
against fish	OECD 203 / LC50 / 96h	>1.0	mg/L		>1- ≤ 10 mg/L		
					based on GHS		
					classification		
or against daphnia	OECD 202 / EC50 / 48h		mg/L				
or against algae	OECD 201 / EC50 / 72h		mg/L				
Aquatic toxicity against bacteria	OECD 209 / IC50 / 3h		mg/L				
WGK (water hazard class)	Class 1, 2 or 3						
only in Germany	(German classification scheme)						
ARS (wastewater relevance	Class I, II or III						
level) not relevant for dyestuffs	(German classification scheme)						
P, total	DIN EN ISO 11885 <sup>e</sup>	0	%		materials don't		
					contain P		
N, total	DIN EN 12260 (TNb)	0.4	%		Cuvette test,		
	or DIN EN 15663 (TKN)e				chromotropic		
					acid		
Aliphatic hydrocarbons	е	0	%				
Organo halogen (AOX)	DIN EN ISO 9562e	0	%				
for reactive dyes, only non-hydrolysable							
AOX content relevant							
Fluorine	Wickbold incineration	0	%				
mostly relevant for Fluorcarbons	DIN 38405-4e						

Comments:

### 2.2. Irritancy and sensitization

Irritancy and Sensitization	Method			S	Comment
				d	
Irritancy skin	OECD 404	⊠ Pos	☐ Neg		based on GHS
					classification
Irritancy eye	OECD 405		☐ Neg		based on GHS
					classification
Sensitization skin	OECD 406	Pos	⊠ Neg		
Experiences at the human being	available?	☐ Yes	⊠ No		
If Yes, please specify:		·			

Comments:

# 2.3. Toxicity

Toxicity	Method	Value	Unit	S	Comment
				d	
Acute oral toxicity	OECD 401, 420, 423 /	2500	mg/kg		based on GHS
	LD50 (specify method used)				classification
if available provide data for:					
Acute dermal toxicity	OECD 402 / LD50		mg/kg		
Mutagenicity / AMES test	OECD 471	Pos	⊠ Neg		not classified
Chromosome aberration test	OECD 473	Pos	⊠ Neg		not classified

Comments:

## 2.4. Air Emission Parameters (only for Finishing and Coating Agents)

Air Emission Parameters	Method	Value	Unit	<b>S</b> d	Comment
Organic carbon (Polyester)	Emission factor concept  °C   minutes	0	g org.C / kg		
Organic carbon (Cotton)	Emission factor concept  °C   minutes	0	g org.C / kg		

Comments:

# 2.5. Components of high concern

Components	declara-	pres	ent?	if yes, pls spe	ecify	
	tion limit	no	_	Chemical name and CAS Number	quantity	Unit
APEO				CAS INGINISCI		
■ NPEO, OPEO	100mg/kg	$\boxtimes$				mg/kg
						mg/kg

Product Screening Form: HUNTEX DMC-KO2

Components	declara-	present?		if yes, pls specify		
	tion limit	no	yes	Chemical name and	quantity	Unit
	<b>&gt;</b>			CAS Number		
■ NP, OP	10 mg/kg	$\boxtimes$				mg/kg
						mg/kg
Condensation products of	100mg/kg	$\boxtimes$				mg/kg
fatty acid derivatives with						mg/kg
AEEA						mg/kg
(Aminoethylethanolamine)						mg/kg

### 3. Substances listed in bluesign® standard substances list

In case the product contains any substances listed in the BSSL or any other critical substance or in case those substances might be formed during application of the product those substances must be listed in detail in table 3.1.

Chemical substance	CAS Number	unit	quantity	intentional component <sup>1</sup>	unintentional component <sup>2</sup>	released component³
Ethylene oxide.	75-21-8	mg/kg	< 1.0			
1,4- dioxane.	123-91-1	mg/kg	< 1.0			
Glycols		mg/kg	< 5.0			
Styrene	100-42-5	mg/kg	24.4			
Phenol	108-95-2	mg/kg	1.1			
		mg/kg				

Table 3.1

The accuracy and reliability of data provided must be met in every case, so as to ensure that the consumer safety limits given in BSSL are met at any time.

#### Comments:

the detection limit of the method of 2-(2 methoxyethoxy)-ethanol is < 1.0 mg/kg

We confirm that the assessed product does not contain any of the substances listed in the "bluesign® standard substances list – BSSL" or any other critical substances or lead to the formation of any such substances during application **except those listed in Table 3.1.** 

Ho chi minh city, August 7, 2019	
	THAI KIEM LINH/ supporter manager,
Place and Date	Name   Function

d Source of data: A: Analogy | C: Calculated | M: Measured Wherever possible provide measured data.

<sup>&</sup>lt;sup>e</sup> Calculating the data is accepted

<sup>1</sup> Substance is an intentional component of the product

<sup>2</sup> Substance is an unintentional impurity or by-product of the product

<sup>3</sup> Substance may be released under recommended application conditions