

Uber Go Style Guide

Table of Contents

- [Uber Go Style Guide](#)
 - [Table of Contents](#)
 - [Introduction](#)
 - [Guidelines](#)
 - [Pointers to Interfaces](#)
 - [Verify Interface Compliance](#)
 - [Receivers and Interfaces](#)
 - [具體的實現分兩種](#)
 - [Zero-value Mutexes are Valid](#)
 - [Copy Slices and Maps at Boundaries](#)
 - [Receiving Slices and Maps](#)
 - [Returning Slices and Maps](#)
 - [Defer to Clean Up](#)
 - [Channel Size is One or None](#)
 - [Start Enums at One](#)
 - [Use "time" to handle time](#)
 - [Use time.Time for instants of time](#)
 - [Use time.Duration for periods of time](#)
 - [Use time.Time and time.Duration with external systems](#)
 - [Errors](#)
 - [Error Types](#)
 - [Error Wrapping](#)
 - [Error Naming](#)
 - [Handle Type Assertion Failures](#)
 - [Don't Panic](#)
 - [Use go.uber.org/atomic](#)
 - [Avoid Mutable Globals](#)
 - [Avoid Embedding Types in Public Structs](#)
 - [Avoid Using Built-In Names](#)
 - [Avoid init\(\)](#)
 - [Exit in Main](#)
 - [Exit Once](#)
 - [Use field tags in marshaled structs](#)
 - [Performance](#)
 - [Prefer strconv over fmt](#)
 - [Avoid string-to-byte conversion](#)
 - [Prefer Specifying Container Capacity](#)
 - [Specifying Map Capacity Hints](#)
 - [Specifying Slice Capacity](#)
 - [Style](#)
 - [Avoid overly long lines](#)

- Be Consistent
- Group Similar Declarations
- Import Group Ordering
- Package Names
- Function Names
- Import Aliasing
- Function Grouping and Ordering
- Reduce Nesting
- Unnecessary Else
- Top-level Variable Declarations
- Prefix Unexported Globals with _
- Embedding in Structs
- Local Variable Declarations
- nil is a valid slice
- Reduce Scope of Variables
- Avoid Naked Parameters
- Use Raw String Literals to Avoid Escaping
- Initializing Structs
 - Use Field Names to Initialize Structs
 - Omit Zero Value Fields in Structs
 - Use `var` for Zero Value Structs
 - Initializing Struct References
- Initializing Maps
- Format Strings outside Printf
- Naming Printf-style Functions
- Patterns
 - Test Tables
 - Functional Options
- Linting
 - Lint Runners

Introduction

Styles are the conventions that govern our code. The term style is a bit of a misnomer, since these conventions cover far more than just source file formatting—gofmt handles that for us.

The goal of this guide is to manage this complexity by describing in detail the Dos and Don'ts of writing Go code at Uber. These rules exist to keep the code base manageable while still allowing engineers to use Go language features productively.

This guide was originally created by [Prashant Varanasi](#) and [Simon Newton](#) as a way to bring some colleagues up to speed with using Go. Over the years it has been amended based on feedback from others.

This documents idiomatic conventions in Go code that we follow at Uber. A lot of these are general guidelines for Go, while others extend upon external resources:

1. [Effective Go](#)
2. [Go Common Mistakes](#)

3. Go Code Review Comments

All code should be error-free when run through `golint` and `go vet`. We recommend setting up your editor to:

- Run `goimports` on save
- Run `golint` and `go vet` to check for errors

You can find information in editor support for Go tools here:

<https://github.com/golang/go/wiki/IDEsAndTextEditorPlugins>

Guidelines

Pointers to Interfaces

You almost never need a pointer to an interface. You should be passing interfaces as values—the underlying data can still be a pointer.

An interface is two fields:

1. A pointer to some type-specific information. You can think of this as "type."
2. Data pointer. If the data stored is a pointer, it's stored directly. If the data stored is a value, then a pointer to the value is stored.

If you want interface methods to modify the underlying data, you must use a pointer.

Verify Interface Compliance

Verify interface compliance at compile time where appropriate. This includes:

- Exported types that are required to implement specific interfaces as part of their API contract
- Exported or unexported types that are part of a collection of types implementing the same interface
- Other cases where violating an interface would break users

Bad Good

```
type Handler struct {  
    // ...  
}  
  
func (h *Handler) ServeHTTP(  
    w http.ResponseWriter,  
    r *http.Request,  
) {  
    ...  
}
```

```

type Handler struct {
    // ...
}

var _ http.Handler = (*Handler)(nil)

func (h *Handler) ServeHTTP(
    w http.ResponseWriter,
    r *http.Request,
) {
    // ...
}

```

The statement `var _ http.Handler = (*Handler)(nil)` will fail to compile if `*Handler` ever stops matching the `http.Handler` interface.

The right hand side of the assignment should be the zero value of the asserted type. This is `nil` for pointer types (like `*Handler`), slices, and maps, and an empty struct for struct types.

```

type LogHandler struct {
    h http.Handler
    log *zap.Logger
}

var _ http.Handler = LogHandler{}

func (h LogHandler) ServeHTTP(
    w http.ResponseWriter,
    r *http.Request,
) {
    // ...
}

```

Receivers and Interfaces

Methods with value receivers can be called on pointers as well as values. Methods with pointer receivers can only be called on pointers or [addressable values](#).

Methods Receivers	Value
(t T)	T and *T
(t *T)	*T

- Rules
 - 值對象只可以使用值接收器方法集(Methods Receivers 是 t T)
 - 指針對像可以使用值接收器方法集 + 指針接收器方法集
- Interface的實現
 - 類型實現了Interface的所有方法, 叫實現

- 具體的講, 要馬是類型的值方法集實現Interface, 要馬是指針方法集實現Interface

For example,

```
type S struct {
    data string
}

func (s S) Read() string {
    return s.data
}

func (s *S) Write(str string) {
    s.data = str
}

sVals := map[int]S{1: {"A"}}

// You can only call Read using a value
sVals[1].Read()

// This will not compile:
// sVals[1].Write("test")

sPtrs := map[int]*S{1: {"A"}}

// You can call both Read and Write using a pointer
sPtrs[1].Read()
sPtrs[1].Write("test")
```

Similarly, an interface can be satisfied by a pointer, even if the method has a value receiver.

具體的實現分兩種

1. 值方法集和Interface實現 給Interface變量賦值的不管是值還是指針對象, 都 ok, 因為都包含值方法集 (t T)
2. 指針方法集和Interface實現 只能將指針對象賦值給Interface變量, 因為只有指針方法集和Interface實現 如果將值對象賦值給Interface變量, 會在編譯期報錯 (會觸發Interface合理性檢查機制)

```
type F interface {
    f()
}

type S1 struct{}

func (s S1) f() {}

type S2 struct{}

func (s *S2) f() {}
```

```

s1Val := S1{}
s1Ptr := &S1{}
s2Val := S2{}
s2Ptr := &S2{}

var i F
i = s1Val
i = s1Ptr
i = s2Ptr

// The following doesn't compile, since s2Val is a value, and there is no
// value receiver for f.
// i = s2Val

```

Effective Go has a good write up on [Pointers vs. Values](#).

Zero-value Mutexes are Valid

The zero-value of `sync.Mutex` and `sync.RWMutex` is valid, so you almost never need a pointer to a mutex.

Bad **Good**

```

mu := new(sync.Mutex)
mu.Lock()

```

```

var mu sync.Mutex
mu.Lock()

```

If you use a struct by pointer, then the mutex should be a non-pointer field on it. Do not embed the mutex on the struct, even if the struct is not exported.

Bad **Good**

```

type SMap struct {
    sync.Mutex

    data map[string]string
}

func NewSMap() *SMap {
    return &SMap{
        data: make(map[string]string),
    }
}

```

```
func (m *SMap) Get(k string) string {
    m.Lock()
    defer m.Unlock()

    return m.data[k]
}
```

```
type SMap struct {
    mu sync.Mutex

    data map[string]string
}

func NewSMap() *SMap {
    return &SMap{
        data: make(map[string]string),
    }
}

func (m *SMap) Get(k string) string {
    m.mu.Lock()
    defer m.mu.Unlock()

    return m.data[k]
}
```

The `Mutex` field, and the `Lock` and `Unlock` methods are unintentionally part of the exported API of `SMap`.

The mutex and its methods are implementation details of `SMap` hidden from its callers.

Copy Slices and Maps at Boundaries

Slices and maps contain pointers to the underlying data so be wary of scenarios when they need to be copied.

Receiving Slices and Maps

Keep in mind that users can modify a map or slice you received as an argument if you store a reference to it.

Bad Good

```
func (d *Driver) SetTrips(trips []Trip) {
    d.trips = trips
}

trips := ...
d1.SetTrips(trips)
```

```
// Did you mean to modify d1.trips?  
trips[0] = ...
```

https://go.dev/play/p/wbz4M_OzOPL

```
package main  
  
import "fmt"  
  
func (d *Driver) SetTripsBad(trips []int) {  
    d.trips = trips  
}  
  
func (d *Driver) SetTripsGood(trips []int) {  
    d.trips = make([]int, len(trips))  
    copy(d.trips, trips)  
}  
  
type Driver struct {  
    trips []int  
}  
  
func main() {  
  
    trips1 := []int{1, 2, 3}  
    var d1 Driver  
    d1.SetTripsBad(trips1)  
    // 修改 trips1 會導致 d1也被修改  
    trips1[0] = 2  
    fmt.Println(trips1)  
  
    trips2 := []int{1, 2, 3}  
    var d2 Driver  
    d2.SetTripsGood(trips2)  
    // Did you mean to modify d1.trips?  
    // 修改 trips2 不會導致 d2被修改  
    trips2[0] = 2  
    fmt.Println(d2.trips)  
}
```

```
func (d *Driver) SetTrips(trips []Trip) {  
    d.trips = make([]Trip, len(trips))  
    copy(d.trips, trips)  
}  
  
trips := ...  
d1.SetTrips(trips)
```



```
// We can now modify trips[0] without affecting d1.trips.
trips[0] = ...
```

Returning Slices and Maps

Similarly, be wary of user modifications to maps or slices exposing internal state.

Bad **Good**

```
type Stats struct {
    mu sync.Mutex
    counters map[string]int
}

// Snapshot returns the current stats.
func (s *Stats) Snapshot() map[string]int {
    s.mu.Lock()
    defer s.mu.Unlock()

    return s.counters
}

// snapshot is no longer protected by the mutex, so any
// access to the snapshot is subject to data races.
snapshot := stats.Snapshot()
```

```
type Stats struct {
    mu sync.Mutex
    counters map[string]int
}

func (s *Stats) Snapshot() map[string]int {
    s.mu.Lock()
    defer s.mu.Unlock()

    result := make(map[string]int, len(s.counters))
    for k, v := range s.counters {
        result[k] = v
    }
    return result
}

// Snapshot is now a copy.
snapshot := stats.Snapshot()
```

Defer to Clean Up

Use defer to clean up resources such as files and locks.

Bad **Good**

```
p.Lock()
if p.count < 10 {
    p.Unlock()
    return p.count
}

p.count++
newCount := p.count
p.Unlock()

return newCount

// easy to miss unlocks due to multiple returns
```

```
p.Lock()
defer p.Unlock()

if p.count < 10 {
    return p.count
}

p.count++
return p.count

// more readable
```

Defer has an extremely small overhead and should be avoided only if you can prove that your function execution time is in the order of nanoseconds. The readability win of using defers is worth the miniscule cost of using them. This is especially true for larger methods that have more than simple memory accesses, where the other computations are more significant than the **defer**.

Channel Size is One or None

Channels should usually have a size of one or be unbuffered. By default, channels are unbuffered and have a size of zero. Any other size must be subject to a high level of scrutiny. Consider how the size is determined, what prevents the channel from filling up under load and blocking writers, and what happens when this occurs.

Bad **Good**

```
// Ought to be enough for anybody!  
c := make(chan int, 64)
```

```
// Size of one  
c := make(chan int, 1) // or  
// Unbuffered channel, size of zero  
c := make(chan int)
```

Start Enums at One

The standard way of introducing enumerations in Go is to declare a custom type and a `const` group with `iota`. Since variables have a 0 default value, you should usually start your enums on a non-zero value.

Bad **Good**

```
type Operation int  
  
const (  
    Add Operation = iota  
    Subtract  
    Multiply  
)  
  
// Add=0, Subtract=1, Multiply=2
```

```
type Operation int  
  
const (  
    Add Operation = iota + 1  
    Subtract  
    Multiply  
)  
  
// Add=1, Subtract=2, Multiply=3
```

There are cases where using the zero value makes sense, for example when the zero value case is the desirable default behavior.

```
type LogOutput int  
  
const (  
    LogToStdout LogOutput = iota  
    LogToFile
```

```
    LogToRemote
)

// LogToStdout=0, LogToFile=1, LogToRemote=2
```

Use "time" to handle time

Time is complicated. Incorrect assumptions often made about time include the following.

1. A day has 24 hours
2. An hour has 60 minutes
3. A week has 7 days
4. A year has 365 days
5. [And a lot more](#)

For example, 1 means that adding 24 hours to a time instant will not always yield a new calendar day.

Therefore, always use the "time" package when dealing with time because it helps deal with these incorrect assumptions in a safer, more accurate manner.

Use time.Time for instants of time

Use `time.Time` when dealing with instants of time, and the methods on `time.Time` when comparing, adding, or subtracting time.

Bad **Good**

```
func isActive(now, start, stop int) bool {
    return start <= now && now < stop
}
```

```
func isActive(now, start, stop time.Time) bool {
    return (start.Before(now) || start.Equal(now)) && now.Before(stop)
}
```

Use time.Duration for periods of time

Use `time.Duration` when dealing with periods of time.

Bad **Good**

```
func poll(delay int) {
    for {
        // ...
    }
}
```

```

    time.Sleep(time.Duration(delay) * time.Millisecond)
  }
}

poll(10) // was it seconds or milliseconds?

```

```

func poll(delay time.Duration) {
  for {
    // ...
    time.Sleep(delay)
  }
}

poll(10*time.Second)

```

Going back to the example of adding 24 hours to a time instant, the method we use to add time depends on intent. If we want the same time of the day, but on the next calendar day, we should use `Time.AddDate`. However, if we want an instant of time guaranteed to be 24 hours after the previous time, we should use `Time.Add`.

```

newDay := t.AddDate(0 /* years */, 0 /* months */, 1 /* days */)
maybeNewDay := t.Add(24 * time.Hour)

```

Use `time.Time` and `time.Duration` with external systems

Use `time.Duration` and `time.Time` in interactions with external systems when possible. For example:

- Command-line flags: `flag` supports `time.Duration` via `time.ParseDuration`
- JSON: `encoding/json` supports encoding `time.Time` as an RFC 3339 string via its `UnmarshalJSON` method
- SQL: `database/sql` supports converting `DATETIME` or `TIMESTAMP` columns into `time.Time` and back if the underlying driver supports it
- YAML: `gopkg.in/yaml.v2` supports `time.Time` as an RFC 3339 string, and `time.Duration` via `time.ParseDuration`.

When it is not possible to use `time.Duration` in these interactions, use `int` or `float64` and include the unit in the name of the field.

For example, since `encoding/json` does not support `time.Duration`, the unit is included in the name of the field.

Bad Good

```
// {"interval": 2}
type Config struct {
    Interval int `json:"interval"`
}
```

```
// {"intervalMillis": 2000}
type Config struct {
    IntervalMillis int `json:"intervalMillis"`
}
```

When it is not possible to use `time.Time` in these interactions, unless an alternative is agreed upon, use `string` and format timestamps as defined in [RFC 3339](#). This format is used by default by `Time.UnmarshalText` and is available for use in `Time.Format` and `time.Parse` via `time.RFC3339`.

Although this tends to not be a problem in practice, keep in mind that the `"time"` package does not support parsing timestamps with leap seconds ([8728](#)), nor does it account for leap seconds in calculations ([15190](#)). If you compare two instants of time, the difference will not include the leap seconds that may have occurred between those two instants.

Errors

Error Types

There are few options for declaring errors. Consider the following before picking the option best suited for your use case.

- Does the caller need to match the error so that they can handle it? If yes, we must support the `errors.Is` or `errors.As` functions by declaring a top-level error variable or a custom type.
- Is the error message a static string, or is it a dynamic string that requires contextual information? For the former, we can use `errors.New`, but for the latter we must use `fmt.Errorf` or a custom error type.
- Are we propagating a new error returned by a downstream function? If so, see the [section on error wrapping](#).

Error matching?	Error Message	Guidance
No	static	<code>errors.New</code>
No	dynamic	<code>fmt.Errorf</code>
Yes	static	top-level <code>var</code> with <code>errors.New</code>
Yes	dynamic	custom <code>error</code> type

For example, use `errors.New` for an error with a static string. Export this error as a variable to support matching it with `errors.Is` if the caller needs to match and handle this error.

No error matching	Error matching
-------------------	----------------

No error matching Error matching

```
// package foo

func Open() error {
    return errors.New("could not open")
}

// package bar

if err := foo.Open(); err != nil {
    // Can't handle the error.
    panic("unknown error")
}
```

```
// package foo

var ErrCouldNotOpen = errors.New("could not open")

func Open() error {
    return ErrCouldNotOpen
}

// package bar

if err := foo.Open(); err != nil {
    if errors.Is(err, foo.ErrCouldNotOpen) {
        // handle the error
    } else {
        panic("unknown error")
    }
}
```

For an error with a dynamic string, use `fmt.Errorf` if the caller does not need to match it, and a custom `error` if the caller does need to match it.

No error matching Error matching

```
// package foo

func Open(file string) error {
    return fmt.Errorf("file %q not found", file)
}

// package bar
```

```
if err := foo.Open("testfile.txt"); err != nil {  
    // Can't handle the error.  
    panic("unknown error")  
}
```

```
// package foo  
  
type NotFoundError struct {  
    File string  
}  
  
func (e *NotFoundError) Error() string {  
    return fmt.Sprintf("file %q not found", e.File)  
}  
  
func Open(file string) error {  
    return &NotFoundError{File: file}  
}  
  
// package bar  
  
if err := foo.Open("testfile.txt"); err != nil {  
    var notFound *NotFoundError  
    if errors.As(err, &notFound) {  
        // handle the error  
    } else {  
        panic("unknown error")  
    }  
}
```

Note that if you export error variables or types from a package, they will become part of the public API of the package.

Error Wrapping

There are three main options for propagating errors if a call fails:

- return the original error as-is
- add context with `fmt.Errorf` and the `%w` verb
- add context with `fmt.Errorf` and the `%v` verb

Return the original error as-is if there is no additional context to add. This maintains the original error type and message. This is well suited for cases when the underlying error message has sufficient information to track down where it came from.

Otherwise, add context to the error message where possible so that instead of a vague error such as "connection refused", you get more useful errors such as "call service foo: connection refused".

Use `fmt.Errorf` to add context to your errors, picking between the `%w` or `%v` verbs based on whether the caller should be able to match and extract the underlying cause.

- Use `%w` if the caller should have access to the underlying error. This is a good default for most wrapped errors, but be aware that callers may begin to rely on this behavior. So for cases where the wrapped error is a known `var` or type, document and test it as part of your function's contract.
- Use `%v` to obfuscate the underlying error. Callers will be unable to match it, but you can switch to `%w` in the future if needed.

When adding context to returned errors, keep the context succinct by avoiding phrases like "failed to", which state the obvious and pile up as the error percolates up through the stack:

Bad Good

```
s, err := store.New()
if err != nil {
    return fmt.Errorf(
        "failed to create new store: %w", err)
}
```

```
s, err := store.New()
if err != nil {
    return fmt.Errorf(
        "new store: %w", err)
}
```

failed to x: failed to y: failed to create new store: the error

x: y: new store: the error

However once the error is sent to another system, it should be clear the message is an error (e.g. an `err` tag or "Failed" prefix in logs).

See also [Don't just check errors, handle them gracefully](#).

Error Naming

For error values stored as global variables, use the prefix `Err` or `err` depending on whether they're exported. This guidance supersedes the [Prefix Unexported Globals with _](#).

```

var (
    // The following two errors are exported
    // so that users of this package can match them
    // with errors.Is.

    ErrBrokenLink = errors.New("link is broken")
    ErrCouldNotOpen = errors.New("could not open")

    // This error is not exported because
    // we don't want to make it part of our public API.
    // We may still use it inside the package
    // with errors.Is.

    errNotFound = errors.New("not found")
)

```

For custom error types, use the suffix `Error` instead.

```

// Similarly, this error is exported
// so that users of this package can match it
// with errors.As.

type NotFoundError struct {
    File string
}

func (e *NotFoundError) Error() string {
    return fmt.Sprintf("file %q not found", e.File)
}

// And this error is not exported because
// we don't want to make it part of the public API.
// We can still use it inside the package
// with errors.As.

type resolveError struct {
    Path string
}

func (e *resolveError) Error() string {
    return fmt.Sprintf("resolve %q", e.Path)
}

```

Handle Type Assertion Failures

The single return value form of a [type assertion](#) will panic on an incorrect type. Therefore, always use the "comma ok" idiom.

Bad **Good**

Bad Good

```
t := i.(string)
```

```
t, ok := i.(string)
if !ok {
    // handle the error gracefully
}
```

Don't Panic

Code running in production must avoid panics. Panics are a major source of [cascading failures](#). If an error occurs, the function must return an error and allow the caller to decide how to handle it.

Bad Good

```
func run(args []string) {
    if len(args) == 0 {
        panic("an argument is required")
    }
    // ...
}

func main() {
    run(os.Args[1:])
}
```

```
func run(args []string) error {
    if len(args) == 0 {
        return errors.New("an argument is required")
    }
    // ...
    return nil
}

func main() {
    if err := run(os.Args[1:]); err != nil {
        fmt.Fprintln(os.Stderr, err)
        os.Exit(1)
    }
}
```

Panic/recover is not an error handling strategy. A program must panic only when something irrecoverable happens such as a nil dereference. An exception to this is program initialization: bad things at program startup that should abort the program may cause panic.

```
var _statusTemplate =
    template.Must(template.New("name").Parse("_statusHTML"))
```

Even in tests, prefer `t.Fatal` or `t.FailNow` over panics to ensure that the test is marked as failed.

Bad Good

```
// func TestFoo(t *testing.T)

f, err := ioutil.TempFile("", "test")
if err != nil {
    panic("failed to set up test")
}
```

```
// func TestFoo(t *testing.T)

f, err := ioutil.TempFile("", "test")
if err != nil {
    t.Fatal("failed to set up test")
}
```

Use go.uber.org/atomic

Atomic operations with the [sync/atomic](https://go.uber.org/atomic) package operate on the raw types (`int32`, `int64`, etc.) so it is easy to forget to use the atomic operation to read or modify the variables.

go.uber.org/atomic adds type safety to these operations by hiding the underlying type. Additionally, it includes a convenient `atomic.Bool` type.

Bad Good

```
type foo struct {
    running int32 // atomic
}

func (f* foo) start() {
    if atomic.SwapInt32(&f.running, 1) == 1 {
        // already running...
        return
    }
}
```

```

    }
    // start the Foo
}

func (f *foo) isRunning() bool {
    return f.running == 1 // race!
}

```

```

type foo struct {
    running atomic.Bool
}

func (f *foo) start() {
    if f.running.Swap(true) {
        // already running...
        return
    }
    // start the Foo
}

func (f *foo) isRunning() bool {
    return f.running.Load()
}

```

Avoid Mutable Globals

Avoid mutating global variables, instead opting for dependency injection. This applies to function pointers as well as other kinds of values.

Bad Good

```

// sign.go

var _timeNow = time.Now

func sign(msg string) string {
    now := _timeNow()
    return signWithTime(msg, now)
}

```

```

// sign.go

type signer struct {
    now func() time.Time
}

```

```
func newSigner() *signer {
    return &signer{
        now: time.Now,
    }
}

func (s *signer) Sign(msg string) string {
    now := s.now()
    return signWithTime(msg, now)
}
```

```
// sign_test.go

func TestSign(t *testing.T) {
    oldTimeNow := _timeNow
    _timeNow = func() time.Time {
        return someFixedTime
    }
    defer func() { _timeNow = oldTimeNow }()

    assert.Equal(t, want, sign(give))
}
```

```
// sign_test.go

func TestSigner(t *testing.T) {
    s := newSigner()
    s.now = func() time.Time {
        return someFixedTime
    }

    assert.Equal(t, want, s.Sign(give))
}
```

Avoid Embedding Types in Public Structs

These embedded types leak implementation details, inhibit type evolution, and obscure documentation.

Assuming you have implemented a variety of list types using a shared `AbstractList`, avoid embedding the `AbstractList` in your concrete list implementations. Instead, hand-write only the methods to your concrete list that will delegate to the abstract list.

```
type AbstractList struct {}

// Add adds an entity to the list.
func (l *AbstractList) Add(e Entity) {
    // ...
}
```

```

}

// Remove removes an entity from the list.
func (l *AbstractList) Remove(e Entity) {
    // ...
}

```

Bad **Good**

```

// ConcreteList is a list of entities.
type ConcreteList struct {
    *AbstractList
}

```

```

// ConcreteList is a list of entities.
type ConcreteList struct {
    list *AbstractList
}

// Add adds an entity to the list.
func (l *ConcreteList) Add(e Entity) {
    l.list.Add(e)
}

// Remove removes an entity from the list.
func (l *ConcreteList) Remove(e Entity) {
    l.list.Remove(e)
}

```

Go allows [type embedding](#) as a compromise between inheritance and composition. The outer type gets implicit copies of the embedded type's methods. These methods, by default, delegate to the same method of the embedded instance.

The struct also gains a field by the same name as the type. So, if the embedded type is public, the field is public. To maintain backward compatibility, every future version of the outer type must keep the embedded type.

An embedded type is rarely necessary. It is a convenience that helps you avoid writing tedious delegate methods.

Even embedding a compatible *AbstractList interface*, instead of the struct, would offer the developer more flexibility to change in the future, but still leak the detail that the concrete lists use an abstract implementation.

Bad **Good**

```
// AbstractList is a generalized implementation
// for various kinds of lists of entities.
type AbstractList interface {
    Add(Entity)
    Remove(Entity)
}

// ConcreteList is a list of entities.
type ConcreteList struct {
    AbstractList
}
```

```
// ConcreteList is a list of entities.
type ConcreteList struct {
    list AbstractList
}

// Add adds an entity to the list.
func (l *ConcreteList) Add(e Entity) {
    l.list.Add(e)
}

// Remove removes an entity from the list.
func (l *ConcreteList) Remove(e Entity) {
    l.list.Remove(e)
}
```

Either with an embedded struct or an embedded interface, the embedded type places limits on the evolution of the type.

- Adding methods to an embedded interface is a breaking change.
- Removing methods from an embedded struct is a breaking change.
- Removing the embedded type is a breaking change.
- Replacing the embedded type, even with an alternative that satisfies the same interface, is a breaking change.

Although writing these delegate methods is tedious, the additional effort hides an implementation detail, leaves more opportunities for change, and also eliminates indirection for discovering the full List interface in documentation.

Avoid Using Built-In Names

The Go [language specification](#) outlines several built-in, [predeclared identifiers](#) that should not be used as names within Go programs.

Depending on context, reusing these identifiers as names will either shadow the original within the current lexical scope (and any nested scopes) or make affected code confusing. In the best case, the compiler will complain; in the worst case, such code may introduce latent, hard-to-grep bugs.

Bad Good

```
var error string
// `error` shadows the builtin

// or

func handleErrorMessage(error string) {
    // `error` shadows the builtin
}
```

```
var errorMessage string
// `error` refers to the builtin

// or

func handleErrorMessage(msg string) {
    // `error` refers to the builtin
}
```

```
type Foo struct {
    // While these fields technically don't
    // constitute shadowing, grepping for
    // `error` or `string` strings is now
    // ambiguous.
    error error
    string string
}

func (f Foo) Error() error {
    // `error` and `f.error` are
    // visually similar
    return f.error
}

func (f Foo) String() string {
    // `string` and `f.string` are
    // visually similar
    return f.string
}
```

```
type Foo struct {
    // `error` and `string` strings are
    // now unambiguous.
    err error
}
```

```

    str string
}

func (f Foo) Error() error {
    return f.err
}

func (f Foo) String() string {
    return f.str
}

```

Note that the compiler will not generate errors when using predeclared identifiers, but tools such as `go vet` should correctly point out these and other cases of shadowing.

Avoid `init()`

Avoid `init()` where possible. When `init()` is unavoidable or desirable, code should attempt to:

1. Be completely deterministic, regardless of program environment or invocation.
2. Avoid depending on the ordering or side-effects of other `init()` functions. While `init()` ordering is well-known, code can change, and thus relationships between `init()` functions can make code brittle and error-prone.
3. Avoid accessing or manipulating global or environment state, such as machine information, environment variables, working directory, program arguments/inputs, etc.
4. Avoid I/O, including both filesystem, network, and system calls.

Code that cannot satisfy these requirements likely belongs as a helper to be called as part of `main()` (or elsewhere in a program's lifecycle), or be written as part of `main()` itself. In particular, libraries that are intended to be used by other programs should take special care to be completely deterministic and not perform "init magic".

Bad **Good**

```

type Foo struct {
    // ...
}

var _defaultFoo Foo

func init() {
    _defaultFoo = Foo{
        // ...
    }
}

```

```

var _defaultFoo = Foo{
    // ...
}

```

```
}

// or, better, for testability:

var _defaultFoo = defaultFoo()

func defaultFoo() Foo {
    return Foo{
        // ...
    }
}
```

```
type Config struct {
    // ...
}

var _config Config

func init() {
    // Bad: based on current directory
    cwd, _ := os.Getwd()

    // Bad: I/O
    raw, _ := ioutil.ReadFile(
        path.Join(cwd, "config", "config.yaml"),
    )

    yaml.Unmarshal(raw, &_config)
}
```

```
type Config struct {
    // ...
}

func loadConfig() Config {
    cwd, err := os.Getwd()
    // handle err

    raw, err := ioutil.ReadFile(
        path.Join(cwd, "config", "config.yaml"),
    )
    // handle err

    var config Config
    yaml.Unmarshal(raw, &config)

    return config
}
```

Considering the above, some situations in which `init()` may be preferable or necessary might include:

- Complex expressions that cannot be represented as single assignments.
- Pluggable hooks, such as `database/sql` dialects, encoding type registries, etc.
- Optimizations to [Google Cloud Functions](#) and other forms of deterministic precomputation.

Exit in Main

Go programs use `os.Exit` or `log.Fatal*` to exit immediately. (Panicking is not a good way to exit programs, please [don't panic](#).)

Call one of `os.Exit` or `log.Fatal*` **only in `main()`**. All other functions should return errors to signal failure.

Bad Good

```
func main() {
    body := readFile(path)
    fmt.Println(body)
}

func readFile(path string) string {
    f, err := os.Open(path)
    if err != nil {
        log.Fatal(err)
    }

    b, err := ioutil.ReadAll(f)
    if err != nil {
        log.Fatal(err)
    }

    return string(b)
}
```

```
func main() {
    body, err := readFile(path)
    if err != nil {
        log.Fatal(err)
    }
    fmt.Println(body)
}

func readFile(path string) (string, error) {
    f, err := os.Open(path)
    if err != nil {
        return "", err
    }
}
```

```

}

b, err := ioutil.ReadAll(f)
if err != nil {
    return "", err
}

return string(b), nil
}

```

Rationale: Programs with multiple functions that exit present a few issues:

- Non-obvious control flow: Any function can exit the program so it becomes difficult to reason about the control flow.
- Difficult to test: A function that exits the program will also exit the test calling it. This makes the function difficult to test and introduces risk of skipping other tests that have not yet been run by `go test`.
- Skipped cleanup: When a function exits the program, it skips function calls enqueued with `defer` statements. This adds risk of skipping important cleanup tasks.

Exit Once

If possible, prefer to call `os.Exit` or `log.Fatal` **at most once** in your `main()`. If there are multiple error scenarios that halt program execution, put that logic under a separate function and return errors from it.

This has the effect of shortening your `main()` function and putting all key business logic into a separate, testable function.

Bad Good

```

package main

func main() {
    args := os.Args[1:]
    if len(args) != 1 {
        log.Fatal("missing file")
    }
    name := args[0]

    f, err := os.Open(name)
    if err != nil {
        log.Fatal(err)
    }
    defer f.Close()

    // If we call log.Fatal after this line,
    // f.Close will not be called.

    b, err := ioutil.ReadAll(f)

```

```
    if err != nil {
        log.Fatal(err)
    }

    // ...
}
```

```
package main

func main() {
    if err := run(); err != nil {
        log.Fatal(err)
    }
}

func run() error {
    args := os.Args[1:]
    if len(args) != 1 {
        return errors.New("missing file")
    }
    name := args[0]

    f, err := os.Open(name)
    if err != nil {
        return err
    }
    defer f.Close()

    b, err := ioutil.ReadAll(f)
    if err != nil {
        return err
    }

    // ...
}
```

Use field tags in marshaled structs

Any struct field that is marshaled into JSON, YAML, or other formats that support tag-based field naming should be annotated with the relevant tag.

Bad **Good**

```
type Stock struct {
    Price int
    Name  string
}
```

```
bytes, err := json.Marshal(Stock{
    Price: 137,
    Name: "UBER",
})
```

```
type Stock struct {
    Price int    `json:"price"`
    Name  string `json:"name"`
    // Safe to rename Name to Symbol.
}

bytes, err := json.Marshal(Stock{
    Price: 137,
    Name: "UBER",
})
```

Rationale: The serialized form of the structure is a contract between different systems. Changes to the structure of the serialized form--including field names--break this contract. Specifying field names inside tags makes the contract explicit, and it guards against accidentally breaking the contract by refactoring or renaming fields.

Performance

Performance-specific guidelines apply only to the hot path.

Prefer `strconv` over `fmt`

When converting primitives to/from strings, `strconv` is faster than `fmt`.

Bad **Good**

```
for i := 0; i < b.N; i++ {
    s := fmt.Sprint(rand.Int())
}
```

```
for i := 0; i < b.N; i++ {
    s := strconv.Itoa(rand.Int())
}
```

BenchmarkFmtSprint-4	143 ns/op	2 allocs/op
----------------------	-----------	-------------

```
BenchmarkStrconv-4    64.2 ns/op    1 allocs/op
```

Avoid string-to-byte conversion

Do not create byte slices from a fixed string repeatedly. Instead, perform the conversion once and capture the result.

Bad **Good**

```
for i := 0; i < b.N; i++ {  
    w.Write([]byte("Hello world"))  
}
```

```
data := []byte("Hello world")  
for i := 0; i < b.N; i++ {  
    w.Write(data)  
}
```

```
BenchmarkBad-4    500000000    22.2 ns/op
```

```
BenchmarkGood-4    500000000    3.25 ns/op
```

Prefer Specifying Container Capacity

Specify container capacity where possible in order to allocate memory for the container up front. This minimizes subsequent allocations (by copying and resizing of the container) as elements are added.

Specifying Map Capacity Hints

Where possible, provide capacity hints when initializing maps with `make()`.

```
make(map[T1]T2, hint)
```

Providing a capacity hint to `make()` tries to right-size the map at initialization time, which reduces the need for growing the map and allocations as elements are added to the map.

Note that, unlike slices, map capacity hints do not guarantee complete, preemptive allocation, but are used to approximate the number of hashmap buckets required. Consequently, allocations may still occur when

adding elements to the map, even up to the specified capacity.

Bad Good

```
m := make(map[string]os.FileInfo)

files, _ := ioutil.ReadDir("./files")
for _, f := range files {
    m[f.Name()] = f
}
```

```
files, _ := ioutil.ReadDir("./files")

m := make(map[string]os.FileInfo, len(files))
for _, f := range files {
    m[f.Name()] = f
}
```

`m` is created without a size hint; there may be more allocations at assignment time.

`m` is created with a size hint; there may be fewer allocations at assignment time.

Specifying Slice Capacity

Where possible, provide capacity hints when initializing slices with `make()`, particularly when appending.

```
make([]T, length, capacity)
```

Unlike maps, slice capacity is not a hint: the compiler will allocate enough memory for the capacity of the slice as provided to `make()`, which means that subsequent `append()` operations will incur zero allocations (until the length of the slice matches the capacity, after which any appends will require a resize to hold additional elements).

Bad Good

```
for n := 0; n < b.N; n++ {
    data := make([]int, 0)
    for k := 0; k < size; k++{
        data = append(data, k)
    }
}
```

```
for n := 0; n < b.N; n++ {  
    data := make([]int, 0, size)  
    for k := 0; k < size; k++{  
        data = append(data, k)  
    }  
}
```

BenchmarkBad-4	1000000000	2.48s
----------------	------------	-------

BenchmarkGood-4	1000000000	0.21s
-----------------	------------	-------

Style

Avoid overly long lines

Avoid lines of code that require readers to scroll horizontally or turn their heads too much.

We recommend a soft line length limit of **99 characters**. Authors should aim to wrap lines before hitting this limit, but it is not a hard limit. Code is allowed to exceed this limit.

Be Consistent

Some of the guidelines outlined in this document can be evaluated objectively; others are situational, contextual, or subjective.

Above all else, **be consistent**.

Consistent code is easier to maintain, is easier to rationalize, requires less cognitive overhead, and is easier to migrate or update as new conventions emerge or classes of bugs are fixed.

Conversely, having multiple disparate or conflicting styles within a single codebase causes maintenance overhead, uncertainty, and cognitive dissonance, all of which can directly contribute to lower velocity, painful code reviews, and bugs.

When applying these guidelines to a codebase, it is recommended that changes are made at a package (or larger) level: application at a sub-package level violates the above concern by introducing multiple styles into the same code.

Group Similar Declarations

Go supports grouping similar declarations.

Bad **Good**

```
import "a"
import "b"
```

```
import (
    "a"
    "b"
)
```

This also applies to constants, variables, and type declarations.

Bad **Good**

```
const a = 1
const b = 2
```

```
var a = 1
var b = 2
```

```
type Area float64
type Volume float64
```

```
const (
    a = 1
    b = 2
)

var (
    a = 1
    b = 2
)

type (
    Area float64
    Volume float64
)
```

Only group related declarations. Do not group declarations that are unrelated.

Bad **Good**

Bad Good

```
type Operation int

const (
    Add Operation = iota + 1
    Subtract
    Multiply
    EnvVar = "MY_ENV"
)
```

```
type Operation int

const (
    Add Operation = iota + 1
    Subtract
    Multiply
)

const EnvVar = "MY_ENV"
```

Groups are not limited in where they can be used. For example, you can use them inside of functions.

Bad Good

```
func f() string {
    red := color.New(0xff0000)
    green := color.New(0x00ff00)
    blue := color.New(0x0000ff)

    // ...
}
```

```
func f() string {
    var (
        red   = color.New(0xff0000)
        green = color.New(0x00ff00)
        blue  = color.New(0x0000ff)
    )

    // ...
}
```

Exception: Variable declarations, particularly inside functions, should be grouped together if declared adjacent to other variables. Do this for variables declared together even if they are unrelated.

Bad Good

```
func (c *client) request() {  
    caller := c.name  
    format := "json"  
    timeout := 5*time.Second  
    var err error  
  
    // ...  
}
```

```
func (c *client) request() {  
    var (  
        caller = c.name  
        format = "json"  
        timeout = 5*time.Second  
        err error  
    )  
  
    // ...  
}
```

Import Group Ordering

There should be two import groups:

- Standard library
- Everything else

This is the grouping applied by goimports by default.

Bad Good

```
import (  
    "fmt"  
    "os"  
    "go.uber.org/atomic"  
    "golang.org/x/sync/errgroup"  
)
```

```
import (  
    "fmt"  
    "os"  
  
    "go.uber.org/atomic"  
    "golang.org/x/sync/errgroup"  
)
```

Package Names

When naming packages, choose a name that is:

- All lower-case. No capitals or underscores.
- Does not need to be renamed using named imports at most call sites.
- Short and succinct. Remember that the name is identified in full at every call site.
- Not plural. For example, `net/url`, not `net/urls`.
- Not "common", "util", "shared", or "lib". These are bad, uninformative names.

See also [Package Names](#) and [Style guideline for Go packages](#).

Function Names

We follow the Go community's convention of using [MixedCaps for function names](#). An exception is made for test functions, which may contain underscores for the purpose of grouping related test cases, e.g., `TestMyFunction_WhatIsBeingTested`.

Import Aliasing

Import aliasing must be used if the package name does not match the last element of the import path.

```
import (  
    "net/http"  
  
    client "example.com/client-go"  
    trace "example.com/trace/v2"  
)
```

In all other scenarios, import aliases should be avoided unless there is a direct conflict between imports.

Bad **Good**

```
import (  
    "fmt"  
    "os"
```

```
nettrace "golang.net/x/trace"
)
```

```
import (
    "fmt"
    "os"
    "runtime/trace"

    nettrace "golang.net/x/trace"
)
```

Function Grouping and Ordering

- Functions should be sorted in rough call order.
- Functions in a file should be grouped by receiver.

Therefore, exported functions should appear first in a file, after **struct**, **const**, **var** definitions.

A **newXYZ()**/**NewXYZ()** may appear after the type is defined, but before the rest of the methods on the receiver.

Since functions are grouped by receiver, plain utility functions should appear towards the end of the file.

Bad **Good**

```
func (s *something) Cost() {
    return calcCost(s.weights)
}

type something struct{ ... }

func calcCost(n []int) int {...}

func (s *something) Stop() {...}

func newSomething() *something {
    return &something{}
}
```

```
type something struct{ ... }

func newSomething() *something {
    return &something{}
}

func (s *something) Cost() {
```

```

    return calcCost(s.weights)
}

func (s *something) Stop() {...}

func calcCost(n []int) int {...}

```

Reduce Nesting

Code should reduce nesting where possible by handling error cases/special conditions first and returning early or continuing the loop. Reduce the amount of code that is nested multiple levels.

Bad **Good**

```

for _, v := range data {
    if v.F1 == 1 {
        v = process(v)
        if err := v.Call(); err == nil {
            v.Send()
        } else {
            return err
        }
    } else {
        log.Printf("Invalid v: %v", v)
    }
}

```

```

for _, v := range data {
    if v.F1 != 1 {
        log.Printf("Invalid v: %v", v)
        continue
    }

    v = process(v)
    if err := v.Call(); err != nil {
        return err
    }
    v.Send()
}

```

Unnecessary Else

If a variable is set in both branches of an if, it can be replaced with a single if.

Bad **Good**

```
var a int
if b {
    a = 100
} else {
    a = 10
}
```

```
a := 10
if b {
    a = 100
}
```

Top-level Variable Declarations

At the top level, use the standard `var` keyword. Do not specify the type, unless it is not the same type as the expression.

Bad **Good**

```
var _s string = F()

func F() string { return "A" }
```

```
var _s = F()
// Since F already states that it returns a string, we don't need to
// specify
// the type again.

func F() string { return "A" }
```

Specify the type if the type of the expression does not match the desired type exactly.

```
type myError struct{}

func (myError) Error() string { return "error" }

func F() myError { return myError{} }

var _e error = F()
// F returns an object of type myError but we want error.
```

Prefix Unexported Globals with _

Prefix unexported top-level **vars** and **consts** with **_** to make it clear when they are used that they are global symbols.

Exception: Unexported error values, which should be prefixed with **err**.

Rationale: Top-level variables and constants have a package scope. Using a generic name makes it easy to accidentally use the wrong value in a different file.

Bad **Good**

```
// foo.go

const (
    defaultPort = 8080
    defaultUser = "user"
)

// bar.go

func Bar() {
    defaultPort := 9090
    ...
    fmt.Println("Default port", defaultPort)

    // We will not see a compile error if the first line of
    // Bar() is deleted.
}
```

```
// foo.go

const (
    _defaultPort = 8080
    _defaultUser = "user"
)
```

Exception: Unexported error values may use the prefix **err** without the underscore. See [Error Naming](#).

Embedding in Structs

Embedded types should be at the top of the field list of a struct, and there must be an empty line separating embedded fields from regular fields.

Bad **Good**

```
type Client struct {
    version int
    http.Client
}
```

```
type Client struct {
    http.Client

    version int
}
```

Embedding should provide tangible benefit, like adding or augmenting functionality in a semantically-appropriate way. It should do this with zero adverse user-facing effects (see also: [Avoid Embedding Types in Public Structs](#)).

Exception: Mutexes should not be embedded, even on unexported types. See also: [Zero-value Mutexes are Valid](#).

Embedding **should not**:

- Be purely cosmetic or convenience-oriented.
- Make outer types more difficult to construct or use.
- Affect outer types' zero values. If the outer type has a useful zero value, it should still have a useful zero value after embedding the inner type.
- Expose unrelated functions or fields from the outer type as a side-effect of embedding the inner type.
- Expose unexported types.
- Affect outer types' copy semantics.
- Change the outer type's API or type semantics.
- Embed a non-canonical form of the inner type.
- Expose implementation details of the outer type.
- Allow users to observe or control type internals.
- Change the general behavior of inner functions through wrapping in a way that would reasonably surprise users.

Simply put, embed consciously and intentionally. A good litmus test is, "would all of these exported inner methods/fields be added directly to the outer type"; if the answer is "some" or "no", don't embed the inner type - use a field instead.

Bad Good

```
type A struct {
    // Bad: A.Lock() and A.Unlock() are
    //       now available, provide no
    //       functional benefit, and allow
```

```
//      users to control details about
//      the internals of A.
sync.Mutex
}
```

```
type countingWriter struct {
    // Good: Write() is provided at this
    //      outer layer for a specific
    //      purpose, and delegates work
    //      to the inner type's Write().
    io.Writer

    count int
}

func (w *countingWriter) Write(bs []byte) (int, error) {
    w.count += len(bs)
    return w.Writer.Write(bs)
}
```

```
type Book struct {
    // Bad: pointer changes zero value usefulness
    io.ReadWriter

    // other fields
}

// later

var b Book
b.Read(...) // panic: nil pointer
b.String()  // panic: nil pointer
b.Write(...) // panic: nil pointer
```

```
type Book struct {
    // Good: has useful zero value
    bytes.Buffer

    // other fields
}

// later

var b Book
b.Read(...) // ok
b.String()  // ok
b.Write(...) // ok
```

```
type Client struct {  
    sync.Mutex  
    sync.WaitGroup  
    bytes.Buffer  
    url.URL  
}
```

```
type Client struct {  
    mtx sync.Mutex  
    wg  sync.WaitGroup  
    buf bytes.Buffer  
    url url.URL  
}
```

Local Variable Declarations

Short variable declarations (`:=`) should be used if a variable is being set to some value explicitly.

Bad **Good**

```
var s = "foo"
```

```
s := "foo"
```

However, there are cases where the default value is clearer when the `var` keyword is used. [Declaring Empty Slices](#), for example.

Bad **Good**

```
func f(list []int) {  
    filtered := []int{}  
    for _, v := range list {  
        if v > 10 {  
            filtered = append(filtered, v)  
        }  
    }  
}
```

```
func f(list []int) {
    var filtered []int
    for _, v := range list {
        if v > 10 {
            filtered = append(filtered, v)
        }
    }
}
```

`nil` is a valid slice

`nil` is a valid slice of length 0. This means that,

- You should not return a slice of length zero explicitly. Return `nil` instead.

Bad Good

```
if x == "" {
    return []int{}
}
```

```
if x == "" {
    return nil
}
```

- To check if a slice is empty, always use `len(s) == 0`. Do not check for `nil`.

Bad Good

```
func isEmpty(s []string) bool {
    return s == nil
}
```

```
func isEmpty(s []string) bool {
    return len(s) == 0
}
```

- The zero value (a slice declared with `var`) is usable immediately without `make()`.

Bad Good

```

nums := []int{}
// or, nums := make([]int)

if add1 {
    nums = append(nums, 1)
}

if add2 {
    nums = append(nums, 2)
}

```

```

var nums []int

if add1 {
    nums = append(nums, 1)
}

if add2 {
    nums = append(nums, 2)
}

```

Remember that, while it is a valid slice, a nil slice is not equivalent to an allocated slice of length 0 - one is nil and the other is not - and the two may be treated differently in different situations (such as serialization).

Reduce Scope of Variables

Where possible, reduce scope of variables. Do not reduce the scope if it conflicts with [Reduce Nesting](#).

Bad **Good**

```

err := ioutil.WriteFile(name, data, 0644)
if err != nil {
    return err
}

```

```

if err := ioutil.WriteFile(name, data, 0644); err != nil {
    return err
}

```

If you need a result of a function call outside of the if, then you should not try to reduce the scope.

Bad **Good**

```

if data, err := ioutil.ReadFile(name); err == nil {
    err = cfg.Decode(data)
    if err != nil {
        return err
    }

    fmt.Println(cfg)
    return nil
} else {
    return err
}

```

```

data, err := ioutil.ReadFile(name)
if err != nil {
    return err
}

if err := cfg.Decode(data); err != nil {
    return err
}

fmt.Println(cfg)
return nil

```

Avoid Naked Parameters

Naked parameters in function calls can hurt readability. Add C-style comments (`/* ... */`) for parameter names when their meaning is not obvious.

Bad **Good**

```

// func printInfo(name string, isLocal, done bool)

printInfo("foo", true, true)

```

```

// func printInfo(name string, isLocal, done bool)

printInfo("foo", true /* isLocal */, true /* done */)

```

Better yet, replace naked `bool` types with custom types for more readable and type-safe code. This allows more than just two states (true/false) for that parameter in the future.


```
type Region int

const (
    UnknownRegion Region = iota
    Local
)

type Status int

const (
    StatusReady Status = iota + 1
    StatusDone
    // Maybe we will have a StatusInProgress in the future.
)

func printInfo(name string, region Region, status Status)
```

Use Raw String Literals to Avoid Escaping

Go supports [raw string literals](#), which can span multiple lines and include quotes. Use these to avoid hand-escaped strings which are much harder to read.

Bad **Good**

```
wantError := "unknown name:\"test\""
```

```
wantError := `unknown error:"test"`
```

Initializing Structs

Use Field Names to Initialize Structs

You should almost always specify field names when initializing structs. This is now enforced by [go vet](#).

Bad **Good**

```
k := User{"John", "Doe", true}
```

```
k := User{
    FirstName: "John",
    LastName: "Doe",
}
```

```
    Admin: true,  
}
```

Exception: Field names *may* be omitted in test tables when there are 3 or fewer fields.

```
tests := []struct{  
    op Operation  
    want string  
}{  
    {Add, "add"},  
    {Subtract, "subtract"},  
}
```

Omit Zero Value Fields in Structs

When initializing structs with field names, omit fields that have zero values unless they provide meaningful context. Otherwise, let Go set these to zero values automatically.

Bad **Good**

```
user := User{  
    FirstName: "John",  
    LastName: "Doe",  
    MiddleName: "",  
    Admin: false,  
}
```

```
user := User{  
    FirstName: "John",  
    LastName: "Doe",  
}
```

This helps reduce noise for readers by omitting values that are default in that context. Only meaningful values are specified.

Include zero values where field names provide meaningful context. For example, test cases in [Test Tables](#) can benefit from names of fields even when they are zero-valued.

```
tests := []struct{  
    give string  
    want int  
}{  
    {give: "0", want: 0},  
}
```

```
// ...  
}
```

Use **var** for Zero Value Structs

When all the fields of a struct are omitted in a declaration, use the **var** form to declare the struct.

Bad **Good**

```
user := User{}
```

```
var user User
```

This differentiates zero valued structs from those with non-zero fields similar to the distinction created for [map initialization](#), and matches how we prefer to [declare empty slices](#).

Initializing Struct References

Use **&T{}** instead of **new(T)** when initializing struct references so that it is consistent with the struct initialization.

Bad **Good**

```
sval := T{Name: "foo"}  
  
// inconsistent  
sptr := new(T)  
sptr.Name = "bar"
```

```
sval := T{Name: "foo"}  
  
sptr := &T{Name: "bar"}
```

Initializing Maps

Prefer **make(...)** for empty maps, and maps populated programmatically. This makes map initialization visually distinct from declaration, and it makes it easy to add size hints later if available.

Bad **Good**

```
var (
    // m1 is safe to read and write;
    // m2 will panic on writes.
    m1 = map[T1]T2{}
    m2 map[T1]T2
)
```

```
var (
    // m1 is safe to read and write;
    // m2 will panic on writes.
    m1 = make(map[T1]T2)
    m2 map[T1]T2
)
```

Declaration and initialization are visually similar.

Declaration and initialization are visually distinct.

Where possible, provide capacity hints when initializing maps with `make()`. See [Specifying Map Capacity Hints](#) for more information.

On the other hand, if the map holds a fixed list of elements, use map literals to initialize the map.

Bad Good

```
m := make(map[T1]T2, 3)
m[k1] = v1
m[k2] = v2
m[k3] = v3
```

```
m := map[T1]T2{
    k1: v1,
    k2: v2,
    k3: v3,
}
```

The basic rule of thumb is to use map literals when adding a fixed set of elements at initialization time, otherwise use `make` (and specify a size hint if available).

Format Strings outside Printf

If you declare format strings for `Printf`-style functions outside a string literal, make them `const` values.

This helps `go vet` perform static analysis of the format string.

Bad Good

```
msg := "unexpected values %v, %v\n"
fmt.Printf(msg, 1, 2)
```

```
const msg = "unexpected values %v, %v\n"
fmt.Printf(msg, 1, 2)
```

Naming Printf-style Functions

When you declare a `Printf`-style function, make sure that `go vet` can detect it and check the format string.

This means that you should use predefined `Printf`-style function names if possible. `go vet` will check these by default. See [Printf family](#) for more information.

If using the predefined names is not an option, end the name you choose with `f`: `Wrapf`, not `Wrap`. `go vet` can be asked to check specific `Printf`-style names but they must end with `f`.

```
$ go vet -printfuncs=wrapf,statusf
```

See also [go vet: Printf family check](#).

Patterns

Test Tables

Use table-driven tests with [subtests](#) to avoid duplicating code when the core test logic is repetitive.

Bad Good

```
// func TestSplitHostPort(t *testing.T)

host, port, err := net.SplitHostPort("192.0.2.0:8000")
require.NoError(t, err)
assert.Equal(t, "192.0.2.0", host)
assert.Equal(t, "8000", port)

host, port, err = net.SplitHostPort("192.0.2.0:http")
require.NoError(t, err)
assert.Equal(t, "192.0.2.0", host)
assert.Equal(t, "http", port)
```

```

host, port, err = net.SplitHostPort(":8000")
require.NoError(t, err)
assert.Equal(t, "", host)
assert.Equal(t, "8000", port)

```

```

host, port, err = net.SplitHostPort("1:8")
require.NoError(t, err)
assert.Equal(t, "1", host)
assert.Equal(t, "8", port)

```

```

// func TestSplitHostPort(t *testing.T)

tests := []struct{
    give      string
    wantHost  string
    wantPort  string
}{
    {
        give:      "192.0.2.0:8000",
        wantHost:  "192.0.2.0",
        wantPort:  "8000",
    },
    {
        give:      "192.0.2.0:http",
        wantHost:  "192.0.2.0",
        wantPort:  "http",
    },
    {
        give:      ":8000",
        wantHost:  "",
        wantPort:  "8000",
    },
    {
        give:      "1:8",
        wantHost:  "1",
        wantPort:  "8",
    },
}

for _, tt := range tests {
    t.Run(tt.give, func(t *testing.T) {
        host, port, err := net.SplitHostPort(tt.give)
        require.NoError(t, err)
        assert.Equal(t, tt.wantHost, host)
        assert.Equal(t, tt.wantPort, port)
    })
}

```

Test tables make it easier to add context to error messages, reduce duplicate logic, and add new test cases.

We follow the convention that the slice of structs is referred to as **tests** and each test case **tt**. Further, we encourage explicating the input and output values for each test case with **give** and **want** prefixes.

```
tests := []struct{
    give      string
    wantHost  string
    wantPort  string
}{
    // ...
}

for _, tt := range tests {
    // ...
}
```

Parallel tests, like some specialized loops (for example, those that spawn goroutines or capture references as part of the loop body), must take care to explicitly assign loop variables within the loop's scope to ensure that they hold the expected values.

```
tests := []struct{
    give string
    // ...
}{
    // ...
}

for _, tt := range tests {
    tt := tt // for t.Parallel
    t.Run(tt.give, func(t *testing.T) {
        t.Parallel()
        // ...
    })
}
```

In the example above, we must declare a **tt** variable scoped to the loop iteration because of the use of **t.Parallel()** below. If we do not do that, most or all tests will receive an unexpected value for **tt**, or a value that changes as they're running.

Functional Options

Functional options is a pattern in which you declare an opaque **Option** type that records information in some internal struct. You accept a variadic number of these options and act upon the full information recorded by the options on the internal struct.

Use this pattern for optional arguments in constructors and other public APIs that you foresee needing to expand, especially if you already have three or more arguments on those functions.

Bad Good

```
// package db

func Open(
    addr string,
    cache bool,
    logger *zap.Logger
) (*Connection, error) {
    // ...
}
```

```
// package db

type Option interface {
    // ...
}

func WithCache(c bool) Option {
    // ...
}

func WithLogger(log *zap.Logger) Option {
    // ...
}

// Open creates a connection.
func Open(
    addr string,
    opts ...Option,
) (*Connection, error) {
    // ...
}
```

The cache and logger parameters must always be provided, even if the user wants to use the default.

```
db.Open(addr, db.DefaultCache, zap.NewNop())
db.Open(addr, db.DefaultCache, log)
db.Open(addr, false /* cache */, zap.NewNop())
db.Open(addr, false /* cache */, log)
```

Options are provided only if needed.

```
db.Open(addr)
db.Open(addr, db.WithLogger(log))
```



```
db.Open(addr, db.WithCache(false))
db.Open(
    addr,
    db.WithCache(false),
    db.WithLogger(log),
)
```

Our suggested way of implementing this pattern is with an `Option` interface that holds an unexported method, recording options on an unexported `options` struct.

```
type options struct {
    cache bool
    logger *zap.Logger
}

type Option interface {
    apply(*options)
}

type cacheOption bool

func (c cacheOption) apply(opts *options) {
    opts.cache = bool(c)
}

func WithCache(c bool) Option {
    return cacheOption(c)
}

type loggerOption struct {
    Log *zap.Logger
}

func (l loggerOption) apply(opts *options) {
    opts.logger = l.Log
}

func WithLogger(log *zap.Logger) Option {
    return loggerOption{Log: log}
}

// Open creates a connection.
func Open(
    addr string,
    opts ...Option,
) (*Connection, error) {
    options := options{
        cache: defaultCache,
        logger: zap.NewNop(),
    }
```

```
for _, o := range opts {
    o.apply(&options)
}

// ...
}
```

Note that there's a method of implementing this pattern with closures but we believe that the pattern above provides more flexibility for authors and is easier to debug and test for users. In particular, it allows options to be compared against each other in tests and mocks, versus closures where this is impossible. Further, it lets options implement other interfaces, including `fmt.Stringer` which allows for user-readable string representations of the options.

See also,

- [Self-referential functions and the design of options](#)
- [Functional options for friendly APIs](#)

Linting

More importantly than any "blessed" set of linters, lint consistently across a codebase.

We recommend using the following linters at a minimum, because we feel that they help to catch the most common issues and also establish a high bar for code quality without being unnecessarily prescriptive:

- [errcheck](#) to ensure that errors are handled
- [goimports](#) to format code and manage imports
- [golint](#) to point out common style mistakes
- [govet](#) to analyze code for common mistakes
- [staticcheck](#) to do various static analysis checks

Lint Runners

We recommend [golangci-lint](#) as the go-to lint runner for Go code, largely due to its performance in larger codebases and ability to configure and use many canonical linters at once. This repo has an example [.golangci.yml](#) config file with recommended linters and settings.

`golangci-lint` has [various linters](#) available for use. The above linters are recommended as a base set, and we encourage teams to add any additional linters that make sense for their projects.