

Shallow Neural Networks

Quiz, 10 questions

✓ **Congratulations! You passed!**

Next Item



1 / 1
points

1.

Which of the following are true? (Check all that apply.)



$a^{[2]}(12)$ denotes activation vector of the 12th layer on the 2nd training example.



Un-selected is correct



$a_4^{[2]}$ is the activation output by the 4th neuron of the 2nd layer



Correct



$a_4^{[2]}$ is the activation output of the 2nd layer for the 4th training example



Un-selected is correct



X is a matrix in which each column is one training example.



Correct



$a^{[2]}(12)$ denotes the activation vector of the 2nd layer for the 12th training example.



Correct



X is a matrix in which each row is one training example.



Un-selected is correct



$a^{[2]}$ denotes the activation vector of the 2nd layer.



Shallow Neural Networks

Quiz, 10 questions



1 / 1
points

2.

The tanh activation usually works better than sigmoid activation function for hidden units because the mean of its output is closer to zero, and so it centers the data better for the next layer. True/False?



True

Correct

Yes. As seen in lecture the output of the tanh is between -1 and 1, it thus centers the data which makes the learning simpler for the next layer.



False



1 / 1
points

3.

Which of these is a correct vectorized implementation of forward propagation for layer l , where $1 \leq l \leq L$?



- $Z^{[l]} = W^{[l-1]} A^{[l]} + b^{[l-1]}$
- $A^{[l]} = g^{[l]}(Z^{[l]})$



- $Z^{[l]} = W^{[l]} A^{[l-1]} + b^{[l]}$
- $A^{[l]} = g^{[l]}(Z^{[l]})$

Correct



- $Z^{[l]} = W^{[l]} A^{[l]} + b^{[l]}$
- $A^{[l+1]} = g^{[l+1]}(Z^{[l]})$



- $Z^{[l]} = W^{[l]} A^{[l]} + b^{[l]}$
- $A^{[l+1]} = g^{[l]}(Z^{[l]})$



1 / 1
points

4. Shallow Neural Networks

You are building a binary classifier for recognizing cucumbers ($y=1$) vs. watermelons ($y=0$). Which one of these activation functions would you recommend using for the output layer?

Quiz Question

- ☐ ReLU
- ☐ Leaky ReLU
- ☒ sigmoid

Correct

Yes. Sigmoid outputs a value between 0 and 1 which makes it a very good choice for binary classification. You can classify as 0 if the output is less than 0.5 and classify as 1 if the output is more than 0.5. It can be done with tanh as well but it is less convenient as the output is between -1 and 1.

- ☐ tanh



1 / 1
points

5.

Consider the following code:

```
1 A = np.random.randn(4,3)
2 B = np.sum(A, axis = 1, keepdims = True)
```

What will be B.shape? (If you're not sure, feel free to run this in python to find out).

- ☐ (, 3)
- ☐ (4,)
- ☒ (4, 1)

Correct

Yes, we use (keepdims = True) to make sure that A.shape is (4,1) and not (4,). It makes our code more rigorous.

- ☐ (1, 3)



1 / 1
points

6.

Shallow Neural Networks

Quiz, 10 questions



Each neuron in the first hidden layer will perform the same computation. So even after multiple iterations of gradient descent each neuron in the layer will be computing the same thing as other neurons.



Correct



Each neuron in the first hidden layer will perform the same computation in the first iteration. But after one iteration of gradient descent they will learn to compute different things because we have “broken symmetry”.



Each neuron in the first hidden layer will compute the same thing, but neurons in different layers will compute different things, thus we have accomplished “symmetry breaking” as described in lecture.



The first hidden layer’s neurons will perform different computations from each other even in the first iteration; their parameters will thus keep evolving in their own way.



1 / 1
points

7.

Logistic regression’s weights w should be initialized randomly rather than to all zeros, because if you initialize to all zeros, then logistic regression will fail to learn a useful decision boundary because it will fail to “break symmetry”, True/False?



True



False



Correct

Yes, Logistic Regression doesn't have a hidden layer. If you initialize the weights to zeros, the first example x fed in the logistic regression will output zero but the derivatives of the Logistic Regression depend on the input x (because there's no hidden layer) which is not zero. So at the second iteration, the weights values follow x 's distribution and are different from each other if x is not a constant vector.



1 / 1
points

8.

You have built a network using the tanh activation for all the hidden units. You initialize the weights to relative large values, using `np.random.randn(...)*1000`. What will happen?



It doesn’t matter. So long as you initialize the weights randomly gradient descent is not affected by whether the weights are large or small.

Shallow Neural Networks

Quiz, 10 questions

This will cause the inputs of the tanh to also be very large, causing the units to be "highly activated" and thus speed up learning compared to if the weights had to start from small values.

- ☐ This will cause the inputs of the tanh to also be very large, thus causing gradients to also become large. You therefore have to set α to be very small to prevent divergence; this will slow down learning.
- ☒ This will cause the inputs of the tanh to also be very large, thus causing gradients to be close to zero. The optimization algorithm will thus become slow.

Correct


Yes. tanh becomes flat for large values, this leads its gradient to be close to zero. This slows down the optimization algorithm.



1 / 1
points

9.

Consider the following 1 hidden layer neural network:



Which of the following statements are True? (Check all that apply).

☐ $W^{[1]}$ will have shape (2, 4)

Un-selected is correct

☐ $b^{[1]}$ will have shape (4, 1)

Correct

☐ $W^{[1]}$ will have shape (4, 2)

Correct

Shallow Neural Networks

Quiz, 10 questions

Un-selected is correct

☐ $W^{[2]}$ will have shape (1, 4)

Correct

☐ $b^{[2]}$ will have shape (4, 1)

Un-selected is correct

☐ $W^{[2]}$ will have shape (4, 1)

Un-selected is correct

☐ $b^{[2]}$ will have shape (1, 1)

Correct

1 / 1
points

10.

In the same network as the previous question, what are the dimensions of $Z^{[1]}$ and $A^{[1]}$?☒ $Z^{[1]}$ and $A^{[1]}$ are (4,m)

Correct

☐ $Z^{[1]}$ and $A^{[1]}$ are (4,2)☐ $Z^{[1]}$ and $A^{[1]}$ are (4,1)☐ $Z^{[1]}$ and $A^{[1]}$ are (1,4)



Shallow Neural Networks

Quiz, 10 questions