

# Artificial Intelligence Foundation – JC3001

Lecture 14: Constraint Satisfaction Problems II

**Prof. Aladdin Ayesh** (aladdin.ayesh@abdn.ac.uk)

**Dr. Binod Bhattarai** (binod.bhattarai@abdn.ac.uk)

**Dr. Gideon Ogunniye**, (g.ogunniye@abdn.ac.uk)

September 2025

Material adapted from:  
Russell and Norvig (AIMA Book): Chapter 6

- Part 1: Introduction
  - ① Introduction to AI ✓
  - ② Agents ✓
- Part 2: Problem-solving
  - ① Search 1: Uninformed Search ✓
  - ② Search 2: Heuristic Search ✓
  - ③ Search 3: Local Search ✓
  - ④ Search 4: Adversarial Search ✓
- Part 3: Reasoning and Uncertainty
  - ① **Reasoning 1: Constraint Satisfaction**
  - ② Reasoning 2: Logic and Inference
  - ③ Probabilistic Reasoning 1: BNs
  - ④ Probabilistic Reasoning 2: HMMs
- Part 4: Planning
  - ① Planning 1: Intro and Formalism
  - ② Planning 2: Algos and Heuristics
  - ③ Planning 3: Hierarchical Planning
  - ④ Planning 4: Stochastic Planning
- Part 5: Learning
  - ① Learning 1: Intro to ML
  - ② Learning 2: Regression
  - ③ Learning 3: Neural Networks
  - ④ Learning 4: Reinforcement Learning
- Part 6: Conclusion
  - ① Ethical Issues in AI
  - ② Conclusions and Discussion

- Defining Constraint Satisfaction Problems (CSP) ✓
- CSP examples ✓
- Backtracking search for CSPs
- Local search for CSPs
- Problem structure and problem decomposition



# Outline

## 1 Backtracking Search for CSPs

- ▶ Backtracking Search for CSPs
  - Variable and Value Ordering
  - Interleaving Search and Inference

- Variable assignments are commutative, i.e.,  
 $[WA = red \text{ then } NT = green]$  same as  $[NT = green \text{ then } WA = red]$
- Only need to consider assignments to a single variable at each node  
 $\Rightarrow b = d$  and there are  $d^n$  leaves
- Depth-first search for CSPs with single-variable assignments is called **backtracking search**
- Backtracking search is the basic uninformed algorithm for CSPs
- Can solve n-queens for  $n \approx 25$

```
1: function Backtracking-Search(csp) returns a solution or failure
2:   return Backtrack({}, csp)

3: function Backtrack(csp, assignment) returns a solution or failure
4:   if assignment is complete then return assignment
5:   var  $\leftarrow$  Select-Unassigned-Variable(csp, assignment)
6:   for each value in Order-Domain-Values(csp, var, assignment) do
7:     if value is consistent with assignment then
8:       add {var = value} to assignment
9:       inferences  $\leftarrow$  Inference(csp, var, assignment)
10:      if inferences  $\neq$  failure then
11:        add inferences to csp
12:        result  $\leftarrow$  Backtrack(csp, assignment)
13:        if result  $\neq$  failure then return result
14:        remove inferences from csp
15:      remove {var = value} from assignment
16:   return failure
```

# Backtracking example

## 1 Backtracking Search for CSPs






# Backtracking example

## 1 Backtracking Search for CSPs




# Backtracking example

## 1 Backtracking Search for CSPs



# Backtracking example

## 1 Backtracking Search for CSPs




General-purpose methods can give huge gains in speed:

- 1 Which variable should be assigned next (Select-Unassigned-Variable)?
- 2 In what order should we try its values (Order-Domain-Values)?
- 3 Can we detect inevitable failure early (Inference and Backtrack)?
- 4 Can we take advantage of problem structure?
- 5 Can we save and reuse partial results from the search?

# Minimum remaining values

Select-Unassigned-Variable


Minimum remaining values (MRV): choose the variable with the fewest legal values



Tie-breaker among MRV variables

Degree heuristic:

- choose the variable with the most constraints on remaining variables




Rationale:

- Most constrained variables will likely fail first, avoiding fruitless search

Given a variable, choose the least constraining value:

- the one that rules out the fewest values in the remaining variables



Rationale:

- Combining these heuristics makes 1000 queens feasible

**Idea:** Keep track of remaining legal values for unassigned variables

Terminate search when any variable has no legal values





**Idea:** Keep track of remaining legal values for unassigned variables

Terminate search when any variable has no legal values



| WA   | NT   | Q  | NSW  | V  | SA   | T  |
|--|--|--|--|--|--|--|
| <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div>Red</div><div>Green</div><div>Blue</div></div> |
| <div><div>Red</div></div>                                | <div><div></div><div>Green</div><div>Blue</div></div>    | <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div>Red</div><div>Green</div><div>Blue</div></div> | <div><div></div><div>Green</div><div>Blue</div></div>    | <div><div>Red</div><div>Green</div><div>Blue</div></div> |


**Idea:** Keep track of remaining legal values for unassigned variables

Terminate search when any variable has no legal values




| WA   | NT   | Q  | NSW  | V  | SA   | T  |
|--|--|--|--|--|--|--|
| <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> |
| <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> |
| <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> | <div><div></div><div></div><div></div></div> |

**Idea:** Keep track of remaining legal values for unassigned variables  
Terminate search when any variable has no legal values




Forward checking propagates information from assigned to unassigned variables, but doesn't provide early detection for all failures:




- *NT* and *SA* cannot both be blue!
- **Constraint propagation** enforces constraints locally


- The simplest form of propagation makes each arc **consistent**
- $X \rightarrow Y$  is consistent iff  
for **every** value  $x$  of  $X$  there is **some** allowed  $y$



- The simplest form of propagation makes each arc **consistent**
- $X \rightarrow Y$  is consistent iff  
for **every** value  $x$  of  $X$  there is **some** allowed  $y$




- The simplest form of propagation makes each arc **consistent**
- $X \rightarrow Y$  is consistent iff  
for **every** value  $x$  of  $X$  there is **some** allowed  $y$



- If  $X$  loses a value, neighbours of  $X$  need to be rechecked

- The simplest form of propagation makes each arc **consistent**
- $X \rightarrow Y$  is consistent iff  
for **every** value  $x$  of  $X$  there is **some** allowed  $y$



- If  $X$  loses a value, neighbours of  $X$  need to be rechecked
- Arc consistency detects failure earlier than forward checking
- Can be run as a preprocessor, or after each assignment



```

1: function AC-3(csp) returns the csp, possibly with reduced domains
2:   queue  $\leftarrow$  a queue of arcs, initially all the arcs in csp
3:   while queue is not empty do
4:      $(X_i, X_j) \leftarrow \text{POP}(\text{queue})$ 
5:     if Revise(csp,  $X_i, X_j$ ) then
6:       if size of  $D_i = 0$  then return false
7:       for each  $X_k$  in  $X_i.\text{Neighbors} - \{X_j\}$  do
8:         add  $(X_k, X_i)$  to queue
9:   return true
  
```

---

```

10: function Revise(csp,  $X_i, X_j$ ) returns true iff we revise the domain of  $X_i$ 
11:   revised  $\leftarrow$  false
12:   for each  $x \in D_i$  do
13:     if no value  $y$  in  $D_j$  allows  $(x, y)$  to satisfy the constraint between  $X_i$  and  $X_j$  then
14:       delete  $x$  from  $D_i$ 
15:   revised  $\leftarrow$  true
  
```

$O(n^2d^3)$  can be reduced to  $O(n^2d^2)$  (but detecting **all** is NP-hard)

To continue in the next session.