

1、编写显示文本内容的 C 程序

```
uiqgnem@uiqgnem-VMware-Virtual-Platform:~$ cd shell_scripts
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ nano c1.c
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ nano Makefile
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ make hello1
gcc -c c1.c
gcc -o hello1 c1.o
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ echo "Good morning!" > text.txt
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ ./hello1 text.txt
Good morning!

uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ make clean
rm -rf *.o
```

2、编写显示当前目录下所有文件名的 C 程序

```
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ nano c2.c
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ nano Makefile
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ make hello2
gcc -c c2.c
gcc -o hello2 c2.o
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ ./hello2
段错误 (核心已转储)
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ ./hello2.
bash: ./hello2.: 没有那个文件或目录
```

3、编写修改当前进程工作目录的 C 程序

```
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ nano c3.c
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ nano Makefile
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ make hello3
gcc -c c3.c
gcc -o hello3 c3.o
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ ./hello3
/home/uiqgnem/shell_scripts
success
/home
uiqgnem@uiqgnem-VMware-Virtual-Platform:~/shell_scripts$ make clean
rm -rf *.o
```