

Package ‘aakmisc’

June 28, 2016

Type Package

Title Miscellany for the King Lab

Version 0.20-1

Date 2016-02-26

Maintainer Aaron A. King <kingaa@umich.edu>

Description Miscellaneous tools, collected in one place.

URL <http://github.com/kingaa/aakmisc>

Contact kingaa at umich dot edu

BugReports <http://github.com/kingaa/aakmisc/issues>

Depends R(>= 3.0.0), plyr, reshape2, ggplot2(>= 1.0.1.9003), grid, magrittr

Imports methods, curl, DBI, RPostgreSQL

License GPL(>=3)

LazyLoad true

LazyData true

Collate aaa.R db.R tunnel.R random.R plotMatrix.R scinot.R

R topics documented:

dbtools	2
plotMatrix	4
random	5
scinot	6
Index	7

dbtools

*Interface with databases***Description**

Interface with project databases.

Usage

```

getMLEs(host = getOption("aakmisc.dbhost", "localhost"),
        dbname = getOption("aakmisc.dbname", NULL),
        port = getOption("aakmisc.port", 5432),
        user = getOption("aakmisc.user", NULL),
        ...)
recMLEs(mle, host = getOption("aakmisc.dbhost", "localhost"),
        dbname = getOption("aakmisc.dbname", NULL),
        port = getOption("aakmisc.port", 5432),
        user = getOption("aakmisc.user", NULL),
        ...)
listScripts(host = getOption("aakmisc.dbhost", "localhost"),
            dbname = getOption("aakmisc.dbname", NULL),
            port = getOption("aakmisc.port", 5432),
            user = getOption("aakmisc.user", NULL),
            ...)
recScript(files, host = getOption("aakmisc.dbhost", "localhost"),
          dbname = getOption("aakmisc.dbname", NULL),
          port = getOption("aakmisc.port", 5432),
          user = getOption("aakmisc.user", NULL),
          ...)
dropScript(script, host = getOption("aakmisc.dbhost", "localhost"),
           dbname = getOption("aakmisc.dbname", NULL),
           port = getOption("aakmisc.port", 5432),
           user = getOption("aakmisc.user", NULL),
           ...)
catScript(script, file = "", host = getOption("aakmisc.dbhost", "localhost"),
          dbname = getOption("aakmisc.dbname", NULL),
          port = getOption("aakmisc.port", 5432),
          user = getOption("aakmisc.user", NULL),
          ...)
getQuery(statement,
         host = getOption("aakmisc.dbhost", "localhost"),
         dbname = getOption("aakmisc.dbname", NULL),
         port = getOption("aakmisc.port", 5432),
         user = getOption("aakmisc.user", NULL),
         ...)
writeDBTable(name, value, overwrite = FALSE, append = FALSE,
             row.names = FALSE,

```

```

        host = getOption("aakmisc.dbhost","localhost"),
        dbname = getOption("aakmisc.dbname",NULL),
        port = getOption("aakmisc.port",5432),
        user = getOption("aakmisc.user",NULL),
        ...)
startTunnel(port = NULL,
            remotehost = getOption("aakmisc.remotehost",NULL),
            sleep = 5)
stopTunnel(..., pid = getOption("aakmisc.tunnelpid",NULL))

```

Arguments

host	Hostname on which to connect to the PostgreSQL server.
dbname	Name of PostgreSQL database.
port	Port on which to connect to PostgreSQL database. If NULL, a random port number will be used.
user	Username to use in connecting to PostgreSQL database. If NULL, Sys.getenv("USER") will be used.
mle	A data-frame of MLEs to be recorded.
files	Files containing R scripts to be recorded.
script	Name of script.
file	File to which the script will be written. See cat .
statement	SQL statement passed to dbGetQuery .
name, value	Name and contents of table to create.
overwrite, append, row.names	See dbWriteTable .
remotehost	Hostname of PostgreSQL server. An ssh tunnel to this host will be created.
pid	ID of ssh tunnel process. Set automatically by startTunnel.
sleep	Time in seconds to sleep after initiating the ssh tunnel.
...	Additional arguments will be passed to dbConnect .

Author(s)

Aaron A. King <kingaa at umich dot edu>

Examples

```

## Not run:
startTunnel()
listScripts()
stopTunnel()

## End(Not run)

```

plotMatrix

A scatterplot matrix with densities on the diagonal.

Description

A special scatterplot matrix.

Usage

```
## S3 method for class 'data.frame'
plotMatrix(data, marg.exp = 0.02, labels = names(data),
            alpha = 1, pch = 16, size = unit(2,"mm"), ...)
## S3 method for class 'list'
plotMatrix(data, marg.exp = 0.02, labels = names(data),
            alpha = 1, pch = 16, size = unit(2,"mm"), ...)
## S3 method for class 'aakplot'
print(x, newpage = is.null(vp), vp = NULL, ...)
```

Arguments

data	Data to plot.
marg.exp	Fraction by which to expand the plot at the margins.
labels	Names of variables plotted.
alpha, pch, size	Refer to the plotted points in the scatterplots.
...	optional arguments, passed to hist .
x	plotMatrix object to display.
newpage	logical; if TRUE, <code>grid.newpage()</code> will be called before the graphics are drawn.
vp	viewport to use. See viewport .

Author(s)

Aaron A. King <kingaa at umich dot edu>

Examples

```
## Not run:
x <- data.frame(a=rexp(n=1000,rate=1/3),b=rnorm(1000))
mutate(x,c=a+b^2,d=a-b^3) -> x

print(plotMatrix(x,alpha=0.2))

g <- plotMatrix(
  x[-2],
  labels=c(
    expression(alpha),
```

```
        expression(beta),
        expression(phi)
    ),
    alpha=0.3
)
print(g)

print(plotMatrix(as.list(x),alpha=0.2,breaks='scott'))

## End(Not run)
```

random

Functions for generating and working with truly random integers.

Description

Functions for generating and working with truly random seeds.

Usage

```
random.org(n = 10, rnd = "new")
urandom(n = 10)
rngControl(expr, seed = NULL)
rngSeeds(n, seed = NULL)
```

Arguments

n	Number of integers required.
rnd	random.org parameter
expr	Expression to be evaluated with RNG control.
seed	RNG seed.

Author(s)

Aaron A. King <kingaa at umich dot edu>

References

<http://www.random.org>

Examples

```
## Not run:
random.org(n=5)
seed <- urandom(n=1)
seeds <- rngSeeds(5,seed=seed)
set.seed(seed)
runif(5)
```

```
rngControl(runif(5),seed=seed[1])
rngControl(runif(5),seed=seed[1])
runif(5)
set.seed(seed)
runif(5)
runif(5)

## End(Not run)
```

scinot

Scientific notation.

Description

Format using scientific notation.

Usage

```
scinot(x, digits = 2, format = c("expression","latex","math"))
```

Arguments

x	Number to format.
digits	Number of significant digits in mantissa.
format	Format specification. type="expression" results in an R expression. type="latex" results in a latex expression. type="math" is like "latex" but wraps the text in "\$".

Author(s)

Aaron A. King <kingaa at umich dot edu>

Examples

```
x <- c(0.0309595,8577676.441)
scinot(x[2],4)
scinot(x[1],2,"latex")
sapply(x,scinot,digits=3,format='math')
```

Index

cat, [3](#)
catScript (dbtools), [2](#)

dbConnect, [3](#)
dbGetQuery, [3](#)
dbtools, [2](#)
dbWriteTable, [3](#)
dropScript (dbtools), [2](#)

getMLEs (dbtools), [2](#)
getQuery (dbtools), [2](#)

hist, [4](#)

listScripts (dbtools), [2](#)

plotMatrix, [4](#)
print.aakplot (plotMatrix), [4](#)

random, [5](#)
recMLEs (dbtools), [2](#)
recScript (dbtools), [2](#)
rngControl (random), [5](#)
rngSeeds (random), [5](#)

scinot, [6](#)
startTunnel (dbtools), [2](#)
stopTunnel (dbtools), [2](#)

urandom (random), [5](#)

viewport, [4](#)

writeDBTable (dbtools), [2](#)