

Package ‘circumstance’

July 14, 2023

R topics documented:

circumstance-package	1
continue	1
mif2	2
pfilter	3
plot_matrix	4
pmcmc	5

Index	7
--------------	----------

circumstance-package	<i>circumstance package</i>
----------------------	-----------------------------

Description

circumstance provides tools for parallelizing certain **pomp** calculations.

continue	<i>Continue an iterative calculation</i>
----------	--

Description

Continue an iterative computation where it left off.

Usage

```
continue(object, ...)  
  
## S4 method for signature 'mif2List'  
continue(object, ..., .options.future = list(seed = TRUE))  
  
## S4 method for signature 'pmcmcList'  
continue(object, ..., .options.future = list(seed = TRUE))
```

Arguments

object the result of an iterative **pomp** computation

... additional arguments will be passed to the underlying method. This allows one to modify parameters used in the original computations.

.options.future list of options for the **doFuture** backend. See [%dofuture%](#) for details.

See Also

[mif2](#)

mif2	<i>Parallel iterated filtering</i>
------	------------------------------------

Description

Runs multiple instances of `mif2` using `foreach`.

Usage

```
## S4 method for signature 'ANY,data.frame'
mif2(data, starts, ..., .options.future = list(seed = TRUE))

## S4 method for signature 'ANY,missing'
mif2(data, starts, ...)

## S4 method for signature 'pompList,missing'
mif2(data, ..., .options.future = list(seed = TRUE))

## S4 method for signature 'pfilterList,missing'
mif2(data, ..., .options.future = list(seed = TRUE))

## S4 method for signature 'mif2List,missing'
mif2(data, ..., .options.future = list(seed = TRUE))
```

Arguments

data passed to [pomp::mif2](#)

starts data frame containing parameters at which to begin iterated filtering

... all additional arguments are passed to [pomp::mif2](#)

.options.future list of options for the **doFuture** backend. See [%dofuture%](#) for details.

See Also

[pomp::mif2](#).

pfilter

Parallel particle filter computations

Description

Runs multiple instances of pfilter using foreach.

Usage

```
## S4 method for signature 'ANY,numeric'
pfilter(data, Nrep, ..., .options.future = list(seed = TRUE))

## S4 method for signature 'ANY,missing'
pfilter(data, Nrep, ...)

## S4 method for signature 'pomplList,numeric'
pfilter(data, Nrep, ..., .options.future = list(seed = TRUE))

## S4 method for signature 'pomplList,missing'
pfilter(data, Nrep, ...)
```

Arguments

data	passed to <code>pomp::pfilter</code>
Nrep	number of replicate particle filter computations to run. By default, Nrep = 1.
...	all additional arguments are passed to <code>pomp::pfilter</code>
.options.future	list of options for the doFuture backend. See <code>%dofuture%</code> for details.

See Also

`pomp::pfilter`.

Examples

```
library(circumstance)
library(doFuture)

ou2() -> ou2

plan(sequential)
system.time(ou2 |> pfilter(Np=10000,Nrep=6) -> pfs)

plan(multicore)
system.time(ou2 |> pfilter(Np=10000,Nrep=6) -> pfs)
```

plot_matrix

A scatterplot matrix with densities on the diagonal.

Description

A special scatterplot matrix.

Usage

```
plot_matrix(data, ...)

## S3 method for class 'list'
plot_matrix(
  data,
  marg.exp = 0.02,
  labels = names(data),
  alpha = 1,
  pch = 16,
  size = unit(0.03, "npc"),
  ...
)

## S3 method for class 'data.frame'
plot_matrix(
  data,
  marg.exp = 0.02,
  labels = names(data),
  alpha = 1,
  pch = 16,
  size = unit(0.03, "npc"),
  ...
)

## S3 method for class 'plotmatrix'
print(x, newpage = is.null(vp), vp = NULL, ...)
```

Arguments

data	Data to plot.
...	optional arguments, passed to hist .
marg.exp	Fraction by which to expand the plot at the margins.
labels	Names of variables plotted.
alpha, pch, size	Refer to the plotted points in the scatterplots.
x	plot_matrix object to display.

`newpage` logical; if TRUE, `grid.newpage()` will be called before the graphics are drawn.
`vp` viewport to use. See [viewport](#).

Examples

```
# requires dplyr
library(dplyr)

data.frame(
  a=rexp(n=1000,rate=1/3),
  b=rnorm(1000)
) |>
  mutate(
    c=a+b^2,
    d=a-b^3
  ) -> x

print(plot_matrix(x,alpha=0.2))

g <- plot_matrix(
  x[-2],
  labels=c(
    expression(alpha),
    expression(beta),
    expression(phi)
  ),
  alpha=0.3
)
print(g)

print(plot_matrix(as.list(x),alpha=0.2,breaks="scott"))
```

Description

Runs multiple instances of pmcmc using foreach.

Usage

```
## S4 method for signature 'ANY,data.frame'
pmcmc(data, starts, ..., .options.future = list(seed = TRUE))

## S4 method for signature 'ANY,missing'
pmcmc(data, starts, ...)

## S4 method for signature 'pomplList,missing'
```

```
pmcmc(data, ..., .options.future = list(seed = TRUE))

## S4 method for signature 'pfilterList,missing'
pmcmc(data, ..., .options.future = list(seed = TRUE))

## S4 method for signature 'pmcmcList,missing'
pmcmc(data, ..., .options.future = list(seed = TRUE))
```

Arguments

data	passed to pomp::pmcmc
starts	data frame containing parameters at which to begin iterated filtering
...	all additional arguments are passed to pomp::pmcmc
.options.future	list of options for the doFuture backend. See %dofuture% for details.

See Also

[pomp::pmcmc](#).

Index

`%dofuture%`, [2](#), [3](#), [6](#)

`circumstance`, package
 (`circumstance`-package), [1](#)
`circumstance`-package, [1](#)
`continue`, [1](#)
`continue`, ANY-method (`continue`), [1](#)
`continue`, `mif2List`-method (`continue`), [1](#)
`continue`, missing-method (`continue`), [1](#)
`continue`, `pmcmcList`-method (`continue`), [1](#)

`hist`, [4](#)

`mif2`, [2](#), [2](#)
`mif2`, ANY, `data.frame`-method (`mif2`), [2](#)
`mif2`, ANY, missing-method (`mif2`), [2](#)
`mif2`, `mif2List`, missing-method (`mif2`), [2](#)
`mif2`, `pfilterList`, missing-method (`mif2`),
 [2](#)
`mif2`, `pomplList`, missing-method (`mif2`), [2](#)

`pfilter`, [3](#)
`pfilter`, ANY, missing-method (`pfilter`), [3](#)
`pfilter`, ANY, numeric-method (`pfilter`), [3](#)
`pfilter`, `pomplList`, missing-method
 (`pfilter`), [3](#)
`pfilter`, `pomplList`, numeric-method
 (`pfilter`), [3](#)
`plot_matrix`, [4](#)
`pmcmc`, [5](#)
`pmcmc`, ANY, `data.frame`-method (`pmcmc`), [5](#)
`pmcmc`, ANY, missing-method (`pmcmc`), [5](#)
`pmcmc`, `pfilterList`, missing-method
 (`pmcmc`), [5](#)
`pmcmc`, `pmcmcList`, missing-method (`pmcmc`),
 [5](#)
`pmcmc`, `pomplList`, missing-method (`pmcmc`), [5](#)
`pomp`: `mif2`, [2](#)
`pomp`: `pfilter`, [3](#)
`pomp`: `pmcmc`, [6](#)

`print.plotmatrix` (`plot_matrix`), [4](#)

`viewport`, [5](#)