

# Package ‘phylopomp’

May 15, 2023

## R topics documented:

phylopomp-package . . . . .	1
as.data.frame . . . . .	2
diagram . . . . .	2
genealogy diagram internals . . . . .	3
getInfo . . . . .	5
lbdp . . . . .	6
lineages . . . . .	7
moran . . . . .	9
newick2df . . . . .	10
plot . . . . .	11
reexports . . . . .	12
seir . . . . .	13
si2r . . . . .	15
siir . . . . .	17
simulate . . . . .	18
sir . . . . .	19
yaml . . . . .	21
<b>Index</b>	<b>22</b>

---

phylopomp-package	<i>Phylogenetics for POMP models</i>
-------------------	--------------------------------------

---

## Description

Super cool.

## Author(s)

Aaron A. King, Qianying Lin

---

as.data.frame

*Coerce to a Data Frame*


---

### Description

Functions to coerce an object to a data frame.

### Usage

```
## S3 method for class 'gplin'
as.data.frame(x, ...)
```

### Arguments

x                      any R object.  
 ...                    additional arguments to be passed to or from methods.

### Details

An object of class ‘gplin’ is coerced to a data frame by means of as.data.frame.

---

diagram

*Genealogy process diagram*


---

### Description

Produces a diagram of the genealogy process state.

### Usage

```
diagram(
  object,
  prune = TRUE,
  obscure = TRUE,
  m = NULL,
  n = NULL,
  ...,
  digits = 1
)

## S3 method for class 'gpdiag'
print(x, newpage = is.null(vp), vp = NULL, ...)
```

**Arguments**

object	gpsim object.
prune	logical; prune the genealogy?
obscure	logical; obscure the demes?
m	width of plotting window, in nodes. By default, the nodes will be adjusted in width to fit the window.
n	height of the pockets, in balls. By default, the balls will be adjusted in size to fit the space available.
...	other arguments, ignored.
digits	non-negative integer; number of decimal digits to print in the node time
x	An R object.
newpage	draw new empty page first?
vp	viewport to draw plot in

**Value**

A **grid** graphics object (grob), invisibly.

**Examples**

```
runSIR(Beta=3,gamma=0.1,psi=0.2,S0=100,I0=5,R0=0,time=2,t0=0) -> x
plot(x,points=TRUE,prune=FALSE,compact=FALSE)
plot_grid(plotlist=list(plot(x,points=TRUE)[[1]],diagram(x)),
  ncol=1,rel_heights=c(4,1))
```

---

genealogy diagram internals

*Diagramming internals*

---

**Description**

Facilities to produce diagrammatic representations of genealogy process states.

**Usage**

```
genealogyGrob(object, m = NULL, n = NULL, vp = NULL, ...)
```

```
nodeGrob(object, digits = 1, n = NULL, vp = NULL)
```

```
pocketGrob(object, n = NULL, vp = NULL)
```

```
ballGrob(object, vp = NULL)
```

```
resizingTextGrob(..., vp = NULL)
```

```
## S3 method for class 'resizingTextGrob'
drawDetails(x, recording = TRUE)

## S3 method for class 'resizingTextGrob'
preDrawDetails(x)

## S3 method for class 'resizingTextGrob'
postDrawDetails(x)

## S3 method for class 'ballGrob'
drawDetails(x, recording = TRUE)

## S3 method for class 'ballGrob'
preDrawDetails(x)

## S3 method for class 'ballGrob'
postDrawDetails(x)

## S3 method for class 'gpsim'
print(x, ...)
```

## Arguments

object	list; pocket structure
m	width of plotting window, in nodes. By default, the nodes will be adjusted in width to fit the window.
n	length of longest genealogy
vp	viewport to draw plot in
...	arguments to be passed to <a href="#">textGrob</a> .
digits	non-negative integer; number of decimal digits to print in the node time
x	An R object.
recording	A logical value indicating whether a grob is being added to the display list or redrawn from the display list.

## Details

Code for the resizing text adapted from a blog post by Mark Heckmann (<https://ryouready.wordpress.com/2012/08/01/creating-a-text-grob-that-automatically-adjusts-to-viewport-size/>).

---

getInfo	<i>getInfo</i>
---------	----------------

---

## Description

Retrieve information from genealogy process simulation

## Usage

```
getInfo(  
  object,  
  prune = TRUE,  
  obscure = TRUE,  
  t0 = FALSE,  
  time = FALSE,  
  description = FALSE,  
  structure = FALSE,  
  yaml = FALSE,  
  lineages = FALSE,  
  tree = FALSE,  
  compact = TRUE  
)
```

## Arguments

object	gpsim object.
prune	logical; prune the genealogy?
obscure	logical; obscure the demes?
t0	logical; return the zero-time?
time	logical; return the current time?
description	logical; return the description?
structure	logical; return the structure in R list format?
yaml	logical; return the structure in YAML format?
lineages	logical; return the lineage-count function?
tree	logical; return the tree?
compact	logical; return the tree in compact representation?

## Value

A list containing the requested elements, including any or all of:

**t0** the initial time

**time** the current time

**tree** the genealogical tree, in Newick format

**description** a human readable description of the state of the genealogy process

**yaml** the state of the genealogy process in YAML format

**structure** the state of the genealogy process in R list format

**lineages** a [tibble](#) containing the lineage count function through time

### Examples

```
simulate("SIIR", time=3, psi1=1, psi2=0) |>
  simulate(Beta1=2, gamma=2, time=10, psi1=10, psi2=1) |>
  plot()
```

```
runSIIR(Beta1=10, Beta2=8,
  S0=200, I1_0=10, I2_0=8, R0=0, time=0, t0=-1) |>
  simulate(psi1=10, time=2) |>
  plot(points=TRUE, obscure=FALSE)
```

```
simulate("SIIR", Beta1=2, Beta2=50, gamma=1, psi1=2,
  S0=300, I1_0=20, I2_0=2, time=5) |>
  lineages() |>
  plot()
```

---

lbdp

---

*Linear birth-death-sampling model*


---

### Description

The genealogy process induced by a simple linear birth-death process with constant-rate sampling.

### Usage

```
runLBDP(time, t0 = 0, lambda = 2, mu = 1, psi = 1, n0 = 5)
```

```
continueLBDP(object, time, lambda = NA, mu = NA, psi = NA)
```

```
lbdp_exact(data, lambda, mu, psi, n0 = 1)
```

```
lbdp_pomp(data, lambda, mu, psi, n0 = 1, t0 = 0)
```

### Arguments

time	final time
t0	initial time
lambda	per capita birth rate
mu	per capita recovery rate.
psi	per capita sampling rate.
n0	initial population size

object	either the name of the model to simulate <i>or</i> a previously computed ‘gpsim’ object
data	data frame containing the genealogy event times.

### Details

`lbdp_exact` gives the exact log likelihood of a linear birth-death process, conditioned on  $n_0 = 0$  (Stadler, 2010, Thm 3.5). The derivation is also given in comments in the code.

`lbdp_pomp` constructs a **pomp** object containing a given set of data and a linear birth-death-sampling process.

### Value

An object of class ‘gpsim’ with ‘model’ attribute “LBDP”.

`lbdp_exact` returns the log likelihood of the genealogy. Note that the time since the most recent sample is informative.

### References

T. Stadler. Sampling-through-time in birth-death trees. *Journal of Theoretical Biology* **267**, 396–404, 2010.

### See Also

More example genealogy processes: [moran](#), [seir](#), [si2r](#), [siir](#), [simulate\(\)](#), [sir](#)

### Examples

```
simulate("LBDP",time=4) |> plot(points=TRUE)

simulate("LBDP",lambda=2,mu=1,psi=3,n0=1,time=1) |>
  simulate(time=10,lambda=1) |>
  plot()

simulate("LBDP",time=4) |>
  lineages() |>
  plot()
```

---

lineages

---

*Lineage-count function*


---

### Description

The number of lineages through time

**Usage**

```
lineages(object, prune = TRUE, obscure = TRUE)

## S3 method for class 'gplin'
plot(x, ..., palette = scales::hue_pal(l = 30, h = c(220, 580)))
```

**Arguments**

<code>object</code>	gpsim object.
<code>prune</code>	logical; prune the genealogy?
<code>obscure</code>	logical; obscure the demes?
<code>x</code>	object of class 'gpsim'
<code>...</code>	passed to <a href="#">treeplot</a>
<code>palette</code>	color palette for branches. This can be furnished either as a function or a vector of colors. If this is a function, it should take a single integer argument, the number of colors required. If it is a vector, ....

**Value**

A [tibble](#) containing the lineage count function. If the genealogy has been obscured (the default), the number in the `lineages` column is the total number of lineages present at the times in the `time` column. If the genealogy has not been obscured (`obscure = FALSE`), the deme-specific lineage counts are returned.

The [tibble](#) returned by `lineages` has a [plot](#) method.

**Examples**

```
library(tidyverse)

pal <- c("#00274c", "#ffcb05")

simulate("SIIR", time=3) -> x
plot_grid(
  x |> plot(),
  x |> lineages() |> plot(),
  x |> plot(obscure=FALSE, palette=pal),
  x |> lineages(obscure=FALSE) |>
    plot(palette=pal, legend.position=c(0.8, 0.9)),
  align="v", axis="b",
  ncol=2, byrow=FALSE
)
```



---

moran	<i>The classical Moran model</i>
-------	----------------------------------

---

### Description

The Markov genealogy process induced by the classical Moran process, in which birth/death events occur at a constant rate and the population size remains constant.

### Usage

```
runMoran(time, t0 = 0, n = 100, mu = 1, psi = 1)
```

```
continueMoran(object, time, mu = NA, psi = NA)
```

```
moran_exact(data, n = 100, mu = 1, psi = 1)
```

### Arguments

time	final time
t0	initial time
n	population size
mu	event rate
psi	sampling rate.
object	either the name of the model to simulate <i>or</i> a previously computed ‘gpsim’ object
data	data frame containing the genealogy event times.

### Details

`moran_exact` gives the exact log likelihood of a genealogy under the uniformly-sampled Moran process.

### Value

An object of class ‘gpsim’ with ‘model’ attribute “Moran”.

`moran_exact` returns the log likelihood of the genealogy.

### See Also

More example genealogy processes: [lbdp](#), [seir](#), [si2r](#), [siir](#), [simulate\(\)](#), [sir](#)

newick2df

*Convert a tree in Newick format to data frame***Description**

Convert a genealogical tree in Newick format to a data frame suitable for use with **pomp**.

**Usage**

```
newick2df(tree, time = NA, root_time = 0)
```

**Arguments**

<code>tree</code>	tree data in Newick format.
<code>time</code>	time of the genealogy.
<code>root_time</code>	time of the root.

**Details**

If `time` is furnished, it is assumed that the absence of samples between the latest leaf and `time` is informative.

Invisible nodes (labeled 'X\_' for any X) are dropped.

**Value**

A data frame suitable for use as **pomp** input, containing three columns:

**time** numeric; time of the genealogy event.

**lineages** integer; the value of the lineage-count function at the specified time. Note that this function is right-continuous with left limits, and constant on the inter-event intervals.

**code** integer; a code describing the nature of the event. 1 indicates a coalescence; 0 indicates a dead sample; -1 indicates a live sample; 2 indicates a root.

**Examples**

```
runSIR(Beta=2,gamma=1,psi=2,S0=100,I0=2,R0=0,time=5,t0=0) |>
  getInfo(tree=TRUE) |>
  getElement("tree") |>
  newick2df()
```

plot

*Fancy tree plotter***Description**

Plots a genealogical tree.

**Usage**

```
## S3 method for class 'gpsim'
plot(
  x,
  ...,
  time,
  t0,
  prune = TRUE,
  obscure = TRUE,
  compact = TRUE,
  palette = scales::hue_pal(l = 30, h = c(220, 580))
)

treeplot(
  tree,
  time = NULL,
  t0 = 0,
  ladderize = TRUE,
  points = FALSE,
  ...,
  palette = scales::hue_pal(l = 30, h = c(220, 580))
)
```

**Arguments**

x	object of class 'gpsim'
...	passed to <a href="#">treeplot</a>
time	numeric; time of the genealogy.
t0	numeric; time of the root.
prune	logical; prune the genealogy?
obscure	logical; obscure the demes?
compact	logical; return the tree in compact representation?
palette	color palette for branches. This can be furnished either as a function or a vector of colors. If this is a function, it should take a single integer argument, the number of colors required. If it is a vector, ....
tree	character; tree representation in Newick format.
ladderize	Ladderize?
points	Show nodes and tips?

**Value**

A printable ggplot object.

**Examples**

```
## Not run:
library(ggplot2)
times <- seq(from=0,to=8,by=0.1)[-1]

png_files <- sprintf(
  file.path(tempdir(),"frame%05d.png"),
  seq_along(times)
)

pb <- utils::txtProgressBar(0,length(times),0,style=3)
x <- simulate("SIIR",time=0,Beta1=5,Beta2=10,gamma=1,delta=0.5,
  psi1=0.2,psi2=0.1,sigma12=1,sigma21=1,S0=200,I1_0=3,I2_0=2)
for (k in seq_len(length(times))) {
  x <- simulate(x,time=times[k])
  ggsave(
    filename=png_files[k],
    plot=plot(
      x, t0=0, time=max(times),
      points=FALSE, prune=FALSE, obscure=FALSE,
      palette=c("#ffcb05", "#dddddd"),
      axis.line=element_line(color="white"),
      axis.ticks=element_line(color="white"),
      axis.text=element_blank(),
      plot.background=element_rect(fill=NA,color=NA),
      panel.background=element_rect(fill=NA,color=NA)
    ),
    device="png",dpi=300,
    height=2,width=3,units="in"
  )
  setTxtProgressBar(pb,k)
}

library(gifski)
gif_file <- "movie1.gif"
gifski(png_files,gif_file,delay=0.02,loop=TRUE)
unlink(png_files)

## End(Not run)
```

## Description

These objects are imported from other packages. Follow the links below to see their documentation.

**cowplot** [plot\\_grid](#)

**foreach** [%dopar%](#), [foreach](#), [registerDoSEQ](#)

**grid** [viewport](#)

**pomp** [bake](#), [freeze](#), [stew](#)

**yaml** [as.yaml](#), [read\\_yaml](#)

---

seir

*Classical susceptible-exposed-infected-recovered model*

---

## Description

The population is structured by infection progression.

## Usage

```
runSEIR(
  time,
  t0 = 0,
  Beta = 4,
  sigma = 1,
  gamma = 1,
  psi = 1,
  delta = 0,
  S0 = 100,
  E0 = 5,
  I0 = 5,
  R0 = 0
)

continueSEIR(
  object,
  time,
  Beta = NA,
  sigma = NA,
  gamma = NA,
  psi = NA,
  delta = NA
)
```

**Arguments**

time	final time
t0	initial time
Beta	transmission rate
sigma	progression rate
gamma	recovery rate
psi	per capita sampling rate
delta	rate of waning of immunity
S0	initial size of susceptible population
E0	initial size of exposed population
I0	initial size of infected population
R0	initial size of immune population
object	either the name of the model to simulate <i>or</i> a previously computed ‘gpsim’ object

**Value**

An object of class ‘gpsim’ with ‘model’ attribute “SEIR”.

**See Also**

More example genealogy processes: [lbdp](#), [moran](#), [si2r](#), [siir](#), [simulate\(\)](#), [sir](#)

**Examples**

```
simulate("SEIR",Beta=2,sigma=2,gamma=1,psi=2,S0=1000,I0=5,time=5) |>
  simulate(Beta=5,gamma=2,time=10,psi=3) |>
  plot()

runSEIR(Beta=3,gamma=1,psi=2,S0=20,I0=5,R0=0,time=5,t0=-1) |>
  plot(points=TRUE,obscure=FALSE)

runSEIR(Beta=3,gamma=0.1,psi=0.2,S0=100,I0=5,R0=0,time=2,t0=0) -> x
plot_grid(plotlist=list(plot(x,points=TRUE),diagram(x)),
  ncol=1,rel_heights=c(4,1))

simulate("SEIR",sigma=1,delta=1,time=20,I0=4) |> plot(obscure=FALSE)

simulate("SEIR",sigma=1,delta=1,time=20,I0=4) |>
  lineages(obscure=FALSE) |>
  plot()
```

---

si2r*Two-deme model of superspreading*

---

## Description

Deme 2 consists of "superspreaders" who engender clusters of infection in "superspreading events".

## Usage

```
runSI2R(  
  time,  
  t0 = 0,  
  Beta = 5,  
  mu = 5,  
  gamma = 1,  
  delta = 0,  
  psi1 = 1,  
  psi2 = 0,  
  sigma12 = 1,  
  sigma21 = 3,  
  S0 = 500,  
  I0 = 10,  
  R0 = 0  
)  
  
continueSI2R(  
  object,  
  time,  
  Beta = NA,  
  mu = NA,  
  gamma = NA,  
  delta = NA,  
  psi1 = NA,  
  psi2 = NA,  
  sigma12 = NA,  
  sigma21 = NA  
)
```

## Arguments

time	final time
t0	initial time
Beta	transmission rate
mu	mean superspreading-event cluster size
gamma	recovery rate

<code>delta</code>	rate of waning of immunity
<code>psi1, psi2</code>	sampling rates for demes 1 and 2, respectively
<code>sigma12, sigma21</code>	movement rates from deme 1 to 2 and 2 to 1, respectively
<code>S0</code>	initial size of susceptible population
<code>I0</code>	initial size of I1 population ( $I_2 = 0$ at $t = 0$ )
<code>R0</code>	initial size of recovered population
<code>object</code>	either the name of the model to simulate <i>or</i> a previously computed ‘gpsim’ object

### Details

Superspreaders (deme 2) behave differently than ordinary infections: transmission events occur at the same rate ( $\beta$ ), but at each event, a superspreader infects  $N$  individuals, where

$$N \sim 1 + \text{Geometric}(1/\mu).$$

Thus, assuming susceptibles are not limiting, the mean number of infections resulting from a superspreading event is  $\mu$  and the variance in this number is  $\mu^2 - \mu$ . If susceptibles are limiting, i.e., if the number of susceptibles is not greater than  $N$ , then all remaining susceptibles are infected.

### Value

An object of class ‘gpsim’ with ‘model’ attribute “SI2R”.

### See Also

More example genealogy processes: [lbdp](#), [moran](#), [seir](#), [siir](#), [simulate\(\)](#), [sir](#)

### Examples

```
simulate("SI2R",time=1) |>
  plot(obscure=FALSE)

runSI2R(Beta=10,S0=2000,time=1,psi1=0) |>
  simulate(time=2,psi1=1) |>
  plot(points=TRUE,obscure=FALSE)

simulate("SI2R",time=5) |>
  lineages() |>
  plot()

simulate("SI2R",time=2) |>
  diagram(m=30)

simulate("SI2R",time=20,delta=0.2,mu=20) -> x
plot_grid(
  x |> plot(obscure=FALSE),
  x |> lineages(obscure=FALSE) |> plot(),
  ncol=1,
```



```

    align="v",axis="b"
)

```

---

siir

*Two-strain SIR model.*


---

## Description

Two distinct pathogen strains compete for susceptibles.

## Usage

```

runSIIR(
  time,
  t0 = 0,
  Beta1 = 5,
  Beta2 = 5,
  gamma = 1,
  psi1 = 1,
  psi2 = 0,
  sigma12 = 0,
  sigma21 = 0,
  delta = 0,
  S0 = 500,
  I1_0 = 10,
  I2_0 = 10,
  R0 = 0
)

continueSIIR(
  object,
  time,
  Beta1 = NA,
  Beta2 = NA,
  gamma = NA,
  psi1 = NA,
  psi2 = NA,
  sigma12 = NA,
  sigma21 = NA,
  delta = NA
)

```

## Arguments

time	final time
t0	initial time
Beta1, Beta2	transmission rates from each of the infectious classes.

gamma	recovery rate.
psi1, psi2	sampling rates.
sigma12, sigma21	movement rates from deme 1 to 2 and 2 to 1, respectively
delta	rate of loss of immunity
S0	initial size of susceptible population.
I1_0	initial size of I2 population.
I2_0	initial size of I2 population.
R0	initial size of recovered population.
object	either the name of the model to simulate <i>or</i> a previously computed ‘gpsim’ object

**Value**

An object of class ‘gpsim’ with ‘model’ attribute “SIIR”.

**See Also**

More example genealogy processes: [lbdp](#), [moran](#), [seir](#), [si2r](#), [simulate\(\)](#), [sir](#)

**Examples**

```
simulate("SIIR",time=3,psi1=1,psi2=0) |>
  simulate(Beta1=2,gamma=2,time=10,psi1=10,psi2=1) |>
  plot()

runSIIR(Beta1=10,Beta2=8,
  S0=200,I1_0=10,I2_0=8,R0=0,time=0,t0=-1) |>
  simulate(psi1=10,time=2) |>
  plot(points=TRUE,obscure=FALSE)

simulate("SIIR",Beta1=2,Beta2=50,gamma=1,psi1=2,
  S0=300,I1_0=20,I2_0=2,time=5) |>
  lineages() |>
  plot()
```

---

simulate	<i>simulate</i>
----------	-----------------

---

**Description**

Simulate Markov genealogy processes

**Usage**

```
simulate(object, ...)

## Default S3 method:
simulate(object, ...)

## S3 method for class 'character'
simulate(object, time, ...)

## S3 method for class 'gpsim'
simulate(object, time, ...)
```

**Arguments**

object	either the name of the model to simulate <i>or</i> a previously computed ‘gpsim’ object
...	additional arguments to the model-specific simulation functions
time	end timepoint of simulation

**Details**

When object is of class ‘gpsim’, i.e., the result of a genealogy-process simulation, `simulate` acts to continue the simulation to a later timepoint. Note that, one cannot change initial conditions or  $t_0$  when continuing a simulation.

**Value**

An object of ‘gpsim’ class.

**See Also**

More example genealogy processes: [lbdp](#), [moran](#), [seir](#), [si2r](#), [siir](#), [sir](#)

---

sir

---

*Classical susceptible-infected-recovered model*


---

**Description**

A single, unstructured population of hosts.

**Usage**

```
runSIR(
  time,
  t0 = 0,
  Beta = 2,
  gamma = 1,
  psi = 1,
  delta = 0,
  S0 = 100,
  I0 = 2,
  R0 = 0
)

continueSIR(object, time, Beta = NA, gamma = NA, psi = NA, delta = NA)

sir_pomp(data, Beta, gamma, psi, delta = 0, S0, I0, R0, t0 = 0)
```

**Arguments**

time	final time
t0	initial time
Beta	transmission rate.
gamma	recovery rate.
psi	sampling rate.
delta	immunity waning rate
S0	initial size of susceptible population.
I0	initial size of infected population.
R0	initial size of recovered population.
object	either the name of the model to simulate <i>or</i> a previously computed ‘gpsim’ object
data	data frame containing the genealogy in the format returned by <a href="#">newick2df</a> .

**Details**

sir\_pomp constructs a **pomp** object containing a given set of data and a SIR model.

**Value**

An object of class ‘gpsim’ with ‘model’ attribute “SIR”.

**See Also**

More example genealogy processes: [lbdp](#), [moran](#), [seir](#), [si2r](#), [siir](#), [simulate\(\)](#)

**Examples**

```
simulate("SIR",Beta=2,gamma=1,psi=2,S0=1000,I0=5,time=5) |>
  simulate(Beta=5,gamma=2,time=10,psi=3) |>
  plot()

runSIR(Beta=3,gamma=1,psi=2,S0=20,I0=5,R0=0,time=5,t0=-1) |>
  plot(points=TRUE)

runSIR(Beta=3,gamma=0.1,psi=0.2,S0=100,I0=5,R0=0,time=2,t0=0) -> x
plot_grid(plotlist=list(plot(x,points=TRUE),diagram(x)),
  ncol=1,rel_heights=c(4,1))

simulate("SIR",delta=1,time=20,I0=4) |> plot()
simulate("SIR",delta=1,time=20,I0=4) |> lineages() |> plot()
```

---

 yaml

---

 YAML output
 

---

**Description**

Human- and machine-readable description

**Usage**

```
yaml(object, prune = TRUE, obscure = TRUE)
```

**Arguments**

object	gpsim object.
prune	logical; prune the genealogy?
obscure	logical; obscure the demes?

**Value**

A string in yaml format.

**Examples**

```
simulate("SIIR",time=1) |> yaml() |> cat()
```

# Index

- \* **Genealogy processes**
  - lbdp, 6
  - moran, 9
  - seir, 13
  - si2r, 15
  - siir, 17
  - simulate, 18
  - sir, 19
- \* **internals**
  - genealogy diagram internals, 3
- \* **internal**
  - as.data.frame, 2
  - genealogy diagram internals, 3
  - reexports, 12
- %dopar% (reexports), 12
- %dopar%, 13
- as.data.frame, 2
- as.yaml, 13
- as.yaml (reexports), 12
- bake, 13
- bake (reexports), 12
- ballGrob (genealogy diagram internals), 3
- continueLBDP (lbdp), 6
- continueMoran (moran), 9
- continueSEIR (seir), 13
- continueSI2R (si2r), 15
- continueSIIR (siir), 17
- continueSIR (sir), 19
- diagram, 2
- drawDetails.ballGrob (genealogy diagram internals), 3
- drawDetails.resizingTextGrob (genealogy diagram internals), 3
- foreach, 13
- foreach (reexports), 12
- freeze, 13
- freeze (reexports), 12
- genealogy diagram internals, 3
- genealogyGrob (genealogy diagram internals), 3
- getInfo, 5
- LBDP (lbdp), 6
- lbdp, 6, 9, 14, 16, 18–20
- lbdp\_exact (lbdp), 6
- lbdp\_pomp (lbdp), 6
- lineages, 7
- Moran (moran), 9
- moran, 7, 9, 14, 16, 18–20
- moran\_exact (moran), 9
- newick2df, 10, 20
- nodeGrob (genealogy diagram internals), 3
- phylopomp-package, 1
- plot, 8, 11
- plot.gplin (lineages), 7
- plot\_grid, 13
- plot\_grid (reexports), 12
- pocketGrob (genealogy diagram internals), 3
- postDrawDetails.ballGrob (genealogy diagram internals), 3
- postDrawDetails.resizingTextGrob (genealogy diagram internals), 3
- preDrawDetails.ballGrob (genealogy diagram internals), 3
- preDrawDetails.resizingTextGrob (genealogy diagram internals), 3
- print.gpdia (diagram), 2

`print.gpsim`(genealogy diagram  
internals), 3

`read_yaml`, 13

`read_yaml` (reexports), 12

`reexports`, 12

`registerDoSEQ`, 13

`registerDoSEQ` (reexports), 12

`resizingTextGrob` (genealogy diagram  
internals), 3

`runLBDP` (lbdp), 6

`runMoran` (moran), 9

`runSEIR` (seir), 13

`runSI2R` (si2r), 15

`runSIIR` (siir), 17

`runSIR` (sir), 19

`SEIR` (seir), 13

`seir`, 7, 9, 13, 16, 18–20

`SI2R` (si2r), 15

`si2r`, 7, 9, 14, 15, 18–20

`SIIR` (siir), 17

`siir`, 7, 9, 14, 16, 17, 19, 20

`simulate`, 7, 9, 14, 16, 18, 18, 20

`SIR` (sir), 19

`sir`, 7, 9, 14, 16, 18, 19, 19

`sir_pomp` (sir), 19

`stew`, 13

`stew` (reexports), 12

`textGrob`, 4

`tibble`, 6, 8

`treeplot`, 8, 11

`treeplot` (plot), 11

`viewport`, 13

`viewport` (reexports), 12

`yaml`, 21