

Package ‘panelPomp’

April 3, 2025

Contents

panelPomp-package	2
.modifyOther	3
.modifySelf	4
as	4
coef<-,pfilterd.ppomp-method	5
contacts	6
get_dim	7
mif2	8
panel-designs	10
panelGompertz	11
panelGompertzLikelihood	13
panelMeasles	13
panelPomp	15
panelPomp_methods	16
panelRandomWalk	19
panel_loglik	20
panel_logmeanexp	21
params	22
pfilter	22
plot	25
shared	26
shared<-	27
simulate	27
specific	28
specific<-	29
twentycities	30
uk_measles	31
unitLogLik	32
unit_objects	33
wQuotes	34

Index	35
--------------	-----------

panelPomp-package	<i>Inference for PanelPOMPs (Panel Partially Observed Markov Processes)</i>
-------------------	---

Description

The **panelPomp** package provides facilities for inference on panel data using panel partially-observed Markov process (PANELPOMP) models. To do so, it relies on and extends a number of facilities that the **pomp** package provides for inference on time series data using partially-observed Markov process (POMP) models.

The **panelPomp** package extends to panel data some of the capabilities of the **pomp** package to fit nonlinear, non-Gaussian dynamic models. This is done accomodating both fixed and random effects. Currently, the focus is on likelihood-based approaches. In addition to these likelihood-based tools, **panelPomp** also provides a framework under which alternative statistical methods for PANELPOMP models can be developed (very much like **pomp** provides a platform upon which statistical inference methods for POMP models can be implemented).

Data analysis using panelPomp

The first step in using **panelPomp** is to encode one's model(s) and data in objects of class `panelPomp`. One does this via a call to the [panelPomp](#) constructor function.

panelPomp version 1.6.0.0 provides algorithms for

1. particle filtering of panel data (AKA sequential Monte Carlo or sequential importance sampling), as proposed in Bretó, Ionides and King (2020). This reference provides the fundamental theoretical support for the averaging of Monte Carlo replicates of panel unit likelihoods as implemented in **panelPomp**; see [pfilter](#)
2. the panel iterated filtering method of Bretó, Ionides and King (2020). This reference provides the fundamental theoretical support for the extensions of the iterated filtering ideas of Ionides et al. (2006, 2011, 2015) to panel data as implemented in **panelPomp**; see [mif2](#)

The package also provides various tools for handling and extracting information on models and data.

Extending the pomp platform for developing inference tools

panelPomp extends to panel data the general interface to the components of POMP models provided by **pomp**. In doing so, it contributes to the goal of the **pomp** project of facilitating the development of new algorithms in an environment where they can be tested and compared on a growing body of models and datasets.

Comments, bug reports, and requests

Contributions are welcome, as are suggestions for improvement, feature requests, and bug reports. Please submit these via the [panelPomp issues page](#). We particularly welcome minimal working examples displaying uninformative, misleading or inaccurate error messages. We also welcome suggestions for clarifying obscure passages in the documentation. Help requests are welcome, but

please consider before sending requests whether they are regarding the use of **panelPomp** or that of **pomp**. For help with **pomp**, please visit [pomp's FAQ](#).

Documentation

Examples are provided via the `contacts()`, `panelGompertz()` and `panelRandomWalk()` functions.

License

panelPomp is provided under the GPL-3 License.

Author(s)

Maintainer: Jesse Wheeler <jeswheel@umich.edu> ([ORCID](#))

Authors:

- Carles Breto <carles.breto@uv.es> ([ORCID](#))
- Edward L. Ionides ([ORCID](#))
- Aaron A. King ([ORCID](#))

Other contributors:

- Aaron Abkemeier <aaronabk@umich.edu> [contributor]

References

Bretó, C., Ionides, E. L. and King, A. A. (2020) Panel Data Analysis via Mechanistic Models. *Journal of the American Statistical Association*, **115**(531), 1178–1188. doi:[10.1080/01621459.2019.1604367](#)

See Also

[pomp package](#), [panelPomp](#)

`.modifyOther`*Internal function for modifying pparamArray in Mif2*

Description

Internal function for modifying pparamArray in Mif2

Usage

```
.modifyOther(x, spnames, indices, unit)
```

Arguments

<code>x</code>	<code>pparamArray</code> in <code>mif2</code> internal
<code>spnames</code>	names of parameters to update
<code>indices</code>	indices that are the output of a <code>mif2</code> call to <code>pomp</code>
<code>unit</code>	unit in the unit loop

<code>.modifySelf</code>	<i>Internal function for modifying <code>pparamArray</code> in <code>Mif2</code></i>
--------------------------	--

Description

Internal function for modifying `pparamArray` in `Mif2`

Usage

```
.modifySelf(x, spnames, M, unit)
```

Arguments

<code>x</code>	<code>pparamArray</code> in <code>mif2</code> internal
<code>spnames</code>	names of parameters to update
<code>M</code>	Matrix of replacement values
<code>unit</code>	unit in the unit loop

<code>as</code>	<i>Coercing <code>panelPomp</code> objects as <code>list</code>, <code>pompList</code> or <code>data.frame</code></i>
-----------------	---

Description

When coercing to a `data.frame`, it coerces a `panelPomp` into a `data.frame`, assuming units share common variable names.

When coercing to a `list`, it extracts the `unit_objects` slot of `panelPomp` objects and attaches associated parameters.

When coercing to a `pompList`, it extracts the `unit_objects` slot of `panelPomp` objects and attaches associated parameters, converting the resulting list to a `pompList` to help the assignment of `pomp` methods.

Value

An object of class matching that specified in the second argument (`to=`).

Author(s)

Carles Bretó

See Also

Other panelPomp methods: [panelPomp_methods](#)

 coef<-,pfilterd.ppomp-method

Modifying parameters of filtered objects

Description

The setter functions for parameters of pfilterd.ppomp objects do not allow users to set parameters of panelPomp objects that have been filtered. This is done to avoid the possibility of having parameter values in an object that do not match other attributes of a filtered object to be saved together.

The setter functions for parameters of pfilterd.ppomp objects do not allow users to set parameters of panelPomp objects that have been filtered. This is done to avoid the possibility of having parameter values in an object that do not match other attributes of a filtered object to be saved together.

The setter functions for parameters of pfilterd.ppomp objects do not allow users to set parameters of panelPomp objects that have been filtered. This is done to avoid the possibility of having parameter values in an object that do not match other attributes of a filtered object to be saved together.

Usage

```
## S4 replacement method for signature 'pfilterd.ppomp'
coef(object, ...) <- value
```

```
## S4 replacement method for signature 'pfilterd.ppomp'
shared(object) <- value
```

```
## S4 replacement method for signature 'pfilterd.ppomp'
specific(object) <- value
```

Arguments

object	pfilterd.ppomp object
...	additional arguments.
value	New parameter value. This function does not allow users to set this value.

 contacts

*Contacts model***Description**

A panel model for dynamic variation in sexual contacts, with data from Vittinghof et al (1999). The model was developed by Romero-Severson et al (2015) and discussed by Bretó et al (2020).

Usage

```
contacts(
  params = c(mu_X = 1.75, sigma_X = 2.67, mu_D = 3.81, sigma_D = 4.42, mu_R = 0.04,
    sigma_R = 0, alpha = 0.9)
)
```

Arguments

params parameter vector.

Value

A panelPomp object.

Author(s)

Edward L. Ionides

References

Bretó, C., Ionides, E. L. and King, A. A. (2020) Panel Data Analysis via Mechanistic Models. *Journal of the American Statistical Association*, **115**(531), 1178–1188. doi:[10.1080/01621459.2019.1604367](https://doi.org/10.1080/01621459.2019.1604367)

Romero-Severson, E.O., Volz, E., Koopman, J.S., Leitner, T. and Ionides, E.L. (2015) Dynamic variation in sexual contact rates in a cohort of HIV-negative gay men. *American journal of epidemiology*, **182**(3), 255–262. doi:[10.1093/aje/kwv044](https://doi.org/10.1093/aje/kwv044)

Vittinghoff, E., Douglas, J., Judon, F., McKiman, D., MacQueen, K. and Buchinder, S.P. (1999) Per-contact risk of human immunodeficiency virus transmission between male sexual partners. *American journal of epidemiology*, **150**(3), 306–311. doi:[10.1093/oxfordjournals.aje.a010003](https://doi.org/10.1093/oxfordjournals.aje.a010003)

See Also

Other panelPomp examples: [panelGompertz\(\)](#), [panelMeasles\(\)](#), [panelRandomWalk\(\)](#)

Examples

```
contacts()
```

get_dim*Get single column or row without dropping names*

Description

Subset matrix dropping dimension but without dropping dimname (as done by `[` by default).

Usage

```
get_col(matrix, rows, col)
```

```
get_row(matrix, row, cols)
```

Arguments

matrix matrix.

rows numeric; rows to subset; like with `[`, this argument can be left empty to designate all rows.

col integer; single column to subset.

row integer; single row to subset.

cols numeric; columns to subset; like with `[`, this argument can be left empty to designate all columns.

Value

A named vector object.

Author(s)

Carles Bretó

Examples

```
m <- matrix(NA,dimnames=list('r1','c1'))
m[1,1] # = NA; R removes both names
get_col(m,rows=1,col=1) # = c(r1=NA) keeps colname
get_row(m,row=1,cols=1) # = c(c1=NA) keeps rowname
```

mif2

PIF: Panel iterated filtering

Description

Tools for applying iterated filtering algorithms to panel data. The panel iterated filtering of Bretó et al. (2020) extends to panel models the improved iterated filtering algorithm (Ionides et al., 2015) for estimating parameters of a partially observed Markov process. Iterated filtering algorithms rely on extending a partially observed Markov process model of interest by introducing random perturbations to the model parameters. The space where the original parameters live is then explored at each iteration by running a particle filter. Convergence to a maximum likelihood estimate has been established for appropriately constructed procedures that iterate this search over the parameter space while diminishing the intensity of perturbations (Ionides et al. 2006, 2011, 2015).

Usage

```
## S4 method for signature 'panelPomp'
mif2(
  data,
  Nmif = 1,
  shared.start,
  specific.start,
  start,
  Np,
  rw.sd,
  cooling.type = c("geometric", "hyperbolic"),
  cooling.fraction.50,
  block = FALSE,
  verbose = getOption("verbose"),
  ...
)

## S4 method for signature 'mif2d.ppomp'
mif2(
  data,
  Nmif,
  shared.start,
  specific.start,
  start,
  Np,
  rw.sd,
  cooling.type,
  cooling.fraction.50,
  block,
  ...
)
```



```
## S4 method for signature 'mif2d.ppomp'
traces(object, pars, ...)
```

Arguments

<code>data</code>	An object of class <code>panelPomp</code> or inheriting class.
<code>Nmif</code>	The number of filtering iterations to perform.
<code>shared.start</code>	named numerical vector; the starting guess of the shared parameters.
<code>specific.start</code>	matrix with row parameter names and column unit names; the starting guess of the specific parameters.
<code>start</code>	A named numeric vector of parameters at which to start the IF2 procedure.
<code>Np</code>	the number of particles to use. This may be specified as a single positive integer, in which case the same number of particles will be used at each timestep. Alternatively, if one wishes the number of particles to vary across timesteps, one may specify <code>Np</code> either as a vector of positive integers of length <code>length(time(object), t0=TRUE))</code> or as a function taking a positive integer argument. In the latter case, <code>Np(k)</code> must be a single positive integer, representing the number of particles to be used at the k-th timestep: <code>Np(0)</code> is the number of particles to use going from <code>timezero(object)</code> to <code>time(object)[1]</code> , <code>Np(1)</code> , from <code>timezero(object)</code> to <code>time(object)[1]</code> , and so on, while when <code>T=length(time(object))</code> , <code>Np(T)</code> is the number of particles to sample at the end of the time-series.
<code>rw.sd</code>	An unevaluated expression of the form <code>quote(rw.sd())</code> to be used for all panel units. If a list of such expressions of the same length as the <code>object</code> argument is provided, each list element will be used for the corresponding panel unit.
<code>cooling.type, cooling.fraction.50</code>	specifications for the cooling schedule, i.e., the manner and rate with which the intensity of the parameter perturbations is reduced with successive filtering iterations. <code>cooling.type</code> specifies the nature of the cooling schedule. See below (under “Specifying the perturbations”) for more detail.
<code>block</code>	A logical variable determining whether to carry out block resampling of unit-specific parameters.
<code>verbose</code>	logical; if TRUE, diagnostic messages will be printed to the console.
<code>...</code>
<code>object</code>	an object resulting from the application of IF2 (i.e., of class <code>mif2d.ppomp</code>)
<code>pars</code>	names of parameters

Value

`mif2()` returns an object of class `mif2d.ppomp`.

`traces()` returns a matrix with estimated parameter values at different iterations of the IF2 algorithm in the natural scale. The default is to return values for all parameters but a subset of parameters can be passed via the optional argument `pars`.

Author(s)

Carles Bretó

References

- Bretó, C., Ionides, E. L. and King, A. A. (2020) Panel Data Analysis via Mechanistic Models. *Journal of the American Statistical Association*, **115**(531), 1178–1188. doi:[10.1080/01621459.2019.1604367](https://doi.org/10.1080/01621459.2019.1604367)
- Ionides, E. L., Bretó, C. and King, A. A. (2006) Inference for nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, **103**(49), 18438–18443. doi:[10.1073/pnas.0603181103](https://doi.org/10.1073/pnas.0603181103)
- Ionides, E. L., Bhadra, A., Atchadé, Y. and King, A. A. (2011) Iterated filtering. *Annals of Statistics*, **39**(3), 1776–1802. doi:[10.1214/11AOS886](https://doi.org/10.1214/11AOS886)
- Ionides, E. L., Nguyen, D., Atchadé, Y., Stoev, S. and King, A. A. (2015) Inference via iterated, perturbed Bayes maps. *Proceedings of the National Academy of Sciences*, **112**(3), 719–724. doi:[10.1073/pnas.1410597112](https://doi.org/10.1073/pnas.1410597112)
- King, A. A., Nguyen, D. and Ionides, E. L. (2016) Statistical inference for partially observed Markov processes via the package **pomp**. *Journal of Statistical Software* **69**(12), 1–43. DOI: [10.18637/jss.v069.i12](https://doi.org/10.18637/jss.v069.i12). An updated version of this paper is available on the [package website](#).

See Also

pomp's `mif2` at [mif2](#), [panel_loglik](#)

Other panelPomp workhorse functions: [panelPomp](#), [panel_loglik](#), [pfilter\(\)](#)

Examples

```
## start with a panelPomp object
p <- panelRandomWalk()
## specify which parameters to estimate via rw_sd() and how fast to cool
mp <- mif2(p, Np=10, rw.sd=rw_sd(X.0=0.2), cooling.fraction.50=0.5, cooling.type="geometric")
mp
## the object resulting from an initial estimation can be used as a new starting point
mmp <- mif2(mp, Np=10, rw.sd=rw_sd(X.0=0.2), cooling.fraction.50=0.5, cooling.type="geometric")
mmp
## convergence can be partly diagnosed by checking estimates and likelihoods at different iterations
traces(mmp)
```

panel-designs

#' Create design matrix for panelPomp calculations

Description

These functions are useful for generating design matrices for the exploration of parameter space.

Usage

```
runif_panel_design(
  lower = numeric(0),
  upper = numeric(0),
  nseq,
  specific_names,
  unit_names
)
```

Arguments

lower, upper	named numeric vectors giving the lower and upper bounds of the ranges, respectively.
nseq	Total number of points requested
specific_names	Character vector containing the names of unit-specific parameters. This argument must be used in conjunction with the argument unit_names; it is used if the search bounds for all unspecified unit-specific parameters are the same.
unit_names	Character vector containing the names of the units of the panel. If not used in conjunction with unit_names this argument is ignored.

Value

runif_panel_design returns a data.frame object with nseq rows. Each row corresponds to a parameter set drawn randomly from a multivariate uniform distribution specified by the lower, upper, specific_names and unit_names arguments.

Author(s)

Jesse Wheeler, Aaron A. King

Examples

```
runif_panel_design(
  lower = c('a' = 0, 'b' = 10, 'a[u2]' = 0.5),
  upper = c('a' = 1, 'b' = 15, 'a[u2]' = 0.75),
  specific_names = c('a'),
  unit_names = paste0(rep('u', 5), 1:5),
  nseq = 10
)
```

panelGompertz

Panel Gompertz model

Description

Builds a collection of independent realizations from the Gompertz model.

Usage

```
panelGompertz(  
  N = 100,  
  U = 50,  
  params = c(K = 1, r = 0.1, sigma = 0.1, tau = 0.1, X.0 = 1),  
  seed = 12345678  
)
```

Arguments

N	number of observations for each unit.
U	number of units.
params	parameter vector, assuming all units have the same parameters.
seed	passed to the random number generator for simulation.

Value

A panelPomp object.

Author(s)

Edward L. Ionides, Carles Bretó

References

Bretó, C., Ionides, E. L. and King, A. A. (2020) Panel Data Analysis via Mechanistic Models. *Journal of the American Statistical Association*, **115**(531), 1178–1188. doi:[10.1080/01621459.2019.1604367](https://doi.org/10.1080/01621459.2019.1604367)

King, A. A., Nguyen, D. and Ionides, E. L. (2016) Statistical inference for partially observed Markov processes via the package **pomp**. *Journal of Statistical Software* **69**(12), 1–43. DOI: [10.18637/jss.v069.i12](https://doi.org/10.18637/jss.v069.i12). An updated version of this paper is available on the [package website](#).

See Also

Other panelPomp examples: [contacts\(\)](#), [panelMeasles\(\)](#), [panelRandomWalk\(\)](#)

Examples

```
panelGompertz()
```

panelGompertzLikelihood

Likelihood for a panel Gompertz model via a Kalman filter

Description

Evaluates the likelihood function for a panel Gompertz model, using a format convenient for maximization by `optim()` to obtain a maximum likelihood estimate. Specifically, estimated and fixed parameters are supplied by two different arguments.

Usage

```
panelGompertzLikelihood(x, panelPompObject, params)
```

Arguments

<code>x</code>	named vector for a subset of parameters, corresponding to those being estimated.
<code>panelPompObject</code>	a panel Gompertz model.
<code>params</code>	named vector containing all the parameters of the panel Gompertz model. Estimated parameters are overwritten by <code>x</code> .

Value

A numeric value.

Author(s)

Edward L. Ionides

Examples

```
pg <- panelGompertz(N=2,U=2)
panelGompertzLikelihood(coef(pg),pg,coef(pg))
```

panelMeasles

Make a panelPomp model using UK measles data.

Description

The model is a modified [panelPomp](#) version of the model of He et al. 2010. The model is a stochastic SEIR model that accounts for population demographics in the form of births and deaths. Because of the increased transmission that results from school-aged children entering the susceptible pool once they begin attending classes for the first time, the model includes a birth-cohort effect, which moves a specified fraction of the cohort into the susceptible pool all at once. The model also includes a seasonality in transmission rate that is larger during school terms than it is during holidays.

Usage

```
panelMeasles(
  units = c("Bedwellty", "Birmingham", "Bradford", "Bristol", "Cardiff", "Consett",
    "Dalton.in.Furness", "Halesworth", "Hastings", "Hull", "Leeds", "Lees", "Liverpool",
    "London", "Manchester", "Mold", "Northwich", "Nottingham", "Oswestry", "Sheffield"),
  starting_pparams = NULL,
  interp_method = c("shifted_splines", "linear"),
  first_year = 1950,
  last_year = 1963,
  dt = 1/365.25
)
```

Arguments

<code>units</code>	Character vector of units in uk_measles to be used in the panel model.
<code>starting_pparams</code>	Parameters in the list format, having shared and specific components. Set to NULL to assign NA values.
<code>interp_method</code>	Method used to interpolate population and births. Possible options are "shifted_splines" and "linear".
<code>first_year</code>	Integer for the first full year of data desired.
<code>last_year</code>	Integer for the last full year of data desired.
<code>dt</code>	Size of the time step.

Value

A panelPomp object.

References

D. He, E.L. Ionides, and A.A. King. Plug-and-play inference for disease dynamics: measles in large and small populations as a case study. *Journal of the Royal Society Interface* **7**, 271–283, 2010.

See Also

Other panelPomp examples: [contacts\(\)](#), [panelGompertz\(\)](#), [panelRandomWalk\(\)](#)

Examples

```
panelMeasles(units = "London")
```

panelPomp

*Constructing panelPomp objects***Description**

This function constructs panelPomp objects, representing PanelPOMP models (as defined in Bretó et al., 2020). PanelPOMP models involve multiple units, each of which can in turn be modeled by a POMP model. Such POMP models can be encoded as a list of pomp objects, a cornerstone that the panelPomp function can use to construct the corresponding panelPomp object.

Usage

```
panelPomp(object, shared, specific, params)
```

Arguments

object required; either (i) a list of pomp objects; or (ii) an object of class panelPomp or inheriting class panelPomp.

If object is a list of pomps, the list must be named. All these pomps must either have no parameters or have the same parameter names. (This is just a format requirement. pomp codes can ignore any parameter that is irrelevant to any given panel unit.)

If object is a panelPomp object, the function allows modifying the shared and unit-specific configuration of object.

shared, specific

optional; these arguments depend on the type of object.

If object is a list of pomps, shared must be a numeric vector specifying parameter values shared among panel units. specific must be a matrix with parameter values that are unit-specific with rows naming parameters and columns naming units (these names must match those of object). If no values are specified and object has parameter values, these are set to be all unit-specific.

If object is a panelPomp object, these arguments can still be used as described above to modify the parameters of object. Alternatively, the parameter configuration of object can be modified providing only a character shared naming parameters of object that should be shared (with values for parameters not originally shared taken from the unit-specific parameters of the first panel unit of object). shared=NULL sets all parameters as unit-specific.

params

optional; a named numeric vector. In this case, the nature of parameters is determined via a naming convention: names ending in "[unit_name]" are assumed to denote unit-specific parameters; all other names specify shared parameters.

Value

A panelPomp object.

Author(s)

Carles Bretó

References

Bretó, C., Ionides, E. L. and King, A. A. (2020) Panel Data Analysis via Mechanistic Models. *Journal of the American Statistical Association*, **115**(531), 1178–1188. doi:[10.1080/01621459.2019.1604367](https://doi.org/10.1080/01621459.2019.1604367)

King, A. A., Nguyen, D. and Ionides, E. L. (2016) Statistical inference for partially observed Markov processes via the package **pomp**. *Journal of Statistical Software* **69**(12), 1–43. DOI: [10.18637/jss.v069.i12](https://doi.org/10.18637/jss.v069.i12). An updated version of this paper is available on the [package website](#).

See Also

pomp's constructor at [pomp](#)

Other panelPomp workhorse functions: [mif2\(\)](#), [panel_loglik](#), [pfilter\(\)](#)

Examples

```
## recreate the 'panelRandomWalk()' example
prw <- panelRandomWalk()
prw2 <- panelPomp(unit_objects(prw), params = coef(prw))
identical(prw, prw2) # TRUE
```

panelPomp_methods	<i>Manipulating panelPomp objects</i>
-------------------	---------------------------------------

Description

Tools for manipulating panelPomp objects.

Usage

```
## S4 method for signature 'panelPomp'
coef(object, format = c("vector", "list"))

## S4 replacement method for signature 'panelPomp'
coef(object, ...) <- value

## S4 method for signature 'panelPomp'
length(x)

## S4 method for signature 'panelPomp'
names(x)

toParamList(value)

## S4 method for signature 'panelPomp'
```



```

print(x, ...)

## S4 method for signature 'panelPomp'
show(object)

## S4 method for signature 'panelPomp'
unit_objects(object)

## S4 method for signature 'panelPomp'
window(x, start, end)

## S4 method for signature 'panelPomp'
x[i]

## S4 method for signature 'panelPomp'
x[[i]]

## S4 method for signature 'panelPomp'
specific(object, ..., format = c("matrix", "vector"))

## S4 replacement method for signature 'panelPomp'
specific(object) <- value

## S4 method for signature 'panelPomp'
shared(object)

## S4 replacement method for signature 'panelPomp'
shared(object) <- value

```

Arguments

object, x	An object of class panelPomp or inheriting class panelPomp.
format	the format (data type) of the return value.
...
value	value to be assigned.
start, end	position in original times(pomp) at which to start.
i	unit index (indices) or name (names).

Value

coef() returns a numeric vector.

length() returns an integer.

names() returns a character vector.

toParamList() returns a list with the model parameters in list form.

When given objects of class panelPomp, unit_objects() returns a list of pomp objects.

window() returns a panelPomp object with adjusted times.

``[`` returns a panelPomp object.

``[[`` returns a pomp object.

`specific()` returns unit-specific parameters as a numeric matrix or vector

`shared()` returns shared parameters from a panelPomp object

Methods

coef Extracts coefficients of panelPomp objects.

coef<- Assign coefficients to panelPomp objects.

length Count the number of units in panelPomp objects.

names Get the unit names of panelPomp objects.

toParamList Converts panel coefficients from vector form to list form.

window Subset panelPomp objects by changing start time and end time.

`[]` Take a subset of units.

`[[[]]` Select the pomp object for a single unit.

specific Extracts the specific coefficients.

specific<- Assigns the specific coefficients.

shared Extracts the shared coefficients.

shared<- Assigns the shared coefficients.

Author(s)

Carles Bretó, Aaron A. King, Edward L. Ionides, Jesse Wheeler

See Also

Other panelPomp methods: [as\(\)](#)

Examples

```
## access and manipulate model parameters and other features
prw <- panelRandomWalk()
coef(prw)
# replace coefficients
coef(prw) <- c(sigmaX=2,coef(prw)[-1])
coef(prw)
length(prw)
names(prw)
# convert vector-form parameters to list-form parameters
toParamList(coef(prw))
## summaries of objects
print(prw)
show(prw)
## access underlying pomp objects
unit_objects(prw)
## select windows of time
```

```

window(prw,start=2,end=4)
## subsetting panelPomp objects
prw[1] # panelPomp of 1 unit (first unit of prw)
prw[[2]] # pomp object corresponding to unit 2 of prw
# access and manipulate model parameters and other features
specific(prw)
# replace unit-specific coefficients
specific(prw) <- c("sigmaX[rw1]"=2)
specific(prw)
# access and manipulate model parameters and other features
shared(prw)
# replace unit-specific coefficients
shared(prw) <- c('sigmaY'=2)
shared(prw)

```

panelRandomWalk	<i>Panel random walk model</i>
-----------------	--------------------------------

Description

Builds a collection of independent realizations from a random walk model.

Usage

```

panelRandomWalk(
  N = 5,
  U = 2,
  params = c(sigmaY = 1, sigmaX = 1, X.0 = 1),
  seed = 3141592
)

```

Arguments

N	number of observations for each unit.
U	number of units.
params	parameter vector, assuming all units have the same parameters.
seed	passed to the random number generator for simulation.

Value

A panelPomp object.

Author(s)

Edward L. Ionides, Carles Bretó

See Also

Other panelPomp examples: [contacts\(\)](#), [panelGompertz\(\)](#), [panelMeasles\(\)](#)

Examples

```
panelRandomWalk()
```

panel_loglik	<i>Handling of loglikelihood replicates</i>
--------------	---

Description

Handling of loglikelihood replicates.

Usage

```
## S4 method for signature 'matrix'
logLik(object, repMargin, first = "aver", aver = "logmeanexp", se = FALSE)
```

Arguments

object	Matrix with the same number of replicated estimates for each panel unit loglikelihood.
repMargin	The margin of the matrix having the replicates (1 for rows, 2 for columns).
first	Whether to "aver"(average replicates) or "aggr"(aggregate units) before performing the other action.
aver	How to average: 'logmeanexp' to average on the likelihood scale before taking logs or 'mean' to average after taking logs (in which case, which action is performed first does not change the result).
se	logical; whether to give standard errors.

Details

When se = TRUE, the jackknife se's from `pomp::logmeanexp` are squared, summed and the squared root is taken.

Value

numeric vector with the average panel log likelihood and, when se = TRUE, the corresponding standard error.

Author(s)

Carles Bretó

See Also

Other panelPomp workhorse functions: [mif2\(\)](#), [panelPomp](#), [pfilter\(\)](#)

Examples

```
ulls <- matrix(c(1,1.1,10.1,10),nr=2)
# when combining log likelihood estimates, the order in which aggregation and
# averaging are done can make a difference: panel_logmeanexp() implements the best
logLik(ulls,repMargin=1,first="aver",aver="logmeanexp")
logLik(ulls,repMargin=1,first="aggr",aver="mean",se=TRUE)
```

panel_logmeanexp	<i>Log-mean-exp for panels</i>
------------------	--------------------------------

Description

This function computes the [logmeanexp](#) for each column or row of a numeric matrix and sums the result. Because the loglikelihood of a panelPomp object is the sum of the loglikelihoods of its units, this function can be used to summarize replicated estimates of the panelPomp model likelihood. If `se = TRUE`, the jackknife SE estimates from [logmeanexp](#) are squared, summed and the squared root is taken.

Usage

```
panel_logmeanexp(x, MARGIN, se = FALSE)
```

Arguments

<code>x</code>	Matrix with the same number of replicated estimates for each panel unit loglikelihood.
<code>MARGIN</code>	The dimension of the matrix that corresponds to a panel unit and over which averaging occurs (1 indicates rows, 2 indicates columns).
<code>se</code>	logical; whether to give standard errors.

Value

A numeric value with the average panel log likelihood or, when `se = TRUE`, a numeric vector adding the corresponding standard error.

Author(s)

Carles Bretó

See Also

`panel_loglik`

Examples

```
ulls <- matrix(c(1,1,10,10),nr=2)
panel_logmeanexp(ulls,MARGIN=2,se=TRUE)
```

params	<i>Manipulating panelPomp object parameter formats</i>
--------	--

Description

These facilitate keeping a record of evaluated log likelihoods.

Usage

```
toParamVec(pParams)
```

```
toMatrixPparams(listPparams)
```

Arguments

pParams	A list with both shared (vector) and unit-specific (matrix) parameters.
listPparams	PanelPomp parameters in list format

Value

toParamVec() returns model parameters in vector form. This function is the inverse of [toParamList](#)
 toMatrixPparams() returns an object of class matrix with the model parameters in matrix form.

Author(s)

Carles Bretó

Examples

```
prw <- panelRandomWalk()
toParamVec(coef(prw, format = 'list'))
toMatrixPparams(coef(prw, format = 'list'))
```

pfilter	<i>Particle filtering for panel data</i>
---------	--

Description

Tools for applying particle filtering algorithms to panel data.

Usage

```
## S4 method for signature 'panelPomp'
pfilter(
  data,
  shared,
  specific,
  params,
  Np,
  verbose = getOption("verbose"),
  ...
)

## S4 method for signature 'pfilterd.ppomp'
logLik(object, ...)

## S4 method for signature 'pfilterd.ppomp'
unitLogLik(object, ...)
```

Arguments

data	An object of class <code>panelPomp</code> or inheriting class <code>panelPomp</code> .
shared, specific	<p>optional; these arguments depend on the type of object.</p> <p>If object is a list of poms, shared must be a numeric vector specifying parameter values shared among panel units. specific must be a matrix with parameter values that are unit-specific with rows naming parameters and columns naming units (these names must match those of object). If no values are specified and object has parameter values, these are set to be all unit-specific.</p> <p>If object is a <code>panelPomp</code> object, these arguments can still be used as described above to modify the parameters of object. Alternatively, the parameter configuration of object can be modified providing only a character shared naming parameters of object that should be shared (with values for parameters not originally shared taken from the unit-specific parameters of the first panel unit of object). shared=NULL sets all parameters as unit-specific.</p>
params	optional; a named numeric vector. In this case, the nature of parameters is determined via a naming convention: names ending in “[unit_name]” are assumed to denote unit-specific parameters; all other names specify shared parameters.
Np	<p>the number of particles to use. This may be specified as a single positive integer, in which case the same number of particles will be used at each timestep. Alternatively, if one wishes the number of particles to vary across timesteps, one may specify Np either as a vector of positive integers of length</p> <p><code>length(time(object, t0=TRUE))</code></p> <p>or as a function taking a positive integer argument. In the latter case, Np(k) must be a single positive integer, representing the number of particles to be used at the k-th timestep: Np(0) is the number of particles to use going from <code>timezero(object)</code> to <code>time(object)[1]</code>, Np(1), from <code>timezero(object)</code> to</p>

time(object)[1], and so on, while when $T = \text{length}(\text{time}(\text{object}))$, $N_p(T)$ is the number of particles to sample at the end of the time-series.

verbose logical; if TRUE, diagnostic messages will be printed to the console.

... additional arguments, passed to the `pfilter` method of **pomp**.

object required; either (i) a list of pomp objects; or (ii) an object of class `panelPomp` or inheriting class `panelPomp`.

If **object** is a list of pomps, the list must be named. All these pomps must either have no parameters or have the same parameter names. (This is just a format requirement. pomp codes can ignore any parameter that is irrelevant to any given panel unit.)

If **object** is a `panelPomp` object, the function allows modifying the shared and unit-specific configuration of object.

Value

`pfilter()` returns an object of class `pfilterd.ppomp` that is also a `panelPomp` object (with the additional filtering details).

When applied to an object of class `pfilterd.ppomp`, `logLik()` returns a numeric value.

When given objects of class `pfilterd.ppomp`, `unitLoglik()` returns a numeric vector.

Methods

logLik Extracts the estimated log likelihood for the entire panel.

unitLogLik Extracts the estimated log likelihood for each panel unit.

Author(s)

Carles Bretó

References

Arulampalam, M. S., Maskell, S., Gordon, N. and Clapp, T. (2002) A Tutorial on Particle Filters for Online Nonlinear/Non-Gaussian Bayesian Tracking. *IEEE Trans. Sig. Proc.*, **50**(2), 174–188. [doi:10.1109/78.978374](https://doi.org/10.1109/78.978374)

Bretó, C., Ionides, E. L. and King, A. A. (2020) Panel Data Analysis via Mechanistic Models. *Journal of the American Statistical Association*, **115**(531), 1178–1188. [doi:10.1080/01621459.2019.1604367](https://doi.org/10.1080/01621459.2019.1604367)

See Also

pomp's pfilter at [pfilter](#), [panel_loglik](#)

Other `panelPomp` workhorse functions: [mif2\(\)](#), [panelPomp](#), [panel_loglik](#)

Examples

```
# filter, which generates log likelihoods
pfrw <- pfilter(panelRandomWalk(),Np=10)
class(pfrw) # "pfilterd.ppomp"
is(pfrw,"panelPomp") # TRUE
pfrw
# extract single log likelihood for the entire panel
logLik(pfrw)
# extract log likelihood for each panel unit
unitLogLik(pfrw)
```

plot

panelPomp plotting facilities

Description

Diagnostic plots for each unit in a panelPomp

Usage

```
## S4 method for signature 'panelPomp_plottable'
plot(
  x,
  variables,
  panel = lines,
  nc = NULL,
  yax.flip = FALSE,
  mar = c(0, 5.1, 0, if (yax.flip) 5.1 else 2.1),
  oma = c(6, 0, 5, 0),
  axes = TRUE,
  ...
)
```

Arguments

x	the object to plot
variables	optional character; names of variables to be displayed
panel	function of prototype panel(x, col, bg, pch, type, ...) which gives the action to be carried out in each panel of the display.
nc	the number of columns to use. Defaults to 1 for up to 4 series, otherwise to 2.
yax.flip	logical; if TRUE, the y-axis (ticks and numbering) should flip from side 2 (left) to 4 (right) from series to series.
mar, oma	the par mar and oma settings. Modify with care!
axes	logical; indicates if x- and y- axes should be drawn
...	ignored or passed to low-level plotting functions

Value

No return value (the function returns NULL).

Author(s)

Edward L. Ionides

Examples

```
plot(panelRandomWalk())
```

shared

Extract shared parameters from a panelPomp object

Description

This function is used to extract the shared parameters from a panelPomp object.

Usage

```
shared(object, ...)
```

Arguments

object	an object that contains shared parameters.
...	additional arguments.

Value

vector containing the shared parameters

Author(s)

Jesse Wheeler

See Also

[panelPomp_methods](#)

Examples

```
prw <- panelRandomWalk()
# extract parameters in list form
shared(prw)
```

shared<-	<i>Set shared parameters of a panelPomp object</i>
----------	--

Description

This function is used to set the shared parameters of a panel pomp object.

Usage

```
shared(object) <- value
```

Arguments

object	an object that contains shared parameters.
value	a named numeric vector containing the desired values of the shared parameter vector.

Author(s)

Jesse Wheeler

See Also

[panelPomp_methods](#)

Examples

```
prw <- panelRandomWalk()
# set parameters in list form
shared(prw) <- c("sigmaX" = 1, "sigmaY" = 2)
```

simulate	<i>Simulations of a panel of partially observed Markov process</i>
----------	--

Description

simulate generates simulations of the state and measurement processes.

Usage

```
## S4 method for signature 'panelPomp'
simulate(object, nsim = 1, shared, specific)
```

Arguments

object	a panelPomp object.
nsim	The number of simulations to perform. Unlike the pomp simulate method, all simulations share the same parameters.
shared	Named vector of the shared parameters.
specific	Matrix of unit-specific parameters, with a column for each unit.

Value

A single panelPomp object (if nsim=1) or a list of panelPomp objects (if nsim>1).

Author(s)

Edward L. Ionides

Examples

```
simulate(panelRandomWalk())
```

specific

Extract unit-specific parameters from a panelPomp object

Description

This function is used to extract the unit-specific parameters from a panel pomp object.

Usage

```
specific(object, ..., format = c("matrix", "vector"))
```

Arguments

object	an object that contains unit-specific parameters
...	additional arguments.
format	character representing how the parameters should be returned

Value

a matrix or vector containing the unit-specific parameters

Author(s)

Jesse Wheeler

See Also

[panelPomp_methods](#)

Examples

```
prw <- panelRandomWalk()
# extract parameters in list form
specific(prw)
```

specific<-

*Set unit-specific parameters of a panelPomp object***Description**

This function is used to set the unit-specific parameters of a panel pomp object.

Usage

```
specific(object) <- value
```

Arguments

object	an object that contains unit-specific parameters.
value	a numeric matrix with column names matching the names of the <code>unit_objects</code> slot, and row names matching the names of the unit-specific parameters. Alternatively, this can be a named vector following the naming convention <code><parameter>[<unit_name>]</code> .

Author(s)

Jesse Wheeler

See Also

[panelPomp_methods](#)

Examples

```
# set parameters in list form
prw <- panelRandomWalk(U = 4)
new_pars <- matrix(c(1, 1, 3, 2), nrow = 1)
dimnames(new_pars) <- list(param = "X.0", unit = c("rw1", "rw2", "rw3", "rw4"))
specific(prw) <- new_pars
```

twentycities

He et al. 2010 twenty UK cities weekly reported measles data

Description

He et al. 2010 twenty UK cities weekly reported measles data

Usage

```
twentycities
```

Format

```
twentycities:
```

A list of 3 data frames.

```
twentycities$measles::
```

unit City name

data Date of observation

cases Number of measles cases reported during the week

```
twentycities$demog::
```

unit City name

year Year that demography was recorded

pop Population

births Births

```
twentycities$coord::
```

unit City name

long Longitude of city

lat Latitude of city

Source

<https://kingaa.github.io/pomp/vignettes/twentycities.rda>

References

D. He, E.L. Ionides, and A.A. King. Plug-and-play inference for disease dynamics: measles in large and small populations as a case study. *Journal of the Royal Society Interface* **7**, 271–283, 2010.

uk_measles

*Weekly reported measles data for 362 locations in the UK***Description**

Weekly reported measles data for 362 locations in the UK

Usage

```
uk_measles
```

Format

```
uk_measles:
```

A list of 3 data frames Unit names ending in .RD are for rural areas; other unit names are for urban areas. NOTE: not all units have coordinates.

```
uk_measles$measles::
```

unit City name

data Date of observation

cases Number of measles cases reported during the week

```
uk_measles$demog::
```

unit City name

year Year that demography was recorded

pop Population

births Births

```
uk_measles$coord::
```

unit City name

long Longitude of city

lat Latitude of city

Source

https://rs.figshare.com/collections/Supplementary_material_from_Structure_space_and_size_competing_drivers_of_variation_in_urban_and_rural_measles_transmission_/5036567/1

References

Korevaar H, Metcalf CJ, Grenfell BT. 2020 Structure, space and size: competing drivers of variation in urban and rural measles transmission. J. R. Soc. Interface 17: 20200010. <http://dx.doi.org/10.1098/rsif.2020.0010>

`unitLogLik`*Extract log likelihood of units of panel models*

Description

`unitLogLik()` is a generic function that extracts the log likelihood for each unit of panel objects returned by panel modeling functions. While the numeric value with the log likelihood for the entire panel is useful and possible via S4 methods `logLik()`, the contributions to it by panel units can be implemented via `unitLogLik()`.

Usage

```
unitLogLik(object, ...)
```

Arguments

<code>object</code>	an object for which log likelihood values for units can be extracted.
<code>...</code>	additional arguments.

Details

This is a generic function: methods can be defined for it.

Value

Log likelihood extracted for each unit of the panel model object.

When given objects of class `pfilterd.ppomp`, `unitLogLik()` returns a numeric vector.

Author(s)

Carles Bretó

See Also

[pfilter](#)

Examples

```
# filter, which generates log likelihoods
pfrw <- pfilter(panelRandomWalk(), Np=10)
# extract log likelihood for each panel unit
unitLogLik(pfrw)
```

unit_objects	<i>Extract units of a panel model</i>
--------------	---------------------------------------

Description

unit_objects() is a generic function that extracts a list of objects corresponding to units of panel objects returned by panel modeling functions.

Usage

```
unit_objects(object, ...)
```

Arguments

object	an object for which extraction of panel units is meaningful.
...	additional arguments.

Details

This is a generic function: methods can be defined for it.

Value

Units extracted from the panel model object.

When given objects of class panelPomp, unit_objects() returns a list of pomp objects.

Author(s)

Carles Bretó

See Also

[panelPomp_methods](#)

Examples

```
prw <- panelRandomWalk()  
## access underlying pomp objects  
unit_objects(prw)
```

`wQuotes`*Interpret shortcuts for `sQuote()`s and `dQuote()`s in character objects*

Description

Concatenate character objects and replace double quotes with `sQuote()` (write `'x'` instead of `dQuote("x")`) and replace asterisks with `dQuote()`.

Usage

```
wQuotes(...)
```

Arguments

`...` objects to be passed to `strsplit`.

Value

A character object.

Author(s)

Carles Bretó

Examples

```
paste0("in ",sQuote("fn_name"),": ",dQuote("object")," is 'a' required argument")
wQuotes("in 'fn_name': *object* is 'a' required argument") # same but shorter
```

Index

- * **datasets**
 - panelPomp-package, 2
 - twentycities, 30
 - uk_measles, 31
- * **internal**
 - shared, 26
 - shared<-, 27
 - specific, 28
 - specific<-, 29
 - unit_objects, 33
 - unitLogLik, 32
 - wQuotes, 34
- * **models**
 - panelPomp-package, 2
- * **panel-designs**
 - panel-designs, 10
- * **panelPomp examples**
 - contacts, 6
 - panelGompertz, 11
 - panelMeasles, 13
 - panelRandomWalk, 19
- * **panelPomp methods**
 - as, 4
 - panelPomp_methods, 16
- * **panelPomp workhorse functions**
 - mif2, 8
 - panel_loglik, 20
 - panelPomp, 15
 - pfilter, 22
- * **ts**
 - panelPomp-package, 2
 - .modifyOther, 3
 - .modifySelf, 4
 - [,panelPomp-method (panelPomp_methods), 16
 - [[,panelPomp-method (panelPomp_methods), 16
- as, 4, 18
- coef,panelPomp-method (panelPomp_methods), 16
- coef<-,pfilterd.ppomp-method, 5
- coef<-,panelPomp-method (panelPomp_methods), 16
- contacts, 6, 12, 14, 19
- get_col (get_dim), 7
- get_dim, 7
- get_row (get_dim), 7
- length,panelPomp-method (panelPomp_methods), 16
- logLik,matrix-method (panel_loglik), 20
- logLik,pfilterd.ppomp-method (pfilter), 22
- logmeanexp, 21
- mif2, 2, 8, 10, 16, 20, 24
- mif2,mif2d.ppomp-method (mif2), 8
- mif2,panelPomp-method (mif2), 8
- mif2d.ppomp-class (mif2), 8
- names,panelPomp-method (panelPomp_methods), 16
- panel-designs, 10
- panel_loglik, 10, 16, 20, 24
- panel_logmeanexp, 21
- panelGompertz, 6, 11, 14, 19
- panelGompertzLikelihood, 13
- panelMeasles, 6, 12, 13, 19
- panelPomp, 2, 3, 10, 13, 15, 20, 24
- panelPomp-class (panelPomp), 15
- panelPomp-package, 2
- panelPomp_methods, 5, 16, 26–29, 33
- panelRandomWalk, 6, 12, 14, 19
- par, 25
- params, 22
- pfilter, 2, 10, 16, 20, 22, 24, 32
- pfilter,panelPomp-method (pfilter), 22

pfilterd.ppomp-class (pfilter), 22
 plot, 25
 plot, panelPomp_plottable-method (plot), 25
 pomp, 16
 pomp package, 3
 print, panelPomp-method (panelPomp_methods), 16

 runif_panel_design (panel-designs), 10

 shared, 26
 shared, panelPomp-method (panelPomp_methods), 16
 shared<-, 27
 shared<-, panelPomp-method (panelPomp_methods), 16
 shared<-, pfilterd.ppomp-method (coef<-, pfilterd.ppomp-method), 5
 show, panelPomp-method (panelPomp_methods), 16
 simulate, 27
 simulate, panelPomp-method (simulate), 27
 specific, 28
 specific, panelPomp-method (panelPomp_methods), 16
 specific<-, 29
 specific<-, panelPomp-method (panelPomp_methods), 16
 specific<-, pfilterd.ppomp-method (coef<-, pfilterd.ppomp-method), 5

 toMatrixPparams (params), 22
 toParamList, 22
 toParamList (panelPomp_methods), 16
 toParamVec (params), 22
 traces, mif2d.ppomp-method (mif2), 8
 twentycities, 30

 uk_measles, 14, 31
 unit_objects, 33
 unit_objects, panelPomp-method (panelPomp_methods), 16
 unitLogLik, 32
 unitLogLik, pfilterd.ppomp-method (pfilter), 22

 window, panelPomp-method (panelPomp_methods), 16
 wQuotes, 34