

YT Equity Service APIPG Specification

(Version 1.0)

Document Revision

Version	Description of change	Author	Date
1.0	Initial Creation	Vithun P.	20 January 2020

CONFIDENTIAL

Table of Contents

Server Name List	4
Get Server Name	4
Check Server available.....	4
Login	5
Logout.....	6
Check Session.....	6
Get Customer Account	7
Get Customer Credit.....	8
Get Customer Position.....	10
Put PG Order	11
Cancel Order	12
Get Order Info	13

Server Name List

Production

Use API Get Server Name

<https://itrade.yuanta.co.th/ytapipg/>

Test

<https://uat.yuantathai.com/ytapipg/>

Get Server Name

URL: <http://yuanta.co.th/getservername.asp>

Return Value

- Servername = Server Name use for another API

Example

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<servername>https://itrade.yuanta.co.th</servername>
</result>
```

Check Server available

URL: (Server Name)/ytapipg/useserver.aspx

Return Value

- Code = ['Y': Can use this server, 'N' or no return: Server unavailable]

Example

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<code>Y</code>
</result>
```

Login

URL: (Server Name)/ytapipg/login.aspx

Parameter

- User = User ID
- Password = Password
- Product = Product Name

Return Value

- Code = [0: success, 1-6: error]
- Success
 - Msg = Message description
 - Invno = [Type 'I': Investor Number, Type 'T': Trader No (according to field type)]
 - Invname = Investor Name
 - Type = User type ['I': Investor Number, 'T': Trader, 'O': Other]
 - Sbl = Can trade SBL
 - Market = ['E': Equity, 'T': TFEX]
 - Sid = Session ID
 - User_grade = User Grade
- Error
 - Msg = Error message description

Message Code

- 0 = Success
- 1 = Nobody is registered
- 2 = Access is Disable
- 3 = Invalid password
- 4 = Access is Forbidden
- 5 = Out of Services
- 6 = Congratulations, Your account has been activated. You can log in to (product) next trade date.

Example

Success

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<code>0</code>
<msg>Success</msg>
<invno>12345678</invno>
<invname>Yuanta Thai</invname>
<type>I</type>
<sbl>Y</sbl>
<market>E</market>
<sid>123456789012345</sid>
<user_grade>0</grade>
</result>
```

Error

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<code>3</code>
<msg>Invalid password</msg>
</result>
```

Logout

URL: (Server Name)/ytapipg/logout.aspx

Parameter

- User = Same user id at login

Return Value

- Code = [0: success, 1-4: error]
- Userid = User ID
- Msg = Message description

Message Code

- 0 = Success
- 1 = Nobody is registered
- 2 = Access is Disable
- 3 = Invalid password
- 4 = Access is Forbidden

Example

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<code>0</code>
<userid>12345678</userid>
<msg>Success</msg>
</result>
```

Check Session

URL: (Server Name)/ytapipg/chksession.aspx

Parameter

- Userid = Same user id at login
- Sid = Field "sid" at login return

Return Value

- Code = [0: success, -1: error]

Example

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<code>0</code>
</result>
```

Get Customer Account

URL: (Server Name)/ytapipg/get_cust_account.aspx

Parameter

- Userid = Same user id at login
- Sid = Field "sid" at login return

Return Value

- Code = [0: success, 1-2: error]
- Msg = Message description
- Accountno = Account number
- Cantrade = [Y: This account can trade, N: This account can view only]
- Market = [E: Equity, T: TFEX]

Message Code

- 0 = Successfully
- 1 = Please relogin.
- 2 = You don't have permission to access.

Example

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<code>0</code>
<msg>Successfully</msg>
<list>
<account>
<accountno>12345678</accountno>
<cantrade>Y</cantrade>
<market>E</market>
</account>
<account>
<accountno>82345678</accountno>
<cantrade>N</cantrade>
<market>E</market>
</account>
<account>
<accountno>C-234567-0</accountno>
<cantrade>N</cantrade>
<market>T</market>
</account>
</list>
</result>
```

Get Customer Credit

URL: (Server Name)/ytapipg/get_cust_credit.aspx

Parameter

- Userid = Same user id at login
- Sid = Field "sid" at login return
- Accountno = Account number from Get Customer Account (optional)

Return Value

- Code = [0: success, 1-3: error]
- Msg = Message description
- Accno = Account Number
- Acctype = Account Type (e.g. Cash, Margin)
- BuyLimit = Buy Limit
- Bvalue = Buy Values
- Svalue = Sell Values
- Netvalue = Net Values
- Margin
 - MarginRate = Client's Margin Rate
 - LoanLimit = Loan Limit
 - PP = Purchasing Power
 - EE = Excess Equity
 - MarEE = Mark EE
 - Equity = Equity
 - MR = MR
 - CreditBalance = Credit Balance
 - LongMarket = Long Market Value
 - ShortMarket = Short Market Value
 - Collateral = Collateral
 - Loan = Loan Limit
 - Call = Call
 - Force = Force
 - ForceSale = Value Force Sale
 - MM = MM

Message Code

- 0 = Successfully
- 1 = Please relogin.
- 2 = You don't have permission to access.
- 3 = Account not found.

Example

Example for 'Margin' Account Type

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<res_code>0</res_code>
<res_msg>Successfully</res_msg>
<accno>87654321</accno>
<acctype>CreditBalance</acctype>
<Buylimit>7177</Buylimit>
<CreditLine>7231</CreditLine>
<Bvalue>0</Bvalue>
<Svalue>0</Svalue>
<Netvalue>0</Netvalue>
<MarginRate>50</MarginRate>
<LoanLimit>5000000</LoanLimit>
<PP>14354</PP>
<EE>7177</EE>
<MarkEE>7231.42</MarkEE>
<Equity>777231.42</Equity>
<MR>770000</MR>
<CreditBalance>7241.42</CreditBalance>
<LongMarket>770000</LongMarket>
<ShortMarket>0</ShortMarket>
<Collateral>0</Collateral>
<Loan>10</Loan>
<Call>0</Call>
<Force>0</Force>
<ForceSale>0</ForceSale>
<MM>100</MM>
</result>
```

Example for other Account Types

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<res_code>0</res_code>
<res_msg>Successfully</res_msg>
<accno>12345678</accno>
<acctype>Cash</acctype>
<Buylimit>9879000</Buylimit>
<Bvalue>4960890</Bvalue>
<Svalue>128778</Svalue>
<Netvalue>-4832112</Netvalue>
</result>
```

Get Customer Position

URL: (Server Name)/ytapipg/get_cust_posi.aspx

Parameter

- Userid = Same user id at login
- Sid = Field "sid" at login return
- Accountno = Account number from Get Customer Account (optional)

Return Value

- Code = [0: success, 1-3: error]
- Msg = Message description
- Stock = Stock name
- Type = [N: Normal, S: Short, B: Borrowed, R: Right, H: Hold (Cannot Sell), C: Collateral]
- Trustid = [0: Normal, 1: TTF, 2: NVDR]
- Sellable = Sellable share
- Onhand = On hand share
- Avgprice = Cost Average Price
- Mktprice = Last Market Price
- Cost = Total Cost
- Gainloss = Gain Loss
- Percentpl = Percent Gain Loss
- Totalcost = Total cost all stock
- Totalmktval = Total Market Value all stock

Message Code

- 0 = Successfully
- 1 = Please relogin.
- 2 = You don't have permission to access.
- 3 = Account not found.

Example

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<res_code>0</res_code>
<res_msg>Successfully</res_msg>
<list>
<port>
<stock>QH</stock>
<type>N</type>
<trustid>0</trustid>
<sellable>300</sellable>
<onhand>300</onhand>
<avgprice>2.1813</avgprice>
<mktprice>2.2</mktprice>
<cost>654.39</cost>
<gainloss>5.61</gainloss>
<percentpl>3</percentpl>
</port>
<totalmktval>575228</totalmktval>
</list>
</result>
```

Put PG Order

URL: (Server Name)/ytapipg/put_pg_order.aspx

Parameter

- Userid = Same user id at login
- Sid = Field "sid" at login return
- Accountno = Account number from Get Customer Account (optional)
- Stock = Stock name
- Side = [B: Buy, S: Sell, C: Cover, H: Short]
- Volume = Order Volume
- Publish = Publish Volume
- Price = Order Price
 - -1: Market Price
 - -2: At Open Price(ATO) or At Close Price(ATC)
 - -3: At Open Price (ATO)
 - -4: At Close Price (ATC)
 - -5: Market Order (MO)
 - -6: Market to Limit (ML)
- TrustID = [0: Normal, 1: TTF, 2: NVDR]
- Condition = [" ": Not used, F: Fill Or Kill, I: Immediately Or Cancel]
- RefID = Reference ID (Maximum 15 characters)
- Pin = Pin number
- Channeltype = Entry order channel [1: local office, 2: other]
- IP = Client IP address
- StrategyID = Strategy ID 4 character

Return Value

- Code = [0: success, 1-2: error]
- Msg = Message description
- Orderno = Order number

Message Code

0 = Successfully
1 = Please relogin.
2 = Error Message.

Example

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<code>0</code>
<msg>Successfully</msg>
<orderno>1234567890</orderno>
</result>
```

Cancel Order

URL: (Server Name)/ytapipg/put_cancel_order.aspx

Parameter

- Userid = Same user id at login
- Sid = Field "sid" at login return
- Accountno = Account number from Get Customer Account
- Orderno = Order number
- Stock = Cancel all order by stock name (optional)
- Stockprc = Cancel all order by stock price (optional)
- Side = Cancel all order by side [B: Buy, S: Sell, C: Cover, H: Short, A: All] (optional)
- Orderdate = Order date [format: YYYYMMDD]
- Pin = Pin number
- IP = Client IP address

Return Value

- Code = [0: success, 1-2: error]
- Msg = Message description

Message Code

- 0 = Successfully
- 1 = Please relogin.
- 2 = Error Message.

Example

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<result>
<code>0</code>
<msg>Successfully</msg>
</result>
```

Get Order Info

URL: (Server Name)/ytapipg/get_order_info.aspx

Parameter

- Userid = Same user id at login
- Sid = Field "sid" at login return
- Accountno = Account number from Get Customer Account (optional)

Return Value

- Code = [0: success, 1-3: error]
- Msg = Message description
- Orderno = Order number
- Stock = Stock name
- Side = Order side [B: Buy, S: Sell]
- Volume = Order volume
- Orderprice = Order price
- Matchedvolume = Matched Volume
- Matchedprice = Matched Price
- Commvat = Commission and Vat
- Entrytime = Order entry time
- Senddate = Send order date
- Trusted = [0: Local, 1: TTF, 2: NVDR]
- StrategyID = Strategy ID 4 character
- Status = Order status
 - O = Open
 - M = Matched
 - R = Reject
 - C = Cancel by SET
 - X = Cancel by Broker
 - PO = Pending Open
 - PX = Pending Cancel
 - A = Need Approve
- sQT = Quote
 - N = Broker got the order (Before starting process e.g. after close order)
 - B = Broker got the order
 - Y = SET got the order

Message Code

- 0 = Successfully
- 1 = Please relogin.
- 2 = You don't have permission to access.
- 3 = Account not found.