

1 Node connection

Five-protocol acquisition · live



3 Goal dispatch

Task/goal composer → lead

Drive film thickness into $50 \pm 2 \mu\text{m}$ on line In-830c92cb (current reading $\approx 55.6 \mu\text{m}$ after the deviation injection).


1. `daq_query(node_id="dn-c8c0d0d4")` — read current thickness;
2. `dcw_control(node_id="dw-4ed89dc8", value=135, hypothesis="mass conservation:  $h \propto N/v$ ,  $N 150 \rightarrow 135$  pulls  $h$  into the window")`;
3. wait, then `daq_query(node_id="dn-c8c0d0d4")` — verify the response;
4. `dcw_judge` the opened optimization record with verdict keep and the acquisition evidence;
5. `complete_task`.

TaskMessage@ opt-lead · L

goallooppipeline

2 AgentTeam deployment

Group roster → channel members



lead: opt-lead
worker: opt-executor
(node bindings)

4 Governed writes

ACK history · convergence

09-201718-05-18	挤膜厚度反馈	ScrewSpeedSP bdeat	150	raw 150	ACK	Manual
09-201718-04-47	挤膜厚度反馈	dieGapSP bdeat	1	raw 1	ACK	Batch n=3aashb4a
09-201718-04-47	挤膜厚度反馈	lineSpeedSP bdeat	95	raw 95	ACK	Batch n=3aashb4a
09-201718-04-47	挤膜厚度反馈	ScrewSpeedSP bdeat	150	raw 150	ACK	Batch n=3aashb4a
09-201718-04-47	挤膜厚度反馈	加热区1SP bdeat	200	raw 200	ACK	Batch n=3aashb4a
09-201718-04-48	挤膜厚度反馈	加热区2SP bdeat	200	raw 200	ACK	Batch n=3aashb4a
09-201718-04-44	挤膜厚度反馈	加热区1SP bdeat	200	raw 200	ACK	Batch n=3aashb4a