REPORT LAB

EMBEDDED SYSTEM - CO3054

Group: **CC02**

Student: **Dương Gia An – 1952163**

I. LAB 3 - Preemptive with Slicing

1. Prioritized Pre-emptive Scheduling with Time Slicing.

Table 14. The FreeRTOSConfig.h settings that configure the kernel to use Prioritized Pre-emptive Scheduling with Time Slicing

Constant	Value
configUSE_PREEMPTION	1
configUSE_TIME_SLICING	1





Code:

```c
#include <stdio.h>
#include "sdkconfig.h"
#include "freertos/FreeRTOS.h"
#include "freertos/task.h"
#include "esp_system.h"
#include "esp_spi_flash.h"
#include "freertos/FreeRTOSConfig.h"

void vTaskFunction(void *pvParameters)
{
        char *pcTaskName;
        const TickType_t xDelay250ms = pdMS_TO_TICKS(250);

        /*The string to print out is passed in via the parameter .
        Cast this to a character pointer . */
        pcTaskName = (char*) pvParameters;
        /*As per most tasks, this task is implemented in
        an infinite loop . */
        for (;;)
        {
                /*Print out the name of this task . */
                printf(pcTaskName);
                printf("Hello\n");

                /*Delay for a period . This time a call to vTaskDelay
()
                 is used which places the task into the Blocked state
```

```
                until the delay period has expired . The parameter
takes
                a time specified in " ticks ", and the pdMS_TO_TICKS
() macro
                is used (where the xDelay250ms constant is declared)
to
               convert 250 milliseconds into an equivalent time in
ticks .*/
               vTaskDelay(xDelay250ms);
        }

        vTaskDelete(NULL);
}

void vTaskFunction1(void *pvParameters)
{
        char *pcTaskName;
        const TickType_t xDelay500ms = pdMS_TO_TICKS(500);

        /*The string to print out is passed in via the parameter .
        Cast this to a character pointer . */
        pcTaskName = (char*) pvParameters;
        /*As per most tasks, this task is implemented in
        an infinite loop . */
        for (;;)
        {
                /*Print out the name of this task . */
                printf(pcTaskName);
                printf("Hello\tYo yo\n");

                /*Delay for a period . This time a call to vTaskDelay
()
                 is used which places the task into the Blocked state
                 until the delay period has expired . The parameter
takes
                 a time specified in " ticks ", and the pdMS_TO_TICKS
() macro
                 is used (where the xDelay250ms constant is declared)
to
               convert 250 milliseconds into an equivalent time in
ticks .*/
               vTaskDelay(xDelay500ms);
        }

        vTaskDelete(NULL);
}

static
const char *pcTextForTask1 = "Task 1 is running \r\n";
static
const char *pcTextForTask2 = "Task 2 is running \r\n";
static
const char *pcTextForTask0 = "Task 0 is running \r\n";
```

```
void app_main(void)
{
        printf("===============\n");

         xTaskCreate(vTaskFunction, " Task 0 Ilde", 2048,
                (void*) pcTextForTask0, 0, NULL);

        /*Create the first task at priority 1.
 The priority is the second to last parameter . */
        xTaskCreate(vTaskFunction1, " Task 1", 2048,
                (void*) pcTextForTask1, 1, NULL);

        /*Create the second task at priority 2,        which is higher
than a priority of 1.
         The priority is the second to last parameter . */
        xTaskCreate(vTaskFunction, " Task 2", 2048,
                (void*) pcTextForTask2, 0, NULL);


        /*Start the scheduler so the tasks start executing . */
        //vTaskStartScheduler();

        /*Will not reach here . */
}
```



Explain result: Task Idle , task 1, task 2 add to schedule same time. And task 1 has Largest Priotirity is 1 so it run first (print Hello Yo yo). Then task 0 (Idle task) and task 2 run.

2. Prioritized Pre-emptive Scheduling (without Time Slicing)

Table 16. The FreeRTOSConfig.h settings that configure the kernel to use Prioritized Pre-emptive Scheduling without Time Slicing

Constant	Value
configUSE_PREEMPTION	1
configUSE_TIME_SLICING	0



Code:

```
void app_main(void)
{
        printf("===============\n");

    xTaskCreate(vTaskFunction, " Task 0 Ilde", 2048,
                (void *)pcTextForTask0, 0, NULL);
    /* Create the first task at priority 1.
 The priority is the second to last parameter . */


    /* Create the second task at priority 2 ,
     which is higher than a priority of 1.
     The priority is the second to last parameter . */
    xTaskCreate(vTaskFunction, " Task 2", 2048,
                (void *)pcTextForTask2, 0, NULL);

    //Delay add Task 1 after 1000ms

    vTaskDelay(1000 / portTICK_PERIOD_MS);

    xTaskCreate(vTaskFunction1, " Task 1", 2048,
                (void *)pcTextForTask1, 1, NULL);

    /* Start the scheduler so the tasks start executing . */
    //vTaskStartScheduler();

    /* Will not reach here . */
}
```

Result:

```
==============
Task 0 is running
Hello
Task 2 is running
Hello
Task 0 is running
Hello
Task 2 is running
Hello
Task 0 is running
Hello
Task 2 is running
Hello
Task 0 is running
Hello
Task 2 is running
Hello
Task 0 is running
Task 1 is running
Hello   Yo yo
Hello
Task 2 is running
Hello
Task 0 is running
Hello
Task 2 is running
Hello
Task 1 is running
Hello   Yo yo
```

Explain Result:

I add Task Idle and Task 2 first and they run. (delay 250ms each)

After 1000ms (4 times for Idle and Task 2 runed) , I add task 1 to schedule. Task 1 has Highest Priority, so it run.

3.

Table 17. The FreeRTOSConfig.h settings that configure the kernel to use co-operative scheduling

Constant	Value
configUSE_PREEMPTION	0
configUSE_TIME_SLICING	Any value



Code:

```
#include <stdio.h>
#include "sdkconfig.h"
#include "freertos/FreeRTOS.h"
#include "freertos/task.h"
#include "esp_system.h"
#include "esp_spi_flash.h"
#include "freertos/FreeRTOSConfig.h"
void vTaskFunction(void *pvParameters)
{
    char *pcTaskName;
    const TickType_t xDelay250ms = pdMS_TO_TICKS(250);
    TickType_t count1000ms = pdMS_TO_TICKS(0);
    /* The string to print out is passed in via the parameter .
    Cast this to a character pointer . */
    pcTaskName = (char *)pvParameters;
    /* As per most tasks , this task is implemented in
    an infinite loop . */
    for (;;)
    {
        /* Print out the name of this task . */
        printf(pcTaskName);
        printf("Hello\n");

        /* Delay for a period . This time a call to vTaskDelay ()
         is used which places the task into the Blocked state
         until the delay period has expired . The parameter takes
         a time specified in " ticks " , and the pdMS_TO_TICKS ()
macro
         is used ( where the xDelay250ms constant is declared ) to
        convert 250 milliseconds into an equivalent time in ticks .*/
        vTaskDelay(xDelay250ms);
        if (count1000ms == pdMS_TO_TICKS(1000)){
            taskYIELD();
        }
        else count1000ms += pdMS_TO_TICKS(250);
    }
    vTaskDelete(NULL);
}

void vTaskFunction1(void *pvParameters)
{
    char *pcTaskName;
    const TickType_t xDelay500ms = pdMS_TO_TICKS(500);

    /* The string to print out is passed in via the parameter .
    Cast this to a character pointer . */
    pcTaskName = (char *)pvParameters;
    /* As per most tasks , this task is implemented in
    an infinite loop . */
```

```
    for (;;)
    {
        /* Print out the name of this task . */
        printf(pcTaskName);
        printf("Hello\tYo yo\n");

        /* Delay for a period . This time a call to vTaskDelay ()
         is used which places the task into the Blocked state
         until the delay period has expired . The parameter takes
         a time specified in " ticks " , and the pdMS_TO_TICKS ()
macro
         is used ( where the xDelay250ms constant is declared ) to
        convert 250 milliseconds into an equivalent time in ticks .*/
        vTaskDelay(xDelay500ms);
    }
    vTaskDelete(NULL);
}
static const char *pcTextForTask1 = "Task 1 is running \r\n";
static const char *pcTextForTask2 = "Task 2 is running \r\n";
static const char *pcTextForTask0 = "Task 0 is running \r\n";

void app_main(void)
{

    printf("===============\n");

    xTaskCreate(vTaskFunction, " Task 0 Ilde", 2048,
                (void *)pcTextForTask0, 0, NULL);
    /* Create the first task at priority 1.
 The priority is the second to last parameter . */


    /* Create the second task at priority 2 ,
     which is higher than a priority of 1.
     The priority is the second to last parameter . */


    //Delay add Task 1 and Task 2 after 1000ms

    vTaskDelay(1000 / portTICK_PERIOD_MS);

    xTaskCreate(vTaskFunction1, " Task 1", 2048,
                (void *)pcTextForTask1, 1, NULL);
    xTaskCreate(vTaskFunction, " Task 2", 2048,
                (void *)pcTextForTask2, 0, NULL);
    /* Start the scheduler so the tasks start executing . */
    //vTaskStartScheduler();

    /* Will not reach here . */
}
```

Result:

```
===============
Task 0 is running
Hello
Task 0 is running
Hello
Task 0 is running
Hello
Task 0 is running
Hello
Task 1 is running
Hello   Yo yo
Task 0 is running
Hello
Task 2 is running
Hello
Task 2 is running
Hello
Task 0 is running
Hello
Task 1 is running
Hello   Yo yo
Task 2 is running
Hello
Task 0 is running
```

Explain Result:

I add task 0 (Idle first).
After 1000ms, I add task 1 and 2. As the same time, TaskYIELD() in Idle run so Task 1 has Largest Priority run then.

4. Extra Exercise

```
#include <stdio.h>
#include "sdkconfig.h"
#include "freertos/FreeRTOS.h"
#include "freertos/task.h"
#include "esp_system.h"
 #include "esp_spi_flash.h"
 #include "freertos/FreeRTOSConfig.h"


void vTaskFunction_Idle(void *pvParameters)
{
    char *pcTaskName;
    const TickType_t xDelay250ms = pdMS_TO_TICKS(250);
    TickType_t count1000ms = pdMS_TO_TICKS(0);
```

```
19.      /* The string to print out is passed in via the parameter
   .
20.      Cast this to a character pointer . */
21.      pcTaskName = (char *)pvParameters;
22.      /* As per most tasks , this task is implemented in
23.      an infinite loop . */
24.      for (;;)
25.      {
26.          /* Print out the name of this task . */
27.          printf(pcTaskName);
28.
             // Hook IDLE TASK
29.          /* Print chip information */
30.          esp_chip_info_t chip_info;
31.          esp_chip_info(&chip_info);
32.          printf("This is %s chip with %d CPU core(s), WiFi%s%s,
   ",
33.              CONFIG_IDF_TARGET,
34.              chip_info.cores,
35.              (chip_info.features & CHIP_FEATURE_BT) ? "/BT" :
   "",
36.              (chip_info.features & CHIP_FEATURE_BLE) ? "/BLE" :
   "");
37.
38.          printf("silicon revision %d, ", chip_info.revision);
39.
40.          printf("%dMB %s flash\n", spi_flash_get_chip_size() /
   (1024 * 1024),
41.              (chip_info.features & CHIP_FEATURE_EMB_FLASH) ?
   "embedded" : "external");
42.
43.          printf("Minimum free heap size: %d bytes\n",
   esp_get_minimum_free_heap_size());
44.
45.
46.          /* Delay for a period . This time a call to vTaskDelay
   ()
47.           is used which places the task into the Blocked state
48.           until the delay period has expired . The parameter
   takes
49.           a time specified in " ticks " , and the pdMS_TO_TICKS
   () macro
50.           is used ( where the xDelay250ms constant is declared
   ) to
51.          convert 250 milliseconds into an equivalent time in
   ticks .*/
52.          vTaskDelay(xDelay250ms);
53.
54.          if (count1000ms == pdMS_TO_TICKS(1000)){
55.              taskYIELD();
56.          }
57.          else count1000ms += pdMS_TO_TICKS(250);
58.      }
```

```
59.      vTaskDelete(NULL);
60.  }
61.  void vTaskFunction2(void *pvParameters)
62.  {
63.      char *pcTaskName;
64.      const TickType_t xDelay250ms = pdMS_TO_TICKS(250);
65.      /* The string to print out is passed in via the parameter
     .
66.      Cast this to a character pointer . */
67.      pcTaskName = (char *)pvParameters;
68.      /* As per most tasks , this task is implemented in
69.      an infinite loop . */
70.      for (;;)
71.      {
72.          /* Print out the name of this task . */
73.          printf(pcTaskName);
74.          printf("Hello \n");
75.          /* Delay for a period . This time a call to vTaskDelay
     ()
76.           is used which places the task into the Blocked state
77.           until the delay period has expired . The parameter
     takes
78.           a time specified in " ticks " , and the pdMS_TO_TICKS
     () macro
79.           is used ( where the xDelay250ms constant is declared
     ) to
80.          convert 250 milliseconds into an equivalent time in
     ticks .*/
81.          vTaskDelay(xDelay250ms);
82.
83.      }
84.      vTaskDelete(NULL);
85.  }
86.  void vTaskFunction1(void *pvParameters)
87.  {
88.      char *pcTaskName;
89.      const TickType_t xDelay500ms = pdMS_TO_TICKS(500);
90.
91.      /* The string to print out is passed in via the parameter
     .
92.      Cast this to a character pointer . */
93.      pcTaskName = (char *)pvParameters;
94.      /* As per most tasks , this task is implemented in
95.      an infinite loop . */
96.      for (;;)
97.      {
98.          /* Print out the name of this task . */
99.          printf(pcTaskName);
100.         printf("Hello\tYo yo\n");
101.
102.         /* Delay for a period . This time a call to vTaskDelay
     ()
103.          is used which places the task into the Blocked state
```

```
104.          until the delay period has expired . The parameter
   takes
105.          a time specified in " ticks " , and the pdMS_TO_TICKS
   () macro
106.          is used ( where the xDelay250ms constant is declared
   ) to
107.         convert 500 milliseconds into an equivalent time in
   ticks .*/
108.         vTaskDelay(xDelay500ms);
109.     }
110.     vTaskDelete(NULL);
111. }
112. static const char *pcTextForTask1 = "Task 1 is running \r\n";
113. static const char *pcTextForTask2 = "Task 2 is running \r\n";
114. static const char *pcTextForTask0 = "Task 0 is running \r\n";
115.
116. void app_main(void)
117. {
118.
119.
120.     printf("===============\n");
121.
122.     xTaskCreate(vTaskFunction_Idle, " Task 0 Ilde", 2048,
123.                 (void *)pcTextForTask0, 0, NULL);
124.     /* Create the first task at priority 1.
125.  The priority is the second to last parameter . */
126.
127.
128.     /* Create the second task at priority 2 ,
129.      which is higher than a priority of 1.
130.      The priority is the second to last parameter . */
131.
132.
133.     //Delay add Task 1 after 1000ms
134.
135.     vTaskDelay(1000 / portTICK_PERIOD_MS);
136.
137.     xTaskCreate(vTaskFunction1, " Task 1", 2048,
138.                 (void *)pcTextForTask1, 1, NULL);
139.     xTaskCreate(vTaskFunction2, " Task 2", 2048,
140.                 (void *)pcTextForTask2, 0, NULL);
141.     /* Start the scheduler so the tasks start executing . */
142.     //vTaskStartScheduler();
143.
144.     /* Will not reach here . */
145. }
```

Result:

```
I (296) cpu_start: Starting scheduler on PRO CPU.
I (0) cpu_start: Starting scheduler on APP CPU.
===============
Task 0 is running
This is esp32 chip with 2 CPU core(s), WiFi/BT/BLE, silicon revision 3, 4MB external flash
Minimum free heap size: 292780 bytes
Task 0 is running
This is esp32 chip with 2 CPU core(s), WiFi/BT/BLE, silicon revision 3, 4MB external flash
Minimum free heap size: 292780 bytes
Task 0 is running
This is esp32 chip with 2 CPU core(s), WiFi/BT/BLE, silicon revision 3, 4MB external flash
Minimum free heap size: 292780 bytes
Task 0 is running
This is esp32 chip with 2 CPU core(s), WiFi/BT/BLE, silicon revision 3, 4MB external flash
Minimum free heap size: 292780 bytes
Task 1 is running
Hello   Yo yo
Task 2 is running
Hello
Task 0 is running
This is esp32 chip with 2 CPU core(s), WiFi/BT/BLE, silicon revision 3, 4MB external flash
Minimum free heap size: 287980 bytes
```

II. FreeRTOS Queue Management

Not finish yet.