Benjamin Moore®

Fresh Start®

High-Hiding All-Purpose Primer K046

General Description

The go-to for significant colour change, our highest-performing, premium quality, 100% acrylic resin primer delivers maximum hide, excellent adhesion, and a uniform finish across most interior and exterior surfaces. Seals and suppresses most bleeding type stains and provides a mildew-resistant coating in a low VOC formulation.

- Provides maximum hide.
- Seals and suppresses most bleeding type stains.
- Provides a mildew-resistant coating.
- Excellent adhesion to multiple substrates.

Usage

New, previously painted and properly prepared wood, drywall, ceiling tile, Formica®, Masonite®, ceramic tile, cured plaster and wall coverings. Use on new, previously painted and properly prepared exterior substrates such as wood, aluminum, hardboard and vinyl siding, shingles, concrete, masonry, brick and non-ferrous metal surfaces.

Seals and suppresses most bleeding type stains such as tannin bleed, water stains, smoke damage, markers, crayons, pens, pencils, nicotine, hand & fingerprints, household stains such as coffee and many more.

Colours	White (00)
Bases	Deep Base (04)
Colorant System	Gennex®

Technical Data

Vehicle		Proprietary 100% Acrylic
Pigment		Titanium Dioxide
Volume Solids		41 ± 2%
Spread Rate Per 3.79 L		37.2 – 41.8 sq. m. (400 – 450 sq. ft.)
Recommended Film Thickness	Wet:	3.6 – 4.0 mils
	Dry:	1.4 – 1.6 mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.

Dry Time @ 25 °C (77 °F) @ 50% RH	To Touch:	30 minutes
	To Recoat:	1 hour

High humidity and cool temperatures will result in longer dry, recoat and service times.

Surface Temperature During Application	Min:	4.4 °C (40 °F)
	Max:	32.2 °C (90 °F)
Viscosity		95 ± 4 KU
Flash Point		None
Sheen / Gloss		7 – 12 @ 85°
Clean Up		Water
Thinner		Water
Weight Per 3.79 L		4.8 kg (10.7 lbs.)
Storage Temperature	Min:	4.4 °C (40 °F)
	Max:	32.2 °C (90 °F)
VOC		< 50 g/L

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion after removing all form release agents and curing compounds. Remove any powder or loose particles before priming.

Primer Systems

Wood, and engineered wood products:
Fresh Start® High-Hiding All-Purpose Primer (K046)

Bleeding Woods (Redwood, Cedar, etc.):
Fresh Start® High-Hiding All-Purpose Primer (K046), Fresh Start® Undercoater & Primer/Sealer (K032) or Fresh Start® Deck & Siding Primer (K094)

Drywall:
Fresh Start® High-Hiding All-Purpose Primer (K046)

Plaster / Masonry (Cured):
Fresh Start® High-Hiding All-Purpose Primer (K046)

Rough or Pitted Masonry:
Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (K571)

Ferrous Metal (Steel and Iron):
High Performance Acrylic Metal Primer (HP1100) or High Performance Alkyd Metal Primer (HP1320)

Non-Ferrous Metal (Galvanized & Aluminum):
All new metal surfaces must be thoroughly cleaned with Oil & Grease Emulsifier (HP6000) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion. High Performance Acrylic Metal Primer (HP1100)

Compliance & Certifications

Eligible for LEED® v4	✓
CDPH Emissions Certified	✓
Eligible for CHPS low emitting credit **(Collaborative for High Performance Schools)**	✓
MPI	6, 17, 39, 50, 137
MPI X-Green™	17, 50, 137

Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84

ASTM D1653 Water vapor permeance:
Method A - 3.5 Perms / Method B - 19.5 Perms

Limitations

- Not recommended for sealing knots or over pine sap.
- On hard, non-porous surfaces, **maximum adhesion and hardness may take 3-4 days to develop.**
- Do not apply when air and surface temperatures are below (4.4 °C (40 °F).
- Two coats of primer may be required on severe stains.

Technical Assistance

Available through your local authorized independent Benjamin Moore retailer.

call 1-800-361-5898
visit www.benjaminmoore.ca

Application

Stir thoroughly before and during use. Apply one or two coats. For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed.

Spray, Airless:
Pressure / 1,500 – 2,500 PSI
Tip / 0.013 – 0.017

Thinning/Cleaning

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added; up to 236 mL (8 fl. oz.) per 3.79 L. Never add other paints or solvents.

Clean Up: Wash brushes, rollers, and other painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental Health & Safety Information

May cause allergic skin reaction.

Do not get on skin or clothing.

Use only with adequate ventilation. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html

.

KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING

Refer to Safety Data Sheet for additional health and safety information.

Benjamin Moore & Co., Ltd. 1651 Stellar Drive, Unit 1, Whitby, ON L1N 6A7 1-800-361-5898 www.benjaminmoore.ca K046 CE 030325