



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA 90038  
1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## Golmex™

*Lime/Cement Based Concrete*

*Look Plaster*

*Low VOC / Eco-Friendly*

**Meoded Golmex™ Plaster** - is a high quality Portland cement composed of lime, graded silica sand and admixtures to create the appearance of polished concrete on interior and exterior wall surfaces. **Golmex™**'s pre-mixed dry powder substrate is formulated for superb adhesion, workability and durability. A wide range of textures can be achieved with **Golmex™**; including the natural look of concrete and textured designer wall finishes from the hands of a skilled plasterer.

### COVERAGE

Depending on surface conditions

1 quart container (2lb) of **Golmex™** will cover between 3.2 - 5.6 sq. ft. up to an 1/8" thickness with two coats.

1 gallon container (10lb) of **Golmex™** will cover between 16-28 sq. ft. up to an 1/8" thickness with two coats.

1 bucket container (50lb) of **Golmex™** will cover between 80-140 sq. ft. up to an 1/8" thickness with two coats.

### TINTING

**Golmex™** plaster comes in a standard cement color that can be custom tinted to darker shades with any universal and powder colorants. It can also be glazed with Meoded's **Velature Glaze™**, a color wash that provides a semi-transparent finish.

### MIXING

For 1 gallon (10lb) add approximately 30-36oz of clean water for desired mixture.

Mix 1 bucket (50lb) of Golmex™ with approximately 150-180oz of clean water. Mixing different batches of Golmex™ with different amounts of water, different mixing speeds/time or adding more water to rehydrate the Golmex™ will alter the color, and cause color variations in the final look. Golmex™ has a working time of 45 min - 1.5 hours when mixing with clean water, only mix as needed.

### PREPARATION

Surface should be clean, dust and oil free. If the surface absorbs the material unevenly the final "look" will be different, (part of the wall is joint compound and the other part is painted drywall).

### NEW DRYWALL

Prime drywall substrate with PVA acrylic primer and let it dry fully. Next, apply one coat of **Meoded Quartz Primer™**, allowing it 3 to 5 hours to dry.

### EXISTING SURFACE

Any surface with sheen should be sanded, then prime the surface with multi-purpose primer and let it dry fully. Next apply one coat of **Meoded Quartz Primer™** allowing it to dry for 3 to 5 hours. Preparation of flat surfaces requires only the application of **Meoded Quartz Primer™**.

### EXTERIOR BROWN COAT

Surface should first be pressure washed and cleaned. When the surface is fully dry, apply **Meoded Quartz Primer™** diluted with up to 30% water. Let it dry for at least 3 to 5 hours. It is recommended to apply three thin coats of **Golmex™** plaster over the brown coat to achieve a smooth surface.



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA 90038  
1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## APPLICATION TOOLS

Use a stainless steel trowel or a spatula to apply the two coats of **Golmex™**.

## FIRST COAT

**Golmex™** should be applied thinly and evenly, covering the entire wall. It is recommended to use a damp sponge in a circular motion over the surface while the first coat is still tacky to raise the grain and make the surface more even. Allow at least 12 hours for the first coat to dry.

## SECOND COAT

Apply the second coat just like the first, making sure to cover the entire surface. Before the material is dry, use a trowel to gently compress the surface to make it smooth, keeping in mind the more you compress the smoother the surface. You can use a spray bottle to spritz the surface while compressing to achieve an even smoother look, but the same amount of water should be sprayed on the entire wall to prevent color inconsistency. Because of the extended dry time of the **Golmex™** formula, you can create different texture effects during the second coat. If a polished concrete look is desired you can sand the surface with 220 grit sandpaper 24 hours after application.

## WORKING WITH GOLMEX

Material is pliable for one hour depending on weather conditions. To avoid spoilage, do not mix more than the amount needed to cover the surface you are working on.

## SPECIAL EFFECTS

To enhance the rich appearance of **Golmex™**, glazing and sculpturing effects can be applied using standard plastering tools.

## SEALER/CLEAN UP

Seal the surface after a minimum of 48 hours of dry time, clean up with warm water and avoid letting spillage to dry.

## STORAGE

Store material in a dry and dark place, void of humidity; protected against damage from weather and direct sunlight. Use within 10 months of production.

## WARNING!

Avoid extended skin contact. Use eye protection and breathing apparatus when sanding material. Keep the room well ventilated when working indoors. Keep away from children's reach. Material can be harmful if swallowed. If product causes any type of reaction, see a physician immediately.

## WARRANTY

**Meoded Paints & Decoration™** warrants its products for the purpose in which they were intended for, when applied and used in accordance with manufacturer's instructions within 10 months of production date. Warranty period of Meoded's products is 5 years from the date of installation. **Meoded Paints & Decoration™** reserves the right to inspect installations prior to resolving any claims made under this warranty. This limited warranty is exclusive and in lieu of all other warranties; either written, oral or otherwise implied. **Meoded Paints & Decoration™** also excluded any liability for consequential damages. Meoded's liability under this warranty is limited to the replacement of products found to be defective or refund to the original purchaser, with proof of purchase.



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA 90038  
1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## TECHNICAL SERVICES & SUPPORT

Meoded provides customers with any level of assistance that may need to gain full value from our products. Designers can call upon our professional staff to match colors or create new colors for custom installations. We're ready to provide color charts and sample boards for texture evaluations and comparisons. Installers can call upon our master craftsman for advice and guidance at every step of the installation process. If you have any questions whatsoever, our enthusiastic and courteous staff will provide the support you need to experience the **Golmex™** advantage.

Every Meoded product comes with instructions that are more than adequate to guide any finish contractor or homeowner to a successful installation. In addition, we offer professional seminars for applicators of all skill and experience levels. We teach everything from the basic installation steps to tips and techniques for artists and artisans.