



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

PlasterGuard

Single Component Sealer
Waterproofing Sealer for Concretta
Interior/Exterior

PlasterGuard is a self-crosslinking nano-based water-borne copolymer that provides a unique set of advantages due to its remarkable adherence, penetration and finish versatility. **PlasterGuard** is perfectly formulated to be the waterproofing top coat for Concretta shower applications. 3-layer application for any wet/humid areas such as showers & backsplashes. For best results apply 4 layers. If applying plasters in high traffic areas or backsplashes and need a strong sealant, **PlasterGuard** is a suitable solution to increase durability and prevent stains.

PREPARATION

Make sure to let the Concretta plaster dry for 72 hours before application. Prior to applying, ensure that the surface is clean of any loose, flaky particles.

Waterproofing for Concretta (Wall Applications)

To waterproof Concretta plaster in wet & humid areas such as showers, apply 3-4 layers of **PlasterGuard** Sealer using a foam roller. Once the final coat of Concretta has cured for at least 72 hours, roll on the first layer of **PlasterGuard** diluted with 20% water. Let dry for 1-2 hours. Then apply 2-3 more layers of **PlasterGuard** full strength, no dilution using a foam roller. Dry time between each layer is approximately 1-2 hours. Allow the final coat to dry for at least 24-48 hours before using the shower. If any water penetration is seen after the 3rd coat, apply another layer of sealer.

Waterproofing for Concretta Floor/Countertop Applications

To waterproof the Concretta plaster on any floor/countertop surfaces, use a foam roller to apply 1 layer of **PlasterGuard** diluted with 20% water. Dry time is approximately 1-2 hours.

Once it is dry, roll on 2 layers of **Meoded PlasterSeal Plus** using a foam roller.

PlasterSeal Plus is a urethane sealant. This 3-part component sealer has a 1-1.5-hour dry time. Roll on the first layer, wait 50 minutes, and apply the second layer with AntiSkid additive (for floors only) before the sealant mix has dried out. Let it dry for 24 hours, and the floor/countertop is ready for use.

SHOWER APPLICATION

Once all sealants are applied and dried, apply a clear caulking/silicone where the walls meet the floor, and around all fixtures. Apply only when the surface and air temperatures are between 50°F and 95°F. Do not apply under high humidity or if rain is expected within 24 hours.

COVERAGE

Pint – Covers between 31-44 sq. ft. per 3 layer application.

Quart – Covers between 62-88 sq. ft. per 3 layer application.

Gallon – Covers between 250-350 sq. ft. per 3 layer application.

AVAILABILITY

Available in Satin, Low Gloss, and Gloss.

Meoded products are sold through the company's network of distributors throughout the United States. Contact Meoded or visit our website www.meodedPaint.com for referrals to local sources.



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

VOC

Material is VOC compliant and contains approximately 95 g/L.

CLEANING & MAINTENANCE

For any cleaning of minor stains or dirt, scrub using a rag with warm soapy water. For any rigid stains, lightly sand and re-apply sealer. Re-apply sealer every 2-5 years depending on usage. If you see water penetration, recommended to apply another coat.

DELIVERY, STORAGE AND HANDLING

Keep materials away from direct sunlight. Store them in original, unopened packages in a dry, dark location at temperatures between 45 to 95 degrees F. Always wear OSHA-compliant eye protection. Wear a respirator to sand or scrape the product. Work only in well-ventilated areas. Avoid prolonged skin contact. Avoid working with the material in temperatures below 45 degrees F or above 95 degrees F. Keep away from children. Do not use products older than one year. Read the entire SDS and product labels.

WARRANTY

Meoded Paints & Decoration™ warrants its products for the purpose in which they were intended for, when applied and used in accordance with manufacturer's instructions within 10 months of production date. Warranty period of Meoded's products is 5 years from the date of installation. **Meoded Paints & Decoration™** reserves the right to inspect installations prior to resolving any claims made under this warranty. This limited warranty is exclusive and in lieu of all other warranties; either written, oral or otherwise implied. **Meoded Paints & Decoration™** also excludes any liability for consequential damages. Meoded's liability

under this warranty is limited to the replacement of products found to be defective or refund to the original purchaser, with proof of purchase.

WARNING!

This product may contain traces of chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

TECHNICAL SERVICES & SUPPORT

Meoded provides customers with any level of assistance that may need to gain full value from our products. Installers can call upon our master craftsman for advice and guidance at every step of the installation process. If you have any questions whatsoever, our enthusiastic and courteous staff will provide the support you need. Every Meoded product comes with instructions that are more than adequate to guide any contractor or homeowner to a successful installation. In addition, we offer professional seminars for applicators of all skills and experience levels. We teach everything from the basic installation steps to tips and techniques for artists and artisans.