



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

PlasterSeal Plus

*3 Part Component Sealer
Waterproofing Sealer for Concretta
Floor & Countertop Installations
Interior/Exterior*

PlasterSeal Plus imparts twice the abrasion resistance of standard urethanes and 4 times that of typical epoxies. Performance characteristics, including high UV, heat and chemical resistance make **PlasterSeal Plus** the ideal finish coat for a wide range of installations. **PlasterSeal Plus** is perfectly formulated to be the waterproofing top coat for all Concretta floor and countertop installations. Installation of **PlasterSeal Plus** over a diluted layer of **PlasteGuard** will provide the highest durability surface.

PREPARATION

Make sure to let the Concretta plaster cure for at least 72 hours before application. Prior to applying, ensure that the surface is clean of any loose, flaky particles.

Waterproofing for Concretta Floor/Countertop Applications

To waterproof the Concretta plaster in areas such as floors & countertops, apply a layer of **PlasterGuard**, and two layers of **PlasterSeal Plus** on top. Dilute the layer of **PlasterGuard** with 20% water for optimum penetration and apply with a **foam roller**. Let it dry for a minimum of 1-2 hours. Mix all 3 parts of the **PlasterSeal Plus** in accordance. Mix Part A and B together for approximately 5 minutes. Let the mixture sit for 15 minutes. This is the induction time. Then add the bottle of Deionized water. Mix for another 1-2 minutes and the sealant is ready for use. The sealant has a working time of about 1-1.5 hours.

Using a foam roller, roll on a thin first layer, wait about 50 minutes and roll on the second layer before the 3-part mix dries out. For floor applications, it is recommended to use an AntiSkid additive. (1 bottle is for 1 gallon) Let the final layer dry for 24-48 hours. If applying on shower floors, apply a clear caulking/silicone over all edges where the wall meets the floor and around all fixtures. Once the caulking/silicone is dry, the shower is ready for use.

MIXING

Totally mix Part "A" by mixing with a drill and dispersion blade. Pour Part "A" (resin) and part "B" (catalyst) into a mixing pail. Blade stir with a drill for 5 minutes at low speed to minimize air entrainment and internal heat. Work pail walls and bottom well, the mix must be totally blended. Wait 15 minutes. This is the induction time to start the reaction. Add the bottle of deionized water. Blade mix again for 1 to 2 minutes at low speed. You now have about 60-90 minutes potlife. Apply two layers with a foam roller before potlife expiration. Apply with a foam roller, or an airless sprayer at lowest pressure with a 6-15 or a 6-17 nozzle and 100' to 150' of hose.

Roller Application

Best to use a foam roller. If a foam roller isn't available, a short nap roller (3/16" or max 1/4") can be used by skilled applicators. Visually measure off an area about 4' x 4'. Load roller and create a "V" or "W" in the above area. Do not pour product onto surface. Working in a pull and push mode away from you and towards you. Quickly spread the material. Work with a free hand. The idea is just to spread the material evenly. Lightly back roll. Do not overwork. Repeat the above adjacent to the first area, overlapping the new "V" or "W" slightly onto



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

the old. You want to work very fast so that the overlaps are wet to wet. You want the look to be foggy/hazy like non fat milk, never white. If there are any white spots from drips or too heavy application, immediately roll out.

COVERAGE

12oz – Covers approximately 35 sq. ft. per 2-layer application.

Quart – Covers approximately 100 sq. ft. per 2-layer application.

Gallon – Covers approximately 400 sq. ft. per 2-layer application.

VOC

Material is VOC compliant and contains approximately 48 g/L.

CLEAN & MAINTENANCE

For any cleaning of minor stains, scrub using a rag and warm soapy water. For any rigid stains, lightly sand and re-apply sealer. Re-apply sealant every 2-5 years, depending on usage. If you see water penetration, it is recommended to apply another layer.

DELIVERY, STORAGE AND HANDLING

Keep materials away from direct sunlight. Store them in original, unopened packages in a dry, dark location at temperatures between 45 to 95 degrees F. Always wear OSHA-compliant eye protection. Wear a respirator to sand or scrape the product. Work only in well-ventilated areas. Avoid prolonged skin contact. Avoid working with the material in temperatures below 45 degrees F or above 95 degrees F. Keep away from children. Do not use products older than one year. Read the entire SDS and product labels.

AVAILABILITY

Meoded products are sold through the company's network of distributors throughout the United States. Contact Meoded or visit our

website www.meodedPaint.com for referrals to our local sources.

WARRANTY

Meoded Paints & Decoration™ warrants its products for the purpose in which they were intended for, when applied and used in accordance with manufacturer's instructions within 10 months of production date. Warranty period of Meoded's products is 5 years from the date of installation. **Meoded Paints & Decoration™** reserves the right to inspect installations prior to resolving any claims made under this warranty. This limited warranty is exclusive and in lieu of all other warranties; either written, oral or otherwise implied. **Meoded Paints & Decoration™** also excludes any liability for consequential damages. Meoded's liability under this warranty is limited to the replacement of products found to be defective or refund to the original purchaser, with proof of purchase.

WARNING!

This product may contain traces of chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

TECHNICAL SERVICES & SUPPORT

Meoded provides customers with any level of assistance that they may need to gain full value from our products. Installers can call upon our master craftsmen for advice and guidance at every step of the installation process. If you have any questions whatsoever, our enthusiastic and courteous staff will provide the support you need. Every Meoded product comes with instructions that are more than adequate to guide any contractor or homeowner to a successful installation. In addition, we offer professional seminars for applicators of all skills and experience levels. We teach everything from the basic installation steps, to tips and techniques for artists and artisans.