



READY SEAL®

EXTERIOR WOOD STAIN

DESCRIPTION AND USES

READY SEAL® Exterior Wood Stain is an oil-based, semi-transparent stain-and-sealer-in-one. It is a unique blend of oil, quality resins, and finely ground pigments that penetrate deeply to protect and preserve the wood from the elements.

READY SEAL semi-transparent stains enhance the natural beauty of the wood by reacting with its natural characteristics and allowing the texture and grain of the wood to remain visible.

READY SEAL may be used on any exterior wood project. READY SEAL is effective on most types of wood and shows excellent results on all species of pressure-treated lumber, Cedar, Redwood, Spruce, Pine, Fir, and North American hardwoods. For exterior, above ground use only.

PRODUCT FEATURES AND BENEFITS

- Leaves "No laps, runs or streaks®" during application
- No back brushing required
- No cracking, chipping, flaking or peeling
- Easy maintenance – no sanding or stripping required
- Is not based on linseed or vegetable oils, which are known to promote algae and fungus growth in wood.

PRODUCTS

1-Gallon	5-Gallon	DESCRIPTION
369954	500	Clear
370010	505	Natural
370011	510	Golden Pine
370012	370045	Natural Cedar
370015	520	Redwood
370021	530	Mahogany
370026	535	Mission Brown
370029	545	Burnt Hickory
115	515	Pecan
123	525	Dark Walnut

COMPANION PRODUCTS

SKU	DESCRIPTION
407	READYbrush™ 7" Staining Brush
410	READYbright™ Wood Brightener (1-Gallon)
412	READYremove™ Wood Stripper (1-Gallon)
414	READYclean™ Wood Cleaner (1-Gallon)

PRODUCT APPLICATION

READ ALL INSTRUCTIONS BEFORE BEGINNING PROJECT.

SURFACE PREPARATION

READY SEAL is an oil-based penetrating product, not a coating. It is not intended to sit on top of the wood like a paint, but to absorb down into the open wood pores. For best results, the wood must be prepped properly and completely dry before applying READY SEAL. Follow the prep processes outlined at readyseal.com according to your particular wood type, and once those steps are successfully completed, allow adequate dry time. Use a wood moisture meter to spot check around the project, especially around knot holes, to check for internal moisture before staining. When the wood is prepped and the moisture readings are consistently 12% or less, the wood is ready for application. *Note – it can take days, weeks, or longer for wood to dry, especially new wood, as it typically has a high moisture content right out of the lumber yard. Be patient.

NEW, UNSTAINED WOOD

Smooth-Milled Wood: New smooth-milled wood, regardless of species, typically has a slick "mill glaze" on the surface, which can act as a barrier for READY SEAL to penetrate. In addition, there is often a surface wax, ink stamps, and/or a greenish tint commonly present in new pressure-treated lumber. It is important to open the wood pores and remove discoloration and any surface barriers which could prevent the proper penetration of READY SEAL into the wood. Use READYbright Wood Brightener (or other similar wood brightener), according to label directions, to remove mill glaze and surface wax, and to open wood pores. Once that is complete and the wood is rinsed well, allow entire surface to dry down to 12% moisture or less before stain application. **Note: DO NOT OVERAPPLY** the stain. New smooth wood is very dense and will typically only take one coat the first year or two.

Rough-Cut Wood: New, rough-cut wood may not require any special preparation other than allowing it to dry. Pressure-treated lumber can require an extra step, as it is typically dipped in a substance to enhance its protection and longevity, and may have a greenish tint or other noticeable markings. In this case, use READYbright Wood Brightener (or other similar wood brightener) according to label instructions to help minimize the effects of the tint and markings. New, non-treated, rough-cut lumber (such as cedar or white pine fence pickets) does not require any specific preparation, other than dry time. Once that is complete and the wood is rinsed well, allow entire surface to dry down to 12% moisture or less before stain application.



READY SEAL®

EXTERIOR WOOD STAIN

PRODUCT APPLICATION (cont.)

SURFACE PREPARATION (cont.)

GREY/WEATHERED, UNSTAINED WOOD

Before applying READY SEAL, grey, weathered wood that has no other products on it must be thoroughly cleaned. Use READYclean Wood Cleaner (or other similar wood cleaner), according to label directions, to remove dirt, stains caused by mold, mildew and algae, and other surface contaminants. Follow with READYbright Wood Brightener (or other similar wood brightener), according to label directions, to neutralize the cleaner, restore pH balance in the wood, and refresh the wood to a more natural tone. Once that is complete and the wood is rinsed well, allow entire surface to dry down to 12% moisture or less before stain application.

PREVIOUSLY STAINED WOOD

Stained with other products: All pre-existing products that are still present need to be completely removed before READY SEAL can be successfully applied. Use READYremove Wood Stripper, or another good quality wood stripper, according to label directions. Acrylic coatings may require a paint stripper. Repeat if residual product remains on the wood. Follow with READYbright Wood Brightener, or other similar wood brightener, according to label directions, to neutralize the stripper, restore pH balance in the wood, and refresh the wood to a more natural tone. Once that is complete and the wood is rinsed well, allow entire surface to dry down to 12% moisture or less before stain application.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Stained with READY SEAL: If applied correctly and maintained properly, READY SEAL does not need to be sanded or stripped off the wood before reapplication. Just clean, dry, and re-apply. Use READYclean Wood Cleaner (or other similar wood cleaner), according to label directions, to remove dirt, stains caused by mold, mildew and algae, and other surface contaminants. Follow with READYbright Wood Brightener (or other similar wood brightener), according to label directions, to neutralize the cleaner, restore pH balance in the wood, and refresh the wood to a more natural tone. If there are no stains from mold, mildew, or algae, you can just use READYbright. Once this is complete and the wood is rinsed well, allow entire surface to dry down to 12% moisture or less before stain application.

Before applying this oil-based product, wait at least 24-48 hours after cleaning, stripping, or power-washing to allow the water-soaked wood to dry down to 12% moisture or less before stain application.

PRODUCT APPLICATION (cont.)

SURFACE PREPARATION (cont.)

It can take days, weeks, or longer for wood to dry, especially new wood, as it typically has a high moisture content right out of the lumber yard. Use a wood moisture meter to ascertain the moisture level of the wood before proceeding. Oil-based finishes will not properly penetrate wood that is wet.

APPLICATION

BEFORE YOU START: Prior to project start date, perform a trial brush-out in several inconspicuous areas to ensure the desired color is achieved. Color appearance will vary depending on wood species, age, and surface porosity. Replace rotted, extremely weathered, or warped boards. This product will not repair existing wood damage such as cracking, checking, splintering, or splitting. Make sure entire wood surface is dry and free of dust, dirt, and debris.

Cover all surrounding areas not intended to be coated. Intermix or box multiple gallons of the same color in a separate container to ensure a uniform color. Stir product thoroughly before use, ensuring to agitate and distribute any pigment that may have settled at the bottom of the container. READY SEAL colors may be intermixed to achieve custom color variations. DO NOT TINT or mix with other brands or types of stains/sealers.

For best results, apply when outside temperatures are between 35-120°F (2-49°C) and humidity is below 85%. Apply using a brush, roller (paint rollers with 3/8" nap is typical; consider a 1/4" nap for smooth decks), pump-up garden sprayer, or airless sprayer (40 - 60 PSI, 0.18 - 0.23 range and 211 or 213 spray tip recommended). If using any type of sprayer, be aware of breeze and wind that can unintentionally carry product to nearby structures. Do not over-saturate surface with product or allow to puddle to prevent shiners, tackiness, excessive drying time, or uneven appearance when dry.

Apply one uniform coat. Thoroughly coat all exposed surfaces until the wood will not absorb additional product and avoid puddling. Most porous woods can take up to two coats. Allow 45 minutes between applications. This product must penetrate the surface to work properly. Do not apply to a sealed wood surface. Do not use as a primer coat.

DRY TIME

Because temperatures and humidity fluctuate, **allow at least 48-72 hours dry time** before using deck/porch or placing furniture on newly stained surface. Avoid dragging furniture across surface. On newly treated surfaces, allow 7 days for coating to cure before using cleaners or chemicals. **CAUTION: BARE WOOD OR COATED SURFACES CAN BECOME SLIPPERY WHEN WET.** Use caution when walking on wet surfaces.



READY SEAL[®]

EXTERIOR WOOD STAIN

PRODUCT APPLICATION (cont.)

CLEANUP

Wipe up wet coating splatters and spills immediately with mineral spirits or paint thinner. Dried spills on smooth, solid surfaces may be able to be removed with paint thinner or mineral spirits, but READY SEAL can penetrate into and stain more porous surfaces, such as concrete, especially if not addressed immediately. A commercial-grade concrete degreaser, following product instructions, may be helpful in some cases. Clean up tools and equipment immediately after use with mineral spirits.

MAINTENANCE

Sweep regularly to remove dirt and debris. Clean annually with mild soap and water to keep coating grime-free and looking its best. If color begins to fade, reapply READY SEAL using the steps above.

PRODUCT APPLICATION (cont.)

STORAGE AND DISPOSAL

DANGER: Rags, steel wool, or other waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool, or waste in a sealed, water-filled, metal container.

DISPOSAL: Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

	TECHNICAL DATA	RSL-01
	READY SEAL® EXTERIOR WOOD STAIN	

PHYSICAL PROPERTIES

			READY SEAL EXTERIOR WOOD STAIN
Resin Type			Alkyd
Pigment Type			Inorganic
Weight	Per Gallon		7.1-7.3 lbs./gal
	Per Liter		0.85-0.87 kg/L
Solids	By Weight		81.5-82.8%
	By Volume		79.5-80.6%
Volatile Organic Compounds			<250 g/L
Practical Coverage at Recommended DFT (assumes 15% material loss)			125-175 sq. ft./gal. Varies with wood type, application, and porosity
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Recoat		45 minutes
	Light Traffic		48-72 hours
	Full Cure		72 hours
Shelf Life			3 years
Flash Point			155°F (68°C)
Safety Information			For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.readyseal.com

Form: EJ-336
Rev.: 051226